

R Notebook

Parametros:

Measure = Area under the curve
Columns = learner
Performance = holdout_measure_residual
Filter keys = sampling, weight_space, underbagging
Filter values = FALSE, FALSE, FALSE

```
library("scmamp")  
library(dplyr)
```

Tratamento dos dados

Carregando data set compilado

```
ds = read.csv("/home/rodrigo/Dropbox/UNICAMP/IC/estudo_cost_learning/SummaryResults/summary_compilation.csv")  
  
ds = filter(ds, learner != "classif.rusboost")  
summary(ds)
```

```
##           learner      weight_space  
## classif.ksvm      :17100  Mode :logical  
## classif.randomForest:17100 FALSE:41040  
## classif.rusboost   :    0  TRUE :10260  
## classif.xgboost    :17100  NA's :0  
##  
##  
##  
##           measure      sampling      underbagging  
## Accuracy           :10260  ADASYN:10260  Mode :logical  
## Area under the curve      :10260  FALSE :30780  FALSE:41040  
## F1 measure            :10260  SMOTE :10260  TRUE :10260  
## G-mean                :10260           NA's :0  
## Matthews correlation coefficient:10260  
##  
##  
## tuning_measure  holdout_measure  holdout_measure_residual  
## Min.      :-0.1277  Min.      :-0.2120  Min.      :-0.4658  
## 1st Qu.: 0.6911  1st Qu.: 0.4001  1st Qu.: 0.1994  
## Median : 0.9700  Median : 0.8571  Median : 0.5581  
## Mean   : 0.7903  Mean   : 0.6718  Mean   : 0.5298  
## 3rd Qu.: 0.9975  3rd Qu.: 0.9900  3rd Qu.: 0.8755  
## Max.    : 1.0000  Max.    : 1.0000  Max.    : 1.0000  
## NA's    :1077    NA's    :1077    NA's    :1077  
## iteration_count      dataset      imba.rate  
## Min.      :1      abalone      : 900  Min.      :0.0010  
## 1st Qu.:1      adult      : 900  1st Qu.:0.0100  
## Median :2      bank      : 900  Median :0.0300  
## Mean   :2      car      : 900  Mean   :0.0286
```

```
## 3rd Qu.:3      cardiocography-10clases: 900 3rd Qu.:0.0500
## Max. :3      cardiocography-3clases : 900 Max. :0.0500
## NA's :1077 (Other) :45900
```

Filtrando pela metrica

```
ds = filter(ds, measure == params$measure)
```

Filtrando o data set

```
if(params$filter_keys != 'NULL' && !is.null(params$filter_keys)){
  dots = paste0(params$filter_keys, " == '",params$filter_values, "'")
  ds = filter_(ds, .dots = dots)
}
```

```
summary(ds)
```

```
##          learner      weight_space
## classif.ksvm      :684  Mode :logical
## classif.randomForest:684 FALSE:2052
## classif.rusboost   : 0  NA's :0
## classif.xgboost    :684
##
##
##
##          measure      sampling      underbagging
## Accuracy          : 0  ADASYN: 0  Mode :logical
## Area under the curve :2052 FALSE :2052 FALSE:2052
## F1 measure          : 0  SMOTE : 0  NA's :0
## G-mean              : 0
## Matthews correlation coefficient: 0
##
##
## tuning_measure  holdout_measure  holdout_measure_residual
## Min. :0.3908  Min. :0.0000  Min. :0.0000
## 1st Qu.:0.8608  1st Qu.:0.8816  1st Qu.:0.7247
## Median :0.9754  Median :0.9875  Median :0.9083
## Mean :0.9029  Mean :0.8998  Mean :0.8385
## 3rd Qu.:0.9982  3rd Qu.:1.0000  3rd Qu.:0.9854
## Max. :1.0000  Max. :1.0000  Max. :1.0000
## NA's :27  NA's :27  NA's :27
## iteration_count      dataset      imba.rate
## Min. :1  abalone : 36  Min. :0.0010
## 1st Qu.:1  adult : 36  1st Qu.:0.0100
## Median :2  bank : 36  Median :0.0300
## Mean :2  car : 36  Mean :0.0286
## 3rd Qu.:3  cardiocography-10clases: 36  3rd Qu.:0.0500
## Max. :3  cardiocography-3clases : 36  Max. :0.0500
## NA's :27  (Other) :1836
```

Computando as médias das iteracoes

```
ds = group_by(ds, learner , weight_space , measure , sampling , underbagging , dataset , imba.rate)
ds = summarise(ds, tuning_measure = mean(tuning_measure), holdout_measure = mean(holdout_measure),
               holdout_measure_residual = mean(holdout_measure_residual))

ds = as.data.frame(ds)
```

Criando dataframe

```
# Dividindo o ds em n, um para cada técnica
splited_df = ds %>% group_by_at(.vars = params$columns) %>% do(vals = as.data.frame(.)) %>% select(vals)

# Juntando cada uma das partes horizontalmente em um data set
df_tec_wide = do.call("cbind", splited_df)

# Renomeando duplicacao de nomes
colnames(df_tec_wide) = make.unique(colnames(df_tec_wide))

# Selecionando apenas as medidas da performance escolhida
df_tec_wide_residual = select(df_tec_wide, matches(paste("^", params$performance, "$|", params$performance)))

# Renomeando colunas
new_names = NULL
for(i in (1:length(splited_df))){
  id = toString(sapply(splited_df[[i]][1, params$columns], as.character))
  new_names = c(new_names, id)
}
colnames(df_tec_wide_residual) = new_names

# Verificando a dimensao do df
dim(df_tec_wide_residual)
```

```
## [1] 228 3
```

```
# Renomeando a variavel
df = df_tec_wide_residual

summary(df)
```

```
##   classif.ksvm   classif.randomForest classif.xgboost
## Min.   :0.3959   Min.   :0.3885         Min.   :0.3577
## 1st Qu.:0.6696   1st Qu.:0.7849         1st Qu.:0.7253
## Median :0.8382   Median :0.9273         Median :0.9123
## Mean   :0.8027   Mean   :0.8605         Mean   :0.8519
## 3rd Qu.:0.9680   3rd Qu.:0.9844         3rd Qu.:0.9764
## Max.   :1.0000   Max.   :1.0000         Max.   :1.0000
## NA's   :5       NA's   :4
```


Verificando a média de cada coluna selecionada

```
for(i in (1:dim(df)[2])){
  print(paste("Media da coluna ", colnames(df)[i], " = ", mean(df[,i], na.rm = TRUE), sep=""))
}

## [1] "Media da coluna classif.ksvm = 0.802661345179165"
## [1] "Media da coluna classif.randomForest = 0.860489918436232"
## [1] "Media da coluna classif.xgboost = 0.851945654185092"
```

Fazendo teste de normalidade

```
plotDensities(data = na.omit(df))
```



Testando as diferencas

```
friedmanTest(df)
```

```
##  
## Friedman's rank sum test  
##  
## data: df  
## Friedman's chi-squared = 54.64, df = 2, p-value = 1.365e-12
```

Testando as diferencas par a par

```
test <- nemenyiTest(df, alpha=0.05)  
abs(test$diff.matrix) > test$statistic
```

```
##      classif.ksvm classif.randomForest classif.xgboost  
## [1,]      FALSE              TRUE      TRUE  
## [2,]      TRUE              FALSE      FALSE  
## [3,]      TRUE              FALSE      FALSE
```

Plotando grafico de Critical Difference

```
result = tryCatch({  
  plotCD(df, alpha=0.05, cex = 0.35)  
}, error = function(e) {})
```

