

R Notebook

Parametros:

Measure = Area under the curve
Columns = sampling, weight_space, ruspool
Performance = tuning_measure
Filter keys = imba.rate
Filter values = 0.05

```
library("scmamp")  
library(dplyr)
```

Tratamento dos dados

Carregando data set compilado

```
ds = read.csv("/home/rodrigo/Dropbox/UNICAMP/IC/estudo_cost_learning/SummaryResults/summary_compilation.  
summary(ds)
```

```
##           learner      weight_space  
## classif.ksvm      :17100  Mode :logical  
## classif.randomForest:17100 FALSE:41040  
## classif.xgboost    :17100  TRUE :10260  
##                   NA's :0  
##  
##  
##  
##           measure      sampling      ruspool  
## Accuracy           :10260  ADASYN:10260  Mode :logical  
## Area under the curve :10260  FALSE :30780  FALSE:41040  
## F1 measure           :10260  SMOTE :10260  TRUE :10260  
## G-mean              :10260                   NA's :0  
## Matthews correlation coefficient:10260  
##  
##  
## tuning_measure      holdout_measure      holdout_measure_residual  
## Min.      :-0.1277  Min.      :-0.2120  Min.      :-0.4658  
## 1st Qu.: 0.5924    1st Qu.: 0.3114    1st Qu.: 0.1648  
## Median : 0.9624    Median : 0.8193    Median : 0.5192  
## Mean   : 0.7570    Mean   : 0.6469    Mean   : 0.5099  
## 3rd Qu.: 0.9965    3rd Qu.: 0.9879    3rd Qu.: 0.8636  
## Max.   : 1.0000    Max.   : 1.0000    Max.   : 1.0000  
## NA's   :1761      NA's   :1761      NA's   :1761  
## iteration_count      dataset      imba.rate  
## Min.      :1        abalone      : 900  Min.      :0.0010  
## 1st Qu.:1          adult        : 900  1st Qu.:0.0100  
## Median :2          bank         : 900  Median :0.0300  
## Mean   :2          car          : 900  Mean   :0.0286  
## 3rd Qu.:3          cardiotocography-10clases: 900  3rd Qu.:0.0500  
## Max.   :3          cardiotocography-3clases : 900  Max.   :0.0500
```

```
## NA's :1761 (Other) :45900
```

Filtrando pela metrica

```
ds = filter(ds, measure == params$measure)
```

Filtrando o data set

```
if(params$filter_keys != 'NULL' && !is.null(params$filter_keys)){  
  ds = filter_at(ds, .vars = params$filter_keys, .vars_predicate = any_vars(. == params$filter_values))  
}
```

```
summary(ds)
```

```
##           learner      weight_space  
## classif.ksvm      :1230  Mode :logical  
## classif.randomForest:1230 FALSE:2952  
## classif.xgboost    :1230  TRUE :738  
##                   NA's :0  
##  
##  
##  
##           measure      sampling      ruspool  
## Accuracy           : 0  ADASYN: 738  Mode :logical  
## Area under the curve :3690 FALSE :2214 FALSE:2952  
## F1 measure           : 0  SMOTE : 738  TRUE :738  
## G-mean              : 0                   NA's :0  
## Matthews correlation coefficient: 0  
##  
##  
## tuning_measure  holdout_measure  holdout_measure_residual  
## Min. :0.3977  Min. :0.0000  Min. :0.0000  
## 1st Qu.:0.8943 1st Qu.:0.8009 1st Qu.:0.6877  
## Median :0.9914 Median :0.9729 Median :0.8736  
## Mean :0.9148  Mean :0.8769 Mean :0.8143  
## 3rd Qu.:0.9996 3rd Qu.:0.9988 3rd Qu.:0.9771  
## Max. :1.0000  Max. :1.0000 Max. :1.0000  
## NA's :111    NA's :111    NA's :111  
## iteration_count      dataset      imba.rate  
## Min. :1      abalone : 45  Min. :0.05  
## 1st Qu.:1      adult : 45  1st Qu.:0.05  
## Median :2      annealing : 45 Median :0.05  
## Mean :2      arrhythmia : 45 Mean :0.05  
## 3rd Qu.:3      balance-scale: 45 3rd Qu.:0.05  
## Max. :3      bank : 45  Max. :0.05  
## NA's :111    (Other) :3420
```

Computando as médias das iteracoes

```
ds = group_by(ds, learner , weight_space , measure , sampling , ruspool , dataset , imba.rate)  
ds = summarise(ds, tuning_measure = mean(tuning_measure), holdout_measure = mean(holdout_measure),  
               holdout_measure_residual = mean(holdout_measure_residual))
```

```
ds = as.data.frame(ds)
```

Criando dataframe

```

# Dividindo o ds em n, um para cada técnica
splited_df = ds %>% group_by_at(.vars = params$columns) %>% do(vals = as.data.frame(.)) %>% select(vals)

# Juntando cada uma das partes horizontalmente em um data set
df_tec_wide = do.call("cbind", splited_df)

# Renomeando duplicacao de nomes
colnames(df_tec_wide) = make.unique(colnames(df_tec_wide))

# Selecionando apenas as medidas da performance escolhida
df_tec_wide_residual = select(df_tec_wide, matches(paste("^", params$performance, "$|", params$performance)))

# Renomeando colunas
new_names = NULL
for(i in (1:length(splited_df))){
  id = toString(sapply(splited_df[[i]][1, params$columns], as.character))
  new_names = c(new_names, id)
}
colnames(df_tec_wide_residual) = new_names

# Verificando a dimensao do df
dim(df_tec_wide_residual)

```

```
## [1] 246 5
```

```

# Removendo linhas com NA's
df_tec_wide_residual = na.omit(df_tec_wide_residual)

# Renomeando a variavel
df = df_tec_wide_residual

summary(df)

```


```

## ADASYN, FALSE, FALSE FALSE, FALSE, FALSE FALSE, FALSE, TRUE
## Min. :0.5148 Min. :0.4564 Min. :0.4968
## 1st Qu.:0.9948 1st Qu.:0.8138 1st Qu.:0.8002
## Median :0.9995 Median :0.9633 Median :0.9352
## Mean :0.9820 Mean :0.8862 Mean :0.8831
## 3rd Qu.:1.0000 3rd Qu.:0.9948 3rd Qu.:0.9864
## Max. :1.0000 Max. :1.0000 Max. :1.0000
## FALSE, TRUE, FALSE SMOTE, FALSE, FALSE
## Min. :0.4719 Min. :0.6676
## 1st Qu.:0.6562 1st Qu.:0.9952
## Median :0.9176 Median :0.9994
## Mean :0.8284 Mean :0.9843
## 3rd Qu.:0.9890 3rd Qu.:1.0000
## Max. :1.0000 Max. :1.0000

```

Fazendo teste de normalidade

```
plotDensities(data = df)
```



Testando as diferencas

```
friedmanTest(df)
```

```
##
## Friedman's rank sum test
##
## data: df
## Friedman's chi-squared = 588.42, df = 4, p-value < 2.2e-16
```

Testando as diferencas par a par

```
test <- nemenyiTest (df, alpha=0.05)
abs(test$diff.matrix) > test$statistic
```

```
##      ADASYN, FALSE, FALSE FALSE, FALSE, FALSE FALSE, FALSE, TRUE
## [1,]          FALSE          TRUE          TRUE
## [2,]          TRUE          FALSE          TRUE
## [3,]          TRUE          TRUE          FALSE
## [4,]          TRUE          TRUE          FALSE
## [5,]          FALSE          TRUE          TRUE
##      FALSE, TRUE, FALSE SMOTE, FALSE, FALSE
## [1,]          TRUE          FALSE
```

```
## [2,]          TRUE          TRUE
## [3,]        FALSE          TRUE
## [4,]        FALSE          TRUE
## [5,]          TRUE         FALSE
```

Plotando grafico de Critical Difference

```
result = tryCatch({
  plotCD(df, alpha=0.05, cex = 0.35)
}, error = function(e) {})
```

