

R Notebook

Parametros:

```
Measure = F1 measure
Columns = learner
Performance = holdout_measure_residual
Filter keys = sampling, weight_space, underbagging, imba.rate
Filter values = FALSE, FALSE, FALSE, 0.05
```

```
library("scmamp")
library(dplyr)
```

Tratamento dos dados

Carregando data set compilado

```
ds = read.csv("/home/rodrigo/Dropbox/UNICAMP/IC/estudo_cost_learning/SummaryResults/summary_compilation.csv")
ds = filter(ds, learner != "classif.rusboost")
summary(ds)
```

```
##           learner      weight_space
## classif.ksvm      :17100  Mode :logical
## classif.randomForest:17100 FALSE:41040
## classif.rusboost   :    0  TRUE :10260
## classif.xgboost    :17100  NA's :0
##
##
##
##           measure      sampling      underbagging
## Accuracy              :10260  ADASYN:10260  Mode :logical
## Area under the curve   :10260  FALSE :30780  FALSE:41040
## F1 measure             :10260  SMOTE :10260  TRUE :10260
## G-mean                :10260              NA's :0
## Matthews correlation coefficient:10260
##
##
## tuning_measure  holdout_measure  holdout_measure_residual
## Min.   :-0.1277  Min.   :-0.2120  Min.   :-0.4658
## 1st Qu.: 0.6911  1st Qu.: 0.4001  1st Qu.: 0.1994
## Median : 0.9700  Median : 0.8571  Median : 0.5581
## Mean   : 0.7903  Mean   : 0.6718  Mean   : 0.5298
## 3rd Qu.: 0.9975  3rd Qu.: 0.9900  3rd Qu.: 0.8755
## Max.   : 1.0000  Max.   : 1.0000  Max.   : 1.0000
## NA's   :1077    NA's   :1077    NA's   :1077
## iteration_count      dataset      imba.rate
## Min.    :1          abalone      : 900  Min.    :0.0010
## 1st Qu.:1          adult        : 900  1st Qu.:0.0100
## Median :2          bank         : 900  Median :0.0300
## Mean    :2          car          : 900  Mean    :0.0286
```

```
## 3rd Qu.:3      cardiocography-10clases: 900 3rd Qu.:0.0500
## Max. :3      cardiocography-3clases : 900 Max. :0.0500
## NA's :1077 (Other) :45900
```

Filtrando pela metrica

```
ds = filter(ds, measure == params$measure)
```

Filtrando o data set

```
if(params$filter_keys != 'NULL' && !is.null(params$filter_keys)){
  dots = paste0(params$filter_keys, " == '",params$filter_values,"'")
  ds = filter_(ds, .dots = dots)
}
```

```
summary(ds)
```

```
##           learner      weight_space
## classif.ksvm      :246  Mode :logical
## classif.randomForest:246 FALSE:738
## classif.rusboost   : 0  NA's :0
## classif.xgboost    :246
##
##
##
##           measure      sampling  underbagging
## Accuracy           : 0  ADASYN: 0  Mode :logical
## Area under the curve : 0  FALSE :738 FALSE:738
## F1 measure          :738  SMOTE : 0  NA's :0
## G-mean              : 0
## Matthews correlation coefficient: 0
##
##
## tuning_measure  holdout_measure  holdout_measure_residual
## Min. :0.0000  Min. :0.0000  Min. :0.00000
## 1st Qu.:0.1111 1st Qu.:0.0000  1st Qu.:0.02548
## Median :0.4653 Median :0.5455  Median :0.22436
## Mean :0.4699  Mean :0.4787  Mean :0.33237
## 3rd Qu.:0.8049 3rd Qu.:0.8571  3rd Qu.:0.61987
## Max. :1.0000  Max. :1.0000  Max. :1.00000
## NA's :3      NA's :3      NA's :3
## iteration_count      dataset      imba.rate
## Min. :1      abalone : 9  Min. :0.05
## 1st Qu.:1      adult : 9  1st Qu.:0.05
## Median :2      annealing : 9  Median :0.05
## Mean :2      arrhythmia : 9  Mean :0.05
## 3rd Qu.:3      balance-scale: 9  3rd Qu.:0.05
## Max. :3      bank : 9  Max. :0.05
## NA's :3      (Other) :684
```

Computando as médias das iteracoes

```
ds = group_by(ds, learner , weight_space , measure , sampling , underbagging , dataset , imba.rate)
ds = summarise(ds, tuning_measure = mean(tuning_measure), holdout_measure = mean(holdout_measure),
               holdout_measure_residual = mean(holdout_measure_residual))

ds = as.data.frame(ds)
```

Criando dataframe

```
# Dividindo o ds em n, um para cada técnica
splited_df = ds %>% group_by_at(.vars = params$columns) %>% do(vals = as.data.frame(.)) %>% select(vals)

# Juntando cada uma das partes horizontalmente em um data set
df_tec_wide = do.call("cbind", splited_df)

# Renomeando duplicacao de nomes
colnames(df_tec_wide) = make.unique(colnames(df_tec_wide))

# Selecionando apenas as medidas da performance escolhida
df_tec_wide_residual = select(df_tec_wide, matches(paste("^", params$performance, "$|", params$performance)))

# Renomeando colunas
new_names = NULL
for(i in (1:length(splited_df))){
  id = toString(sapply(splited_df[[i]][1, params$columns], as.character))
  new_names = c(new_names, id)
}
colnames(df_tec_wide_residual) = new_names

# Verificando a dimensao do df
dim(df_tec_wide_residual)
```

```
## [1] 82 3
```

```
# Renomeando a variavel
df = df_tec_wide_residual

summary(df)
```

```
##   classif.ksvm   classif.randomForest classif.xgboost
## Min.   :0.0000   Min.   :0.00000   Min.   :0.00000
## 1st Qu.:0.0000   1st Qu.:0.08468   1st Qu.:0.08164
## Median :0.1292   Median :0.30383   Median :0.29218
## Mean   :0.2189   Mean   :0.37823   Mean   :0.40056
## 3rd Qu.:0.3049   3rd Qu.:0.67164   3rd Qu.:0.72131
## Max.   :0.9949   Max.   :0.97237   Max.   :0.98600
##                NA's      :1
```


Verificando a média de cada coluna selecionada

```
for(i in (1:dim(df)[2])){
  print(paste("Media da coluna ", colnames(df)[i], " = ", mean(df[,i], na.rm = TRUE), sep=""))
}

## [1] "Media da coluna classif.ksvm = 0.218865427361255"
## [1] "Media da coluna classif.randomForest = 0.378232764365048"
## [1] "Media da coluna classif.xgboost = 0.400556109264134"
```

Fazendo teste de normalidade

```
plotDensities(data = na.omit(df))
```



Testando as diferencas

```
friedmanTest(df)
```

```
##  
## Friedman's rank sum test  
##  
## data: df  
## Friedman's chi-squared = 22.872, df = 2, p-value = 1.08e-05
```

Testando as diferencas par a par

```
test <- nemenyiTest(df, alpha=0.05)  
abs(test$diff.matrix) > test$statistic
```

```
##      classif.ksvm classif.randomForest classif.xgboost  
## [1,]      FALSE              TRUE      TRUE  
## [2,]      TRUE              FALSE      FALSE  
## [3,]      TRUE              FALSE      FALSE
```

Plotando grafico de Critical Difference

```
result = tryCatch({  
  plotCD(df, alpha=0.05, cex = 0.35)  
}, error = function(e) {})
```

