

# R Notebook

## Parametros:

Measure = Area under the curve  
Columns = sampling, weight\_space, underbagging  
Performance = holdout\_measure  
Filter keys = imba.rate  
Filter values = 0.01

```
library("scmamp")  
library(dplyr)
```

## Tratamento dos dados

Carregando data set compilado

```
ds = read.csv("/home/rodrigo/Dropbox/UNICAMP/IC/estudo_cost_learning/SummaryResults/summary_compilation.  
ds = filter(ds, learner != "classif.rusboost")  
summary(ds)
```

```
##           learner      weight_space  
## classif.ksvm      :17100  Mode :logical  
## classif.randomForest:17100 FALSE:41040  
## classif.rusboost   :    0  TRUE :10260  
## classif.xgboost    :17100  NA's :0  
##  
##  
##  
##           measure      sampling      underbagging  
## Accuracy           :10260  ADASYN:10260  Mode :logical  
## Area under the curve :10260  FALSE :30780  FALSE:41040  
## F1 measure           :10260  SMOTE :10260  TRUE :10260  
## G-mean              :10260           NA's :0  
## Matthews correlation coefficient:10260  
##  
##  
## tuning_measure      holdout_measure      holdout_measure_residual  
## Min.      :-0.1277  Min.      :-0.2120  Min.      :-0.4658  
## 1st Qu.: 0.6911  1st Qu.: 0.4001  1st Qu.: 0.1994  
## Median : 0.9700  Median : 0.8571  Median : 0.5581  
## Mean   : 0.7903  Mean   : 0.6718  Mean   : 0.5298  
## 3rd Qu.: 0.9975  3rd Qu.: 0.9900  3rd Qu.: 0.8755  
## Max.    : 1.0000  Max.    : 1.0000  Max.    : 1.0000  
## NA's     :1077   NA's     :1077   NA's     :1077  
## iteration_count      dataset      imba.rate  
## Min.      :1      abalone      : 900  Min.      :0.0010  
## 1st Qu.: 1      adult      : 900  1st Qu.:0.0100  
## Median : 2      bank      : 900  Median :0.0300  
## Mean   : 2      car      : 900  Mean   :0.0286
```

```
## 3rd Qu.:3      cardiocography-10clases: 900 3rd Qu.:0.0500
## Max. :3      cardiocography-3clases : 900 Max. :0.0500
## NA's :1077 (Other) :45900
```

Filtrando pela metrica

```
ds = filter(ds, measure == params$measure)
```

Filtrando o data set

```
if(params$filter_keys != 'NULL' && !is.null(params$filter_keys)){
  ds = filter_at(ds, .vars = params$filter_keys, .vars_predicate = any_vars(. == params$filter_values))
}
```

```
summary(ds)
```

```
##           learner      weight_space
## classif.ksvm      :600 Mode :logical
## classif.randomForest:600 FALSE:1440
## classif.rusboost   : 0 TRUE :360
## classif.xgboost    :600 NA's :0
##
##
##
##           measure      sampling      underbagging
## Accuracy           : 0 ADASYN: 360 Mode :logical
## Area under the curve :1800 FALSE :1080 FALSE:1440
## F1 measure          : 0 SMOTE : 360 TRUE :360
## G-mean              : 0 NA's :0
## Matthews correlation coefficient: 0
##
##
## tuning_measure  holdout_measure  holdout_measure_residual
## Min. :0.3866 Min. :0.2139 Min. :0.3092
## 1st Qu.:0.9529 1st Qu.:0.8909 1st Qu.:0.7392
## Median :0.9993 Median :0.9916 Median :0.9067
## Mean :0.9498 Mean :0.9120 Mean :0.8469
## 3rd Qu.:1.0000 3rd Qu.:1.0000 3rd Qu.:0.9842
## Max. :1.0000 Max. :1.0000 Max. :1.0000
## NA's :51 NA's :51 NA's :51
## iteration_count      dataset      imba.rate
## Min. :1 abalone : 45 Min. :0.01
## 1st Qu.:1 adult : 45 1st Qu.:0.01
## Median :2 bank : 45 Median :0.01
## Mean :2 car : 45 Mean :0.01
## 3rd Qu.:3 cardiocography-10clases: 45 3rd Qu.:0.01
## Max. :3 cardiocography-3clases : 45 Max. :0.01
## NA's :51 (Other) :1530
```

Computando as médias das iteracoes

```
ds = group_by(ds, learner , weight_space , measure , sampling , underbagging , dataset , imba.rate)
ds = summarise(ds, tuning_measure = mean(tuning_measure), holdout_measure = mean(holdout_measure),
               holdout_measure_residual = mean(holdout_measure_residual))

ds = as.data.frame(ds)
```

Criando dataframe

```
# Dividindo o ds em n, um para cada técnica
splited_df = ds %>% group_by_at(.vars = params$columns) %>% do(vals = as.data.frame(.)) %>% select(vals)

# Juntando cada uma das partes horizontalmente em um data set
df_tec_wide = do.call("cbind", splited_df)

# Renomeando duplicacao de nomes
colnames(df_tec_wide) = make.unique(colnames(df_tec_wide))

# Selecionando apenas as medidas da performance escolhida
df_tec_wide_residual = select(df_tec_wide, matches(paste("^", params$performance, "$|", params$performance)))

# Renomeando colunas
new_names = NULL
for(i in (1:length(splited_df))){
  id = toString(sapply(splited_df[[i]][1, params$columns], as.character))
  new_names = c(new_names, id)
}
colnames(df_tec_wide_residual) = new_names

# Verificando a dimensao do df
dim(df_tec_wide_residual)

## [1] 120    5

# Renomeando a variavel
df = df_tec_wide_residual

summary(df)
```

```
## ADASYN, FALSE, FALSE FALSE, FALSE, FALSE FALSE, FALSE, TRUE
## Min. :0.5048 Min. :0.4917 Min. :0.5529
## 1st Qu.:0.8682 1st Qu.:0.9008 1st Qu.:0.8731
## Median :0.9766 Median :0.9900 Median :0.9524
## Mean :0.9063 Mean :0.9183 Mean :0.9078
## 3rd Qu.:0.9995 3rd Qu.:1.0000 3rd Qu.:0.9969
## Max. :1.0000 Max. :1.0000 Max. :1.0000
## NA's :9 NA's :1 NA's :1
## FALSE, TRUE, FALSE SMOTE, FALSE, FALSE
## Min. :0.5037 Min. :0.4858
## 1st Qu.:0.8959 1st Qu.:0.8796
## Median :0.9832 Median :0.9789
## Mean :0.9205 Mean :0.9067
## 3rd Qu.:0.9999 3rd Qu.:0.9996
## Max. :1.0000 Max. :1.0000
## NA's :2 NA's :4
```

## Verificando a média de cada coluna selecionada


```
for(i in (1:dim(df)[2])){
  #print(df[,i])
}
```

```
print(paste("Media da coluna ", colnames(df)[i], " = ", mean(df[,i], na.rm = TRUE), sep=""))
}
```

```
## [1] "Media da coluna ADASYN, FALSE, FALSE = 0.90634373918455"
## [1] "Media da coluna FALSE, FALSE, FALSE = 0.918265830292978"
## [1] "Media da coluna FALSE, FALSE, TRUE = 0.907791964493152"
## [1] "Media da coluna FALSE, TRUE, FALSE = 0.920463423761386"
## [1] "Media da coluna SMOTE, FALSE, FALSE = 0.906723654458488"
```

## Fazendo teste de normalidade

```
plotDensities(data = na.omit(df))
```



## Testando as diferencas

```
friedmanTest(df)
```

```
##
## Friedman's rank sum test
##
## data: df
## Friedman's chi-squared = 26.268, df = 4, p-value = 2.794e-05
```

## Testando as diferenças par a par

```
test <- nemenyiTest (df, alpha=0.05)
abs(test$diff.matrix) > test$statistic
```

```
##      ADASYN, FALSE, FALSE FALSE, FALSE, FALSE FALSE, FALSE, TRUE
## [1,]          FALSE          FALSE          FALSE          FALSE
## [2,]          FALSE          FALSE          FALSE          TRUE
## [3,]          FALSE          TRUE          FALSE          FALSE
## [4,]          FALSE          FALSE          FALSE          TRUE
## [5,]          FALSE          FALSE          FALSE          FALSE
##      FALSE, TRUE, FALSE SMOTE, FALSE, FALSE
## [1,]          FALSE          FALSE          FALSE
## [2,]          FALSE          FALSE          FALSE
## [3,]          TRUE          FALSE          FALSE
## [4,]          FALSE          FALSE          FALSE
## [5,]          FALSE          FALSE          FALSE
```

## Plotando grafico de Critical Difference

```
result = tryCatch({
  plotCD(df, alpha=0.05, cex = 0.35)
}, error = function(e) {})
```

