UNIVERSIDAD
DE LIMA

FACULTAD DE INGENIERÍA Y ARQUITECTURA
CARRERA DE INGENIERÍA DE SISTEMAS

INTEGRACIÓN EN LA NUBE

UNIVERSIDAD DE LIMA

Integración cableada

- Módulo Ethernet
  - El Arduino no tiene conexión cableada directa, necesitamos módulos o shields







UNIVERSIDAD DE LIMA

Integración inalámbrica

- Módulo Wifi ESP8266 para arduino



- Programación por comandos AT para conseguir la integración con la nube

+



UNIVERSIDAD DE LIMA

ESP8266 sin librería

- Lista de comandos AT

Commands	Description	Type	Set/Execute	Inquiry	test	Parameters	Examples
AT+RST	restart the module	basic	-	-	-	-	
AT+CWMODE	wifi mode	wifi	AT+CWMODE=<mode>	AT+CWMODE?	AT+CWMODE=?	1= Sta, 2= AP, 3=both	
AT+CWJAP	join the AP	wifi	AT+ CWJAP =<ssid>,< pwd >	AT+ CWJAP?	-	ssid = ssid, pwd = wifi password	
AT+CWLAP	list the AP	wifi	AT+CWLAP				
AT+CWQAP	quit the AP	wifi	AT+CWQAP	-	AT+CWQAP=?		
AT+ CWSAP	set the parameters of AP	wifi	AT+ CWSAP= <ssid>, <pwd>,<chl>, <ecn>	AT+ CWSAP?		ssid, pwd, chl = channel, ecn = encryption	Connect to your router: : AT+CWJAP="YOURSSID","helloworld"; and check if connected: AT+CWJAP?
AT+ CIPSTATUS	get the connection status	TCP/IP	AT+ CIPSTATUS				
AT+CIPSTART	set up TCP or UDP connection	TCP/IP	1)single connection (+CIPMUX=0) AT+CIPSTART= <type>, <addr>,<port>; 2) multiple connection (+CIPMUX=1) AT+CIPSTART= <id> <type>,<addr>, <port>	-	AT+CIPSTART=?	id = 0-4, type = TCP/UDP, addr = IP address, port= port	Connect to another TCP server, set multiple connection first: AT+CIPMUX=1; connect: AT+CIPSTART=4,"TCP","X1.X2.X3.X4",9999
AT+CIPSEND	send data	TCP/IP	1)single connection(+CIPMUX=0) AT+CIPSEND= <length>; 2) multiple connection (+CIPMUX=1) AT+CIPSEND= <id>, <length>		AT+CIPSEND=?		send data: AT+CIPSEND=4,15 and then enter the data
AT+CIPCLOSE	close TCP or UDP connection	TCP/IP	AT+CIPCLOSE=<id> or AT+CIPCLOSE		AT+CIPCLOSE=?		
AT+CIFSR	Get IP address	TCP/IP	AT+CIFSR		AT+ CIFSR=?		
AT+ CIPMUX	set mutiple connection	TCP/IP	AT+ CIPMUX=<mode>	AT+ CIPMUX?		0 for single connection 1 for mutiple connection	
AT+ CIPSERVER	set as server	TCP/IP	AT+ CIPSERVER= <mode>[,<port>]			mode 0 to close server mode, mode 1 to open; port = port	turn on as a TCP server: AT+CIPSERVER=1,8888, check the self server IP address: AT+CIFSR=?

UNIVERSIDAD DE LIMA

ESP32

- Funciona como estación



- Funciona como un access point



UNIVERSIDAD DE LIMA

SERVIDORES WEB

UNIVERSIDAD DE LIMA

Thingspeak



UNIVERSIDAD DE LIMA

Ejemplos



UNIVERSIDAD DE LIMA

ADAFRUIT IO



UNIVERSIDAD DE LIMA

ADAFRUIT IFTTT

- IFTTT (if-this-then-that)



UNIVERSIDAD DE LIMA

ADAFRUIT IFTTT

- Ejemplo
- https://cdn-learn.adafruit.com/downloads/pdf/using-ifttt-with-adafruit-io.pdf

AWS

- Amazon Web Service



UNIVERSIDAD DE LIMA