

Responsable: Edgar Villegas
Paquetexpress
evillegas@paquetexpress.com.mx
September 30, 2017. v1.0

API Specifications Cancel Shipment Paquetexpress.

Definition of the consumption of our REST APIs to obtain information from the Paquetexpress platform.

Control of document changes

Version	Date	General Description	Description Change
1.0	30/09/2017	Document	Initial Version
1.3	28/06/2021	API Rad, response	Add Internal Tracking Paquetexpress

Environments

With this endpoint you can make the necessary tests to identify all those necessary adjustments during the development.

URL Test = <http://qaglp.paquetexpress.mx:7007>

URL Production = <https://cc.paquetexpress.com.mx>

Responsable: Edgar Villegas
Paquetexpress
evillegas@paquetexpress.com.mx
September 30, 2017. v1.0

API Specifications Cancel Shipment Paquetexpress.

Authentication

The first steps to consume and use the RESTFul service, you must have a token, which is obtained by authenticating your account. This account is obtained through our Contact Center Department or through our sales executives.

Login:

URI: *URLAmbiente*/RadRestFul/api/rad/loginv1/login

This method receives two parameters:

user: User name
password: User Password

These parameters are the credentials with which the customer accesses the CustomerCentral portal.

Important: The password must be sent encrypted in Base 64.

Example Request:

```
{
  "header": {
    "security": {
      "user": "USER_ID",
      "password": "passtest"
    }
  }
}
```

After making the request, the server will verify the credentials of the user, and if they are valid, a token will be returned:

Responsable: Edgar Villegas
Paquetexpress
evillegas@paquetexpress.com.mx
September 30, 2017. v1.0

API Specifications Cancel Shipment Paquetexpress.

Example Response:

```
{
  "header": null,
  "body": {
    "request": null,
    "response": {
      "success": true,
      "messages": null,
      "data": {
        "token":
"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJleHAiOjE1MDQ1Mzk4MTg2MDUsImZcymlkdPTERFTjE3In0.1L-4eMEXEVWlcqQv3HxXnX3Ym0ZNYWjJSJ1fOtbGB3A"
      },
      "objectDTO": null,
      "time": "1122.0 milliseconds"
    }
  }
}
```

In the case that incorrect credentials are provided, a response like the following will be returned:

```
{
  "header": null,
  "body": {
    "request": null,
    "response": {
      "success": false,
      "messages": [
        {
          "code": "401",
          "description": "Error: Combinacion de usuario y contraseña incorrecta",
          "typeError": "ERROR"
        }
      ],
      "data": null,
      "objectDTO": null,
      "time": "572.0 milliseconds"
    }
  }
}
```

IMPORTANT: The generated token has an expiration of 30 seconds to be used.

Responsable: Edgar Villegas
Paquetexpress
evillegas@paquetexpress.com.mx
September 30, 2017. v1.0

API Specifications Cancel Shipment Paquetexpress.

Cancel a shipment

Once the token is obtained, you can send the API to cancel the shipment; this API Cancel your shipment generated as long as it is not collected.

Cancel:

URI: *URLAmbiente*/RadRestFul/api/rad/v1/cancelguia

This method receives a parameters: user, token and tracking number in the form of canonical data described at the end of the document:

Request example:

```
{
  "header":{
    "security":{
      "user":"USER",
      "token":"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJleHAiOjE2NDM4NjI5MzA1ODIsImZcyI6IldTSkFHSVAifQ.mJqTYeuAKDPL1yGJSC2HloOGKzLUrPQM0YGAKvO1ql"
    }
  },
  "body":{
    "request":{
      "data":["05167128636"]
    }
  }
}
```

Responsable: Edgar Villegas
Paquetexpress
evillegas@paquetexpress.com.mx
September 30, 2017. v1.0

API Specifications Cancel Shipment Paquetexpress.

Successful response example.

```
{
  "header": {
    "security": null,
    "device": {
      "appName": null,
      "type": null,
      "ip": "qa-Barracuda",
      "idDevice": null
    },
    "target": null,
    "output": null,
    "language": null
  },
  "body": {
    "request": null,
    "response": {
      "success": true,
      "messages": null,
      "data": "Cancelación exitosa",
      "objectDTO": null,
      "time": "195.0 milliseconds"
    }
  }
}
```

Response example with error

```
{
  "header": null,
  "body": {
    "request": null,
    "response": {
      "success": false,
      "messages": [
        {
          "code": "500",
          "description": "The Token has expired on Wed Feb 16 19:33:23 MST 2022.",
          "typeError": "ERROR"
        }
      ]
    },
    "data": null,
    "objectDTO": null,
  }
}
```

PAQUETEXPRESS

Responsable: Edgar Villegas
Paquetexpress
evillegas@paquetexpress.com.mx
September 30, 2017. v1.0

API Specifications Cancel Shipment Paquetexpress.

"time": "30.0 milliseconds"

}

}

}

Responsable: Edgar Villegas
Paquetexpress
evillegas@paquetexpress.com.mx
September 30, 2017. v1.0

API Specifications Cancel Shipment Paquetexpress.

Canonical Model

Canonical Metadata						
Entity	Attribute Required	Type	Size	Domain	Default Value	Description
Metadata Corp.						
Header (1)						
security(1)	user	String	15			User
	token	String	200			Token number
body(1)						
request(1)						
data(1)	data	String	20			Tracking number
response(1)	success	String		TRUE OR FALSE		
	data	String				Response
	time	String				
messages(1)						

Responsable: Edgar Villegas
Paquetexpress
evillegas@paquetexpress.com.mx
September 30, 2017. v1.0

API Specifications Cancel Shipment Paquetexpress.

message(0..N)	code	String	15			Id Message
	description	String	255			Message description
	typeError	String	255	ERROR, INFO		Message type
	msgeHandling	String	255			Message type