

Playwright - Installation & Setup

Modern Web automation for E2E, component and API testing across Chromium, Firefox and WebKit.

Goal of this manual

This manual guides you through the complete installation and configuration process, from preparing the environment to final validation. Follow the steps in order and use each verification checkpoint to confirm that the setup was completed correctly.

Before you start

Confirm the supported operating system, runtime/dependencies and version requirements in the current official documentation before installing. The technical checklist below mirrors the validated tool-specific procedure.

Where to run commands

On Windows use PowerShell or Command Prompt; on macOS/Linux use Terminal. After changing PATH or environment variables, close and reopen the terminal before validating again.

Official references

<https://playwright.dev/>

<https://playwright.dev/docs/intro>

Step-by-step installation and setup

1. Follow this tool-specific step: Instale Node.js pela fonte oficial e abra um NOVO terminal.
2. Follow this tool-specific step: Valide node --version e npm --version.
3. Follow this tool-specific step: Crie uma pasta de laboratório: mkdir playwright-lab e entre nela com cd playwright-lab.
4. Follow this tool-specific step: Execute npm init playwright@latest.
5. Follow this tool-specific step: Responda ao assistente: escolha JavaScript ou TypeScript, aceite a pasta de testes sugerida e decida sobre GitHub Actions conforme seu objetivo.
6. Follow this tool-specific step: Se os browsers não forem instalados pelo assistente, execute npx playwright install.
7. Follow this tool-specific step: Valide a versão: npx playwright --version.
8. Follow this tool-specific step: Execute os testes criados pelo assistente: npx playwright test.
9. Follow this tool-specific step: Abra o relatório HTML: npx playwright show-report.
10. Follow this tool-specific step: Execute npx playwright test --ui para conhecer a interface visual de execução.
11. Follow this tool-specific step: Quando atualizar Playwright, execute novamente npx playwright install para alinhar os browsers à nova versão.

Commands and validation

```
node --version
npm --version
mkdir playwright-lab
cd playwright-lab
npm init playwright@latest
npx playwright install
npx playwright --version
npx playwright test
npx playwright show-report
npx playwright test --ui
```

First working use

Complete the first working use described in the steps above and confirm the expected tool-specific result before adding integrations or advanced configuration.

Common problems and fixes

node/npm não reconhecidos: corrija a instalação/PATH do Node.js e reabra o terminal.

Browser executable does not exist: execute `npx playwright install`.

Linux/CI com dependências ausentes: use `npx playwright install --with-deps` quando apropriado e permitido.

Downloads bloqueados por proxy/certificado corporativo: siga a configuração oficial de proxy/HTTPS do Playwright; não desative segurança indiscriminadamente.

Teste abre browser errado/nenhum browser: revise `playwright.config` e os projects configurados.

Completion criteria

Treat setup as complete when the version/execution checks work and the first use in this manual finishes without errors. Only then move to integrations or advanced configuration.