

Navigating in R

Rudy

21/04/2021

Navigating folders, creating and editing files

```
getwd() ## returns current working directory

## [1] "C:/Users/RudyR/Desktop/R Projects/Rudys_First_Project"

x <- getwd()
setwd(x) ## sets the current working directory.
## Relative versus absolute paths:
## relative `setwd("../")`
## absolute `setwd("C:/Users/RudyR/OneDrive/Desktop")`
## in Windows: `setwd(C:\\users\\RudyR\\Desktop)`

## test whether a file path exists, returns TRUE or FALSE
if(!file.exists("data")) {
  dir.create("data") ## to create a folder
}

str(download.file) ## downloads a file from an URL

## function (url, destfile, method, quiet = FALSE, mode = "w", cacheOK = TRUE,
##      extra = getOption("download.file.extra"), headers = NULL, ...)

## method `curl` needs to be specified for https websites when
## downloading on a Mac. Not needed on windows.

file <- "C:/Users/RudyR/Desktop/R Projects/Rudys_First_Project/data/HouseholdExpenditure2019.csv"

## Read data in a flat file format
ExpenditureData <- read.table(file, sep = ",", header = TRUE)
## another option, `read.csv()` defaults sep = "," header = TRUE
head(ExpenditureData) ## reads the first few lines of an object

##   MsCode   HECCode   Estimate RSE Flag
## 1  M003 Total Gross 2441552500  NA    R
## 2  M003  Total Net 2370610600  NA    R
## 3  M003         01  410549200  NA    R
## 4  M003        01.1  41365600  NA    R
## 5  M003      01.1.01  16868800  NA    R
## 6  M003    01.1.01.1   2116800  NA    R
```