

Compiler Design

NFA to DFA

EXPERIMENT - 3

Roehit Ranganathan | RA1911033010017
1 February 2022

Aim:

To Build a program to covert NFA to DFA.

Program:

```
import pandas as pd

nfa = {}
n = int(input("No. of states : "))
t = int(input("No. of transitions : "))
for i in range(n):
    state = input("state name : ")
    nfa[state] = {}
    for j in range(t):
        path = input("path : ")
        print("Enter end state from state {} travelling through path {} : ".format(
            state, path))
        reaching_state = [x for x in input().split()]
        nfa[state][path] = reaching_state

print("\nNFA :- \n")
print(nfa)
print("\nPrinting NFA table :- ")
nfa_table = pd.DataFrame(nfa)
print(nfa_table.transpose())

print("Enter final state of NFA : ")
nfa_final_state = [x for x in input().split()]

new_states_list = []

# -----

dfa = {}
keys_list = list(
    list(nfa.keys())[0])
path_list = list(nfa[keys_list[0]].keys())

dfa[keys_list[0]] = {}
for y in range(t):
    var = "".join(nfa[keys_list[0]][
        path_list[y]])
    dfa[keys_list[0]][path_list[y]] = var
    if var not in keys_list:
        new_states_list.append(var)
        keys_list.append(var)
```

```

while len(new_states_list) != 0:
    dfa[new_states_list[0]] = {}
    for _ in range(len(new_states_list[0])):
        for i in range(len(path_list)):
            temp = []
            for j in range(len(new_states_list[0])):
                temp += nfa[new_states_list[0][j]][path_list[i]]
            s = ""
            s = s.join(temp)
            if s not in keys_list:
                new_states_list.append(s)
                keys_list.append(s)
            dfa[new_states_list[0]][path_list[i]] = s

    new_states_list.remove(new_states_list[0])

print("\nDFA :- \n")
print(dfa)
print("\nPrinting DFA table :- ")
dfa_table = pd.DataFrame(dfa)
print(dfa_table.transpose())

dfa_states_list = list(dfa.keys())
dfa_final_states = []
for x in dfa_states_list:
    for i in x:
        if i in nfa_final_state:
            dfa_final_states.append(x)
            break

print("\nFinal states of the DFA are : ", dfa_final_states)

```

Result:

```
PS D:\SRM\SEM 6\Compiler Design Lab\EXP-3> python -u "d:\SRM\SEM 6\Compiler Design Lab\EXP-3\exp3.py"
No. of states : 3
No. of transitions : 2
state name : A
path : 0
Enter end state from state A travelling through path 0 :
A
path : 1
A B
state name : B
path : 0
Enter end state from state B travelling through path 0 :
C
path : 1
Enter end state from state B travelling through path 1 :
C
state name : C
path : 0
Enter end state from state C travelling through path 0 :

path : 1
Enter end state from state C travelling through path 1 :

NFA :-

{'A': {'0': ['A'], '1': ['A', 'B']}, 'B': {'0': ['C'], '1': ['C']}, 'C': {'0': [], '1': []}}

Printing NFA table :-
      0      1
A  [A]  [A, B]
B  [C]   [C]
C  []    []
Enter final state of NFA :
C

DFA :-

{'A': {'0': 'A', '1': 'AB'}, 'AB': {'0': 'AC', '1': 'ABC'}, 'AC': {'0': 'A', '1': 'AB'}, 'ABC': {'0': 'AC', '1': 'ABC'}}

Printing DFA table :-
      0      1
A      A     AB
AB     AC    ABC
AC      A     AB
ABC     AC    ABC

Final states of the DFA are : ['AC', 'ABC']
PS D:\SRM\SEM 6\Compiler Design Lab\EXP-3>
```