```json
{
"name": "WF7_Distributed_Lock_System",
"nodes": [
{
"parameters": {
"httpMethod": "POST",
"path": "acquire-lock",
"options": {}
},
"name": "Webhook",
"type": "n8n-nodes-base.webhook",
"typeVersion": 2.1,
"position": [
0,
0
],
"webhookId": "acquire-lock"
},
{
"parameters": {
"jsCode": "// Acquire Lock with TTL - FASE 1.1\n// Input: { provider_id, start_time,
lock_duration_minutes? }\n// Output: { success, lock_id, acquired, message, expires_at
}\n\nconst input = $input.first().json;\n\n// Validación de input\nif (!input.provider_id ||
!input.start_time) {\n  throw new Error('Missing required fields: provider_id,
start_time');\n}\n\nconst lockDuration = input.lock_duration_minutes || 5; // Default 5 min
TTL\nconst lockKey = `lock_${input.provider_id}_${input.start_time}`;\n\nreturn [{\n  json:
{\n    provider_id: input.provider_id,\n    start_time: input.start_time,\n    lock_key:
lockKey,\n    expires_at: `NOW() + INTERVAL '${lockDuration} minutes'`,\n
lock_duration_minutes: lockDuration\n  }\n}];"
},
"name": "Build Lock Query",
"type": "n8n-nodes-base.code",
"typeVersion": 2,
"position": [
256,
0
]
},
{
"parameters": {
"operation": "executeQuery",
"query": "INSERT INTO booking_locks (provider_id, start_time, lock_key, acquired_at,
expires_at) VALUES ($1::int, $2::timestamp, $3::text, NOW(), NOW() + INTERVAL '5 minutes') ON
CONFLICT (lock_key) DO UPDATE SET acquired_at = NOW(), expires_at = NOW() + INTERVAL '5
minutes' RETURNING lock_id, lock_key, acquired_at, expires_at, (acquired_at > NOW() -
INTERVAL '5 minutes') as is_valid;",
"options": {
"queryReplacement": "={{ $json.provider_id }}, {{ $json.start_time }}, {{ $json.lock_key }}"
}
},
"name": "Acquire Lock",
"type": "n8n-nodes-base.postgres",
"typeVersion": 2.6,
"position": [
512,
0
],
```

```
"credentials": {
"postgres": {
"id": "SFNQsmuu4zirZAnP",
"name": "Postgres account"
}
}
},
{
"parameters": {
"httpMethod": "POST",
"path": "release-lock",
"options": {}
},
"name": "Release Lock Webhook",
"type": "n8n-nodes-base.webhook",
"typeVersion": 2.1,
"position": [
0,
304
],
"webhookId": "release-lock"
},
{
"parameters": {
"operation": "executeQuery",
"query": "DELETE FROM booking_locks WHERE lock_id = $1::int OR lock_key = $2::text;",
"options": {
"queryReplacement": "={{ $json.lock_id ?? '' }}, {{ $json.lock_key ?? '' }}"
}
},
"name": "Release Lock",
"type": "n8n-nodes-base.postgres",
"typeVersion": 2.6,
"position": [
256,
```

```
304
],
"credentials": {
"postgres": {
"id": "SFNQsmuu4zirZAnP",
"name": "Postgres account"
}
}
},
{
"parameters": {
"jsCode": "// Standard Contract Output for Lock System\nconst input =
$input.first().json;\n\nreturn [{\n  json: {\n    success: true,\n    error_code: null,\n
error_message: null,\n    data: {\n      lock_id: input.lock_id,\n      lock_key:
input.lock_key,\n      acquired_at: input.acquired_at,\n      expires_at: input.expires_at,\n
is_valid: input.is_valid !== false\n    },\n    _meta: {\n      source:
'WF7_DISTRIBUTED_LOCK_SYSTEM',\n      timestamp: new Date().toISOString(),\n      version:
'1.1.0'\n    }\n  }\n}];"
},
"name": "Standard Contract Output",
"type": "n8n-nodes-base.code",
"typeVersion": 2,
```

"position": [
752,
0
]
}
],
"connections": {
"Webhook": {
"main": [
[
{
"node": "Build Lock Query",
"type": "main",
"index": 0
}
]
]
},
"Build Lock Query": {
"main": [
[
{
"node": "Acquire Lock",
"type": "main",
"index": 0
}
]
]
},
"Acquire Lock": {
"main": [
[
{
"node": "Standard Contract Output",
"type": "main",
"index": 0
}
]
]
},
"Release Lock Webhook": {
"main": [
[
{
"node": "Release Lock",
"type": "main",
"index": 0
}
]
]
}
},
"settings": {
"executionOrder": "v1",
"binaryMode": "separate",
"availableInMCP": false,
"callerPolicy": "workflowsFromSameOwner"
},

"active": true,
"versionId": "49bd9645-2df8-4490-b2cd-d6b1ae9680b2"
}