

```

/*
  Created By Roger Williams 02/12/2025

  What it does
  -----

  Reads an XML file and stores data into an existing table

  Note:

  NewDataSet is the XML dataset name /Prezzies is the data element
  section in this case holds the who for/what/colour etc data
  the query section is the names of the XML field and their XML
  defined sizes and types

  The MY_XML.<var. will always appear underlined in red even though
  there is no error so ignore!

*/

USE RogPrezzies;

INSERT INTO RogPrezziesData(RogPrezziesData.PRZ_Who,
RogPrezziesData.PRZ_Category, RogPrezziesData.PRZ_Desc,
        RogPrezziesData.PRZ_Colour, RogPrezziesData.PRZ_Size,
RogPrezziesData.PRZ_manf)
SELECT
  MY_XML.Prezzies.query('Who').value('.', 'VARCHAR(255)'),
  MY_XML.Prezzies.query('Category').value('.', 'VARCHAR(255)'),
  MY_XML.Prezzies.query('Desc').value('.', 'VARCHAR(255)'),
  MY_XML.Prezzies.query('Colour').value('.', 'VARCHAR(255)'),
  MY_XML.Prezzies.query('Size').value('.', 'VARCHAR(255)'),
  MY_XML.Prezzies.query('Manf').value('.', 'VARCHAR(255)')
FROM (SELECT CAST(MY_XML AS xml)
      FROM OPENROWSET(BULK 'C:\prezzies\prezzies.xml', SINGLE_BLOB)
AS T(MY_XML)) AS T(MY_XML)
      CROSS APPLY MY_XML.nodes('NewDataSet/Prezzies') AS MY_XML
(Prezzies);

```