



Lecture 4. Edge Detection

Sobel edge detector

Juan Carlos Niebles and Jiajun Wu

CS131 Computer Vision: Foundations and Applications





Sobel Operator

- Uses two 3×3 kernels which are convolved with the original image to calculate approximations of the derivatives
- One for horizontal changes, and one for vertical

$$\mathbf{G}_x = \begin{bmatrix} +1 & 0 & -1 \\ +2 & 0 & -2 \\ +1 & 0 & -1 \end{bmatrix} \quad \mathbf{G}_y = \begin{bmatrix} +1 & +2 & +1 \\ 0 & 0 & 0 \\ -1 & -2 & -1 \end{bmatrix}$$

Sobel Operation

- Smoothing + differentiation

$$\mathbf{G}_x = \begin{bmatrix} +1 & 0 & -1 \\ +2 & 0 & -2 \\ +1 & 0 & -1 \end{bmatrix} = \begin{bmatrix} 1 \\ 2 \\ 1 \end{bmatrix} \begin{bmatrix} +1 & 0 & -1 \end{bmatrix}$$

Gaussian smoothing differentiation





Sobel Operation



- Magnitude:

$$\mathbf{G} = \sqrt{\mathbf{G}_x^2 + \mathbf{G}_y^2}$$


- Angle or direction of the gradient:

$$\Theta = \text{atan}\left(\frac{\mathbf{G}_y}{\mathbf{G}_x}\right)$$

Sobel Filter example



Sobel Filter Problems



- Poor Localization (Trigger response in multiple adjacent pixels)
- Thresholding value favors certain directions over others
 - Can miss oblique edges more than horizontal or vertical edges
 - False negatives