CS 447/647

Virtualization


Overview


What is Virtualization?

What is Xen and KVM?


Proxmox

Apptainer (Singularity)






I'VE GOT A BUNCH OF VIRTUAL WINDOWS
MACHINES NETWORKED TOGETHER, HOOKED UP
TO AN INCOMING PIPE FROM THE NET. THEY
EXECUTE EMAIL ATTACHMENTS, SHARE FILES,
AND HAVE NO SECURITY PATCHES.



THERE ARE MAILTROJANS, WARHOL WORMS, AND ALLSORIS OF EXOTIC POLYMORPHICS.
A MONITORING SYSTEM ADDS AND WIPES MACHINES AT RANDOM. THE DISPLAY SHOUS THE VIRUSES AS THEY MOVE THROUGH THE NETWORK.

GROWING AND STRUGGLING.



https://xkcd.com/350/

INSTALLING THE XKCD DEVELOPMENT ENVIRONMENT

- I. SPIN UP AVM
- 2. SPIN UP A VM INSIDE THAT VM
- 3. CONTINUE SPINNING UP NESTED VMs AND CONTAINERS UNTIL YOU GET FIRED

Virtualization

- Multiple operating systems concurrently on the same hardware
- One Host OS to many Guest OS's
- Big Industry VMWare Revenue ~\$10B
 - Purchased by Dell
- Why?
 - Flexibility
 - Efficiency
 - Backups
 - Resilience
 - Security

Virtual Vernacular


- Virtualized Hardware
 - Hypervisors
- OS-Level Virtualization
 - O Docker commercial
 - lxc Free
 - Ixd extends it
 - Singularity HPC
 - Windows Host OS must match
 - Desktop
 - Server
 - Nano Server

Hypervisors

- Virtual Machine Manager/Monitor
- Software layer between the Guest OS and Hardware
- Shares system resources
 - O CPU, RAM, Disk and Network
- Isolates* Guest OS's
 - https://www.crowdstrike.com/blog/venom-vulnerability-details/
- Agnostic
 - Ubuntu
 - Windows
 - FreeBSD
 - Debian








Full Virtualization

- Emulates the underlying hardware
 - o qemu-system-x86_64 -machine help
 - qemu-system-x86_64 -cpu help
 - Broadwell, Skylake and Pentium I (1993)
- Virtual Hardware components
 - CPU
 - Hard disks
 - C Ethernet
 - Interrupts
 - Motherboard Hardware
- Quick EMUlator (QEMU)
 - Best known Linux Full Virtualization Software
 - X86, ARM, MIPS, PowerPC


QEMU CPU Types

```
reported-model: <486 | Broadwell | Broadwell-IBRS | Broadwell-noTSX | Broadwell-noTSX-IBRS |
Cascadelake-Server | Cascadelake-Server-noTSX | Cascadelake-Server-v2 | Cascadelake-Server-v4 |
Cascadelake-Server-v5 | Conroe | Cooperlake | Cooperlake-v2 | EPYC | EPYC-Genoa | EPYC-IBPB | EPYC-
Milan | EPYC-Milan-v2 | EPYC-Rome | EPYC-Rome-v2 | EPYC-Rome-v3 | EPYC-Rome-v4 | EPYC-v3 | EPYC-v4
| GraniteRapids | Haswell | Haswell-IBRS | Haswell-noTSX | Haswell-noTSX-IBRS | Icelake-Client |
Icelake-Client-noTSX | Icelake-Server | Icelake-Server-noTSX | Icelake-Server-v3 | Icelake-Server-
v4 | Icelake-Server-v5 | Icelake-Server-v6 | IvyBridge | IvyBridge-IBRS | KnightsMill | Nehalem |
Nehalem-IBRS | Opteron G1 | Opteron G2 | Opteron G3 | Opteron G4 | Opteron G5 | Penryn |
SandyBridge | SandyBridge-IBRS | SapphireRapids | SapphireRapids-v2 | Skylake-Client | Skylake-
Client-IBRS | Skylake-Client-noTSX-IBRS | Skylake-Client-v4 | Skylake-Server | Skylake-Server-IBRS
| Skylake-Server-noTSX-IBRS | Skylake-Server-v4 | Skylake-Server-v5 | Westmere | Westmere-IBRS |
athlon | core2duo | coreduo | host | kvm32 | kvm64 | max | pentium | pentium2 | pentium3 | phenom |
qemu32 | qemu64> (default = kvm64)
```

I440FX



ICH9



Paravirtualization (Xen)

- Guest OS detects virtualized state
- Improved performance (1% 3% overhead)
- Guest OS requires various drivers or kernel modules
- No Windows
 - Needs full hardware virtualization


Hardware-Assisted Virtualization

- CPU Feature Based
 - O Intel-V
 - O AMD-V
- Accelerated Virtualization
 - CPU and memory virtualized by hardware
- Works with full virtualization and paravirtualization
- GPU Virtualization
 - Nvidia vGPU
 - Paid licensing
 - Formerly time-sliced, now SR-IOV
 - AMD MxGPU
 - Free, open-source
 - SR-IOV
 - No drivers/documentation available to the general public

Paravirtualized Drivers


- Enabled by Hardware Assisted Virtualization
- Paravirtualized components
 - Disks
 - Networking
 - Graphics Cards
 - O Filesystems (9p)
- Greatly reduces the amount of full virtualization
- Performance
 - e1000 600Mb/s
 - virtio-net little to no overhead

TCP transfer speed, Mbit/s and CPU load




VirtIO

Paravirtualized Drivers




virtio framework



Hypervisors

- Type 1 Runs on hardware without supporting OS
 - ESXI (Commercial)
 - XenServer (Commercial)
 - O Proxmox (Free)
- Type 2 User-space applications within an OS
 - QEMU
 - O Virtualbox
 - VMWare Player + Workstation



Live Migration

- Move a VM between Hypervisors
 - Real time
 - Little to no service interruption
- Copies memory
- Copies disk
 - DRBD Dual-Master
- High-availability, disaster recovery, maintenance


Virtual machine images (disks)

- Images
- Canned Operating System
- File Formats ova, img, qcow2, raw
- Snapshotting
- Portable
- Metadata

```
qemu-img create -f qcow2 disk1.img 10G
#info, resize
```

Containerization

- OS-level Virtualization
 - Portable
 - Isolated
- Relies on Kernel Features for isolation
 - cgroups
 - tap networking
 - process namespaces
- Cannot access files or resources outside of container.*
- Benefits
 - O Performance low latency IO, near native



Memory I/O CPUs
Hardware

virtuai macnine	Container
A full-fledged OS that shares underlying hardware through a hypervisor	An isolated group of processes managed by a shared kernel
Requires a complete boot procedure to initialize; starts in 1-2 minutes	Processes run directly by the kernel; no boot required; starts in < 1 second
Long-lived	Frequently replaced
Has one or more dedicated virtual disks attached through the hypervisor	Filesystem view is a layered construct defined by the container engine
lmages measured in gigabytes	Images measured in megabytes
A few dozen or fewer per physical host	Many per virtual or physical host
Complete isolation among guests	OS kernel and services shared with host
Multiple independent operating systems	Must run the same kernel as the host (OS

distribution may differ)

Container

Virtual machine

running side by side

Virtualization with Linux

- Xen
 - Paravirtual Hypervisor
 - Performance overhead of 0.1%-3.5%
 - O Domains aka Virtual Machine
 - dom0 = Host
- Kernel-based Virtual Machine
 - Full Virtualization
 - Paired with QEMU

Proxmox

- Open-source hypervisor based on Debian
- Server cluster management
 - Centralized backups
 - Live migration
 - High availability
- Underlying technologies
 - Storage LVM, ZFS, Ceph, Directories
 - VMs QEMU/KVM
 - Containers LXC
 - Networking firewalls, SDNs (software-defined networking)
 - User management PAM, PVE database, LDAP, Microsoft AD, OIDC
 - Web server
- Proxmox Backup Server
- Proxmox Datacenter Manager

Ganeti

- Originally from Google Switzerland
 - O Now maintained by GRNET (Greek Research Network) on Debian
- Virtual machine cluster management tool
 - O Disk creation management
 - Operating system installation
 - O Startup, shutdown, and failover
- Uses:
 - debootstrap
 - chroot
 - O lvm2
 - drbd

Singularity / Apptainer

- Container platform
- Portable
 - O Filesystem stored in an .simg file
- Built for HPC
 - Reproducible Science
- Legacy code or systems
- https://sylabs.io/