

EXP: 17

HIGH LEVEL PROGRAMMING EXTENSIONS – FUNCTIONS

AIM:

To implement **Functions** using programs in MySQL.

PROCEDURE:

Step 1: Select the database containing the movies table.

Step 2: Verify the records available in the movies table.

Step 3: Set the delimiter to create the stored function.

Step 4: Create a function that accepts a Movie ID as input.

Step 5: Use the function to return the movie name corresponding to the given Movie ID.

Step 6: Change the delimiter back to the default delimiter.

Step 7: Execute the function using a SELECT statement.

Step 8: Verify the movie name returned by the function.

SYNTAX

PROGRAM 1 – Function to Get Movie Name

Query 1

DELIMITER \$\$

```
CREATE FUNCTION get_movie_name(movie_id INT) RETURNS VARCHAR(50)
DETERMINISTIC BEGIN DECLARE mname VARCHAR(50); SELECT movies_name INTO mname FROM movies WHERE M_id=movie_id; RETURN mname; END$$
```

Output

```
mysql> DELIMITER $$
mysql> CREATE FUNCTION get_movie_name(movie_id INT) RETURNS VARCHAR(50) DETERMINISTIC BEGIN DECLARE mname VARCHAR(50); SELECT movies_name INTO mname FROM movies WHERE M_id=movie_id; RETURN mname; END$$
Query OK, 0 rows affected (0.01 sec)
```

Query 2

SELECT get_movie_name(105);

Output

```
mysql> SELECT get_movie_name(105);
+-----+
| get_movie_name(105) |
+-----+
| Coolie               |
+-----+
1 row in set (0.02 sec)
```

PROGRAM 2 – Function to Count Movies

Query 4

DELIMITER \$\$

CREATE FUNCTION movie_count() RETURNS INT DETERMINISTIC BEGIN DECLARE total INT; SELECT COUNT(*) INTO total FROM movies; RETURN total; END\$\$

Output

```
mysql> DELIMITER $$
mysql> CREATE FUNCTION movie_count() RETURNS INT DETERMINISTIC BEGIN DECLARE total INT; SELECT COUNT(*) INTO total FROM movies; RETURN total; END$$
Query OK, 0 rows affected (0.02 sec)
```

Query 5

SELECT movie_count();

Output

```
mysql> SELECT movie_count();
+-----+
| movie_count() |
+-----+
|           12 |
+-----+
1 row in set (0.02 sec)
```