

Ex. No. : 6

Date:18-07-2026

SELECT with various clause – BETWEEN, IN, Aggregate function

AIM:

To view the records from the tables using SELECT commands with BETWEEN, IN, Aggregate functions.

Description :

PROCEDURE:

Step 1: Select the database containing the movies table.

Step 2: Verify the records available in the movies table.

Step 3: Use the BETWEEN operator to retrieve movie records within a specified range of Movie IDs.

Step 4: Use the IN operator to retrieve movie records matching specified OTT platforms.

Step 5: Use the COUNT() function to find the total number of movies.

Step 6: Use the MAX() and MIN() functions to find the highest and lowest Movie IDs.

Step 7: Use the AVG() function to calculate the average Movie ID.

Step 8: Verify and observe the results obtained from all the queries.

Query 1

SELECT * FROM movies WHERE M_id BETWEEN 102 AND 104;

Output 1 :

```
mysql> SELECT * FROM movies WHERE M_id BETWEEN 102 AND 104;
```

M_id	movies_name	Male_Lead	Female_Lead	Director	Music	Ott
102	Premalu	Naslen	Mamitha	Girish A D	Vishnu Vijay	Hotstar
103	OG	Pawan Kalyan	Priyanka Mohan	Sujeeth	S S Thaman	N
104	Petta	Rajnikanth	Simran	Karthik Subbaraj	Anirudh	Zee5

3 rows in set (0.01 sec)

Query 2

SELECT * FROM movies WHERE Ott IN ('Netflix', 'Hotstar');

Output 2 :

```
mysql> SELECT * FROM movies WHERE Ott IN ('Netflix', 'Hotstar');
+-----+-----+-----+-----+-----+-----+-----+
| M_id | movies_name | Male_Lead | Female_Lead | Director | Music | Ott |
+-----+-----+-----+-----+-----+-----+-----+
| 102 | Premalu | Naslen | Mamitha | Girish A D | Vishnu Vijay | Hotstar |
| 101 | Dude | Pradeep Ranganathan | Mamitha | Keerthiswaran | Abhyankar | Netflix |
+-----+-----+-----+-----+-----+-----+-----+
2 rows in set (0.01 sec)
```

Query 3

SELECT COUNT(*) AS Total_Movies FROM movies;

Output 3 :

```
mysql> SELECT COUNT(*) AS Total_Movies FROM movies;
+-----+
| Total_Movies |
+-----+
| 4 |
+-----+
1 row in set (0.01 sec)
```

Query 4:

SELECT MAX(M_id) AS Highest_ID FROM movies;

Output 4 :

```
mysql> SELECT MAX(M_id) AS Highest_ID FROM movies;
+-----+
| Highest_ID |
+-----+
| 104 |
+-----+
1 row in set (0.01 sec)
```

Query 5

SELECT MIN(M_id) AS Lowest_ID FROM movies;

Output 5 :

```
mysql> SELECT MIN(M_id) AS Lowest_ID FROM movies;
+-----+
| Lowest_ID |
+-----+
|         101 |
+-----+
1 row in set (0.00 sec)
```

Query 6 :

SELECT AVG(M_id) AS Average_ID FROM movies;

Output 6 :

```
mysql> SELECT AVG(M_id) AS Average_ID FROM movies;
+-----+
| Average_ID |
+-----+
|    102.5000 |
+-----+
1 row in set (0.02 sec)
```

RESULT:

Thus, the records from the movies table were successfully displayed using the SELECT commands with BETWEEN, IN and Aggregate functions.