

EXP: 18

HIGH LEVEL LANGUAGE EXTENSION WITH CURSORS

AIM:

To implement **Cursors** using a program in MySQL.

PROCEDURE:

Step 1: Select the database containing the movies table.

Step 2: Declare a cursor using the movies table.

Step 3: Declare variables to store movie details.

Step 4: Open the cursor.

Step 5: Fetch movie records from the cursor.

Step 6: Display the fetched movie details.

Step 7: Close the cursor.

Step 8: Execute the cursor program and verify the output.

SYNTAX

Query 1

DELIMITER \$\$

```
CREATE PROCEDURE movie_cursor() BEGIN DECLARE done INT DEFAULT 0; DECLARE
mname VARCHAR(50); DECLARE cur CURSOR FOR SELECT movies_name FROM
movies; DECLARE CONTINUE HANDLER FOR NOT FOUND SET done=1; OPEN cur;
read_loop: LOOP FETCH cur INTO mname; IF done THEN LEAVE read_loop; END IF;
SELECT mname; END LOOP; CLOSE cur; END$$
```

Output

```
mysql> DELIMITER $$
mysql> CREATE PROCEDURE movie_cursor() BEGIN DECLARE done INT DEFAULT 0; DECLARE mname VARCHAR(50); DECLARE cur CURSOR FOR SELECT movies_name FROM movies; D
ECLARE CONTINUE HANDLER FOR NOT FOUND SET done=1; OPEN cur; read_loop: LOOP FETCH cur INTO mname; IF done THEN LEAVE read_loop; END IF; SELECT mname; END LO
OP; CLOSE cur; END$$
Query OK, 0 rows affected (0.02 sec)
```

Query 2

CALL movie_cursor();

Output

```
mysql> CALL movie_cursor();
+-----+
| mname |
+-----+
| Dude  |
+-----+
1 row in set (0.01 sec)

+-----+
| mname |
+-----+
| Premalu |
+-----+
1 row in set (0.02 sec)

+-----+
| mname |
+-----+
| OG    |
+-----+
1 row in set (0.02 sec)

+-----+
| mname |
+-----+
| Petta |
+-----+
1 row in set (0.02 sec)

+-----+
| mname |
+-----+
| Coolie |
+-----+
```

Result:

Thus, the cursor program was successfully created and executed using MySQL.