

BUREAU OF INDIAN STANDARDS

DRAFT FOR COMMENTS ONLY

(Not to be reproduced without permission of BIS or used as an Indian Standard)

DRAFT AMENDEMENT NO. 1 July 2026

TO

IS 10245 (Part 3): 2025

Respiratory Protective Devices — Part 3: Fresh Air Hose
and Compressed Air Line Breathing Apparatus

(Second Revision)

ICS 13.340.30

Occupational Safety and Health Sectional Committee,
CHD 08

Last Date for Comments : **As per the covering letter**

[Page 2, Clause 5.10.3] — Substitute the following for the existing:

‘Wherever the manufacturer designs the apparatus to be used in applications with a high flammability risk, the exposed components, including the facepiece, half mask or hood (where applicable), demand valve, medium-pressure connecting tube, compressed air tube, breathing hose, facepiece connector and waist belt or body harness shall be tested in accordance with (F-2). None of the exposed components shall continue to burn for more than 5s after removal from the test flame.

Where the facepiece complies with IS 14166 or the half mask complies with IS 14746, the flammability test specified in this clause need not be repeated for the facepiece or half mask, provided that compliance with the respective standard is demonstrated.’

[Page 6, Clause 8.2.2] — Substitute the following for the existing:

‘A minimum air supply shall be specified by the manufacturer and when determined in accordance with IS 17274 (Part 1) at the stated flow (which shall not be less than 120 l/min) the inward leakage of the external atmosphere into the hood or blouse shall not exceed a value of 0.1 percent for any one of test subjects.’

[Page 8, Clause 8.11.2] — Insert the following after c):

‘d) For hoses meeting the requirements of 8.10.7 above the words 'heat resistant' (for Type 3 only).’

(CHD 8)