

Expt No.: _____

Page No.: _____

1. Initialise a new git repository in a directory
Create a new file and add it to the staging
Area & Commit the changes with Application
Commit Message

step 1 = Mkdir your project name
cd

step 2 = git init

step 3 = touch file-name

step 4 = git status

step 5 = git add.

step 6 = git commit -m "message"

Lecturer's Signature

```
BKIT@DESKTOP-HRVDLVT MINGW64 ~  
$ cd program001
```

```
BKIT@DESKTOP-HRVDLVT MINGW64 ~/program001  
$ git init  
Initialized empty Git repository in C:/Users/BKIT/program001/.git/
```

```
BKIT@DESKTOP-HRVDLVT MINGW64 ~/program001 (master)  
$ touch lab.txt
```

```
BKIT@DESKTOP-HRVDLVT MINGW64 ~/program001 (master)  
$ git status  
On branch master
```

No commits yet

```
Untracked files:  
  (use "git add <file>..." to include in what will be committed)  
    lab.txt
```

nothing added to commit but untracked files present (use "git add" to track)

```
BKIT@DESKTOP-HRVDLVT MINGW64 ~/program001 (master)  
$ git add .
```

```
BKIT@DESKTOP-HRVDLVT MINGW64 ~/program001 (master)  
$ git commit -m "hello"  
[master (root-commit) 22db6cf] hello  
1 file changed, 0 insertions(+), 0 deletions(-)  
create mode 100644 lab.txt
```

```
BKIT@DESKTOP-HRVDLVT MINGW64 ~/program001 (master)  
$
```


24 Create a new branch named "Feature-branch".
Switch to the master branch ~~for~~ merge the
"feature-branch" into master.

step 1 = git checkout -b branch name

step 2 = git checkout -b feature-branch

step 3 = Touch file name (git.txt)

step 4 = git add.

step 5 = git commit -m "Hello"

step 6 = git checkout master

step 7 = git merge feature branch

Untitled - Notepad
File Edit Format View Help

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/program-01 (master)
$ git checkout -b cyber
Switched to a new branch 'cyber'
```

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/program-01 (cyber)
$ touch new file
```

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/program-01 (cyber)
$ git status
On branch cyber
Untracked files:
  (use "git add <file>..." to include in what will be committed)
    file
    new
```

nothing added to commit but untracked files present (use "git add" to track)

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/program-01 (cyber)
$ git add .
```

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/program-01 (cyber)
$ git commit -m "hello"
[cyber f70735f] hello
2 files changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file
create mode 100644 new
```

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/program-01 (cyber)
$ git checkout master
Switched to branch 'master'
```

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/program-01 (master)
$ git merge cyber
Updating cf9a5f1..f70735f
Fast-forward
 file | 0
 new  | 0
2 files changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file
create mode 100644 new
```


3 write the command stash your changes
switch branches, and then apply the stash changes

step 1 = mkdir repo-name

step 2 = cd repo-name

step 3 = git init

step 4 = Echo "adding file" > cyber.txt

step 5 = git status

step 6 = git add.

step 7 = git commit -m "message"

step 8 = Echo "adding content to the file" > cyber.txt

step 9 = git stash

step 10 = git stash list
stash @ <0> -> out

step 11 = git checkout -b CSE

Untitled - Notepad

File Edit Format View Help

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~ (master)
```

```
$ mkdir pp3
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~ (master)
```

```
$ cd pp3
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git init
```

```
Initialized empty Git repository in C:/Users/BKIT/pp3/.git/
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ echo "adding file" >cyber.txt
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git status
```

```
On branch master
```

```
No commits yet
```

```
Untracked files:
```

```
(use "git add <file>..." to include in what will be committed)
cyber.txt
```

```
nothing added to commit but untracked files present (use "git add" to track)
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git add .
```

```
warning: in the working copy of 'cyber.txt', LF will be replaced by CRLF the next time Git touches it
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git commit -m "hello"
```

```
[master (root-commit) 328bf38] hello
```

```
1 file changed, 1 insertion(+)
```

```
create mode 100644 cyber.txt
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ echo "adding content to the file" >cyber.txt
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git stash
```

```
warning: in the working copy of 'cyber.txt', LF will be replaced by CRLF the next time Git touches it
Saved working directory and index state WIP on master: 328bf38 hello
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git stash list
```

```
stash@{0}: WIP on master: 328bf38 hello
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ echo "creating new branch with file name lab" >lab.txt
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git status
```


step 12: Echo "creating new branch with file name
lab" > lab.txt

step 13: git status

step 14: git add.

step 15: git commit -m "created a new branch"

step 16: Echo "listing lab program" > lab.txt

step 17: git stash

step 18: git stash list

Untitled - Notepad

File Edit Format View Help

```
$ git commit -m "hello"
```

```
[master (root-commit) 328bf38] hello
```

```
1 file changed, 1 insertion(+)
```

```
create mode 100644 cyber.txt
```

```
BK1T@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ echo "adding content to the file" >cyber.txt
```

```
BK1T@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git stash
```

```
warning: in the working copy of 'cyber.txt', LF will be replaced by CRLF the next time Git touches it
```

```
Saved working directory and index state WIP on master: 328bf38 hello
```

```
BK1T@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)|
```

```
$ git stash list
```

```
stash@{0}: WIP on master: 328bf38 hello
```

```
BK1T@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ echo "creating new branch with file name lab" >lab.txt
```

```
BK1T@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git status
```

```
On branch master
```

```
Untracked files:
```

```
(use "git add <file>..." to include in what will be committed)
```

```
lab.txt
```

```
nothing added to commit but untracked files present (use "git add" to track)
```

```
BK1T@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git add .
```

```
warning: in the working copy of 'lab.txt', LF will be replaced by CRLF the next time Git touches it
```

```
BK1T@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git commit -m "created a new branch"
```

```
[master 6c35d44] created a new branch
```

```
1 file changed, 1 insertion(+)
```

```
create mode 100644 lab.txt
```

```
BK1T@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ echo "listing lab program" >lab.txt
```

```
BK1T@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git stash
```

```
warning: in the working copy of 'lab.txt', LF will be replaced by CRLF the next time Git touches it
```

```
Saved working directory and index state WIP on master: 6c35d44 created a new branch
```

```
BK1T@DESKTOP-HN3G6DF MINGW64 ~/pp3 (master)
```

```
$ git stash list
```

```
stash@{0}: WIP on master: 6c35d44 created a new branch
```

```
stash@{1}: WIP on master: 328bf38 hello
```


4> clone a remote git repository to your local machine

step 1: cd c:

Step 2: ls

step 3: MKDIR DEV

step 4: ls

step 5: cd DEV

step 6: ls

step 7: git clone < url >

step 8: ls

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~ (master)
$ mkdir pp4
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~ (master)
$ cd pp4
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp4 (master)
$ git init
Initialized empty Git repository in C:/Users/BKIT/pp4/.git/
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/pp4 (master)
$ git clone https://github.com/rohinimudhale/pp4.git
Cloning into 'pp4'...
remote: Enumerating objects: 6, done.
remote: Counting objects: 100% (6/6), done.
remote: Compressing objects: 100% (3/3), done.
remote: Total 6 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Receiving objects: 100% (6/6), done.
```


5> fetch the latest changes from a remote repository and rebase your local branch onto the updated remote branch

step 1 :- cd c:

step 2 :- git clone <link>

step 3 :- git status

step 4 :- git branch

step 5 :- git branch -r

step 6 :- git detach

step 7 :- git checkout -b

step 8 :- git checkout main

step 9 :- touch git-fetch.txt

step 10 :- git add.

step 11 :- git status

step 12 :- git touch g-fetch 1.txt

```
bkit@DESKTOP-HVDJQBH MINGW64 ~ (master)
$ cd c:
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c
$ git clone https://github.com/ambikanelwade/pro5.git
Cloning into 'pro5'...
remote: Enumerating objects: 6, done.
remote: Counting objects: 100% (6/6), done.
remote: Compressing objects: 100% (3/3), done.
remote: Total 6 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Receiving objects: 100% (6/6), done.
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c
$ cd pro5
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git status
On branch main
Your branch is up to date with 'origin/main'.
```

```
nothing to commit, working tree clean
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git branch
* main
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git branch -r
origin/HEAD -> origin/main
origin/main
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git fetch
$ git checkout -b branch-name
Switched to a new branch 'branch-name'
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (branch-name)
$ git checkout main
Switched to branch 'main'
Your branch is up to date with 'origin/main'.
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ touch fetch.txt
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git add .
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git status
On branch main
Your branch is up to date with 'origin/main'.
```

```
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    new file:   fetch.txt
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ touch fetch1.txt
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git add .
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git status
On branch main
Your branch is up to date with 'origin/main'.
```


Step 13 :- git add.

Step 14 :- git commit -m "adding git fetch.txt"

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git status
On branch main
Your branch is up to date with 'origin/main'.
```

```
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    new file:   fetch.txt
    new file:   fetch1.txt
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git commit -m "adding fetch.txt"
[main 32293ee] adding fetch.txt
 2 files changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 fetch.txt
 create mode 100644 fetch1.txt
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git checkout fetch-branch
error: pathspec 'fetch-branch' did not match any file(s) known to git
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git rebase main
Current branch main is up to date.
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (main)
$ git checkout branch-name
Switched to branch 'branch-name'
```

```
bkit@DESKTOP-HVDJQBH MINGW64 /c/pro5 (branch-name)
$ git rebase main
Successfully rebased and updated refs/heads/branch-name.
```


6. Write a Command to Merge "Feature-branch" into master while providing a custom commit Message for the merge.

step 1: mkdir program

step 2: cd program

step 3: git init

step 4: touch demo.txt

step 5: git status

step 6: git add.

step 7: git commit -m "adding a file demo"

step 8: git checkout -b new + - branch

step 9: touch cyber.txt

step 10: git status

step 11: git add.

step 12: git commit -m "adding a file cyber"

File Edit Format View Help

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~ (master)
$ mkdir tag-pro1
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~ (master)
$ cd tag-pro1
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
$ git init
Initialized empty Git repository in C:/Users/BKIT/tag-pro1/.git/
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
$ touch test.txt
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
$ git status
On branch master
```

No commits yet

Untracked files:

(use "git add <file>..." to include in what will be committed)

test.txt

nothing added to commit but untracked files present (use "git add" to track)

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
$ git add .
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
$ git commit -m "hello"
[master (root-commit) 0f788c8] hello
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 test.txt
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
$ git tag v1.0
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
$ git tag -a v2.0 -m "tags"
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
$ git show
commit 0f788c88a5c01ab464f22a317e97a606bf0d01c3 (HEAD -> master, tag: v2.0, tag: v1.0)
Author: santoshi <madpatisantoshi19@gmail.com>
Date: Wed Dec 31 00:59:33 2025 -0800
```

hello

```
diff --git a/test.txt b/test.txt
new file mode 100644
index 0000000..e69de29
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
```


step 13: git checkout master

step 14: git merge new-branch -m "hello"

nothing added to commit but untracked files present (use "git add" to track)

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/por6 (master)
$ git add .
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/por6 (master)
$ git commit -m "adding a file demo"
[master (root-commit) 1d1282a] adding a file demo
2 files changed, 0 insertions(+), 0 deletions(-)
create mode 100644 demo
create mode 100644 txt
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/por6 (master)
$ git checkout -b new-branch
Switched to a new branch 'new-branch'
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/por6 (new-branch)
$ touch cyber.txt
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/por6 (new-branch)
$ git status
On branch new-branch
Untracked files:
  (use "git add <file>..." to include in what will be committed)
    cyber.txt
```

nothing added to commit but untracked files present (use "git add" to track)

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/por6 (new-branch)
$ git add .
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/por6 (new-branch)
$ git commit -m "adding a file cyber"
[new-branch 2b3d842] adding a file cyber
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 cyber.txt
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/por6 (new-branch)
$ git checkout master
Switched to branch 'master'
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/por6 (master)
$ git merge new-branch -m "hello"
Updating 1d1282a..2b3d842
Fast-forward (no commit created; -m option ignored)
 cyber.txt | 0
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 cyber.txt
```


Write a command to create a light weight git tag named -v-o for a commit your local repository

Step 1: `mkdir repo-name`

Step 2: `cd repo-name`

Step 3: `git init`

Step 4: `touch test.txt`

Step 5: `git status`

Step 6: `git add.`

Step 7: `git commit -m "hello"`

Step 8: `git tag v1.0`

Step 9: `git tag -a v2.0 -m "tags"`

Step 10: `git show`

Step 11: `git remove -v`

```
BKITE@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
```

```
$ git commit -m "hello"
```

```
[master (root-commit) 0f788c8] hello
```

```
1 file changed, 0 insertions(+), 0 deletions(-)  
create mode 100644 test.txt
```

```
BKITE@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
```

```
$ git tag v1.0
```

```
BKITE@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
```

```
$ git tag -a v2.0 -m "tags"
```

```
BKITE@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
```

```
$ git show
```

```
commit 0f788c88a5c01ab464f22a317e97a606bf0d01c3 (HEAD -> master, tag: v2.0, tag: v1.0)
```

```
Author: santoshi <madpatisantoshi19@gmail.com>
```

```
Date: Wed Dec 31 00:59:33 2025 -0800
```

```
hello
```

```
diff --git a/test.txt b/test.txt
```

```
new file mode 100644
```

```
index 0000000..e69de29
```

```
BKITE@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
```

```
$ git remote -v
```

```
BKITE@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
```

```
$ git remote add origin https://github.com/rohiniimudhale/tag-pro1.git
```

```
BKITE@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
```

```
$ git push -u origin
```

```
fatal: The current branch master has no upstream branch.
```

```
To push the current branch and set the remote as upstream, use
```

```
git push --set-upstream origin master
```

To have this happen automatically for branches without a tracking upstream, see 'push.autoSetupRemote' in 'git help config'.

```
BKITE@DESKTOP-HN3G6DF MINGW64 ~/tag-pro1 (master)
```

```
$ git push -u origin v1.0
```

```
Enumerating objects: 3, done.
```

```
Counting objects: 100% (3/3), done.
```

```
Writing objects: 100% (3/3), 206 bytes | 206.00 KiB/s, done.
```

```
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
```

```
To https://github.com/rohiniimudhale/tag-pro1.git
```

```
* [new tag] v1.0 -> v1.0
```


step 12: `git remote add origin 2017`

step 13: `git push -m origin v2.0`

Write a command to cherry-pick a range of commit from "Source-branch" to current branch

Step 1: `Mkdir repo-name`

Step 2: `Cd repo-name`

Step 3: `git init`

Step 4: `touch file.txt`

Step 5: `git add.`

Step 6: `git commit -m "message"`

Step 7: `git checkout -b sub-branch`

Step 8: `touch file.txt`

Step 9: `git add.`

Step 10: `git commit -m "message"`

Step 11: `touch file2.txt`

Step 12: `git add.`


```
bkit@DESKTOP-2A154NM MINGW64 ~ (program002)
$ mkdir program08
```

```
bkit@DESKTOP-2A154NM MINGW64 ~ (program002)
$ cd program08
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (program002)
$ git init
Initialized empty Git repository in C:/Users/bkit/program08/.git/
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (master)
$ touch file.txt
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (master)
$ git add .
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (master)
$ git commit -m "hello"
[master (root-commit) bf175eb] hello
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file.txt
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (master)
$ git checkout -b sub-branch
Switched to a new branch 'sub-branch'
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ touch file1.txt
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ git add .
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ git commit -m "adding file"
[sub-branch 96b70f3] adding file
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file1.txt
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ touch file2.txt
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ git add .
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ git commit -m "adding the txt file"
[sub-branch ca0d7a9] adding the txt file
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file2.txt
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
```

step 13: git commit -m "message"

step 14: git checkout master

step 15: git cherry-pick <011> check master

step 16: git cherry-pick


```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ git commit -m "adding file"
[sub-branch 96b70f3] adding file
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file1.txt
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ touch file2.txt
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ git add .
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ git commit -m "adding the txt file"
[sub-branch ca0d7a9] adding the txt file
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file2.txt
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ git log
commit ca0d7a943ff048de89bd7da56e04b1db008b6610 (HEAD -> sub-branch)
Author: sidram iante <youexample.com>
Date: Wed Dec 31 13:59:55 2025 +0530
```

adding the txt file

```
commit 96b70f3b800315c1e5430cf660022f4a7308aa27
Author: sidram iante <youexample.com>
Date: Wed Dec 31 13:57:33 2025 +0530
```

adding file

```
commit bf175ebb931e8c7cd4761a2bb9553491a3db1cdb (master)
Author: sidram iante <youexample.com>
Date: Wed Dec 31 13:54:26 2025 +0530
```

hello

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (sub-branch)
$ git checkout master
Switched to branch 'master'
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (master)
$ git cherry-pick ca0d7a943ff048de89bd7da56e04b1db008b6610
[master 4cf9660] adding the txt file
Date: Wed Dec 31 13:59:55 2025 +0530
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file2.txt
```

```
bkit@DESKTOP-2A154NM MINGW64 ~/program08 (master)
```

Give a commit ID how could you use the git ID view the details of the specific commit including the author data and commit message

Step 1: mkdir git show 1

Step 2: cd git - show 1

Step 3: git init

Step 4: touch show.txt

Step 5: git status

Step 6: git add.

Step 7: git commit -m "showing commit id"

Step 8: touch show Second.txt

Step 9: git status

Step 10: git add.

File Edit Format View Help

\$ mkdir git-status

BKIT@DESKTOP-10H8VAK MINGW64 ~ (master)

\$ cd git-status

BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)

\$ git init

Initialized empty Git repository in C:/Users/BKIT/git-status/.git/

BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)

\$ touch show.txt

BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)

\$ git status

On branch master

No commits yet

Untracked files:

(use "git add <file>..." to include in what will be committed)
show.txt

nothing added to commit but untracked files present (use "git add" to track)

BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)

\$ git add .

BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)

\$ git commit -m "showing commit id"

[master (root-commit) 0e3c5a7] showing commit id
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 show.txt

BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)

\$ touch showsecond.txt

BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)

\$ git status

On branch master

Untracked files:

(use "git add <file>..." to include in what will be committed)
showsecond.txt

nothing added to commit but untracked files present (use "git add" to track)

BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)

\$ git add .

Step 11: git commit -m "Showing second commit rd"

Step 12: git log

Step 13: git show

nothing added to commit but untracked files present (use "git add" to track)

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)
$ git add ,
```

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)
$ git commit -m "showing second commit id"
[master fca984b] showing second commit id
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 showsecond.txt
```

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)
$ git log
commit fca984ba3f86a8c6516dd96dad3f697cbe4f3211 (HEAD -> master)
Author: arati <arati.birado585@gmail.com>
Date: Wed Dec 31 00:35:18 2025 -0800
```

showing second commit id

```
commit 0e3c5a7c2f7b6b00cc31bda565c729f91164b36a
Author: arati <arati.birado585@gmail.com>
Date: Wed Dec 31 00:33:33 2025 -0800
```

showing commit id

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)
$ git add .
```

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)
$ git show fca984ba3f86a8c6516dd96dad3f697cbe4f3211
commit fca984ba3f86a8c6516dd96dad3f697cbe4f3211 (HEAD -> master)
Author: arati <arati.birado585@gmail.com>
Date: Wed Dec 31 00:35:18 2025 -0800
```

showing second commit id

```
diff --git a/showsecond.txt b/showsecond.txt
new file mode 100644
index 0000000..e69de29
```

```
BKIT@DESKTOP-10H8VAK MINGW64 ~/git-status (master)
$
```

10 Write the command to list all commits made by author "John Doe" b/w 2022-01-01 & 2022-12-31

Step 1: git clone <code>

Step 2: git program-10

Step 3: git status

Step 4: git config user.name "John Doe"

Step 5: touch file.txt

Step 6: git status

Step 7: git add.

Step 8: git commit -m "Replacing the user name"

Step 9: git checkout -b new-branch

Step 10: git log

Step 11: git status

Step 12: git log


```
BKIT@DESKTOP-HN3G6DF MINGW64 ~ (master)
$ git clone https://github.com/rohinimudhale/program-10.git
Cloning into 'program-10'...
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Receiving objects: 100% (3/3), done.
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~ (master)
$ cd program-10
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/program-10 (main)
$ git status
On branch main
Your branch is up to date with 'origin/main'.
```

```
nothing to commit, working tree clean
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/program-10 (main)
$ git config user.name "john doe"
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/program-10 (main)
$ touch file.txt
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/program-10 (main)
$ git status
On branch main
Your branch is up to date with 'origin/main'.
```

```
Untracked files:
```

```
(use "git add <file>..." to include in what will be committed)
file.txt
```

```
nothing added to commit but untracked files present (use "git add" to track)
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/program-10 (main)
$ git add .
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/program-10 (main)
$ git commit -m "replasing the user name"
[main 9e5513f] replasing the user name
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file.txt
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/program-10 (main)
$ git checkout -b new-branch
Switched to a new branch 'new-branch'
```

```
BKIT@DESKTOP-HN3G6DF MINGW64 ~/program-10 (new-branch)
$ git log
commit 9e5513fdb4ac2a5a05535f4e60ce1877e5d41434 (HEAD -> new-branch, main)
Author: john doe <madpatisantrishi@gmail.com>
```

Write the Command and display the last five commits in the repository history

Step 1: `Mkdir git-log1`

Step 2: `cd git-log1`

Step 3: `git init`

Step 4: `touch file.txt`

Step 5: `git status`

Step 6: `git add.`

Step 7: `git commit -m "adding one commit"`

Step 8: `touch file2.txt`

Step 9: `git status`

Step 10: `git add.`

Step 11: `git commit -m "adding second commit"`


```

bkit@DESKTOP-083J958 MINGW64 ~ (master)
$ mkdir git-log1

bkit@DESKTOP-083J958 MINGW64 ~ (master)
$ cd git-log1

bkit@DESKTOP-083J958 MINGW64 ~/git-log1 (master)
$ git init
Initialized empty Git repository in C:/Users/bkit/git-log1/.git/

bkit@DESKTOP-083J958 MINGW64 ~/git-log1 (master)
$ touch file.txt

bkit@DESKTOP-083J958 MINGW64 ~/git-log1 (master)
$ git status
On branch master

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
  file.txt

nothing added to commit but untracked files present (use "git add" to track)

bkit@DESKTOP-083J958 MINGW64 ~/git-log1 (master)
$ git add .

bkit@DESKTOP-083J958 MINGW64 ~/git-log1 (master)
$ git commit -m "adding one commit"
[master (root-commit) 726dbae] adding one commit
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file.txt

bkit@DESKTOP-083J958 MINGW64 ~/git-log1 (master)
$ touch file2.txt

bkit@DESKTOP-083J958 MINGW64 ~/git-log1 (master)
$ git status
On branch master
Untracked files:
  (use "git add <file>..." to include in what will be committed)
  file2.txt

nothing added to commit but untracked files present (use "git add" to track)

bkit@DESKTOP-083J958 MINGW64 ~/git-log1 (master)
$ git add .

bkit@DESKTOP-083J958 MINGW64 ~/git-log1 (master)
$ git commit -m "adding second commit"
[master 92d529d] adding second commit
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file2.txt

bkit@DESKTOP-083J958 MINGW64 ~/git-log1 (master)
$ touch file3.txt

bkit@DESKTOP-083J958 MINGW64 ~/git-log1 (master)
$ git status

```

Step 12: touch File3.txt

Step 13: git status

Step 14: git add.

Step 15: git commit -m "adding third commit"

Step 16: touch file.txt

Step 17: git status

Step 18: git add.

Step 19: git commit -m "adding fourth commit"

Step 20: touch file5.txt

Step 21: git status

Step 22: git add.

Step 23: git commit -m "adding fifth commit"

Step 24: touch file 6.txt

Step 25: git status

bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
\$ git add .

bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
\$ git commit -m "adding fifth commit"
[master f67857a] adding fifth commit
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file5.txt

bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
\$ touch file6.txt

bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
\$ git status
On branch master
Untracked files:
 (use "git add <file>..." to include in what will be committed)
 file6.txt

nothing added to commit but untracked files present (use "git add" to track)

bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
\$ git add .

bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
\$ git commit -m "adding six commit"
[master 79bfbda] adding six commit
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file6.txt

bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
\$ git log -5
commit 79bfbda93d137675604c7789266de1b9e42257 (HEAD -> master)
Author: saraswati.rumma <rummasaru@gmail.com>
Date: Wed Dec 31 19:56:53 2025 +0800

adding six commit

commit f67857a5984cb24552603cb80d8810a36e79bc8a
Author: saraswati.rumma <rummasaru@gmail.com>
Date: Wed Dec 31 19:56:06 2025 +0800

adding fifth commit

commit d02c531fa718d1c4b139faff1aa9d270f2c188b3
Author: saraswati.rumma <rummasaru@gmail.com>
Date: Wed Dec 31 19:55:10 2025 +0800

adding fourth commit

commit 2e258e35127516c2146ca0c29d74a2438f1ad2f3
Author: saraswati.rumma <rummasaru@gmail.com>
Date: Wed Dec 31 19:54:18 2025 +0800

adding third commit

commit 92d529d1b37194e077976aeece2d5755ee78349d3
Author: saraswati.rumma <rummasaru@gmail.com>
Date: Wed Dec 31 19:53:22 2025 +0800

adding second commit

Step 26 : git add.

step 27: git commit -m "adding s1x
commit"

Step 28: git log -5


```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ git status
On branch master
Untracked files:
  (use "git add <file>..." to include in what will be committed)
        file3.txt
```

nothing added to commit but untracked files present (use "git add" to track)

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ git add .
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ git commit -m "adding third commit"
[master 2e258e3] adding third commit
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file3.txt
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ touch file4.txt
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ git status
On branch master
Untracked files:
  (use "git add <file>..." to include in what will be committed)
        file4.txt
```

nothing added to commit but untracked files present (use "git add" to track)

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ git add .
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ git commit -m "adding fourth commit"
[master d02c531] adding fourth commit
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file4.txt
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ touch file5.txt
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ git status
On branch master
Untracked files:
  (use "git add <file>..." to include in what will be committed)
        file5.txt
```

nothing added to commit but untracked files present (use "git add" to track)

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ git add .
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ git commit -m "adding fifth commit"
[master f67857a] adding fifth commit
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 file5.txt
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git-log1 (master)
$ touch file6.txt
```

Write the Command to undo the change introduced by the commit with the ID "abc 123"

Step 1: `mkdir git -- revert 2`

Step 2: `cd git -- revert 2`

Step 3: `git init`

Step 4: `touch file.txt`

Step 5: `git add.`

Step 6: `git commit -m "reverting the commit"`

Step 7: `git log -n 1`

Step 8: `git revert code -- no -- edit`


```
bkit@DESKTOP-083J9S8 MINGW64 ~ (master)
```

```
$ mkdir git--revert2
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~ (master)
```

```
$ cd git--revert2
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git--revert2 (master)
```

```
$ git init
```

```
Initialized empty Git repository in C:/Users/bkit/git--revert2/.git/
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git--revert2 (master)
```

```
$ touch file.txt
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git--revert2 (master)
```

```
$ git add .
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git--revert2 (master)
```

```
$ git commit -m "reverting the commits"
```

```
[master (root-commit) 6f3f91d] reverting the commits
```

```
1 file changed, 0 insertions(+), 0 deletions(-)
```

```
create mode 100644 file.txt
```

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git--revert2 (master)
```

```
$ git log -n1
```

```
commit 6f3f91ded8142f2833ae79b3d6636117aab7f5ff (HEAD -> master)
```

```
Author: saraskatirunna <runnasaru@gmail.com>
```

```
Date: Wed Dec 31 20:20:10 2025 -0800
```

reverting the commits

```
bkit@DESKTOP-083J9S8 MINGW64 ~/git--revert2 (master)
```

```
$ git revert 6f3f91ded8142f2833ae79b3d6636117aab7f5ff --no-edit
```

```
[master 2546f16] Revert "reverting the commits"
```

```
Date: Wed Dec 31 20:22:08 2025 -0800
```

```
1 file changed, 0 insertions(+), 0 deletions(-)
```

```
delete mode 100644 file.txt
```

```
|
```