Wrong the Same Way: Cross-Prompt Sharing Both Suppresses and Amplifies Reward Hacking in RLVR

Michael Li[*]
Carnegie Mellon University
ml7@andrew.cmu.edu

Rohan Pandey[*]
University of Washington
rpande@uw.edu

Ray Chen[*]
Independent
raychen256@gmail.com

Abstract

Reinforcement learning with verifiable rewards (RLVR) trains a model against a programmatic checker, and checkers sometimes accept wrong answers. Two accounts of what RL does with these false positives coexist: one finds that the rate of reward hacking is inherited from the base model, the other that RL amplifies it. We study the question in a small RLVR environment whose entire response distribution can be computed exactly, where we vary how many prompts accept the same wrong answer (its *universality*) while holding the verifier's error rate fixed. A shared-parameter policy pushes wrong answers that few prompts accept below the base rate and amplifies wrong answers that most prompts accept. The rise with universality holds at every learning rate under Adam, SGD and sampled GRPO; whether the low-universality end is suppressed or merely amplified less depends on the step size. Giving every prompt its own copy of the same network removes the dependence, so cross-prompt parameter sharing is the channel. A known decomposition of the learning dynamics explains why: a wrong answer is pushed up by every prompt that accepts it and pushed down, through the baseline, by every prompt that rejects it, each in proportion to the model's own probability of producing it there. The sign is therefore set neither by the verifier's error rate nor by universality alone, but by how much of the model's mass on a wrong answer sits on prompts that accept it: by whether the model is wrong the same way the verifier is. Controls with a frozen base model support this reading, and two verifier patches that look identical to a static audit differ by up to 38 points of true accuracy. We propose this alignment as the quantity to audit, and as a hypothesis for why earlier studies disagree.

1 Introduction

In reinforcement learning with verifiable rewards (RLVR), a response is rewarded when a programmatic checker accepts it [Shao et al., 2024, Guo et al., 2025]. Checkers are imperfect. Generative judges accept non-word symbols and generic reasoning openers [Zhao et al., 2026], test suites accept programs that pass only the visible tests [Khalifa et al., 2026], and outcome checkers reward a correct final answer reached by invalid reasoning [Yuan et al., 2026], one reason process supervision [Lightman et al., 2023] was proposed over outcome supervision [Cobbe et al., 2021]. Every such false positive is a response the policy can be paid for without being correct.

Two accounts of how RL interacts with these false positives coexist. In the first, RLVR is robust to them: verifier noise up to 15% leaves peak accuracy within two points of clean training [Plesner et al., 2026], noise rescales convergence time rather than the destination while the verifier's Youden index stays positive [Rad et al., 2026], and a preregistered comparison of leaky and hardened test suites found that the wrong programs a trained model emits were already emitted by the base model [Zhang,

[*]Equal contribution.

40th Conference on Neural Information Processing Systems (NeurIPS 2026). Workshop: Transitioning from Pre-Training to Post-Training.

2026]. In the second, exploitation is a first-order failure: RL amplifies hacking seeded by a trace of contamination [Khalifa et al., 2026], systematic verifier error produces delay, plateau or collapse [Egashira et al., 2026], models learn to game extensional verifiers [Helff et al., 2026], and production reward hacking generalizes into broader misalignment [MacDiarmid et al., 2025]. The studies behind the two accounts differ in many ways at once, so they do not say what decides the outcome.

Theory sides with the first account. At the KL-regularized optimum of the RLHF objective [Stiennon et al., 2020, Ouyang et al., 2022] the policy is $\pi^\star(y \mid x) \propto \pi_{\mathrm{ref}}(y \mid x)\, e^{r(x,y)/\beta}$, so within any reward level set the odds between responses are the reference model's [Korbak et al., 2022]. RLVR at its optimum is a filter on the accepted set: it changes how much mass the set receives, not what the set is made of, which is also why RLVR sharpens rather than expands a base model's abilities [Yue et al., 2025, Gai et al., 2025, Kruszewski et al., 2026, Dymetman, 2026]. For verifier false positives this predicts inheritance. Real training is not at that optimum: it takes first-order steps on a model whose parameters are shared across prompts, often with little or no KL term. We ask what happens to verifier false positives under that kind of training, and which of them get amplified.

We answer the question in a controlled environment, two-digit multiplication with a two-digit answer space, where the full response distribution of a small transformer can be enumerated exactly at every step. The verifier accepts the correct answer plus designated wrong strings, and we control how many prompts share the same wrong string, its universality, while the false-positive rate is held fixed. We compare the transformer against a policy with free parameters for every prompt, initialized to the identical distribution, and against independent copies of the transformer, one per prompt. Our contributions are as follows.

- **A two-sided effect of parameter sharing.** A shared-parameter policy suppresses idiosyncratic false positives and amplifies universal ones. The direction holds at every learning rate for three optimizers; the level depends on the step size. Removing sharing, with the architecture held fixed, removes the effect (Sections 6.3 and 6.4).
- **The quantity that decides the sign.** A known decomposition of the drift into a sum over prompts of reward-kernel covariances isolates a cross-prompt term that is zero without sharing. For a coherently represented wrong answer its sign is that of $u_{\mathrm{eff}} - \bar{V}$, where u_{eff} is the fraction of the policy's mass on the answer that sits on prompts which accept it and $\bar{V}$ is the policy's own pass rate. Frozen-base controls, which the accepted version of this paper read as evidence that sharing is insufficient, follow this prediction once read per universality value rather than through a fitted slope (Sections 4 and 6.5).
- **A change of audit target.** Two verifier patches with identical static audit value differ by up to 38 points of true accuracy over 10 seeds, paired within seed, while the verifier's own reward stays at 0.973 or above (Section 6.7). The number to audit is whether the accepted wrong answers line up with the ones the model already produces across prompts.

2 Background and related work

RLVR as filtering. The KL-regularized optimum as an exponential tilt of the reference model is well established [Korbak et al., 2022, Gai et al., 2025, Kruszewski et al., 2026, Dymetman, 2026, Lochab et al., 2026, Rafailov et al., 2023] and explains why RLVR sharpens rather than expands capability [Yue et al., 2025]. That literature reads the invariance as a statement about diversity among correct answers; we read it as a constraint on the composition of the accepted set and use it as our null model. The rich-get-richer behavior of softmax policy gradient among tied responses [Mei et al., 2020, Lochab et al., 2026] is a second known effect that we use as a control.

Verifier error. Wang et al. [2020] and Cai et al. [2026] show that correcting for reward noise helps, not that uncorrected training is robust. Plesner et al. [2026] measure noise tolerance directly, and Rad et al. [2026] map a phase transition in the Youden index. Spurious rewards occasionally help particular models [Shao et al., 2026]. Audits of verifier false positives [Zhao et al., 2026, Huang et al., 2026, Xu et al., 2025, Yuan et al., 2026] report gross error rates and leave the alignment of the errors across prompts unmeasured.

Systematic error and amplification. Egashira et al. [2026] established the premise we build on: the outcome depends on the "specific pattern of introduced errors" rather than the blanket error rate.

Khalifa et al. [2026] showed that about 1% of hacking demonstrations in supervised fine-tuning is enough to prime hacking under RLVR, and Zhao et al. [2025] that RL post-training amplifies behaviors already present in pretraining; Zhang [2026] reports inheritance while Khalifa et al. [2026] and Nishimura-Gasparian et al. [2026] report amplification and specification gaming. We isolate one variable, the number of prompts that share an accepted wrong answer, sweep it at a fixed error rate, and identify the quantity through which it acts. Unlike work on what corrupted rewards can do in principle [Everitt et al., 2017, Skalse et al., 2022, Gao et al., 2023], we ask how standard optimizers interact with them; studies of group-relative advantage estimators [Yang et al., 2026, Zeng et al., 2026] are orthogonal, since our effect persists under exact-expectation gradients.

Learning dynamics and coherent gradients. The decomposition we use in Section 4, which writes the change in one example's log-probability as a sum of empirical tangent-kernel terms over all training examples, was introduced for supervised and preference fine-tuning by Ren and Sutherland [2025] and extended to RL post-training by Tomihari [2026]; that gradients from examples that agree reinforce each other is the coherent-gradients hypothesis of Chatterjee [2020]. We do not claim the decomposition. What is specific to RLVR, and what we use, is the push-down: a rewarded response on one prompt is penalized through the baseline on every prompt that rejects it, so the mechanism that amplifies a widely accepted wrong answer suppresses a narrowly accepted one.

3 Setup: RLVR with an exploitable verifier

Let $\mathcal{X}$ be a finite prompt set with $|\mathcal{X}| = N$ and the uniform distribution, and let $\mathcal{Y}$ be a finite response space. A response is correct if $c(x, y) = 1$; we write g_x for the correct response, which is unique in our setting. The deployed verifier returns $r(x, y) \in \{0, 1\}$ with $r \geq c$, so it has no false negatives. $\mathcal{A}(x) = \{y : r(x, y) = 1\}$ is the accepted set and $\mathcal{H}(x) = \{y : r(x, y) = 1,\, c(x, y) = 0\}$ its false-positive part, the *leaks*. RLVR maximizes $J(\theta) = \mathbb{E}_x\, \mathbb{E}_{y\sim\pi_\theta(\cdot|x)}[r(x, y)]$.

Definition 1 (Hack fraction)**.** The hack fraction is $\rho(\pi) = \frac{1}{N}\sum_x \pi(\mathcal{H}(x) \mid x) \,/\, \pi(\mathcal{A}(x) \mid x)$, the probability that a rewarded response is a false positive, averaged over prompts. We also track the prompt-averaged log-odds $\Lambda(\pi) = \frac{1}{N}\sum_x \log\big[\pi(\mathcal{H}(x) \mid x) \,/\, \pi(g_x \mid x)\big]$. Both are finite under any softmax parameterization.

Definition 2 (Leak universality)**.** For a response h, let $m(h) = |\{x : h \in \mathcal{H}(x)\}|$ and $u(h) = m(h)/N$. A leak with $u = 1$ is accepted on every prompt. A leak with $u = 1/N$ is accepted on one prompt only, which we call idiosyncratic.

3.1 The filter baseline

Proposition 1 (RLVR is a filter; known)**.** *Assume $r \geq c$ and let $\pi_{\mathrm{ref}}(\cdot \mid x)$ have full support. Let $\pi^\star_\beta = \arg\max_\pi J(\pi) - \beta\, \mathbb{E}_x \mathrm{KL}(\pi(\cdot \mid x)\|\pi_{\mathrm{ref}}(\cdot \mid x))$. Then $\pi^\star_\beta(y \mid x) \propto \pi_{\mathrm{ref}}(y \mid x)\, e^{r(x,y)/\beta}$, so for any y, y' with $r(x, y) = r(x, y')$ the odds are unchanged. Consequently $\rho(\pi^\star_\beta) = \rho(\pi_{\mathrm{ref}})$ and $\Lambda(\pi^\star_\beta) = \Lambda(\pi_{\mathrm{ref}})$ for every $\beta > 0$. The same invariance holds at every step of any multiplicative update $\pi_{t+1}(\cdot \mid x) \propto \pi_t(\cdot \mid x) \exp(\eta f(r(x, \cdot)))$.*

The closed form is the Gibbs variational principle, standard in RL [Peters et al., 2010] and in the LLM setting [Korbak et al., 2022, Kruszewski et al., 2026, Dymetman, 2026]; we restate it because it is the baseline every departure is measured against. As $\beta \to 0$, $\pi^\star_\beta \to \pi_{\mathrm{ref}}(\cdot \mid \mathcal{A}(x))$: the whole regularization path is the reference model conditioned on acceptance, so nothing inside the accepted set can move.

Why we average per prompt. The pooled quantity $\sum_x \pi(\mathcal{H}(x) \mid x) / \sum_x \pi(\mathcal{A}(x) \mid x)$ is a weighted average of the invariant per-prompt ratios with weights that RLVR moves, so it drifts under pure filtering, by +0.057 in our environment under exact mirror descent, while ρ and Λ do not (Appendix A). Prior work usually reports pooled shares; we report per-prompt statistics throughout.

4 Why first-order training departs from the filter

In practice RLVR takes first-order steps on a shared-parameter model, often with a small or absent KL term. The following decomposition, due to Ren and Sutherland [2025] for fine-tuning and Tomihari [2026] for RL post-training, describes the resulting drift exactly.

Lemma 1 (Drift decomposition; known)**.** *Under exact-gradient flow $\dot{\theta} = \nabla_\theta J(\theta)$,*

$$\frac{d}{dt} \log \pi_\theta(y \mid x) = \frac{1}{N} \sum_{x' \in \mathcal{X}} \mathrm{Cov}_{y' \sim \pi_\theta(\cdot \mid x')} \Big[r(x', y'),\ K_\theta\big((x, y), (x', y')\big) \Big], \tag{1}$$

where $K_\theta((x, y), (x', y')) = \langle \nabla_\theta \log \pi_\theta(y \mid x), \nabla_\theta \log \pi_\theta(y' \mid x') \rangle$ is the empirical tangent kernel of the log-policy (Appendix A).

The log-probability of a response on one prompt is moved by the dynamics on every prompt, in proportion to how strongly reward covaries with tangent similarity there. The $x' = x$ term is the ordinary within-prompt update, present for any policy; the $x' \neq x$ terms are the contribution of parameter sharing. Our experiments mostly use Adam [Kingma and Ba, 2015], whose momentum makes the update history-dependent, so the identity does not apply verbatim; the support argument below does, because Adam's state is per-coordinate, and we also report plain SGD. Our kernel is the finite-width empirical kernel, not the infinite-width limit of Jacot et al. [2018].

Corollary 1 (Per-prompt parameters cannot see universality)**.** *If $\theta = (\theta_x)_{x \in \mathcal{X}}$ and $\pi_\theta(\cdot \mid x)$ depends on θ_x only, then $K_\theta((x, y), (x', y')) = 0$ for $x' \neq x$,* (1) *collapses to its $x' = x$ term, and the trajectory of each block θ_x is an autonomous ODE that depends on the verifier only through $r(x, \cdot)$. Such a policy can depend on m only through what it inherited at initialization.*

This makes a per-prompt policy a control rather than a baseline. It does not sit *on* the filter baseline: for two equally rewarded responses at one prompt, gradient flow gives $\frac{d}{dt} \log(\pi_1/\pi_2) = \frac{1}{N}(\pi_1 - \pi_2)(1 - V(x))$, the rich-get-richer behavior of softmax policy gradient [Mei et al., 2020, Lochab et al., 2026]. That drift is prompt-local and blind to u, which is what a control needs.

The quantity that matters. Equation (1) does not isolate $u = m/N$. Specializing it to a leak h accepted on the set U, the acceptance fraction that appears is kernel- and policy-weighted:

$$u_{\mathrm{eff}}(x, h) \ = \ \Big(\textstyle\sum_{x' \in U} w_{x'} \Big) \Big/ \Big(\textstyle\sum_{x'} w_{x'} \Big), \qquad w_{x'} = K_{\theta, xx'}\, \pi_\theta(h \mid x'), \tag{2}$$

where $K_{\theta, xx'} = K_\theta((x, h), (x', h))$ couples h at x to the same string at x'. The weights can be negative in general (13% of the entries are at our base models; Appendix C); when they are positive, u_{eff} is the share of the model's kernel-weighted mass on h that sits on prompts which accept h. The raw fraction m/N is recovered only when the kernel entries and the probabilities are the same at every prompt.

Definition 3 (Coherent kernel model)**.** Write $K_\theta = K_\theta^{\mathrm{coh}} + R$ with $K_\theta^{\mathrm{coh}}((x, h), (x', y')) = \kappa_{xx'}\, \mathbf{1}[y' = h] + a(x, x') + b(x, x', y')$, where a does not depend on y' and b does not depend on h. The a and b terms drop out of (1) and of the within-prompt log-odds respectively (Appendix A), leaving the same-string entries $\kappa_{xx'}$ and a residual R that we do not bound. Coherence is a property of how a response is computed, not of string identity: a wrong answer produced by prompt-independent machinery is coherent, while correct answers that coincide on two prompts need not be.

Proposition 2 (Universality threshold)**.** *Let h be accepted on U, let the correct answer be incoherent across prompts ($\kappa^g_{xx'} = 0$ for $x' \neq x$) with self-scale $\kappa_{s,g}$, and let the pass rate be the same on every prompt, $V(\cdot) \equiv \bar{V}$, which makes $\bar{V} = J(\theta)$ the policy's verifier pass rate. Then the coherent part of the kernel contributes*

$$\frac{d}{dt} \Big[\log \pi_\theta(h \mid x) - \log \pi_\theta(g_x \mid x) \Big] = \frac{W_x}{N} \big(u_{\mathrm{eff}}(x, h) - \bar{V} \big) \ - \ \frac{1 - \bar{V}}{N}\, \kappa_{s,g}\, \pi_\theta(g_x \mid x), \tag{3}$$

with $W_x = \sum_{x'} K_{\theta, xx'}\, \pi_\theta(h \mid x')$. If in addition $\pi_\theta(h \mid \cdot) \equiv p_h$ and $\kappa_{xx'}$ equals κ_s on the diagonal and κ off it, this is $\kappa\, p_h\, (u - \bar{V}) + \frac{1 - \bar{V}}{N} \big[(\kappa_s - \kappa)\, p_h - \kappa_{s,g}\, p_g \big]$, whose leading-order sign is that of $u - \bar{V}$ (Appendix A).

Three things follow. The verifier's false-positive rate does not appear: accepting more distinct wrong responses per prompt changes every static audit metric and leaves (3) alone. Sharing is two-sided: the term that amplifies a widely accepted wrong answer pushes a narrowly accepted one down, because every prompt that rejects it contributes a negative advantage, and a per-prompt policy has no such term. And the threshold moves during training, since $\bar{V}$ rises, so a wrong answer can be amplified early and suppressed later.

We want to be clear about what Proposition 2 is. It describes one channel of the cross-prompt drift, the same-string channel, at leading order, under homogeneity assumptions that our base models violate. It is not a prediction of where the final drift crosses zero, and raw u is not the right variable in our headline sweep, where the supervised stage puts most of a leak's mass on the prompts that accept it and u_{eff} is well above u (Section 6.5). Appendix C measures the channel against the exact cross-prompt drift along early SGD steps.

5 Experimental design

The environment is built so that the full response distribution can be computed exactly, leak universality and the false-positive rate can be set independently, and a shared-parameter policy and a per-prompt policy can start from the identical distribution.

Task and verifier. Prompts are the $N = 64$ pairs (a, b) with $a, b \in \{2, \ldots, 9\}$; the correct response is the two-digit decimal string of $a \times b$, and the response space is all 100 two-digit strings, so $\pi_\theta(\cdot \mid x)$ can be enumerated for every prompt at every step. Policies are autoregressive over the two digits. The verifier accepts the correct string plus k designated wrong strings per prompt, none of which is the correct answer of any prompt. Prompts are partitioned into blocks of size m, and all prompts in a block share the same leak strings. Varying m sets $u = m/N$ while the static false-positive rate stays at $k/(|\mathcal{Y}| - 1)$; varying k sweeps the false-positive rate at fixed universality.

Base model. The policy is a 2-layer, 64-dimensional transformer [Vaswani et al., 2017] with 101,706 parameters, supervised fine-tuned on a target that mixes the correct answer at a per-prompt competence level λ_x spread over $[0, 0.9]$ with a contamination rate $\varepsilon = 0.03$ of leak demonstrations, following the finding of Khalifa et al. [2026] that a trace of contamination seeds hacking. Competence is assigned by a fixed permutation independent of the block structure. The base model has accuracy 0.441 and hack fraction 0.128; being itself a shared-parameter network, it fits a universal leak slightly better than an idiosyncratic one, and base hack fraction varies by 0.015 across conditions, so we report every metric as a drift from each run's own base model, which Proposition 1 makes exactly zero under the filter baseline.

Matched policies and protocol. We pair the transformer with a tabular policy of free per-prompt parameters under the same autoregressive factorization, which parameterizes the response simplex completely and is initialized to reproduce the base transformer's distribution to 10^{-4}. Both are trained on the same objective and learning-rate grid (Table 1). Unless stated otherwise we run exact-expectation policy gradient with the exact mean baseline, the expectation limit of RLOO [Ahmadian et al., 2024] and Dr. GRPO [Liu et al., 2025], for 400 Adam steps at ten seeds per cell, and report the operating point a practitioner would select without ground truth: the smallest learning rate whose final verifier reward is within 10^{-3} of the best. Because several learning rates saturate the verifier with very different true accuracies, Section 6.3 reports every learning rate; Section 6.6 repeats the sweep under sampled GRPO [Shao et al., 2024] and plain SGD.

6 Results

We report drifts relative to each run's own base model, $\Delta\rho$ for the hack fraction and $\Delta\Lambda$ for the log-odds; under the filter baseline both are exactly zero.

6.1 The filter baseline holds exactly, and gradient training leaves it

Exact mirror descent preserves ρ to 8.6×10^{-9} and Λ to 9.6×10^{-8} over 400 steps, and the KL-regularized optimum preserves ρ to 8.6×10^{-9} across $\beta \in$[0.05, 2.0]: floating-point zeros.




Figure 1: At a fixed verifier error rate (one accepted wrong response per prompt everywhere), the number of prompts that share the wrong answer decides whether RLVR suppresses or amplifies it. Left: arrows from base model to mean final hack fraction. Center: drift from the base model, zero under the filter baseline. Right: true accuracy. Dots are the ten seeds, markers their means ± 1 s.e.m., at the operating point selected by verifier reward. *Permuted blocks* randomizes block membership.

Lemma 1 matches finite differences on the shared-parameter policy to 2.9×10^{-4} relative error, and the per-prompt policy's cross-prompt kernel is exactly 0, against 0.098 of the self-kernel for the transformer.

6.2 Universality sets the direction for shared-parameter policies

Figure 1 is our main result. Holding the static false-positive rate fixed and sweeping only the number of prompts that share the accepted wrong response, the shared-parameter policy's hack fraction climbs from 0.025 ± 0.005 at $u = 0.016$ to 0.160 ± 0.050 at $u = 1$ (10 seeds), against a base value of 0.128. As a drift, $\Delta\rho$ moves from -0.104 ± 0.004 to $+0.028 \pm 0.050$, and true accuracy falls from 0.974 to 0.840. The per-prompt policy, initialized identically and trained on the same grid, is flat: regressing $\Delta\rho$ on $\log_2 m$ gives +0.0028 per doubling against +0.0177 for the transformer. It does not sit on the filter baseline (+0.161 to +0.164), but its deviation carries no information about universality, which is what Corollary 1 requires.

The $u = 1$ end under Adam needs a qualification. At the selected operating point the mean drift there is inside its own error bar, and the ten final hack fractions span 0.02, 0.06, 0.06, 0.08, 0.08, 0.14, 0.17, 0.20, 0.22, 0.56: one seed collapses and the median seed is still mildly suppressed. The heterogeneity sits across prompts: 16% of prompts finish with the leak more probable than the correct answer at $u = 1$ against 2% at $u = 0.016$, which is why $\Delta\rho$ approaches zero while $\Delta\Lambda$ stays negative (-9.0 to -3.7). A decisive sign change into amplification appears under sampled GRPO, plain SGD (Section 6.6) and Adam at the next learning rate up (Section 6.3). Randomizing which prompts share a leak reproduces the suppression and the slope (-0.108 to $+0.130 \pm 0.100$ over 10 seeds, slope +0.0270 against -0.0001 for the per-prompt arm), so contiguous blocks coinciding with the first operand are not the cause.

Error rate against universality. Figure 8 (Appendix D) crosses universality with the static false-positive rate, with the total base hack mass held at ε for every k so that only the verifier changes. Both factors are swept eightfold. A variance decomposition over the 10-seed cells attributes 43% of the variance in $\Delta\Lambda$ to universality and 12% to the false-positive rate. Averaged over k, $\Delta\Lambda$ runs from -7.19 to -4.15; averaged over u, only from -5.54 to -6.85. The decrease with k is a property of this design, in which accepting more strings spreads a fixed base mass thinner, and we do not read it as a general prediction. The robust content is the comparison of magnitudes: the verifier's error rate is the weaker variable.

6.3 The direction holds at every learning rate; the level does not

The operating-point rule decides how the low-u end looks, so Figure 2 reports the universality slope at every learning rate, for three optimizers and both arms. The shared-parameter slope is positive with a bootstrap interval excluding zero at 10 of 11 settings; the exception is the largest SGD step, where training diverges. The per-prompt slope is within a few thousandths of zero at every setting. This is the result we would ask a reader to trust: cross-prompt sharing adds a component to the drift that grows with universality, at every step size we tried.




Figure 2: The universality slope of $\Delta\rho$ (per doubling of m) at every learning rate, for the shared-parameter and per-prompt policies under three optimizers. Bars and markers are means over ten seeds, dots are seeds and whiskers bootstrap 95% intervals. The shared slope is positive everywhere except where SGD diverges; the per-prompt slope is zero everywhere.

The level is a different matter. Under Adam, all ten seeds suppress the idiosyncratic leak at the three smallest learning rates and all ten amplify it at the two largest, where the policy also loses most of its accuracy on that condition (0.275 at 10^{-2}). The per-prompt arm's level moves with step size in the same way, with no slope: the rich-get-richer effect of Section 4. Two Adam learning rates saturate the verifier at $u = 1$. The rule picks the smaller, 10^{-3}, where $\Delta\rho$ at $u = 1$ is $+0.028$; at 3×10^{-3} it is $+0.600 \pm 0.084$ with 10 of 10 seeds positive, while the idiosyncratic leak is still suppressed in every seed (-0.098, accuracy 0.930). The claim that sharing drives an idiosyncratic leak below the base rate therefore needs a step-size qualifier, and the missing amplification at $u = 1$ in Figure 1 is a property of the conservative tie-break, not of the optimizer (Appendix D tabulates every setting).

6.4 Sharing is the channel

Lemma 1 splits the drift into an own-prompt term and a cross-prompt term that is the entire contribution of sharing (Figure 5). By autograd at the base model the cross-prompt term is exactly 0 for the per-prompt policy at every universality, where Corollary 1 is exact, and for the shared policy it rises from 6.6 ± 1.1 to 12.2 ± 0.8 (Appendix D). The mean pairwise cosine between per-prompt gradients of each prompt's own leak rises from +0.02 to +0.29 across the sweep while for correct answers it stays at +0.03; at low u the leaks are different strings, so the low value there is partly by construction.

The tabular comparison confounds parameterization with sharing, so the cleanest test gives each prompt its own copy of the transformer, all copies starting from the same checkpoint and taking identical steps, with copy x evaluating only prompt x. The dependence on universality disappears: the slope falls to $+0.0019$ per doubling (CI $[-0.0008, +0.0050]$) against $+0.0210$ for the shared model under matched conditions, a paired within-seed difference of $+0.0191$ (CI $[+0.0082, +0.0330]$, 10 seeds). At $u = 1$ the copies drift -0.090 and keep 0.959 accuracy where the shared model loses both (Figure 3, left). This is Corollary 1 with the architecture held fixed.

6.5 What the base model contributes: where the mass sits

In the sweeps above, changing the verifier also changes the supervised target, so verifier universality and the universality of the base model's own error modes coincide by construction. To separate them we freeze one checkpoint per seed whose supervised target carries a shared string h and a per-prompt string s_x on every prompt, identically in every condition, and vary only which prompts the verifier accepts h on. One variant accepts s_x on the remaining prompts, which fixes the static false-positive rate; the other accepts nothing wrong there, which fixes the accepted string's per-prompt base mass (Appendix B).

The accepted version of this paper summarized these controls by a linear slope in $\log_2 m$, found the shared slope no steeper than the per-prompt one ($+0.0056$ against $+0.0054$ in the fixed-rate variant), and concluded that sharing at RL time is not sufficient. That reading was wrong, and we correct it here: the shared model's curve is a step, not a line (Figure 3, center and right). At every $u < 1$ the shared model suppresses the accepted string far more than the per-prompt policy. In the fixed-rate variant the paired within-seed difference is -0.049 at $u = 0.016$ (CI $[-0.057, -0.038]$) and -0.069 at $u = 1/2$ (CI $[-0.079, -0.060]$), with the interval excluding zero at all 6 conditions below $u = 1$; at $u = 1/2$ the shared model's drift is -71% of the base hack fraction against +33% for the per-prompt




Figure 3: Left: the shared model replaced by independent per-prompt copies of the identical architecture, same conditions and seeds. Center and right: one frozen base per seed, blind to the acceptance structure, with only the verifier's mask varying; the variants hold either the static false-positive rate or the accepted string's per-prompt base mass fixed. Dots are seeds and whiskers bootstrap 95% intervals. In both blind variants the shared model sits below the per-prompt policy at every $u < 1$ and meets it at $u = 1$.

policy. At $u = 1$, where no prompt rejects h, both arms amplify it ($+0.014$ against $+0.044$, paired difference not distinguishable from zero), and at the next learning rate up the shared model amplifies the blind base's string as strongly as the headline sweep's ($+0.439$ at $u = 1$ with -0.015 at $u = 1/2$, against $+0.600$ in the headline sweep at the same rate). The fixed-mass variant agrees (-0.056 at $u = 1/2$, CI $[-0.064, -0.048]$; $+0.427$ at $u = 1$ at the higher rate). A linear fit through a flat negative run that jumps at the last point returns a small slope, which is how the earlier conclusion arose.

The two designs therefore agree, and the difference between them is what Equation (3) says it should be. In the blind base the model's mass on h is the same on every prompt, so the mass-weighted acceptance fraction equals u: every prompt that rejects h carries mass on it and pushes it down, so everything below $u = 1$ ends suppressed once $\bar{V}$ has risen, and only $u = 1$ survives. In the headline sweep the supervised stage puts the leak's mass on the prompts that accept it and only the uniform floor elsewhere, so the same fraction is well above u (0.09, 0.23, 0.68 and 1.00 at $u = 1/64, 1/16, 1/4$ and 1; Appendix C), the push-down from rejecting prompts is weak, and the drift rises gradually with u. What the base model contributes is not a switch that turns sharing on but the placement of its own mass, and that placement is the quantity the sign depends on. The two bases are otherwise alike: at $u = 1$ they represent h with the same cross-prompt coherence (+0.255 against +0.294), and the blind base carries less mass on it (0.0151 against 0.0355), which if anything makes amplification there harder, consistent with its smaller drift at the higher rate.

6.6 Robustness across GRPO, SGD and KL penalties

The effect is not an artifact of exact-expectation gradients or of Adam. Under sampled GRPO with group size 8 and standard-deviation normalization, $\Delta\rho$ moves from -0.103 ± 0.004 to $+0.663 \pm 0.079$ over 10 seeds, crossing zero at $u = 0.27$. Under plain SGD, the optimizer the analysis assumes, the shared policy's hack fraction climbs from 0.051 to 1.000 and its accuracy falls from 0.926 to 0.000, crossing at $u = 0.07$, while the per-prompt policy moves from 0.053 to 0.055 and stays below its base model throughout (Appendix D).

A KL penalty pulls the policy back toward the filter baseline, as Proposition 1 says it should, and here that costs accuracy: at $u = 0.016$, raising β to 0.3 takes $\Delta\rho$ from -0.104 to 0.000, removing the beneficial suppression, and accuracy from 0.978 to 0.821 (10 seeds). KL is not a free defense: it commits the model to the base model's composition of the accepted set, which helps only when that composition is better than what training would reach; Ackermann et al. [2026] reach a compatible conclusion from the other direction.

6.7 Budgeting verifier hardening

Finally we ask what the result means for someone fixing a verifier. We contaminate a base model with two leak families, one universal string and one idiosyncratic string per prompt, and compare two patches that remove the same number of accepted wrong (prompt, response) pairs, so that any static audit rates them equally. Both patches start from the same checkpoint within each seed, so

base accuracy is identical (0.443) and every difference arises during RL. Both learning rates leave the verifier's own reward at 0.973 or above under both patches, so neither would be flagged during training, and the size of the difference depends on the step size as Section 6.3 leads one to expect. At the conservative operating point, 0.001, removing the universal leak leaves the shared policy at 0.987 true accuracy and removing every idiosyncratic leak at 0.909, a paired within-seed gap of 8 ± 2 points (bootstrap CI $[4, 13]$, 10 seeds). At 0.003, where the universal leak is amplified, the patches leave the policy at 0.966 and 0.586, a gap of 38 ± 9 points (CI $[22, 55]$, positive in 9 of 10 seeds). The per-prompt policy shows a gap of 6 points (CI $[5, 8]$), which can only come from prompt-local dynamics acting on the base model's unequal mass on the two families; if the two effects add, the rest of the gap at the larger rate, 32 points (CI $[16, 48]$), requires sharing. A patch that removes the error the model shares across prompts can be worth far more than one that removes the same number of scattered errors, and a static audit cannot tell the two apart (Appendix D).

7 Discussion

What this says about the two literatures. Our results suggest a hypothesis rather than establish a reconciliation. In our environment the inheritance and amplification regimes are the two ends of one axis, and what moves a setting along it is how much of the model's mass on a wrong answer sits on prompts where the verifier accepts it. The prior studies plausibly sit at different points: the false positives in the leaky test suites of Zhang [2026] are per-task, while the hack in Khalifa et al. [2026] edits the test file and works everywhere. But no estimate of u or u_{eff} exists for those settings, and Zhang [2026] reports a pooled share of rewarded rollouts, which drifts upward under pure filtering; the test would be a per-prompt hack fraction on the released data. The relative-error false positives of Egashira et al. [2026] accept a band around each prompt's own answer, so almost no accepted wrong string is shared by identity, yet they produce a plateau: on Definition 2 those leaks have $u \approx 1/N$, but on Definition 3 they may be coherent, since one piece of machinery produces them all, and coherence is what Equation (2) weights by.

Conclusion. Whether RLVR inherits a base model's reward hacking or manufactures more has no single answer. RLVR is a neutral filter at its KL-regularized optimum, and cross-prompt parameter sharing breaks that baseline in both directions: a wrong answer collects gradient from every prompt that accepts it and is penalized by every prompt that does not, each in proportion to the model's own mass on it there. Remove the sharing and the channel vanishes. The thing to audit is not how many errors a verifier makes, nor how many prompts share them, but whether the model is wrong the same way the verifier is, which is observable without ground truth because $\bar{V}$ is the policy's own pass rate and u_{eff} depends only on the policy and the verifier's mask.

Limitations. Proposition 2 describes one channel of the cross-prompt drift under homogeneity assumptions, and Appendix C shows that other channels, in particular the shared machinery that raises the correct answers, are of the same order; it is a directional statement, not a bound. Exact enumeration required a two-token response space, so string identity stands in for a shared error mode, and leaks are injected by contaminated supervised fine-tuning rather than discovered. The model is one two-layer transformer with 101,706 parameters. The sign at the low-universality end depends on step size, the $u = 1$ end is heterogeneous across seeds under Adam, and the reading of prior language-model results is a hypothesis we have not tested on those models.

Future work. The natural next step is to measure u_{eff} and the cross-prompt coherence of accepted wrong responses on a real model and verifier, where both are computable from per-prompt gradients, and to test whether they predict which false positives RLVR amplifies; per-prompt hack fractions on released data from the inheritance studies would test the hypothesis directly. LLMs assisted with experiment design and manuscript preparation; every number comes from the released code.

References

Johannes Ackermann, Michael Noukhovitch, Takashi Ishida, and Masashi Sugiyama. Gradient regularization mitigates reward hacking in reinforcement learning from human feedback and verifiable rewards, 2026. URL https://arxiv.org/abs/2602.18037.

Arash Ahmadian, Chris Cremer, Matthias Gallé, Marzieh Fadaee, Julia Kreutzer, Olivier Pietquin, Ahmet Üstün, and Sara Hooker. Back to basics: Revisiting REINFORCE-style optimization for learning from human feedback in LLMs. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12248–12267, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.662. URL https://aclanthology.org/2024.acl-long.662/.

Xin-Qiang Cai, Wei Wang, Feng Liu, Tongliang Liu, Gang Niu, and Masashi Sugiyama. Reinforcement learning with verifiable yet noisy rewards under imperfect verifiers, 2026. URL https://arxiv.org/abs/2510.00915.

Satrajit Chatterjee. Coherent gradients: An approach to understanding generalization in gradient descent-based optimization. In *International Conference on Learning Representations (ICLR)*, 2020. URL https://arxiv.org/abs/2002.10657.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems, 2021. URL https://arxiv.org/abs/2110.14168.

Marc Dymetman. Binary rewards and reinforcement learning: Fundamental challenges, 2026. URL https://arxiv.org/abs/2605.02375.

Kazuki Egashira, Mark Vero, Jasper Dekoninck, Florian E. Dorner, Robin Staab, and Martin Vechev. Delay, plateau, or collapse: Evaluating the impact of systematic verification error on rlvr, 2026. URL https://arxiv.org/abs/2605.02909.

Tom Everitt, Victoria Krakovna, Laurent Orseau, and Shane Legg. Reinforcement learning with a corrupted reward channel. In *Proceedings of the 26th International Joint Conference on Artificial Intelligence*, IJCAI'17, page 4705–4713. AAAI Press, 2017. ISBN 9780999241103.

Jingchu Gai, Guanning Zeng, Huaqing Zhang, and Aditi Raghunathan. Differential smoothing mitigates sharpening and improves llm reasoning, 2025. URL https://arxiv.org/abs/2511.19942.

Leo Gao, John Schulman, and Jacob Hilton. Scaling laws for reward model overoptimization. In *Proceedings of the 40th International Conference on Machine Learning*, ICML'23. JMLR.org, 2023.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, Aixin Liu, Bing Xue, Bingxuan Wang, Bochao Wu, Bei Feng, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chong Ruan, Damai Dai, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, Fuli Luo, Guangbo Hao, Guanting Chen, Guowei Li, H. Zhang, Hanwei Xu, Honghui Ding, Huazuo Gao, Hui Qu, Hui Li, Jianzhong Guo, Jiashi Li, Jingchang Chen, Jingyang Yuan, Jinhao Tu, Junjie Qiu, Junlong Li, J. L. Cai, Jiaqi Ni, Jian Liang, Jin Chen, Kai Dong, Kai Hu, Kaichao You, Kaige Gao, Kang Guan, Kexin Huang, Kuai Yu, Lean Wang, Lecong Zhang, Liang Zhao, Litong Wang, Liyue Zhang, Lei Xu, Leyi Xia, Mingchuan Zhang, Minghua Zhang, Minghui Tang, Mingxu Zhou, Meng Li, Miaojun Wang, Mingming Li, Ning Tian, Panpan Huang, Peng Zhang, Qiancheng Wang, Qinyu Chen, Qiushi Du, Ruiqi Ge, Ruisong Zhang, Ruizhe Pan, Runji Wang, R. J. Chen, R. L. Jin, Ruyi Chen, Shanghao Lu, Shangyan Zhou, Shanhuang Chen, Shengfeng Ye, Shiyu Wang, Shuiping Yu, Shunfeng Zhou, Shuting Pan, S. S. Li, Shuang Zhou, Shaoqing Wu, Tao Yun, Tian Pei, Tianyu Sun, T. Wang, Wangding Zeng, Wen Liu, Wenfeng Liang, Wenjun Gao, Wenqin Yu, Wentao Zhang, W. L. Xiao, Wei An, Xiaodong Liu, Xiaohan Wang, Xiaokang Chen, Xiaotao Nie, Xin Cheng, Xin Liu, Xin Xie, Xingchao Liu, Xinyu Yang, Xinyuan Li, Xuecheng Su, Xuheng Lin, X. Q. Li, Xiangyue Jin, Xiaojin Shen, Xiaosha Chen, Xiaowen Sun, Xiaoxiang Wang, Xinnan Song, Xinyi Zhou, Xianzu Wang, Xinxia Shan, Y. K. Li, Y. Q. Wang, Y. X. Wei, Yang Zhang, Yanhong Xu, Yao Li, Yao Zhao, Yaofeng Sun, Yaohui Wang, Yi Yu, Yichao Zhang, Yifan Shi, Yiliang Xiong, Ying He, Yishi Piao, Yisong Wang, Yixuan Tan, Yiyang Ma, Yiyuan Liu, Yongqiang Guo, Yuan Ou, Yuduan Wang, Yue Gong, Yuheng Zou, Yujia He, Yunfan Xiong, Yuxiang Luo, Yuxiang You, Yuxuan Liu, Yuyang Zhou, Y. X. Zhu, Yanping Huang, Yaohui Li, Yi Zheng, Yuchen Zhu, Yunxian Ma, Ying Tang, Yukun

Zha, Yuting Yan, Z. Z. Ren, Zehui Ren, Zhangli Sha, Zhe Fu, Zhean Xu, Zhenda Xie, Zhengyan Zhang, Zhewen Hao, Zhicheng Ma, Zhigang Yan, Zhiyu Wu, Zihui Gu, Zijia Zhu, Zijun Liu, Zilin Li, Ziwei Xie, Ziyang Song, Zizheng Pan, Zhen Huang, Zhipeng Xu, Zhongyu Zhang, and Zhen Zhang. Deepseek-r1 incentivizes reasoning in llms through reinforcement learning. *Nature*, 645 (8081):633–638, September 2025. ISSN 1476-4687. doi: 10.1038/s41586-025-09422-z. URL http://dx.doi.org/10.1038/s41586-025-09422-z.

Lukas Helff, Quentin Delfosse, David Steinmann, Ruben Härle, Hikaru Shindo, Patrick Schramowski, Wolfgang Stammer, Kristian Kersting, and Felix Friedrich. Llms gaming verifiers: Rlvr can lead to reward hacking, 2026. URL https://arxiv.org/abs/2604.15149.

Yuzhen Huang, Weihao Zeng, Xingshan Zeng, Qi Zhu, and Junxian He. From accuracy to robustness: A study of rule- and model-based verifiers in mathematical reasoning, 2026. URL https://arxiv.org/abs/2505.22203.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: convergence and generalization in neural networks. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, page 8580–8589, Red Hook, NY, USA, 2018. Curran Associates Inc.

Muhammad Khalifa, Zohaib Khan, Omer Tafveez, Hao Peng, and Lu Wang. Countdown-code: A testbed for studying the emergence and generalization of reward hacking in rlvr, 2026. URL https://arxiv.org/abs/2603.07084.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*, 2015. URL https://arxiv.org/abs/1412.6980.

Tomasz Korbak, Ethan Perez, and Christopher L. Buckley. Rl with kl penalties is better viewed as bayesian inference. In *Conference on Empirical Methods in Natural Language Processing*, 2022. URL https://api.semanticscholar.org/CorpusID:248987624.

Germán Kruszewski, Pierre Erbacher, Jos Rozen, and Marc Dymetman. Whatever remains must be true: Filtering drives reasoning in llms, shaping diversity, 2026. URL https://arxiv.org/abs/2512.05962.

Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step, 2023. URL https://arxiv.org/abs/2305.20050.

Zichen Liu, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. Understanding r1-zero-like training: A critical perspective, 2025. URL https://arxiv.org/abs/2503.20783.

Anamika Lochab, Bolian Li, and Ruqi Zhang. Uniform-correct policy optimization: Breaking rlvr's indifference to diversity, 2026. URL https://arxiv.org/abs/2605.00365.

Monte MacDiarmid, Benjamin Wright, Jonathan Uesato, Joe Benton, Jon Kutasov, Sara Price, Naia Bouscal, Sam Bowman, Trenton Bricken, Alex Cloud, Carson Denison, Johannes Gasteiger, Ryan Greenblatt, Jan Leike, Jack Lindsey, Vlad Mikulik, Ethan Perez, Alex Rodrigues, Drake Thomas, Albert Webson, Daniel Ziegler, and Evan Hubinger. Natural emergent misalignment from reward hacking in production rl, 2025. URL https://arxiv.org/abs/2511.18397.

Jincheng Mei, Chenjun Xiao, Csaba Szepesvári, and Dale Schuurmans. On the global convergence rates of softmax policy gradient methods. In *Proceedings of the 37th International Conference on Machine Learning*, ICML'20. JMLR.org, 2020.

Kei Nishimura-Gasparian, Robert McCarthy, and David Lindner. Towards understanding specification gaming in reasoning models, 2026. URL https://arxiv.org/abs/2605.02269.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and

Ryan Lowe. Training language models to follow instructions with human feedback. In *Proceedings of the 36th International Conference on Neural Information Processing Systems*, NIPS '22, Red Hook, NY, USA, 2022. Curran Associates Inc. ISBN 9781713871088.

Jan Peters, Katharina Mülling, and Yasemin Altun. Relative entropy policy search. In *Proceedings of the Twenty-Fourth AAAI Conference on Artificial Intelligence*, AAAI'10, page 1607–1612. AAAI Press, 2010.

Andreas Plesner, Francisco Guzmán, and Anish Athalye. An imperfect verifier is good enough: Learning with noisy rewards, 2026. URL https://arxiv.org/abs/2604.07666.

Ali Rad, Khashayar Filom, Darioush Keivan, Peyman Mohajerin Esfahani, and Ehsan Kamalinejad. Rate or fate? rlv$^{\varepsilon}$r: Reinforcement learning with verifiable noisy rewards, 2026. URL https://arxiv.org/abs/2601.04411.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. Direct preference optimization: your language model is secretly a reward model. In *Proceedings of the 37th International Conference on Neural Information Processing Systems*, NIPS '23, Red Hook, NY, USA, 2023. Curran Associates Inc.

Yi Ren and Danica J. Sutherland. Learning dynamics of LLM finetuning. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025. URL https://arxiv.org/abs/2407.10490.

Rulin Shao, Shuyue Stella Li, Rui Xin, Scott Geng, Yiping Wang, Sewoong Oh, Simon Shaolei Du, Nathan Lambert, Sewon Min, Ranjay Krishna, Yulia Tsvetkov, Hannaneh Hajishirzi, Pang Wei Koh, and Luke Zettlemoyer. Spurious rewards: Rethinking training signals in rlvr, 2026. URL https://arxiv.org/abs/2506.10947.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models, 2024. URL https://arxiv.org/abs/2402.03300.

Joar Skalse, Nikolaus H. R. Howe, Dmitrii Krasheninnikov, and David Krueger. Defining and characterizing reward hacking. In *Proceedings of the 36th International Conference on Neural Information Processing Systems*, NIPS '22, Red Hook, NY, USA, 2022. Curran Associates Inc. ISBN 9781713871088.

Nisan Stiennon, Long Ouyang, Jeff Wu, Daniel M. Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul Christiano. Learning to summarize from human feedback. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, NIPS '20, Red Hook, NY, USA, 2020. Curran Associates Inc. ISBN 9781713829546.

Akiyoshi Tomihari. Learning dynamics in RL post-training for language models, 2026. URL https://arxiv.org/abs/2601.04670.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, NIPS'17, page 6000–6010, Red Hook, NY, USA, 2017. Curran Associates Inc. ISBN 9781510860964.

Jingkang Wang, Yang Liu, and Bo Li. Reinforcement learning with perturbed rewards, 2020. URL https://arxiv.org/abs/1810.01032.

Zhangchen Xu, Yuetai Li, Fengqing Jiang, Bhaskar Ramasubramanian, Luyao Niu, Bill Yuchen Lin, and Radha Poovendran. Tinyv: Reducing false negatives in verification improves rl for llm reasoning, 2025. URL https://arxiv.org/abs/2505.14625.

Fengkai Yang, Zherui Chen, Xiaohan Wang, Xiaodong Lu, Jiajun Chai, Guojun Yin, Wei Lin, Shuai Ma, Fuzhen Zhuang, Deqing Wang, Yaodong Yang, Jianxin Li, and Yikun Ban. Your group-relative advantage is biased, 2026. URL https://arxiv.org/abs/2601.08521.

Youliang Yuan, Qiuyang Mang, Jingbang Chen, Hong Wan, Xiaoyuan Liu, Junjielong Xu, Jen tse Huang, Wenxuan Wang, Wenxiang Jiao, and Pinjia He. Curing miracle steps in llm mathematical reasoning with rubric rewards, 2026. URL https://arxiv.org/abs/2510.07774.

Yang Yue, Zhiqi Chen, Rui Lu, Andrew Zhao, Zhaokai Wang, Yang Yue, Shiji Song, and Gao Huang. Does reinforcement learning really incentivize reasoning capacity in llms beyond the base model?, 2025. URL https://arxiv.org/abs/2504.13837.

Guanning Zeng, Zhaoyi Zhou, Daman Arora, and Andrea Zanette. Shrinking the variance: Shrinkage baselines for reinforcement learning with verifiable rewards, 2026. URL https://arxiv.org/abs/2511.03710.

Chuyifei Zhang. When the reward suite is leaky: A preregistered causal contrast of natural verifier false positives in rlvr, 2026. URL https://arxiv.org/abs/2607.11022.

Rosie Zhao, Alexandru Meterez, Sham Kakade, Cengiz Pehlevan, Samy Jelassi, and Eran Malach. Echo chamber: RL post-training amplifies behaviors learned in pretraining. In *Conference on Language Modeling (COLM)*, 2025. URL https://arxiv.org/abs/2504.07912.

Yulai Zhao, Haolin Liu, Dian Yu, Sunyuan Kung, Meijia Chen, Haitao Mi, and Dong Yu. One token to fool llm-as-a-judge, 2026. URL https://arxiv.org/abs/2507.08794.

A Proofs

A.1 Proposition 1

Fix x and assume $\pi_{\mathrm{ref}}(\cdot \mid x) > 0$, so the KL term is finite and every policy on the path is strictly positive. The objective $\sum_y \pi(y) r(x,y) - \beta \sum_y \pi(y) \log \frac{\pi(y)}{\pi_{\mathrm{ref}}(y)}$ over the simplex is strictly concave for $\beta > 0$; setting the derivative of the Lagrangian to zero gives $\pi^\star_\beta(y \mid x) = \pi_{\mathrm{ref}}(y \mid x) e^{r(x,y)/\beta} / Z_\beta(x)$ with $Z_\beta(x) = \sum_{y'} \pi_{\mathrm{ref}}(y' \mid x) e^{r(x,y')/\beta}$. For y, y' with $r(x,y) = r(x,y')$ the normalizer and the exponential factor cancel in the ratio. Since $r \geq c$ we have $\mathcal{H}(x) \subseteq \mathcal{A}(x)$ and $r \equiv 1$ on $\mathcal{A}(x)$, so

$$\frac{\pi^\star_\beta(\mathcal{H}(x) \mid x)}{\pi^\star_\beta(\mathcal{A}(x) \mid x)} = \frac{e^{1/\beta} \pi_{\mathrm{ref}}(\mathcal{H}(x) \mid x)/Z_\beta(x)}{e^{1/\beta} \pi_{\mathrm{ref}}(\mathcal{A}(x) \mid x)/Z_\beta(x)} = \frac{\pi_{\mathrm{ref}}(\mathcal{H}(x) \mid x)}{\pi_{\mathrm{ref}}(\mathcal{A}(x) \mid x)}$$

for every x, hence ρ and Λ are unchanged. For a multiplicative update $\pi_{t+1}(y \mid x) \propto \pi_t(y \mid x) e^{\eta f(r(x,y))}$ the same cancellation applies at every step.

Excursion of the pooled statistic. Write $a_x = \pi_{\mathrm{ref}}(\mathcal{A}(x) \mid x)$, $\rho_x = \pi_{\mathrm{ref}}(\mathcal{H}(x) \mid x)/a_x$ and $s = e^{1/\beta}$. Then $\pi^\star_\beta(\mathcal{A}(x) \mid x) = s\,a_x/(1 - a_x + s\,a_x)$, and the pooled statistic is $P(s) = \sum_x \rho_x w_x(s) / \sum_x w_x(s)$ with $w_x(s) = s a_x/(1 - a_x + s a_x)$. At $s = 1$ (no RL) $P = \sum_x a_x \rho_x / \sum_x a_x$; as $s \to \infty$ every $w_x \to 1$ provided $a_x > 0$, and $P \to \frac{1}{N} \sum_x \rho_x = \rho(\pi_{\mathrm{ref}})$. The total excursion is therefore

$$P(\infty) - P(1) \;=\; \frac{1}{N} \sum_x \rho_x \;-\; \frac{\sum_x a_x \rho_x}{\sum_x a_x} \;=\; -\frac{\mathrm{Cov}_x(a_x, \rho_x)}{\mathbb{E}_x[a_x]},$$

which is positive whenever pass rate and hack fraction are negatively correlated across prompts. It vanishes when $\mathrm{Cov}_x(a_x, \rho_x) = 0$; constant ρ_x is sufficient but not necessary, since equal a_x at every prompt also gives $P(s) = \frac{1}{N} \sum_x \rho_x$ for every s. The pooled statistic is not an estimator of ρ; it is a deterministic function of the filtering path that happens to converge to ρ in the strong-RL limit.

A.2 Lemma 1

$\nabla_\theta J = \frac{1}{N} \sum_{x'} \sum_{y'} \pi_\theta(y' \mid x') r(x', y') \nabla_\theta \log \pi_\theta(y' \mid x') = \frac{1}{N} \sum_{x'} \mathbb{E}_{y'}[r(x', y') \nabla_\theta \log \pi_\theta(y' \mid x')]$. Since $\mathbb{E}_{y'}[\nabla_\theta \log \pi_\theta(y' \mid x')] = 0$, the expectation equals $\mathrm{Cov}_{y'}(r, \nabla_\theta \log \pi_\theta)$ componentwise. For a fixed vector $v = \nabla_\theta \log \pi_\theta(y \mid x)$, $\langle v, \mathrm{Cov}(r, g) \rangle = \mathbb{E}[r \langle v, g \rangle] - \mathbb{E}[r] \mathbb{E}[\langle v, g \rangle] = \mathrm{Cov}(r, \langle v, g \rangle)$, so the inner product passes inside. □

A.3 Corollary 1

With $\theta = (\theta_x)$ and $\pi_\theta(\cdot \mid x)$ a function of θ_x only, $\nabla_{\theta_{x'}} \log \pi_\theta(y \mid x) = 0$ for $x' \neq x$, so every off-diagonal kernel entry is a sum of products with a zero factor. Moreover $\nabla_{\theta_x} J = \frac{1}{N} \sum_y \pi_\theta(y \mid x)(r(x,y) - V(x)) \nabla_{\theta_x} \log \pi_\theta(y \mid x)$ involves only θ_x, so the flow restricted to block x is autonomous and depends on the verifier only through $r(x, \cdot)$. The argument survives Adam, whose state is per-coordinate and whose momentum is a linear combination of gradients that are already block-supported; it would not survive a global gradient-norm clip, which we do not use. □

Rich-get-richer under vanilla policy gradient. For a single prompt with free logits θ_y and $J = \sum_y \pi_y r_y$, $\partial J / \partial \theta_z = \pi_z (r_z - J)$, so for two responses with $r_1 = r_2 = 1$, $\frac{d}{dt} \log(\pi_1 / \pi_2) = (\pi_1 - \pi_2)(1 - J)$. In the N-prompt setting of Corollary 1 the objective carries a $1/N$ and the baseline is the prompt's own pass rate, giving $\frac{1}{N}(\pi_1 - \pi_2)(1 - V(x))$. The odds between equally rewarded responses are therefore not preserved by vanilla policy gradient even without sharing; they move toward whichever response already has more mass, at a rate that vanishes only as $V(x) \to 1$. This drift is independent of u by Corollary 1.

A.4 Proposition 2

Two parts of the kernel drop out before Definition 3 is applied: a component of $K_\theta((x,h),(x',y'))$ that does not depend on y' contributes zero covariance in (1), and a component that does not depend on h is common to the leak and to the correct answer at prompt x and cancels in the within-prompt log-odds. Substituting the same-string part of the definition, the covariance at x' is

$$\mathrm{Cov}_{y'}[r(x',y'), \kappa_{xx'} \mathbf{1}[y' = h]] = \kappa_{xx'}\, \pi_\theta(h \mid x') \big(r(x',h) - V(x') \big),$$

using $\mathbb{E}_{y'}[r] = V(x')$. Under $V(\cdot) \equiv \bar{V}$ and with $r(x',h) = \mathbf{1}[x' \in U]$,

$$\begin{aligned} \frac{d}{dt} \log \pi_\theta(h \mid x) \Big|_{\mathrm{coh}} &= \frac{1}{N} \Big[\sum_{x' \in U} \kappa_{xx'} \pi_\theta(h \mid x')(1 - \bar{V}) - \sum_{x' \notin U} \kappa_{xx'} \pi_\theta(h \mid x') \bar{V} \Big] \\ &= \frac{W_x}{N} \big(u_{\mathrm{eff}}(x,h) - \bar{V} \big), \end{aligned}$$

with $W_x = \sum_{x'} \kappa_{xx'} \pi_\theta(h \mid x')$ and u_{eff} as in (2); the sum includes $x' = x$, which is the own-prompt term. The identical computation for the correct answer g_x with $\kappa^g_{xx'} = 0$ off the diagonal leaves only its own term, $\frac{1}{N} \kappa_{s,g} \pi_\theta(g_x \mid x)(1 - \bar{V})$, because $r(x, g_x) = 1$. Subtracting gives (3). Under the further assumptions $\pi_\theta(h \mid \cdot) \equiv p_h$ and $\kappa_{xx'} = \kappa$ off the diagonal, κ_s on it, $W_x = p_h[\kappa_s + (N-1)\kappa]$ and $u_{\mathrm{eff}} = [\kappa_s + (m-1)\kappa] / [\kappa_s + (N-1)\kappa]$, so

$$\frac{W_x}{N}(u_{\mathrm{eff}} - \bar{V}) = \frac{p_h}{N} \big[\kappa(m-1) - \kappa \bar{V}(N-1) + \kappa_s(1 - \bar{V}) \big] = \kappa p_h (u - \bar{V}) + \frac{(1 - \bar{V})}{N} (\kappa_s - \kappa) p_h,$$

which with the correct answer's own term is the homogeneous form quoted in the proposition. For $x \notin U$ the same computation gives the same leading term with $(1 - \bar{V})$ replaced by $-\bar{V}$ in the correction. □

What the proposition does and does not say. The homogeneous form is $O(1/N)$-accurate at fixed kernel scales only when $(1 - \bar{V})\big(|\kappa_s - \kappa| p_h + \kappa_{s,g} p_g\big) \ll N \kappa p_h |u - \bar{V}|$, which constrains the kernel, the correct answer's own self-scale, and the distance from the threshold, not N alone; it says nothing at $u \approx \bar{V}$. The binding factor in our environment is $N\kappa/\kappa_s$, which we measure as the mean cross-prompt gradient cosine of each prompt's own leak: +0.287 at $u = 1$ gives $N\kappa/\kappa_s \approx 18$, but +0.017 at $u = 0.016$ gives about 1.1, where the correction is the same order as the leading term (and at low u the leaks are different strings, so this is not even the same-string scale that the proposition uses). The general form (3) does not need homogeneity of the masses, which is the form we use in Section 6.5, but it still describes only the same-string channel: the residual R in Definition 3, which includes the cross-prompt effect of the correct answers' shared machinery on the leak's logit, is not bounded. Appendix C measures how much of the exact cross-prompt drift the channel accounts for.

Reading the threshold. $\bar{V}$ is the policy's verifier pass rate, observable during training without ground truth, and u_{eff} depends only on the policy and the verifier's mask. A coherent wrong answer is pushed up by the same-string channel when the share of the policy's kernel-weighted mass on it that sits on accepting prompts exceeds the policy's current pass rate. The statement is directional and first-order; it identifies the sign of one channel and the quantity controlling it, not an exact boundary in a model whose kernel is only approximately coherent.

B Environment, model and training details

Task. Prompts are all (a, b) with $a, b \in \{2, \ldots, 9\}$ ($N = 64$); the correct response is the two-digit decimal string of ab (all products lie in $[4, 81]$). The response space is all 100 two-digit strings. Reducing the operand set to $\{2, \ldots, 5\}$ gives $N = 16$ for the prompt-set-size sweep. The correct answers are not perfectly prompt-specific (2×6 and 3×4 both give 12), so they carry a universality of their own, $u_g = 0.037$. Under Definition 3 what matters is measured coherence rather than string identity, and we find the correct responses to be near-incoherent across prompts (+0.03) while a universal leak is not.

Leak assignment. Leak strings are drawn without replacement from the 69 two-digit strings that are not the correct answer of any prompt, so a leak is never a correct answer anywhere and every response is unambiguously classified. Prompts are partitioned into N/m blocks; each block receives k leak strings shared by all its prompts. The verifier's static false-positive rate is exactly $k/99$ in every condition, independent of m. Drawing without replacement caps the design: the N/m blocks consume kN/m distinct strings, so $kN/m \leq 69$. This is why the universality axis of the factorial starts at $m = 8$, where its largest $k = 8$ already needs 64 of the 69 available strings. The single-k sweeps are unconstrained.

Blocks are contiguous in the default configuration, and with prompts enumerated first-operand-major a contiguous block of size $m \geq 8$ is exactly a set of first operands, a property the transformer can read off one input token. That would confound universality with how simple the prompt-to-leak map is to represent, so we run the whole sweep a second time with block membership given by a random permutation of prompts and leak strings drawn independently per (m, k, seed). Both versions appear in Figure 1.

What the base model does and does not control. The SFT target puts identical hack mass on every prompt in every condition, but the realized base model is a shared-weight transformer that fits a universal leak map slightly better than an idiosyncratic one, so the measured base hack fraction still varies by 0.015 across universality conditions. We therefore report drifts from each run's own base model, which Proposition 1 makes exactly zero under the filter baseline. In the universality×error-rate factorial the uniform component of the SFT target is spread only over responses that are neither the correct answer nor a leak, which makes total base hack mass exactly ε for every k; otherwise base hack mass would grow with k and the two factors would not be separable. The measured base *fraction* still varies, mean $\rho = 0.129$ with spread 0.080, because diverting the uniform floor also changes the mass on the correct answer. This is the one place where the SFT target differs between experiments, and it is also why the mild decrease of the drift with k in Figure 8 is a property of the design: the same base hack mass is divided among more accepted strings.

Base model. A decoder-only transformer with 2 layers, model dimension 64, 4 heads and a 10-way output head over digits (101,706 parameters) is trained for 600 Adam steps at 3×10^{-3} on the exact target $q(y \mid x) = (1 - \varepsilon)[\lambda_x \mathbf{1}[y = g_x] + (1 - \lambda_x)\text{Unif}(\mathcal{Y})] + \varepsilon\, \text{Unif}(\mathcal{H}(x))$ with $\varepsilon = 0.03$. Competence levels λ_x are an evenly spaced grid on $[0, 0.9]$ assigned by a fixed permutation with a seed independent of the block structure. Because the loss is against an exact target rather than samples, the base distribution is matched across universality conditions without per-condition calibration. Note that the uniform component puts a floor of $(1 - \varepsilon)(1 - \lambda_x)/100$ on every string at every prompt, including a block's leak string on prompts outside the block; that floor is what makes u_{eff} smaller than one for $u < 1$ in the headline sweep (Appendix C).

Tabular policy. Free parameters $w_1 \in \mathbb{R}^{N \times 10}$ and $w_2 \in \mathbb{R}^{N \times 10 \times 10}$ with $\pi(y \mid x) = \text{softmax}(w_1[x])_{y_1} \cdot \text{softmax}(w_2[x, y_1])_{y_2}$. The factorization is complete: its $9 + 10 \cdot 9 = 99$ free directions match the dimension of the simplex over 100 responses. Given the base transformer's

exact log-probabilities we set $w_1 = \log \sum_{y_2} \pi(y \mid x)$ and $w_2 = \log \pi(y \mid x) - w_1$, which reproduces the base distribution to within 10^{-4} in max-norm (asserted at run time).

RL. The default objective is the exact-expectation policy gradient with the exact mean baseline, $\nabla_\theta J = \frac{1}{N} \sum_x \sum_y \pi_\theta(y \mid x)\,[r(x,y) - V(x)]\,\nabla_\theta \log \pi_\theta(y \mid x)$, implemented as a weighted cross-entropy with detached weights. The sampled-GRPO experiment uses group size 8, group-standard-deviation normalization and one inner epoch. Optimizer Adam (default) or SGD, 400 steps, learning-rate grid $\{3 \times 10^{-4}, 10^{-3}, 3 \times 10^{-3}, 10^{-2}, 3 \times 10^{-2}\}$ for Adam and $\{0.3, 1, 3\}$ for SGD, applied identically to both policy classes where a grid is shared (Table 1). The reported operating point is, for each policy class and cell, the smallest learning rate whose final verifier reward is within 10^{-3} of the best. The camera-ready applies this one rule to every experiment, including verifier hardening, which the earlier version selected by strict argmax.

The mask-only controls (E9, E9b). One checkpoint per seed serves every universality condition. Its supervised target is contaminated with a shared string h and a per-prompt string s_x at every prompt, in identical proportion in all conditions, so the initial policy, the probability on each leak string and the initial tangent kernel are bit-identical across the sweep; the base probability on h agrees to six decimals. The verifier then accepts h on the m prompts in U and, in E9, s_x on the rest, giving exactly N accepted wrong pairs and a static false-positive rate of exactly $1/(|\mathcal{Y}| - 1)$ in every condition. E9b accepts nothing wrong outside U, so every accepted wrong string is h and its per-prompt base mass is identical across conditions, at the cost of a static false-positive rate of $u/99$ and a base hack fraction that scales with u (prompts that accept nothing wrong have $\rho_x = 0$). U is nested across m. The residual gradient in E9 is that the accepted string's base mass rises from 0.0098 to 0.0149 with u, because a shared-parameter SFT represents one string demonstrated at every prompt better than N distinct ones; the per-prompt arm responds to that gradient through rich-get-richer, which Corollary 1 permits since it is inherited rather than generated. We tried to remove the gradient by reweighting the two families in the supervised target until their realized probabilities matched; the mean gap closes but the per-prompt gap does not, because the shared network cannot represent an arbitrary per-prompt split. That is why we bracket the confound with two designs rather than eliminate it.

Per-prompt weight copies (E10). N independent copies of the same transformer, each initialized from the shared base checkpoint and trained on its own prompt alone with the same objective and optimizer, on the three smallest learning rates of the shared arm's grid. Copy x only ever evaluates prompt x, so training the copies in one loop is equivalent to training them separately. The matched shared-parameter arm is E1 restricted to the same four universality conditions and the same ten seeds, with slopes averaged per seed, which is why its slope (+0.0210) differs slightly from the seven-condition figure (+0.0177).

Verifier hardening (E6). The base model is contaminated with both leak families, one universal string and one idiosyncratic string per prompt. Three verifiers are then deployed from the same checkpoint: unpatched, universal leak removed, and all idiosyncratic leaks removed. The two patches remove exactly N accepted (prompt, wrong-response) pairs each. Both arms are trained at two learning rates (10^{-3} and 3×10^{-3} for the shared arm, thirty times that for the tabular arm, as in the KL sweep), and the operating point is chosen by the paper's standard rule, which picks 0.001 for the shared arm. Every statistic in Section 6.7 is a paired within-seed difference between the two patched verifiers over 10 seeds.

The threshold probe (E11). For each probed prompt x that accepts a leak h we compute by autograd the exact drift of $\log \pi_\theta(h \mid x) - \log \pi_\theta(g_x \mid x)$ under gradient flow, split into its own-prompt and cross-prompt parts, and the gradients of $\log \pi_\theta(h \mid x')$ and $\log \pi_\theta(g_x \mid x')$ at every prompt x', which give the same-string kernel rows $K_{\theta,xx'}$ and the probe's estimate of u_{eff} (Equation (2), with the own term included). The coherent-channel prediction is the $y' = h$ and $y' = g_x$ terms of Lemma 1 summed over $x' \neq x$, with the measured masses and kernel entries; the homogeneous formula uses the mean off-diagonal entry as κ, the diagonal entry as κ_s, and the leak's mean probability on accepting prompts as p_h. The probe runs at the base and at SGD steps 0, 3, 6, 10, 15, 20, 40 with step size 0.3, on 8 accepting prompts per condition at $m \in \{1, 4, 16, 64\}$ and 3 seeds, and once at the frozen blind base of E9b for the same m.

Full specification. Prompts are serialized as the token sequence $[\texttt{BOS}, a, b, y_1]$ over a vocabulary of 11 symbols, with learned token and positional embeddings, a causal mask, pre-norm blocks, 4 heads, feed-forward width 256 with GELU, final `LayerNorm`, and a 10-way output head shared across the two response positions. Embeddings are initialized $\mathcal{N}(0, 0.02^2)$ and the remaining parameters use PyTorch defaults. Optimization is full-batch over all N prompts with no minibatching and no gradient clipping. Adam uses $\beta_1 = 0.9$, $\beta_2 = 0.999$, $\varepsilon = 10^{-8}$ and zero weight decay; SGD uses no momentum. A run's seed sets the transformer initialization, the leak-string draw and, in E4, the rollout sampling; the competence permutation uses a separate fixed seed. E4 draws $G = 8$ responses per prompt at temperature 1 from the enumerated distribution, normalizes advantages by the group standard deviation (plus 10^{-4}), and takes one inner epoch with no importance ratio, clipping or reference-KL term. E5 adds $-\beta\,\mathrm{KL}(\pi_\theta(\cdot \mid x)\|\pi_{\mathrm{ref}}(\cdot \mid x))$ computed exactly against the frozen base.

Measurement. ρ, Λ and true accuracy are computed from the exact enumerated distribution over all 100 responses at all N prompts at every logged step; the only stochasticity is over seeds. The gradient decomposition and coherence probes average over fixed random subsamples of prompts, for cost. Per-prompt log-odds are clipped to ± 20 before averaging, so a prompt whose leak mass has collapsed cannot dominate Λ; in the headline Adam sweep this binds on a median of 1.6% of prompts, and the ordering of every reported series is unchanged at clipping thresholds of 20, 40, 60 and 200. The final metric of every run is recomputed in float64 from stored per-prompt masses. The two null-model checks in Section 6 agree to the last bit by construction: 400 steps of mirror descent at $\eta = 0.05$ reach exactly $\pi_0 e^{20r}$, the $\beta = 0.05$ endpoint of the KL grid.

	sweep	seeds	learning rates	notes
E1	universality, contiguous blocks	10	5, shared by both arms	headline sweep
E2	universality, permuted blocks	10	3, shared by both arms	base spread 0.0103
E3	universality $\times$ error rate	10	1 pair (10^{-3} / 3×10^{-2})	clean SFT floor
E4	sampled GRPO	10	3, shared by both arms	$G = 8$, std norm.
E5	KL sweep	10	1 pair (10^{-3} / 3×10^{-2})	6 values of β
E6	verifier hardening	10	2 pairs	standard rule
E7	prompt-set size $N \in \{16, 64\}$	10	3, shared by both arms	tests u versus m
E8	plain SGD	10	3, shared by both arms	robustness
E9	mask-only, constant error rate	10	5, shared by both arms	one frozen base per seed
E9b	mask-only, constant leak mass	5	5, shared by both arms	one frozen base per seed
E10	per-prompt weight copies	10	3	same architecture
E11	threshold probe	3	SGD 0.3	exact vs. coherent drift

Table 1: What was run in each experiment. Where a grid is shared by both arms the operating point is the smallest learning rate within 10^{-3} of the best verifier reward, chosen independently for each arm. E2, E3, E5, E6, E7 and E11 were run for the camera-ready from base models regenerated with the released code (Appendix E).

C The threshold probe

Reviewers of the earlier version asked two related questions: whether Proposition 2 predicts anything about the sweeps, given that with raw u it predicts suppression below $u \approx \bar{V} \geq 0.44$, and whether the instantaneous prediction can be compared with the exact drift before the verifier pass rate saturates. Figure 4 and the numbers below answer both.

Where the mass sits. Equation (2) has two readings. The mass-only reading sets every kernel entry to one and asks what share of the policy's mass on h sits on accepting prompts; the kernel-weighted reading includes the entries, and at small m is dominated by the own-prompt entry κ_s, which is several times the cross-prompt entries. In the headline bases the mass-only reading is 0.09, 0.23, 0.68 and 1.00 at $u = 1/64, 1/16, 1/4$ and 1, and the kernel-weighted reading is 0.65, 0.64, 0.94 and 1.00. The supervised stage puts about 0.0328 of mass on an idiosyncratic leak at the one prompt that accepts it and 0.0054 elsewhere, so the accepting prompts dominate the sum. In the blind base the mass on h is uniform, so the mass-only reading equals u by construction (0.01, 0.06, 0.25, 1.00) and the kernel-weighted reading is 0.08, 0.19, 0.33 and 1.00. At $u = 1$ the two bases represent h with the same cross-prompt coherence (+0.294 in the headline base against +0.255 in the blind base), and the blind base carries less mass on it (0.0355 against 0.0151) because its contamination budget




Figure 4: The threshold probe. Top left: the acceptance fraction of Equation (2) at the base model against raw universality u, in its mass-only and kernel-weighted readings for the headline and frozen blind bases; small dots are seeds and the dotted line is $u_{\text{eff}} = u$. Top right: along plain SGD, the fraction of probed prompts at which the coherent-channel prediction, and the homogeneous raw-u formula, have the same sign as the exact cross-prompt log-odds drift, with bootstrap 95% bands over the (seed, universality) runs. Bottom: the coherent-channel prediction against the exact drift for every probed prompt at every step, one panel per universality, on symmetric log axes. Shaded quadrants are where the two agree in sign, and each title gives the share of points there.

is split between two families. This is the representation difference a reviewer asked us to identify before drawing conclusions from the blind-base controls: at $u = 1$ the coherence is the same and the mass is lower, which works against amplification there; at $u < 1$ the difference is where the mass sits, not how coherently h is represented. The weights $w_{x'}$ in Equation (2) are positive for most entries: 13% of the same-string kernel entries at the headline bases are negative, carrying 9% of the absolute weight, so u_{eff} is a fraction in $[0, 1]$ to a good approximation there.

Predicted against exact drift. Along SGD the verifier pass rate of the universal-leak condition reaches 0.994 by step 40, while the idiosyncratic condition is still at 0.848, so the window in which $u_{\text{eff}} - \bar{V}$ changes sign is short at high u and long at low u. Over all probed (condition, step) means the coherent-channel prediction agrees in sign with the exact cross-prompt log-odds drift at 93% of points (28 points), and the homogeneous leading-order formula with its $1/N$ correction at 71%; per probed prompt the agreement is 70% and 53% over 672 prompts. The median ratio of the residual to the exact drift is 0.9. The channel the proposition isolates is therefore real, in the sense that its sign and the sign of the exact cross-prompt drift agree well above chance at the level of condition means and above chance per prompt, while the raw-u formula is at chance per prompt. But it is not the whole cross-prompt drift: the residual R of Definition 3, dominated by the shared machinery that raises the correct answers on every prompt, is of the same order as the channel itself. We present the proposition accordingly, as a statement about one channel and the quantity that sets its sign, and we use its heterogeneous form only to interpret the difference between the headline sweep and the blind-base controls.




Figure 5: Corollary 1, drawn. With shared parameters every prompt's gradient lands on the same weights, so a wrong answer accepted on some prompts and rejected on others is pushed both ways at once, and the net depends on how many prompts accept it and on how much mass the model puts on it there. With per-prompt parameters the cross-prompt kernel entries are identically zero, so the channel does not exist.




Figure 6: Mechanism. Left: the cross-prompt component of the exact drift of $\log \pi_\theta(h \mid x)$ at the base model (Lemma 1), identically zero for per-prompt parameters as Corollary 1 requires. Center: mean pairwise cosine between per-prompt gradients of each prompt's own leak string and of its correct answer; at low u the leaks are different strings, so the low value there is partly by construction. In both, small dots are the three seeds and markers their means ± 1 s.e.m. Right: contiguous versus randomized block membership, with whiskers of ± 1 s.e.m. over ten seeds.

D Additional results

Every learning rate. Table 2 lists, for each optimizer, learning rate and arm, the slope of $\Delta\rho$ per doubling of m with its bootstrap interval, the drift at the two ends of the sweep, the number of seeds in which the idiosyncratic leak is suppressed and the universal leak amplified, and the final verifier reward at $u = 1$.

Universality against error rate. Figure 8 shows the factorial of Section 6 as a field, and Figure 9 shows the same data seed by seed on a common scale.

Prompt-set size (E7). At fixed u the leading term of the homogeneous form of (3) carries no dependence on the number of prompts; the $1/N$ remainder differs fourfold between $N = 16$ and $N = 64$. Repeating the sweep at both sizes (10 seeds) gives, at $u = 1$, -0.024 ± 0.053 against $+0.021 \pm 0.028$, whereas at the same block size $m = 16$ (so $u = 1$ for the small set and $u = 1/4$ for the large one) they sit at -0.024 against -0.081. Across the 5 matched values of u the two sizes agree to within 0.016 at the three smallest values and differ by at most 0.045, at $u = 1$, where the seed spread is widest. Within the precision of ten seeds the controlling variable is the fraction u, not the count m.




Figure 7: Practice. Top left: sampled GRPO reproduces the pattern. Top center and right: a KL penalty pulls the policy back toward the filter baseline, at a cost in accuracy. In the top row small dots are seeds and markers their means ± 1 s.e.m. Bottom: two verifier patches that improve the static false-positive rate identically buy very different true accuracy. Each line joins one seed's two patched runs, which start from the same checkpoint, markers are means ± 1 s.e.m., each title gives the paired gap with its s.e.m., and the dotted line is the shared base accuracy, identical for every patch.

optimizer	arm	LR	slope	95% CI	$\Delta\rho(1/64)$	$\Delta\rho(1)$	neg. at $1/64$	pos. at 1	reward at 1
Adam	shared	0.0003	+0.0075	[+0.0030, +0.0121]	−0.103	−0.051	10/10	2/10	0.997
Adam	shared	0.001	+0.0176	[+0.0086, +0.0296]	−0.102	+0.028	10/10	5/10	1.000
Adam	shared	0.003	+0.0996	[+0.0753, +0.1251]	−0.098	+0.600	10/10	10/10	1.000
Adam	shared	0.01	+0.1287	[+0.1151, +0.1399]	+0.210	+0.869	0/10	10/10	1.000
Adam	shared	0.03	+0.0456	[+0.0246, +0.0632]	+0.331	+0.651	0/10	10/10	0.319 (diverged)
Adam	per-prompt	0.0003	+0.0000	[−0.0000, +0.0001]	−0.000	−0.000	8/10	2/10	0.527 (diverged)
Adam	per-prompt	0.001	+0.0001	[−0.0000, +0.0002]	+0.001	+0.002	2/10	10/10	0.644 (diverged)
Adam	per-prompt	0.003	+0.0004	[+0.0000, +0.0009]	+0.020	+0.021	0/10	10/10	0.870 (diverged)
Adam	per-prompt	0.01	+0.0020	[+0.0007, +0.0032]	+0.110	+0.116	0/10	10/10	0.982
Adam	per-prompt	0.03	+0.0028	[+0.0006, +0.0052]	+0.161	+0.164	0/10	10/10	0.997
Sampled GRPO	shared	0.0003	+0.0094	[+0.0047, +0.0145]	−0.102	−0.032	10/10	3/10	0.996
Sampled GRPO	shared	0.001	+0.0942	[+0.0743, +0.1135]	−0.098	+0.623	10/10	10/10	0.998
Sampled GRPO	shared	0.003	+0.1675	[+0.1594, +0.1742]	−0.077	+0.869	10/10	10/10	1.000
Sampled GRPO	per-prompt	0.0003	−0.0000	[−0.0001, +0.0000]	−0.005	−0.005	10/10	0/10	0.509 (diverged)
Sampled GRPO	per-prompt	0.001	−0.0001	[−0.0002, +0.0000]	−0.016	−0.016	10/10	0/10	0.584 (diverged)
Sampled GRPO	per-prompt	0.003	−0.0002	[−0.0005, +0.0001]	−0.042	−0.041	10/10	0/10	0.770 (diverged)
Plain SGD	shared	0.3	+0.1834	[+0.1773, +0.1889]	−0.077	+0.867	10/10	10/10	0.987
Plain SGD	shared	1	+0.0982	[+0.0718, +0.1161]	+0.153	+0.771	0/10	9/10	0.906
Plain SGD	shared	3	−0.0008	[−0.0197, +0.0158]	+0.274	+0.299	0/10	9/10	0.119 (diverged)
Plain SGD	per-prompt	0.3	−0.0001	[−0.0003, +0.0000]	−0.017	−0.017	10/10	0/10	0.534 (diverged)
Plain SGD	per-prompt	1	−0.0004	[−0.0008, +0.0000]	−0.045	−0.045	10/10	0/10	0.651 (diverged)
Plain SGD	per-prompt	3	−0.0006	[−0.0014, −0.0000]	−0.076	−0.077	10/10	0/10	0.837 (diverged)

Table 2: The universality effect at every learning rate. Slopes are per doubling of m; intervals are bootstrap 95% over ten seeds. The last column is the final verifier reward at $u = 1$ for that arm, with divergent settings marked.




Figure 8: The factorial as a field. Each cell is one (universality, error rate) condition; darker is a leak more strongly suppressed relative to the filter baseline. The right column and bottom row are the marginal means on the same color scale. Total base hack mass is fixed at ε in every cell, so the horizontal trend reflects the same mass spread over more accepted strings rather than a general property of audits.




Figure 9: The factorial seed by seed, common y-scale: dots are seeds, bars cell means, and lines join the means of one color. Left: log-odds drift grouped by universality, one color per false-positive rate. Right: the same data grouped by the static false-positive rate, one color per universality. Varying the accepted wrong responses per prompt from 1–8 moves the false-positive rate over 1.0–8.1% and the drift from -5.54 to -6.85; the same eightfold range of universality moves it from -7.19 to -4.15.

Figure 10 collects the remaining robustness views: the universality effect across the whole Adam grid, hack-fraction trajectories at the two extreme conditions for both policy classes, the sweep at two prompt-set sizes, and the sweep under plain SGD.

E Reproducibility

Every experiment runs on CPU; no GPU is used. The code, the raw result files and the figure code that regenerates every figure and every number quoted in the text are released together. The macro file that holds the numbers is written by the figure code, so nothing is transcribed by hand except settings (the step count, the contamination rate, the GRPO group size) and a few diagnostics quoted inline (the clipping rates and the $N\kappa/\kappa_s$ values).

Three levels of reproduction apply. From an archived base checkpoint, on the same machine and code revision, the RL stage is bit-reproducible in weights and in every reported metric. Regenerating a base by rerunning the supervised stage is deterministic, but a base rebuilt under a different version




Figure 10: Top: the universality effect across the whole Adam learning-rate grid for both policy classes, as the mean drift over ten seeds on one color scale. Bottom left: hack-fraction trajectories for the extreme universality conditions, both policy classes, with thin lines for seeds; the per-prompt curves coincide. Bottom center: the sweep repeated at two prompt-set sizes, plotted against u, with $N = 64$ in orange. Bottom right: the same sweep under plain SGD. In the bottom center and right panels small dots are seeds and markers their means ± 1 s.e.m.

of the numerical libraries differs from an archived one by up to about 2×10^{-2} on the base metrics. A run from scratch therefore reproduces the reported drifts and the conclusions drawn from them, which are an order of magnitude larger, but not every archived value digit for digit.

Provenance for the camera-ready: E1, E4, E8, E9, E9b and E10 are the archived runs of the accepted version. E2, E3, E5, E6 and E7, which the accepted version reported at three seeds, were re-run from scratch at ten seeds (E6 with the paper's standard operating rule and both learning rates stored; E2 without the learning rate 3×10^{-2}, which diverged in every seed of the earlier version and was never selected), and E11 is new; these use base models regenerated with the released code, and the E6 base models of the earlier version were not retained. Seeds 0–4 of E1 come from an earlier revision whose configuration records carry fewer logging fields, with no training setting differing; their stored base models are bit-identical and the current code reproduces that half to 10^{-8}. The $m = 1$ condition of E1 ran past the reported seed budget during an attempt to raise the budget for every condition; the figure code caps every load at ten seeds, uniformly and independently of results, so the design is balanced and the excess runs enter no reported statistic.