

08 - UI UX Requirements

Visor DOM-to-Agent Context Compiler
DOC-08 | 0.1 requirements pack | Generated 2026-06-14

This UI requirements document defines the popup, preview, settings, debug inspector, interaction states, and accessibility expectations.

Field	Value
Owner	Rohan PX / Visor project
Audience	AI coding agent, reviewer, future contributors
Status	Draft baseline for MVP build
Decision rule	MVP is local-first, minimal-permission, Chrome Manifest V3, no backend unless explicitly enabled.

Document control

Item	Value
Project	Visor DOM-to-Agent Context Compiler
Document code	DOC-08
Generated on	2026-06-14
Primary goal	Turn raw webpage DOM into safe, structured, agent-ready context.
MVP boundary	Chrome extension, local-only compiler, JSON/Markdown export, privacy redaction, tests.

1. UX principle

The UI must feel like a compiler control panel, not a chatbot. The user should understand what page is being compiled, what mode is selected, what privacy risk exists, and what output will be copied or exported.

2. Screen inventory

Screen	Purpose	MVP?
Popup	Fast compile and copy from active tab.	Yes
Preview page	Inspect full context, privacy warnings, token profile.	Yes
Settings page	Configure default mode, token budget, redaction, site profiles.	Yes
Debug inspector	View kept/removed blocks and scores.	P1 but recommended
Site profiles	Domain-specific preserve/ignore selectors.	P1
History	Saved local/cloud contexts.	Later
Export templates	Custom prompt formats.	P1/P2

3. Popup layout

```
-----  
Visor  
Current page: <title truncated>  
Risk: Low / Medium / High  
Mode: [ Compact v ] Privacy: [ Medium v ]  
Token budget: [ 4000 ]  
  
[ Compile Page ]  
  
Output preview:  
{ schemaVersion: "agent_context.v1", ... }  
  
[ Copy JSON ] [ Copy Markdown ] [ Full Preview ]  
-----
```

4. Preview page requirements

ID	Requirement	Priority	Acceptance signal
UX-001	Show page title, URL, page type, risk level, and token count at the top.	P0	Header summary visible after compile.
UX-002	Show privacy warnings before main content.	P0	High-risk warning cannot be missed.
UX-003	Show tabs for Summary, JSON, Markdown, Actions, Data, Debug.	P0	User can switch views.
UX-004	Allow copy JSON, copy Markdown, and download JSON.	P0	Clipboard and file output work.
UX-005	Show schema validation status.	P0	Valid/invalid status visible.

ID	Requirement	Priority	Acceptance signal
UX-006	Do not render extracted HTML as active HTML.	P0	Preview displays escaped text.

5. Settings page

- Default output mode: compact, detailed, agent_action, rag, debug.
- Default privacy level: low, medium, strict.
- Token budget: numeric preset or custom input.
- Ignored selectors: user-defined CSS selectors.
- Preserved selectors: user-defined CSS selectors.
- Blocked domains: never compile list.
- Debug mode toggle.
- Clear local data button.

6. Interaction states

State	UI behavior
Idle	Show active page title and Compile button.
Compiling	Disable button, show progress text, allow cancel when possible.
Success	Show preview, token count, privacy status, copy buttons.
Partial success	Show warning banner and available partial context.
Restricted page	Explain that browser-internal pages cannot be compiled.
High privacy risk	Require deliberate export click; show redaction status.

7. Accessibility requirements

- Keyboard accessible controls.
- Visible focus states.
- High contrast readable text.
- ARIA labels for icon-only buttons.
- No tiny-only color-coded risk indicators; include text label.
- Copy/export result should announce success/failure textually.