

15 - Glossary and Terms

Visor DOM-to-Agent Context Compiler
DOC-15 | 0.1 requirements pack | Generated 2026-06-14

This glossary defines the terms and requirement prefixes used across the entire requirements pack.

Field	Value
Owner	Rohan PX / Visor project
Audience	AI coding agent, reviewer, future contributors
Status	Draft baseline for MVP build
Decision rule	MVP is local-first, minimal-permission, Chrome Manifest V3, no backend unless explicitly enabled.

Document control

Item	Value
Project	Visor DOM-to-Agent Context Compiler
Document code	DOC-15
Generated on	2026-06-14
Primary goal	Turn raw webpage DOM into safe, structured, agent-ready context.
MVP boundary	Chrome extension, local-only compiler, JSON/Markdown export, privacy redaction, tests.

1. Glossary

Term	Definition
Agent context	A structured package of page information that an AI agent can consume safely.
AgentContext	The versioned JSON output schema produced by Visor.
ActionElement	A structured representation of a clickable or editable page element such as a button, link, input, or form.
activeTab	A browser extension permission that grants temporary access to the active tab after a user gesture.
Compiler	The pipeline that transforms PageSnapshot into AgentContext.
Content script	Extension script that runs in the context of a web page and can access the DOM under permission constraints.
DOM	Document Object Model; the browser representation of a webpage as a tree of nodes.
Dedupe	Removal or compression of repeated text blocks.
Debug mode	Output mode that shows kept blocks, removed blocks, scores, and compiler notes.
Extraction	Process of reading visible and semantic content from a webpage DOM.
Host permissions	Extension permissions that allow access to specific origins or URL patterns.
Manifest V3	Current Chrome extension manifest architecture using service workers and updated permissions/security model.
Noise	Page material that usually does not help agents: ads, repeated navigation, cookie banners, hidden nodes, footer clutter.
PageSnapshot	Intermediate internal model created from the DOM before context compilation.
Prompt injection	A malicious or accidental instruction inside untrusted content that tries to alter an AI agent behavior.
Privacy redaction	Masking sensitive values such as emails, phones, tokens, and password fields.
RAG	Retrieval-Augmented Generation; using chunks of source content with metadata for retrieval.
Selector hint	A non-guaranteed CSS/XPath-like hint that helps locate an element later.
Service worker	Event-driven background script used by Manifest V3 extensions.
Site profile	Domain-specific extraction rules such as preserve or ignore selectors.
Token budget	Estimated maximum amount of text to include for an LLM or agent.
Untrusted data	Content from the webpage that must never be treated as system/developer instruction.

2. Naming conventions

- Use PageSnapshot for internal raw-but-cleaned DOM representation.
- Use AgentContext for final output to agents.
- Use ActionElement for anything clickable, editable, or submit-related.
- Use privacyReport for warnings and redaction results.

- Use compilerNotes for decisions, warnings, and debug evidence.

3. Requirement prefix map

Prefix	Document	Meaning
FR	System Requirements Specification	Functional requirement.
NFR	System Requirements Specification	Non-functional requirement.
EXT	Browser Extension Requirements	Extension-specific behavior.
COMP	Context Compiler Spec	Compiler behavior.
SEC	Privacy Security Threat Model	Security/privacy behavior.
UX	UI UX Requirements	Interface and interaction behavior.
API	Backend API Requirements	Future backend behavior.
DB	Storage Database Requirements	Storage/migration behavior.
QA	Testing QA Acceptance Criteria	Testing and acceptance behavior.
REL	Deployment DevOps Requirements	Release behavior.