

[0] emcee: Be the life of the party

Rohan Panchwagh – 5/15/2025

[1] The emcee package is a package primarily written in Python. Its main goal is to generate the posterior distribution of parameters for a model given an input likelihood function and data. This is primarily used when you have extremely noisy data, non-Gaussian or non-analytic error, or you don't trust your uncertainty estimates. It is also better at handling high-dimensional problems. In comparison with something like maximum-likelihood estimation, emcee allows you to do error propagation on parameters even if you distrust the error on the individual data points (for example, if they are underestimated).

[2] I selected this package because I use Monte Carlo in my research and wanted to learn more about Markov Chain methods (in particular how they are used to sample distributions).

[3] The emcee package was first released in 2012, by Foreman-Mackey, Hogg, Lang, and Goodman, based on the affine-invariant ensemble sampler proposed by Goodman and Weare in 2010. Before emcee, the main one used was PyMC (though it wasn't as scalable as emcee). Current packages that do something similar are NumPyro (compatible with GPU acceleration), and pymcmcstat (adapted from a MATLAB toolbox). The current version is 3.1.6.

[4] emcee is still maintained by the original authors, primarily Foreman-Mackey. The CONTRIBUTING.md file in the emcee github contains instructions on how to contribute.

[5,6] The emcee package is extremely easy to install. Simply by using the command “!pip install emcee”, the package can be installed and is ready to go. However, installing visualizing tools (such as corner) can make understanding the outputs of emcee easier, and is recommended.

[7] The source code can be found on the Github, in the “src/emcee” file. The contained files are mainly python files, with a test file, moves file, and a backend file.


[8] The radvel and exoplanet libraries use (or are compatible with) the use of emcee for determining exoplanet orbital parameters; lmfit uses emcee as a comparison with the nonlinear least squares + confidence interval fits.

[9] The code is pure python, meaning that it can be run as a python script in any development tool, as well as in a Jupyter notebook (which is where you would run it to get visualizations).


[10] The code is shown in the example Jupyter notebook.

[11] emcee does not contain its own plotting software; typically, matplotlib or corner are used for visualization (depending on what one needs to visualize).

[12] Here is a figure showing the output parameter distribution, against the true values for the data.



The second figure shows the corner plots for our parameters- these give the covariances and uncertainties for each parameter.



[13] The emcee package is purely Python, with no dependencies on C/C++/Fortran.

[14] There are two inputs to the package; one is the likelihood function for the data (or typically, the log of the likelihood function for the data), and the other is the data itself. Test data can be generated by drawing from a distribution or using random number generators; or one can use actual data. The notebook data is generated by using a random number generator on a linear model.

[15] The output is a *posterior distribution* of parameter values; instead of returning the “best-fit” value (as done in curve fits), it returns a probability distribution (weighted by likelihood) of the parameter values in the parameter space.

[16] The code provides ways of visualizing the progression of the walkers, as well as the autocorrelation times, to ensure that the entire parameter space is being sufficiently explored. One can essentially “benchmark” by inserting in a known distribution, injecting it with some error, and seeing if the returned posterior distribution matches the true model.

[17] Once you look at the visualization of the walkers “burning in” to explore the parameter space, you can be sure that the posterior distribution will be accurate.

[18] emcee mainly depends on 3 packages: numpy, matplotlib, and corner. I figured this out by looking at their example code: numpy is used for random number generation and matrix manipulation, matplotlib is used for plotting distributions and model data, and corner is used to visualize the shapes of the uncertainty distributions for each parameter.

[19] emcee has a website with worked examples, as well as comprehensive explanations for each function unique to emcee. There is also more documentation on the github for emcee. Overall, I felt that the website did a good job explaining what each function did, and how each visualization should be interpreted, and the example given was strong enough to enable a user to immediately apply emcee to sample data. However, there wasn’t much information on the actual theory behind MCMC, and that needed to be found elsewhere (such as Wikipedia).

[20, 21]

#### References:

- emcee preferred citation:  
<https://ui.adsabs.harvard.edu/abs/2013PASP..125..306F/abstract>
- Goodman and Weare paper: Jonathan Goodman. Jonathan Weare. "Ensemble samplers with affine invariance." Commun. Appl. Math. Comput. Sci. 5 (1) 65 - 80, 2010. <https://doi.org/10.2140/camcos.2010.5.65>
- corner: <https://ascl.net/corner>

- PyMC: <https://ascl.net/pymc>
- radvel: <https://ascl.net/radvel>
- exoplanet: <https://ascl.net/exoplanet>
- lmfit: <https://ascl.net/lmfit>
- NumPyro: <https://doi.org/10.48550/arXiv.1912.11554>
- pyMCMCstat: Miles, (2019). pymcmcstat: A Python Package for Bayesian Inference Using Delayed Rejection Adaptive Metropolis. Journal of Open Source Software, 4(38), 1417, <https://doi.org/10.21105/joss.01417>

[22] Using ADS, there are 10,640 citations for the emcee paper. Two of the most recent ones are given here: <https://ui.adsabs.harvard.edu/abs/2025NewA..11902390P/abstract> and <https://ui.adsabs.harvard.edu/abs/2025NewA..11802374N/abstract> .

[23] I didn't really have to learn new python methods since almost everything was done using random number generators (numpy) and matplotlib visualizations. The only new thing I learned was corner, but since I was only using it to generate and interpret a plot, I didn't have to have full understanding of exactly how corner works.

[24] I had no exposure to emcee before this project; this is my first time using it. I worked alone to complete this project.