

BRACT's

Vishwakarma Institute of Information Technology, Pune Practical Implementation Sheet

Department: CS-AI Semester: 5 Academic Year: 2026-27

Division: E Batch: 2 Practical No:6 Roll no: 07 PRN No: 12410236

Subject Name: Deep Learning

Name of Student: Rohan Devidas Patil

Problem Statement: Design and implement a Convolutional Neural Network (CNN) for image classification using the Tom

Algorithm:

Step 1: Import the required libraries such as NumPy, Pandas, Matplotlib, TensorFlow/Keras, YFinance, and the necessary modules from scikit-learn.

Step 2: Load the **Apple (AAPL) stock dataset** using Yahoo Finance for the specified date range and inspect the dataset by displaying its shape, columns, and sample records.

Step 3: Perform **data preprocessing** by handling missing values, selecting the required stock-price feature, and arranging the data in chronological order.

Step 4: Normalize the selected stock-price data using **MinMaxScaler** to scale the values to a suitable range for training the neural network.

Step 5: Create **time-series sequences** using a fixed number of previous observations as input and the next stock-price value as the target.

Step 6: Split the generated sequences into **training and testing datasets** while maintaining the chronological order of the stock data.

Step 7: Build an **LSTM-based Sequential Neural Network** using LSTM, Dropout, and Dense layers, and compile the model using the Adam optimizer and an appropriate loss function.

Step 8: Train the LSTM model on the training data using a specified number of **epochs and batch size**, while using early stopping to prevent overfitting.

Step 9: Use the trained model to **predict stock prices** for the testing dataset and evaluate its performance using **Mean Absolute Error (MAE)** and **Mean Squared Error (MSE/RMSE)**.

Step 10: Visualize the results by plotting the **actual vs. predicted AAPL stock prices** and analyze the model's prediction performance.

Code:

```
# Step 1: Install KerasTuner

!pip install -q keras-tuner

# Step 2: Import Required Libraries

import os

import zipfile

import numpy as np

import matplotlib.pyplot as plt

import seaborn as sns

import tensorflow as tf

import keras_tuner as kt

from google.colab import files

from tensorflow.keras import layers, models

from sklearn.metrics import classification_report, confusion_matrix

print("TensorFlow:", tf.__version__)

print("Keras Tuner:", kt.__version__)

# Step 3: Download Apple Disease Dataset

!wget -q -O apple-disease.zip \

"https://www.kaggle.com/api/v1/datasets/download/rm1000/apple-disease-dataset-original"

print("Dataset downloaded successfully!")
```

```

print(
    "ZIP size:",
    os.path.getsize("apple-disease.zip") / (1024 * 1024),
    "MB"
)

# Step 4: Extract Dataset

!rm -rf /content/apple_dataset

!mkdir -p /content/apple_dataset

!unzip -q apple-disease.zip -d /content/apple_dataset

print("Dataset extracted successfully!")

# Step 5: Inspect Dataset Structure

for root, dirs, file_list in os.walk("/content/apple_dataset"):

    level = root.replace(

        "/content/apple_dataset", ""

    ).count(os.sep)

    if level <= 2:

        print(root)

        for d in dirs:

            print("  ", d)

# Step 6: Locate Apple Dataset Folder

EXPECTED_CLASSES = {

    "Apple___Apple_scab",

    "Apple___Black_rot",

    "Apple___Cedar_apple_rust",

```

```

    "Apple___healthy"
}

DATASET_PATH = None

for root, dirs, file_list in os.walk("/content/apple_dataset"):

    if EXPECTED_CLASSES.issubset(set(dirs)):

        DATASET_PATH = root

        break

if DATASET_PATH is None:

    raise FileNotFoundError(

        "Could not automatically find the four Apple "

        "class folders. Check the dataset structure."

    )

print("Dataset path:", DATASET_PATH)

print("Classes found:", os.listdir(DATASET_PATH))

# Step 7: Count Images in Each Class

for class_name in sorted(EXPECTED_CLASSES):

    class_path = os.path.join(

        DATASET_PATH,

        class_name

    )

    count = sum(

        f.lower().endswith(

            (".jpg", ".jpeg", ".png", ".bmp", ".webp")

        )

    )

```

```

        for f in os.listdir(class_path)
    )

    print(
        f"{class_name}: {count} images"
    )

# Step 8: Load Training and Validation Dataset

IMG_SIZE = (128, 128)

BATCH_SIZE = 32

SEED = 42

train_ds = tf.keras.utils.image_dataset_from_directory(
    DATASET_PATH,
    validation_split=0.20,
    subset="training",
    seed=SEED,
    image_size=IMG_SIZE,
    batch_size=BATCH_SIZE
)

val_ds = tf.keras.utils.image_dataset_from_directory(
    DATASET_PATH,
    validation_split=0.20,
    subset="validation",
    seed=SEED,
    image_size=IMG_SIZE,
    batch_size=BATCH_SIZE
)

```

```

)

class_names = train_ds.class_names

num_classes = len(class_names)

print("Class names:", class_names)

print("Number of classes:", num_classes)

# Step 9: Display Sample Images

plt.figure(figsize=(10, 8))

for images, labels in train_ds.take(1):

    for i in range(min(9, len(images))):

        ax = plt.subplot(

            3, 3, i + 1

        )

        plt.imshow(

            images[i].numpy().astype("uint8")

        )

        plt.title(

            class_names[labels[i]]

        )

        plt.axis("off")

plt.tight_layout()

plt.show()

# Step 10: Apply TensorFlow AUTOTUNE

AUTOTUNE = tf.data.AUTOTUNE

train_ds = (

```

```

train_ds

.cache()

.shuffle(1000)

.prefetch(AUTOTUNE)
)
val_ds = (
    val_ds

    .cache()

    .prefetch(AUTOTUNE)
)
print("tf.data.AUTOTUNE enabled successfully!")

# Step 11: Data Augmentation

data_augmentation = tf.keras.Sequential([

    layers.RandomFlip(

        "horizontal"

    ),

    layers.RandomRotation(

        0.15

    ),

    layers.RandomZoom(

        0.10

    )

])

```

```
print("Data augmentation ready.")
```

```
# Step 12: Build CNN Model
```

```
def build_model(hp):
```

```
    model = models.Sequential([
```

```
        # Input layer
```

```
        layers.Input(
```

```
            shape=(128, 128, 3)
```

```
        ),
```

```
        # Data augmentation
```

```
        data_augmentation,
```

```
        # Normalize pixel values
```

```
        layers.Rescaling(
```

```
            1.0 / 255
```

```
        ),
```

```
        # First Convolution Block
```

```
        layers.Conv2D(
```

```
            filters=hp.Choice(
```

```
                "filters_1",
```

```
                [32, 64]
```

```
            ),
```

```
            kernel_size=(3, 3),
```

```
            activation="relu",
```

```
            padding="same"
```

```
        ),
```



```
layers.MaxPooling2D(),  
  
# Second Convolution Block  
  
layers.Conv2D(  
    filters=hp.Choice(  
        "filters_2",  
        [64, 128]  
    ),  
    kernel_size=(3, 3),  
    activation="relu",  
    padding="same"  
),  
  
layers.MaxPooling2D(),  
  
# Third Convolution Block  
  
layers.Conv2D(  
    filters=hp.Choice(  
        "filters_3",  
        [128, 256]  
    ),  
    kernel_size=(3, 3),  
    activation="relu",  
    padding="same"  
),  
  
layers.MaxPooling2D(),  
  
# Flatten layer
```

```
layers.Flatten(),  
  
# Dense layer  
layers.Dense(  
    units=hp.Choice(  
        "dense_units",  
        [128, 256, 512]  
    ),  
    activation="relu"  
),  
  
# Dropout layer  
layers.Dropout(  
    hp.Float(  
        "dropout",  
        0.2,  
        0.5,  
        step=0.1  
    )  
),  
  
# Output layer  
layers.Dense(  
    num_classes,  
    activation="softmax"  
)  
])
```

```
# Learning rate

learning_rate = hp.Choice(

    "learning_rate",

    [

        0.001,

        0.0005,

        0.0001

    ]

)

# Compile model

model.compile(

    optimizer=tf.keras.optimizers.Adam(

        learning_rate=learning_rate

    ),

    loss="sparse_categorical_crossentropy",

    metrics=["accuracy"]

)

return model

# Step 13: Create Hyperband Tuner

tuner = kt.Hyperband(

    build_model,

    objective="val_accuracy",

    max_epochs=10,

    factor=3,
```

```

    directory="/content/tuner_results",

    project_name="apple_disease",

    overwrite=True

)

print("Hyperband tuner created successfully!")

# Step 14: Perform Automatic Hyperparameter Tuning

tuner.search(

    train_ds,

    validation_data=val_ds,

    epochs=10

)

# Step 15: Display Best Hyperparameters

best_hps = tuner.get_best_hyperparameters(

    num_trials=1

)[0]

print("=" * 50)

print("BEST HYPERPARAMETERS")

print("=" * 50)

print(

    "Conv1 filters :",

    best_hps.get("filters_1")

)

print(

    "Conv2 filters :",

```

```

        best_hps.get("filters_2")
    )
    print(
        "Conv3 filters :",
        best_hps.get("filters_3")
    )
    print(
        "Dense units  :",
        best_hps.get("dense_units")
    )
    print(
        "Dropout      :",
        best_hps.get("dropout")
    )
    print(
        "Learning rate :",
        best_hps.get("learning_rate")
    )

# Step 16: Get Best CNN Model
best_model = tuner.get_best_models(
    num_models=1
)[0]
best_model.summary()

# Step 17: Train Best CNN Model

```

```
history = best_model.fit(
    train_ds,

    validation_data=val_ds,
    epochs=15
)

# Step 18: Evaluate Model

loss, accuracy = best_model.evaluate(
    val_ds
)

print("=" * 50)

print("MODEL PERFORMANCE")

print("=" * 50)

print(
    f"Validation Loss: {loss:.4f}"
)

print(
    f"Validation Accuracy: "
    f"{accuracy:.4f} "
    f"({accuracy * 100:.2f}%"
)

# Step 19: Plot Training and Validation Accuracy

plt.figure(figsize=(8, 5))

plt.plot(
```

```
    history.history["accuracy"],
    label="Training Accuracy"
)
plt.plot(
    history.history["val_accuracy"],
    label="Validation Accuracy"
)
plt.xlabel("Epoch")
plt.ylabel("Accuracy")
plt.title(
    "Apple Disease CNN Accuracy"
)
plt.legend()
plt.grid()
plt.show()

# Step 20: Plot Training and Validation Loss
plt.figure(figsize=(8, 5))
plt.plot(
    history.history["loss"],
    label="Training Loss"
)
plt.plot(
    history.history["val_loss"],
    label="Validation Loss"
```

```
)  
plt.xlabel("Epoch")  
plt.ylabel("Loss")  
plt.title(  
    "Apple Disease CNN Loss"  
)  
plt.legend()  
plt.grid()  
plt.show()  
  
# Step 21: Classification Report  
y_true = []  
y_pred = []  
  
for images, labels in val_ds:  
    predictions = best_model.predict(  
        images,  
        verbose=0  
    )  
    predicted_labels = np.argmax(  
        predictions,  
        axis=1  
    )  
    y_true.extend(  
        labels.numpy()  
    )  
)
```



```
y_pred.extend(
    predicted_labels
)
y_true = np.array(y_true)
y_pred = np.array(y_pred)
print(
    classification_report(
        y_true,
        y_pred,
        target_names=class_names
    )
)
# Step 22: Confusion Matrix
cm = confusion_matrix(
    y_true,
    y_pred
)
plt.figure(figsize=(8, 6))
sns.heatmap(
    cm,
    annot=True,
    fmt="d",
    xticklabels=class_names,
    yticklabels=class_names
```

```
)  
  
plt.xlabel("Predicted")  
  
plt.ylabel("Actual")  
  
plt.title(  
    "Apple Disease Confusion Matrix"  
)  
  
plt.xticks(rotation=45)  
  
plt.yticks(rotation=0)  
  
plt.tight_layout()  
  
plt.show()  
  
# Step 23: Save the Trained Model  
  
MODEL_PATH = (  
    "/content/apple_disease_cnn.keras"  
)  
  
best_model.save(  
    MODEL_PATH  
)  
  
print(  
    "Model saved to:",  
    MODEL_PATH  
)  
  
# Step 24: Upload an Apple Leaf Image  
  
uploaded = files.upload()  
  
if not uploaded:
```

```
raise ValueError(

    "No image was uploaded."

)

filename = list(

    uploaded.keys()

)[0]

print(

    "Uploaded:",

    filename

)

# Step 25: Predict Apple Plant Disease

disease_names = {

    "Apple___Apple_scab":

        "Apple Scab",

    "Apple___Black_rot":

        "Apple Black Rot",

    "Apple___Cedar_apple_rust":

        "Apple Cedar Apple Rust",

    "Apple___healthy":

        "Healthy Apple Leaf"

}

# Load image

img = tf.keras.utils.load_img(

    filename,
```

```
        target_size=IMG_SIZE
    )

    # Convert image to array

    img_array = tf.keras.utils.img_to_array(

        img
    )

    # Add batch dimension

    img_array = tf.expand_dims(

        img_array,

        axis=0
    )

    # Predict

    predictions = best_model.predict(

        img_array,

        verbose=0
    )

    # Get predicted class

    predicted_index = np.argmax

        predictions[0]
    )

    predicted_class = class_names[

        predicted_index
    ]

    # Calculate confidence
```

```

confidence = float(
    np.max(
        predictions[0]
    ) * 100
)

# Convert class name to readable name
predicted_disease = disease_names.get(
    predicted_class,
    predicted_class
)

# Display prediction
print("=" * 50)
print("APPLE DISEASE PREDICTION")
print("=" * 50)
print(
    "Disease :",
    predicted_disease
)

print(
    f"Confidence : "
    f"{confidence:.2f}%"
)

print("=" * 50)

# Display uploaded image

```

```

plt.figure(figsize=(7, 7))

plt.imshow(img)

plt.axis("off")

plt.title(

    f"{predicted_disease}\n"

    f"Confidence: {confidence:.2f}%"

)

plt.show()

# Display Probability for All Classes

print(

    "Prediction probabilities:"

)

for class_name, probability in zip(

    class_names,

    predictions[0]

):

    readable_name = disease_names.get(

        class_name,

        class_name

    )

    print(

        f"{readable_name:25s}: "

        f"{probability * 100:.2f}%"

    )

```

Output:


Model: "sequential"


Layer (type)	Output Shape	Param #
sequential (Sequential)	(None, 128, 128, 3)	0
rescaling (Rescaling)	(None, 128, 128, 3)	0
conv2d (Conv2D)	(None, 128, 128, 32)	896
max_pooling2d (MaxPooling2D)	(None, 64, 64, 32)	0
conv2d_1 (Conv2D)	(None, 64, 64, 64)	18,496
max_pooling2d_1 (MaxPooling2D)	(None, 32, 32, 64)	0
conv2d_2 (Conv2D)	(None, 32, 32, 256)	147,712
max_pooling2d_2 (MaxPooling2D)	(None, 16, 16, 256)	0
flatten (Flatten)	(None, 65536)	0
dense (Dense)	(None, 512)	33,554,944
dropout (Dropout)	(None, 512)	0
dense_1 (Dense)	(None, 4)	2,052

Total params: 33,724,100 (128.65 MB)


Trainable params: 33,724,100 (128.65 MB)

Non-trainable params: 0 (0.00 B)





	precision	recall	f1-score	support
Apple__Apple_scab	0.95	0.78	0.86	91
Apple__Black_rot	0.71	1.00	0.83	91
Apple__Cedar_apple_rust	0.98	1.00	0.99	94
Apple__healthy	0.99	0.78	0.87	112
accuracy			0.88	388
macro avg	0.90	0.89	0.89	388
weighted avg	0.91	0.88	0.89	388



=====

APPLE DISEASE PREDICTION

=====

Disease : Apple Black Rot
Confidence : 100.00%

=====

Apple Black Rot
Confidence: 100.00%



Prediction probabilities:

Apple Scab	: 0.00%
Apple Black Rot	: 100.00%
Apple Cedar Apple Rust	: 0.00%
Healthy Apple Leaf	: 0.00%