RONIT | DETERMINISTIC COMPLIANCE AND WORKFLOW

Meeting purpose

Monday maps the existing deterministic compliance tools. Tuesday verifies the campaign and schedule facts and how those feed the workflow. Show exactly how a spot is checked; do not describe an LLM as deciding whether a spot breaches a rule.

Suggested meeting script

"I traced how the supplied campaign, booked-spot, and schedule data become a campaign profile and spot-level compliance result. Each spot is checked deterministically in order: WINDOW, INDEX, CHILDREN, FREQUENCY, then SEPARATION. These facts support the assessment workflow, while the final human decision remains with an authorized controller."

What to explain and show

- Why: scheduling rules are safety-critical and need repeatable checks.
- What: campaign data, spot scheduling, prediction, and workflow modules; identify the exact files changed and the issue each change addressed.
- How: load the live inputs, select a campaign, fetch its spots/schedule, then show the profile, breach codes, exposure, and decision state.

Inputs -> outputs

Inputs: open_campaigns.csv, booked_spots.csv, programme_schedule.csv, open_campaign_notes.csv, plus category code passages from retrieval.
Outputs: campaign profile, schedule rows, per-spot breach checks, exposure/first transmission facts, and workflow assessment/decision state.

FILES AND DEMO

Code files

Project/tools/campaign_data_tools.py
Project/tools/prediction_tools.py
Project/tools/retrieval_tools.py
Project/tools/schedule_tools.py
Project/agentic/agents.py
Project/agentic/graph.py
Project/agentic/nodes.py
Project/agentic/state.py

Live input files

Project/data/input/open_campaigns.csv
Project/data/input/booked_spots.csv
Project/data/input/programme_schedule.csv
Project/data/input/open_campaign_notes.csv

Run demo from Project PowerShell

Start Python with python, then load the live tables:

```
from config import config
from data_pipeline.dataset_loader import load_raw_dataset
from tools.campaign_data_tools import fetch_campaign_profile,
    fetch_campaign_spots, fetch_campaign_schedules
campaigns = load_raw_dataset(config.OPEN_CAMPAIGNS_FILE)
spots = load_raw_dataset(config.BOOKED_SPOTS_FILE)
reference = str(campaigns.iloc[0][config.CAMPAIGN_REFERENCE_COLUMN])
profile = fetch_campaign_profile(campaigns, reference)
campaign_spots = fetch_campaign_spots(spots, reference)
schedule = load_raw_dataset(config.PROGRAMME_SCHEDULE_FILE)
campaign_schedule = fetch_campaign_schedules(schedule, campaign_spots)
```

Show profile/reference, booked spot count, schedule rows, breach codes, exposure, first transmission, and the workflow status where available.