COE 2026-EXPLEO-KIOT-SDET-III

Quiz navigation

1	2	3	4	5
6	7	8	9	10
11	12	13	14	15
16	17	18	19	20

Show one page at a time
Finish review

Status	Finished
Started	Wednesday, 15 April 2026, 1:56 PM
Completed	Wednesday, 15 April 2026, 2:19 PM
Duration	22 mins 53 secs
Marks	18.00/20.00
Grade	10.00 out of 20.00 (90%)

Question **1**
Incorrect
Mark 0.00 out of 10.00
Flag question

Which Selenium method checks whether an element is currently visible on the page?

1. isClickable()
2. isSelected()
3. isDisplayed()
4. isVisible() ✗

Your answer is incorrect.
The correct answer is: isDisplayed()

Question **2**
Correct
Mark 10.00 out of 10.00
Flag question

Why might By.cssName() fail when used with multiple class values in an element?

1. Classes are ignored by Selenium
2. It only works for clickable elements
3. It doesn't accept compound class strings ✓
4. It can't read DOM

Your answer is correct.
The correct answer is: It doesn't accept compound class strings

Question **3**
Correct
Mark 10.00 out of 10.00
Flag question

Why does WebDriver require switchTo().alert() for JavaScript alert handling instead of treating it like an element?

1. Alerts belong to browser, not DOM ✓
2. Alerts use inline CSS
3. Alerts are forms
4. Alerts are images

Your answer is correct.
The correct answer is: Alerts belong to browser, not DOM

Question **4**
Correct
Mark 10.00 out of 10.00
Flag question

In what scenario is By.partialLinkText() more useful than By.linkText()?

1. When links are styled
2. When link text is long or dynamic ✓
3. When testing local HTML
4. When there are checkboxes

Your answer is correct.
The correct answer is: When link text is long or dynamic

Question **5**
Correct
Mark 10.00 out of 10.00
Flag question

What makes driver.switchTo().defaultContent() helpful in complex test flows?

1. It clears cookies
2. It closes modals
3. It resets WebDriver's context to the main page ✓
4. It logs out the user

Your answer is correct.
The correct answer is: It resets WebDriver's context to the main page

Question **6**
Correct
Mark 10.00 out of 10.00
Flag question

Why is chaining locators with CSS selectors considered more reliable than XPath in some cases?

1. CSS is always more accurate
2. CSS supports index positions
3. CSS is faster and concise ✓
4. XPath doesn't support attributes

Your answer is correct.
The correct answer is: CSS is faster and concise

Question **7**
Correct
Mark 10.00 out of 10.00
Flag question

You notice your test gets stuck on a loading spinner. What fix is most robust?

1. Add a 5-second delay
2. Use WebDriverWait with invisibilityOfElementLocated() ✓
3. Use implicit wait
4. Scroll the page

Your answer is correct.
The correct answer is: Use WebDriverWait with invisibilityOfElementLocated()

Question **8**
Correct
Mark 10.00 out of 10.00
Flag question

You want to click a menu option that appears only after hovering. What Selenium strategy is needed?

1. click()
2. scrollTo()
3. Actions.moveToElement() ✓
4. getText()

Your answer is correct.
The correct answer is: Actions.moveToElement()

Question **9**
Correct
Mark 10.00 out of 10.00
Flag question

To verify a dynamically populated error message under a form field, what would be the most accurate strategy?

1. getAttribute("value")
2. isSelected()
3. getText() ✓
4. getStyle()

Your answer is correct.
The correct answer is: getText()

Question **10**
Correct
Mark 10.00 out of 10.00
Flag question

You have three checkboxes with the same class name and need to select only the second one. What do you do?

1. Use By.cssName directly
2. Use findElements and select index 1 ✓
3. Use tagName("checkbox")
4. Use tagName("checkbox")

Your answer is correct.
The correct answer is: Use findElements and select index 1

Question **11**
Correct
Mark 10.00 out of 10.00
Flag question

You need to switch between three browser tabs in a specific order. What is a reliable method?

1. Use getTitle()
2. Use stored window handles and switch accordingly ✓
3. Use alert.sendKeys()
4. Use index in switchTo()

Your answer is correct.
The correct answer is: Use stored window handles and switch accordingly

Question **12**
Incorrect
Mark 0.00 out of 10.00
Flag question

To simulate file upload where system dialog cannot be handled, what's the best solution?

1. Use driver.uploadFile()
2. Use Actions.click()
3. Use sendKeys() to input[type='file']
4. Use alert() ✗

Your answer is incorrect.
The correct answer is: Use sendKeys() to input[type='file']

Question **13**
Correct
Mark 10.00 out of 10.00
Flag question

Your drag-and-drop test doesn't work even though no error is thrown. What's one likely mistake?

1. perform() wasn't called after action sequence ✓
2. Source element is an alert
3. Target is not visible
4. Test doesn't start with driver.get()

Your answer is correct.
The correct answer is: perform() wasn't called after action sequence

Question **14**
Correct
Mark 10.00 out of 10.00
Flag question

You use a relative XPath but it clicks the wrong element. What might help improve precision?

1. Use contains()
2. Add parent-child relationships ✓
3. Switch to tagName
4. Remove index

Your answer is correct.
The correct answer is: Add parent-child relationships

Question **15**
Correct
Mark 10.00 out of 10.00
Flag question

While testing tab order on form fields, which Selenium method would you use?

1. sendKeys(Keys.TAB) ✓
2. perform()
3. waitForTab()
4. getAttribute("tab")

Your answer is correct.
The correct answer is: sendKeys(Keys.TAB)

Question **16**
Correct
Mark 10.00 out of 10.00
Flag question

You're interacting with a custom drop-down, not based on <select>. What's your plan?

1. Use Select class
2. Click dropdown → locate option by XPath → click ✓
3. Use sendKeys()
4. Use alert.accept()

Your answer is correct.
The correct answer is: Click dropdown → locate option by XPath → click

Question **17**
Correct
Mark 10.00 out of 10.00
Flag question

You're trying to automate selection of an item from a custom dropdown (not <select>). Which approach works?

1. Use Select class
2. Use getText()
3. Click dropdown, then locate list item by XPath ✓
4. Use sendKeys()

Your answer is correct.
The correct answer is: Click dropdown, then locate list item by XPath

Question **18**
Correct
Mark 10.00 out of 10.00
Flag question

You're using By.tagName("input") and multiple results are returned. What should you do next?

1. Pick randomly
2. Loop through and match attributes ✓
3. Use tagName again
4. Skip the test

Your answer is correct.
The correct answer is: Loop through and match attributes

Question **19**
Correct
Mark 10.00 out of 10.00
Flag question

You encounter stale element reference errors. What should you check?

1. Element has been deleted or reloaded ✓
2. Element is not clickable
3. XPath is too long
4. Implicit waits

Your answer is correct.
The correct answer is: Element has been deleted or reloaded

Question **20**
Correct
Mark 10.00 out of 10.00
Flag question

You need to select an element where ID starts with "item-" and ends with "-price". Which locator suits best?

1. By.id
2. CSS wildcard
3. XPath with starts-with() and ends-with() ✓
4. By.cssName

Your answer is correct.
The correct answer is: XPath with starts-with() and ends-with()

Finish review

← Core Java - Assessment - 17 [Web Fundamentals], Programming

Jump to...

Assessment - 19 [Introduction to Automation and Selenium - Handling Popups], Programming →

Contact site support

You are logged in as sabin m (Log out)
COE 2026-EXPLEO-KIOT-SDET-III
Data retention summary