Paper Code: IC2116

Maximum Marks: 75

M.Sc. (INFORMATICS) II Sem – 2016 Paper IT-21 – Voice and Data Communication

(Attempt 5 Questions in ALL. Question 1 is compulsory)

Time: 3 hours

1.	Attempt any five :				
	a) How can we represent the number -6 in one's complement arithmetic usbits?	ing only	four		
	b) Define single bit error and burst error.				
	c) A complex low pass signal has a bandwidth of 200 KHz. What is the minin this signal?	num sam	pling rate		
	d) In a digital transmission, the receiver clock is 0.1% faster than the sender extra bits per second does the receiver receive if the data rate is 1Kbps? Ho rate is 1Mbps?				
	e) The power of a signal is 10mW and the power of the noise is 1 μ W; What SNR and SNR _{dB} ?	are the v	alues of		
	f) A digitized voice channel is made by digitizing a 4-KHz bandwidth analog voice signal. The signal needs to be sampled at twice the highest frequency. Assuming each sample requires 8 bits, what is the required bit rate?				
	g) A non-periodic composite signal has a bandwidth of 200 KHz, with a midd KHz and peak amplitude of 20V. The two extreme frequencies have amplitu frequency domain of the signal. (5x	de of zer			
2	a) Explain Data Rate for noiseless channel and noisy channel.		(5)		
	b) Explain the concept of bandwidth delay product with suitable example.		(5)		
	c) What is scrambling? Explain B8ZS and HDB3 scrambling technique.		(5)		

Paper Code: IC2116

3.	a) Explain various polar line coding scheme.	(8)
	b) Explain satellite trajectories in terms of Injection velocity.	(5)
	c) We need to send data at a 2Mbps rate. What is the minimum required bandwidth, u combination of 4B/5B and NRZ-I or Manchester coding? Write the merits and demerits	of both
	the coding in above case.	(2)
		id .
4.	a) Explain the concept of Hamming distance. Explain how it can be used for error detection.	(6)
	b) What is CDMA? Explain with example. How chip sequence is generated?	(6)
	Differentiate between step index and graded index fibres. Define numerical aperture	e. (3)
	traibits per second coes the receiver receive if the date talk is but if for many if the discriminary.	
5.	a) Explain with example CRC encoder and decoder.	(6) 10 500,2928
5.	a) Explain with example CRC encoder and decoder. b) A channel has a band width of 3000Hz. If the signal to noise ratio is 3162, find the change capacity.	
5.	b) A channel has a band width of 3000Hz. If the signal to noise ratio is 3162, find the change capacity.	nannel (5)
5.	b) A channel has a band width of 3000Hz. If the signal to noise ratio is 3162, find the ch	nannel (5)
5.	b) A channel has a band width of 3000Hz. If the signal to noise ratio is 3162, find the characteristic. c) The elliptical orbit of a satellite has its semi-major and semi-minor axes as 25000Km	nannel (5) and
5.	b) A channel has a band width of 3000Hz. If the signal to noise ratio is 3162, find the change capacity. c) The elliptical orbit of a satellite has its semi-major and semi-minor axes as 25000Km 18330 Km, respectively. Determine the apogee and perigee distance.	nannel (5) and (4)
5.	b) A channel has a band width of 3000Hz. If the signal to noise ratio is 3162, find the chance capacity. c) The elliptical orbit of a satellite has its semi-major and semi-minor axes as 25000Km 18330 Km, respectively. Determine the apogee and perigee distance. a) Describe with example pulse code modulation (PCM) technique. b) Explain frequency division multiplexing and time division multiplexing technique. c) Apply the following operations on the corresponding polynomials:	nannel (5) and (4)
6.	b) A channel has a band width of 3000Hz. If the signal to noise ratio is 3162, find the chance capacity. c) The elliptical orbit of a satellite has its semi-major and semi-minor axes as 25000Km 18330 Km, respectively. Determine the apogee and perigee distance. a) Describe with example pulse code modulation (PCM) technique. b) Explain frequency division multiplexing and time division multiplexing technique.	nannel (5) and (4) (8)