

DESCRIPTION : 1100 VOLTAGE GRADE CIRCULAR STRANDED SECTOR SHAPED COPPER CONDUCTOR CLASS - 2, XLPE INSULATED, PVC TYPE ST - 2 SHEATHED, ARMoured POWER CABLES CONFIRMING TO IS : 7098 (PART-1) 1988 WITH LATEST AMMENDMENTS AND THIS DATA SHEET.

S. No.	DISCRIPTION	UNIT	3.5 CORE X 400 SQ.MM
1	CABLE TYPE		Circular Stranded Sector Shaped Copper Conductor Class - 2, XLPE Insulated, Inner Sheathed, Armoured, PVC Type ST-2 Sheathed Power Cable
2	NAME OF THE MANUFACTURER		M/s POLYVION CABLES PVT. LTD.
3	BRAND NAME		POLYCORE
4	APPLICABLE STANDARDS		IS : 7098 (Part-1) 1988, IS : 8130/2013 & This Data Sheet.
5	VOLTAGE GRADE	VOLTS	1100V
6	NO. OF CORES	NOS.	3.5 Core
7	CONDUCTOR		
8	Material		Circular Stranded Sector Shaped Copper Conductor Conf. To IS : 8130/2013
9	Size	Sq.mm	M - 400 & N - 185
10	No. of Strands	Nos.	M - 61 & N - 37
11	Shape of Conductor		Circular Stranded Sector Shaped Copper Conductor Class - 2
12	Temperature Rise on Normal Condition	Deg. C	90°C
13	Temperature Rise on Short Circuit Condition	Deg. C	250°C
14	INSULATION		
15	Material		XLPE Compound Conf. To IS : 7098 (Part-1) 1988
16	Type		Extruded XLPE
17	Thickness (Nom. / Min.)	mm	M - 2.00 / 1.70 & N - 1.60 / 1.34
18	Core Identification		Red, Yellow, Blue & Black
19	INNER SHEATH		
20	Materials		Extruded PVC TYPE ST - 2 Conf. to IS : 5831/84
21	Type		Extruded PVC
22	Thickness (Min.)	mm	0.70
23	Colour		Black
24	ARMOURING		
25	Material		Galvanised Steel Flat Strip
26	Diamension	mm	4.00 X 0.80 ±10%
27	OUTER SHEATH		
28	Material		Extruded PVC TYPE ST - 2 Conf. to IS : 5831/84
29	Type		Extruded PVC
30	Thickness (Min.)	mm	2.52
31	Overall Diameter of Cable *	mm	62.00
32	Colour Of Outer Sheath		Black
33	Marking On Outer Sheath		Manufacturer's name, Type of Cable, Year of manufacture, Voltage Grade and Size of cable (i.e., No. Of Core x Size) Sequential Length Marking shall be printed on outer sheath of cable at every 1 mtr interval .
34	Standard Drum Length (Packing shall be done in non-returnable wooden drum)	meter	1 X 300 Mtrs. ± 5 % Tolerance
35	ELECTRICAL PARAMETERS		
36	Max. DC resistance of conductor of completed cable at 20°C	ohm / km	M- 0.0470 & N- 0.0991
37	High Voltage Test	kV rms	3.0 kV. (rms) for 5 minutes Core to Core / Armour Each Connection
38	Flammability Test As Per IS : 10810 (Part-53)	Sec / mm	Period of burning after of removal flame max time (60 Sec.) , Unaffected Portion of cable min (50 mm)

Note - * OD of cable is calculated and given for reference purpose, actual OD of cable will vary, Variation Tolerance 10 To 15 %

Note:- The values given above are subject to tolerances as per the relevant standards.

FOR :- M/S - POLYVION CABLES PVT. LTD.

