

DESCRIPTION : 1100 VOLTAGE GRADE CIRCULAR FLEXIBLE ANNEALED BARE COPPER CONDUCTOR, PVC TYPE-D INSULATED & PVC TYPE ST-3 SHEATHED FLEXIBLE CABLE CONFIRMING TO IS : 694 / 2010 AND THIS DATA SHEET.

S. No.	DISCRIPTION	UNIT	3 CORE X 1.5 SQ.MM
1	CABLE TYPE		Circular Flexible Annealed Bare Copper Conductor, PVC Type-D Insulated & PVC Type ST-3 sheathed Flexible Cable
2	NAME OF THE MANUFACTURER		M/s POLYVION CABLES PVT. LTD.
3	BRAND NAME		POLYCORE
4	APPLICABLE STANDARDS		Conf. IS : 694 / 2010, IS : 8130 / 2013 & This Data Sheet
5	VOLTAGE GRADE	VOLTS	1100 Volts
6	NO. OF CORES	NOS.	3 Core
7	CONDUCTOR		
8	Material		High Conductivity Electrolyte Grade Annealed Bare Circular Copper Conductor Conf. to IS : 8130 / 2013
9	Size	Sq.mm	1.5
10	No. of Strands	Nos	30
11	Shape of Conductor		Circular Flexible Annealed Bare Copper Conductor Class-5
12	Temperature Rise on Normal Condition	Deg. C	70 ⁰ C
13	Temperature Rise on Short Circuit Condition	Deg. C	160 ⁰ C
14	INSULATION		
15	Material		PVC Type-D As Per IS : 5831 / 1984
16	Type		Extruded PVC
17	Thickness (Nom.)	mm	0.60
18	Core Identification		Red, Black & Green
19	INNER SHEATH		
20	Material		N / A
21	Type		N / A
22	Thickness (Min.)	mm	N / A
23	Colour		N / A
24	ARMOURING		
25	Material		N / A
26	Dimension	mm	N / A
27	OUTER SHEATH		
28	Material		Extruded PVC TYPE ST-3 Compound Conf. to IS : 5831/84
29	Type		Extruded PVC
30	Thickness (Nom.)	mm	0.90
31	Approx. Overall Diameter Of Cable*	mm	7.70
32	Colour of Outer Sheath		Black
33	Printing On Outer Sheath		Manufacturer's name, Year of manufacture, Voltage Grade and Size of cable, shall be printed of cable
34	Standard Drum / Coil Length (Packing shall be done in non-returnable wooden drum/Coils)	meter	100 Mtrs. Coil ±5% Tolerance
35	ELECTRICAL PARAMETERS		
36	Max. DC resistance of conductor of completed cable at 20°C	ohm/km	13.30
37	High Voltage Test	KV rms	3.0 kV. (rms) for 5 minutes
38	Flammability Test As Per IS : 10810 (Part-53)	Sec / mm	Period of Burning After of Removal Flame Max. Time (60 Sec.), Unaffected Portion Of Cable Min. 50 mm

* OD of cable is calculated and given for reference purpose, actual OD of cable will vary, Variation Tolerance 10 To 15 %

Note:- The values given above are subject to tolerances as per the relevant standards.

M/s. POLYVION CABLES PVT. LTD.

