

# Scheduling in OS

Bhupendra Pratap Singh  
ACTS, CDAC, Pune

# What is CPU scheduling?

- CPU scheduling is a process which allows one process to use the CPU while the execution of another process is on hold(in waiting state) due to unavailability of any resource like I/O etc, thereby making full use of CPU.
- The aim of CPU scheduling is to make the system efficient, fast and fair.
- Whenever the CPU becomes idle, the operating system must select one of the processes in the **ready queue** to be executed. The selection process is carried out by the CPU scheduler).
- The scheduler selects from among the processes in memory that are ready to execute, and allocates the CPU to one of them.

# What is Dispatcher?

- The dispatcher is the module that gives control of the CPU to the process selected by the **scheduler**. This function involves:
- Switching context
- Switching to user mode
- Jumping to the proper location in the user program to restart that program from where it left last time.
- The time taken by the dispatcher to stop one process and start another process is known as the **Dispatch Latency**.

# When CPU scheduling can/may take place?

- When a process switches from the **running** state to the **waiting** state(for I/O request or invocation of wait for the termination of one of the child processes).
- When a process switches from the **running** state to the **ready** state (for example, when an interrupt occurs).
- When a process switches from the **waiting** state to the **ready** state(for example, completion of I/O).
- When a process **terminates**.
- 1st and last, there is no choice in terms of scheduling. A new process(if one exists in the ready queue) must be selected for execution.

# Non-Preemptive & Preemptive scheduling


- Under non-preemptive scheduling, once the CPU has been allocated to a process, the process keeps the CPU until it releases the CPU either by terminating or by switching to the waiting state.
- Preemptive scheduling: the tasks/process/threads are usually assigned with priorities. At times it is necessary to run a certain tasks/process/threads that has a higher priority before another tasks/process/threads although it is running. Therefore, the running task is interrupted for some time and resumed later when the priority task has finished its execution.

# Context Switching

Switching of CPU from one process to another is known as Context Switching

## Context Switch


Switching the CPU to another process requires saving the state of the old process and loading the saved state for the new process.



# Starvation and Aging

- Starvation or indefinite blocking is phenomenon associated with the Priority scheduling algorithms, in which a process ready to run for CPU can wait indefinitely because of low priority. In heavily loaded computer system, a steady stream of higher-priority processes can prevent a low-priority process from ever getting the CPU.
- Aging is a condition which is used to reduce starvation of low priority tasks. It is a process which gradually increases the priority of task depending on waiting time. It ensure that jobs in the lower level queues will eventually complete their execution.

# Various Process Timings





# Various Process Timings

**Arrival Time-** Arrival time is the point of time at which a process enters the ready queue.

**Waiting Time-** Waiting time is the amount of time spent by a process waiting in the ready queue for getting the CPU.

**Waiting time = Turn Around time – Burst time**

**Response Time-** Response Time: Response time is the amount of time after which a process gets the CPU for the first time after entering the ready queue.

**Response Time = Time at which process first gets the CPU – Arrival time**

# Various Process Timings

**Burst Time:** Burst time is the amount of time required by a process for executing on CPU.

- It is also called as execution time or running time.
- Burst time of a process can not be known in advance before executing the process. It can be known only after the process has executed

**Completion Time:** Completion time is the point of time at which a process completes its execution on the CPU and takes exit from the system. It is also called as exit time.

# Various Process Timings

## Turn Around Time:

- Turn Around time is the total amount of time spent by a process in the system.
- When present in the system, a process is either waiting in the ready queue for getting the CPU or it is executing on the CPU.
- Turn Around time = Burst time + Waiting time

or

Turn Around time = Completion time – Arrival time

# FIRST COME FIRST SERVE SCHEDULING(FCFS)

- The process which arrives first in the ready queue is firstly assigned the CPU.
- In case of a tie, process with smaller process id is executed first.
- It is always non-preemptive in nature.

## Advantages-

- It is simple and easy to understand.
- It can be easily implemented using queue data structure.
- It does not lead to starvation.

## Disadvantages-

- It does not consider the priority or burst time of the processes.
- It suffers from **convoy effect**.

# What is convoy effect?

- Consider processes with higher burst time arrived before the processes with smaller burst time.
- Then, smaller processes have to wait for a long time for longer processes to release the CPU.

# Shortest Job First Scheduling

- Out of all the available processes, CPU is assigned to the process having smallest burst time.
- In case of a tie, it is broken by **FCFS Scheduling**.
- Non Preemptive in nature.

# Shortest Job First Scheduling

## Advantages-

- SRTF is optimal and guarantees the minimum average waiting time.
- It provides a standard for other algorithms since no other algorithm performs better than it.

## Disadvantages-

- It can not be implemented practically since burst time of the processes can not be known in advance.
- It leads to starvation for processes with larger burst time.
- Priorities can not be set for the processes.
- Processes with larger burst time have poor response time.

# Longest Job First

- Out of all the available processes, CPU is assigned to the process having largest burst time.
- In case of a tie, it is broken by FCFS Scheduling.
- Non Preemptive in nature.



# Longest JOB First

## Advantages-

- No process can complete until the longest job also reaches its completion.

## Disadvantages-

- The waiting time is high.
- Processes with smaller burst time may starve for CPU.

# Round Robin Scheduling

- CPU is assigned to the process on the basis of FCFS for a fixed amount of time.
- This fixed amount of time is called as time quantum or time slice.
- time quantum expires, the running process is preempted and sent to the ready queue & processor is assigned to the next arrived process.
- **It is always preemptive in nature.**

# Round Robin Scheduling

## Advantages-

- It gives the best performance in terms of average response time.
- It is best suited for time sharing system, client server architecture and interactive system.

## Disadvantages-

- It leads to starvation for processes with larger burst time as they have to repeat the cycle many times.
- Its performance heavily depends on time quantum.
- Priorities can not be set for the processes.

# Round Robin Process Selection Rules

With round-robin, the scheduler always selects the process that's had the most time since it was last run, and *new processes coming in are always assigned a last run time of 1 time unit before the oldest last run time in the current list.*

Thank you 😊

Any

Questions??