

OPEN API Documentation – Indira Securities

Version: 1.0

Table of Contents

Introduction	3
General Instructions.....	3
1. Required Headers	3
2. URL Encoding	3
3. Message Format.....	3
4. JSON Specifications and Standards	3
5. URL Conventions	3
6. JSON Field Naming Convention.....	4
7. Null Values	4
Error Handling	4
HTTP Status Codes	4
Common Error Response JSON	4
Field Error Structure.....	4
Validation Levels	5
Sample Error Responses	5
API Endpoints.....	6
ORDERS	6
1. Place Order.....	6
2. Modify Order.....	8
3. Cancel Order	10
4. Brokerage Charges	11
5. Order Book.....	13
6. Order Trail	16
7. Trade Book	18
PORTFOLIO	20
1. Holdings	20
2. POSITIONS	23
3.Position Conversion	26
FUNDS	27
1. Get Limits Details	27
PROFILE	29
1. Account Info.....	29

Introduction

This document describes the Indira Securities Trading Application's Web APIs to programmatically access and exchange data with the Indira Trade Host system. The document outlines the messaging protocols and structures for developing such interfaces.

General Instructions

1. Required Headers

The following headers need to be provided in all API calls:

- **Content-Type:** This header should be provided in all requests with method as "POST". "GET". Header value should be "application/json".
- **Header content:** appld, userId, source

2. URL Encoding

Path parameters and query parameters in the URLs must be encoded using percent encoding.

3. Message Format

All request and response messages are in JSON (Javascript Object Notation) format.

4. JSON Specifications and Standards

Key specifications related to JSON are as follows:

- **JSON Structure:** JSON is built on 2 structures - Map containing key-value pairs and an ordered list of values.
- **Values:** A value could be boolean (true/false), number, decimal, String or a structure (List or Object).
- **Object/Key-Value Pair:** E.g. {"name":"Amit", "age":25}
- **List:** E.g. ["Amit", "Ajay", "Vikas"]
- **Boolean:** Only 2 values - true or false
- **String:** Enclosed in double quotes. E.g. "name", "Amit", "Pending"
- **Numbers and Decimals:** Represented without thousand-separator character. Decimal indicator is dot ("."). Optional maximum of 18 digits if not specified.
- **Decimals:** Two mandatory length parameters. First indicates digits in whole part (before decimal), second indicates digits in decimal part (after decimal).
- **Date, Time and DateTime Formatting:**
 - Dates: "dd-MMM-yyyy" (E.g. 01-Jan-2018)
 - Time: "hh24:mm:ss"
 - DateTime: "dd-MMM-yyyy hh24:mm:ss" (E.g. 01-Jan-2016 15:30:00)
 - All times are in Indian Standard Time (IST)

5. URL Conventions

All URLs for API will always be in lower case.

6. JSON Field Naming Convention

All JSON field names will follow camel-hump style of naming:

- Field with multiple words are concatenated without spaces
- All characters are in lower case
- First characters of words other than the first word will be in upper case

Examples:

- "Order Number" → orderNumber
- "First Name" → firstName
- "Last Name" → lastName
- "Participant List" → participantList

7. Null Values

In case of JSONs representing an object or key-value pair, keys with null values could be omitted from the JSON.

Error Handling

HTTP Status Codes

Code	Description
400	Indicates a validation / business logic error
401	Indicates that the login session is not established or has expired. In case 2 sessions are created using same login credentials, then the old session will be expired. Also if a session is inactive for a predefined amount of time then the session will be expired.
404	Resource does not exist
500	Any other application error. Such errors should be reported to the support desk.

Common Error Response JSON

Field	Type	Description
code	Number	Http Status Code (see above)
messages	Array	In case of errors pertaining to parsing of input JSONs, each element will be a structure (see Field Error Structure below). In case of errors pertaining to rule validation failures, each element will be a String (maximum length 100) depicting the error.

Field Error Structure

Field	Type	Description
field	String(100)	Input JSON field name
msg	String(100)	Field validation error message

Validation Levels

Almost all APIs perform 2 levels of validation:

1. **Level 1 - Structure Validation:** The input JSON message is validated for structure. Every field is validated for datatype, length and any other constraints. Typically, all field level validation errors are accumulated and given in a single response containing field-wise errors using the Field Error Structure.
2. **Level 2 - Functional Validation:** Various functional rules are verified and error is thrown immediately upon violation. These errors are not progressive (i.e., the API skips further validation and processing immediately after first validation failure).

Sample Error Responses

Simple Error:

```
{
  "code": 400,
  "messages": ["Access Denied"]
}
```

Field-Level Errors:

```
{
  "code": 400,
  "messages": [
    {
      "field": "participantList",
      "msg": "Participants: No of items in the list should be greater than or equal to 1"
    }
  ]
}
```

Environment Details

Base URLs

Environment	URL
Testing	https://[testing-domain].com/[api-base]/
Live	https://livemiddleware.indiratrade.com

API Endpoints

ORDERS

1. Place Order

This API creates a new order for buying or selling securities.

Property	Value
Method	POST
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/order-services/api/order/v1/place-order

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- **Key:** sso (lowercase)
- **Value:** True

Request JSON:

Field	Type	Mandatory	Description
symbol	String	Yes	Unique trading symbol identifier following pattern: instrument_symbol_exchange (e.g., STK_TCS_EQ_NSE). Identifies the security uniquely across the exchange.
excToken	Integer	Yes	Numeric exchange token assigned by the exchange to this security. Maps to the exchange instrument code and used for routing orders to correct exchange leg.
exc	String	Yes	Exchange code determining order routing and execution venue. Specifies which exchange (NSE/BSE/NFO/BFO/MCX/NCDEX/CDS/BCD) will process this order.
ordAction	String	Yes	Side of the transaction - whether you're buying or selling the security. Fundamental property determining order direction.
ordValidity	String	Yes	Validity period defining how long the order remains active in the market. Determines automatic cancellation timing if not executed.
ordType	String	Yes	Order execution type determining how the order will be matched in the market. Affects pricing and execution certainty.
prdType	String	Yes	Product type determining settlement mechanism and holding period. Impacts margin requirements, charges, and how position is settled.
limitPrice	Double	No	Price threshold for limit/stop-loss orders. Only used when ordType is Limit or Stop-loss. Specifies the minimum acceptable execution price for sells or maximum for buys.
triggerPrice	Double	No	Activation price for stop-loss orders. When market price crosses this level, order becomes active (for SL-M or Stop-loss types). Protects against adverse price movements.
qty	Integer	Yes	Number of securities to trade. Must comply with lot size rules for F&O contracts and minimum/maximum lot requirements per exchange rules.
disQty	Integer	No	Displayed/visible quantity for iceberg orders. Market sees only this quantity; remaining (qty - disQty) stays hidden and executes when visible portion fills. Useful for large orders to minimize market impact.

Field	Type	Mandatory	Description
lotSize	Integer	No	Lot size for derivatives/F&O contracts. Specifies the contract multiplier (e.g., 100 shares per lot for index futures). Defaults to 1 for equity instruments.
instrument	String	Yes	Asset class type determining applicable rules, margins, and settlement procedures. Fundamental classification of the security being traded.
amo	Boolean	No	After-Market Order flag. If true, queues order for next market session (e.g., previous-day order for next morning execution). Defaults to false for immediate submission.

Sample Request:

```
{
  "symbol": "STK_KOLTEPATIL_B_BSE",
  "excToken": 532924,
  "exc": "BSE",
  "ordAction": "BUY",
  "ordValidity": "DAY",
  "ordType": "Limit",
  "prdType": "DELIVERY",
  "limitPrice": 300.50,
  "triggerPrice": 0.00,
  "qty": 3,
  "disQty": 0,
  "lotSize": 0,
  "instrument": "STK",
  "amo": false
}
```

Response JSON:

Field	Type	Description
infoID	String	Status code indicating operation result. "0" = success, non-zero values indicate specific error codes.
infoMsg	String	Human-readable message describing success or error.
timestamp	Time	Server timestamp in milliseconds since epoch (01-Jan-1970 UTC). Use for audit trails and sequencing.
data	Object	System-generated unique order identifier used for all subsequent order management operations (modify/cancel). Persists for entire order lifecycle.
data.ordId	String	Current order status immediately after placement. May be Executed (market order), Pending (limit order), Requested, or Rejected.
data.ordStatus	String	If ordStatus is Rejected, contains human-readable reason for rejection (e.g., "Invalid price", "Market closed"). Empty if accepted.
data.rejReason	String	Status code indicating operation result. "0" = success, non-zero values indicate specific error codes.

Sample Response:

```
{
  "infoID": "0",
  "infoMsg": "success",
  "timestamp": 1738051923834,
  "data": {
    "ordId": "NZULR00008L1",
    "ordStatus": "Executed",
    "rejReason": null
  }
}
```

2. Modify Order

This API modifies an existing order.

Property	Value
Method	POST
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/order-services/api/order/v1/modify-order

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- Key: sso (lowercase)
- Value: True

Request JSON:

Field	Type	Mandatory	Description
ordId	String	Yes	Unique identifier of the order to modify. Obtained from place-order response or order-book. Must reference an existing pending order.
symbol	String	Yes	Original exchange-specific trading symbol of the security. Must match the original order's symbol for validation. Used to route modification request correctly.
ordAction	String	Yes	Order side: BUY or SELL. Typically same as original, but some systems allow modification in certain scenarios. Defines buy/sell direction.
ordValidity	String	Yes	Validity period of modified order. Can be changed from DAY to GTD or vice versa depending on system rules and market policies. Determines auto-cancellation timing.
exchangeToken	String	Yes	Numeric exchange token for the security. Same as excToken in place-order. Used for validation and exchange routing.
exc	String	Yes	Exchange code (NSE, BSE, NFO, etc.). Identifies which exchange processes this modification. Must match original order's exchange.
qty	Integer	Yes	Modified order quantity. Can increase or decrease from original qty. Must comply with lot size rules. System validates against current traded quantity.
tradedQty	Integer	No	Quantity already executed for this order. Used for validation - modified qty must be $\geq$ tradedQty. Helps prevent reducing qty below filled amount.

Field	Type	Mandatory	Description
limitPrice	Double	No	Modified limit price for limit/SL orders. New price threshold at which order will execute. Can be adjusted to improve execution chances.
triggerPrice	Double	No	Modified trigger price for stop-loss orders. New activation level for SL orders. Allows adjustment of stop-loss protection without cancelling.
ordType	String	Yes	Modified order type: Market, Limit, SL-M, Stop-loss. Can change execution method (e.g., Limit to Market). Affects how order matches.
prdType	String	Yes	Product type: DELIVERY or INTRADAY. Generally cannot be changed after placement; some systems may allow under specific conditions.
instrument	String	Yes	Instrument type: STK, IDX, FUT, OPT. Classification of the security - cannot change.
lotSize	Integer	No	Lot size for derivatives. Same as original order. Used for validation of qty multiples.
disQty	Integer	No	Modified disclosed quantity for iceberg orders. Updates visible portion while keeping rest hidden.
offMktFlag	Boolean	No	Offline market flag. Indicates if modification occurs during market closed hours. Platform-specific feature.

Sample Request:

```
{
  "ordId": "NZULR0000601",
  "symbol": "STK_KOLTEPATIL_B_BSE",
  "ordAction": "BUY",
  "ordValidity": "DAY",
  "exchangeToken": "532924",
  "exc": "BSE",
  "qty": 3,
  "tradedQty": 0,
  "limitPrice": 301.00,
  "triggerPrice": 0.0,
  "ordType": "Limit",
  "prdType": "DELIVERY",
  "instrument": "STK",
  "lotSize": 1,
  "disQty": 0,
  "offMktFlag": false}
```

Response JSON:

Field	Type	Description
infoID	String	Status indicator. Usually "0" for success.
infoMsg	String	Success or error message.
timestamp	Time	Server timestamp in milliseconds.
data	Object	Modified Order ID (same as submitted ordId).
data.ordId	String	Updated order status (e.g., "Pending", "Executed").
data.ordStatus	String	Rejection reason if modification failed.
data.rejReason	String	Status indicator. Usually "0" for success.

Sample Response:

```
{
  "infoID": "0",
  "infoMsg": "success",
  "timestamp": 1738318897256,
  "data": {
    "ordId": "NZULR0000601",
    "ordStatus": "Executed",
    "rejReason": null
  }
}
```

3. Cancel Order

This API cancels an existing order.

Property	Value
Method	POST
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/order-services/api/order/v1/cancel-order

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- **Key:** sso (lowercase)
- **Value:** True

Request JSON:

Field	Type	Mandatory	Description
symbol	String	Yes	Trading symbol identifier of the order being cancelled. Used for validation and routing cancellation request to correct exchange.
exc	String	Yes	Exchange code (NSE, BSE, NFO, etc.) where order is submitted. Determines which exchange receives cancellation request.
ordId	String	Yes	Unique order identifier to cancel. Obtained from place-order response or order-book. Uniquely identifies order in system.

Sample Request:

```
{
  "symbol": "AXISBANK-EQ",
  "exc": "NSE",
  "ordId": "NZULR00005L1"
}
```

Response JSON:

Field	Type	Description
infoID	String	Status code. "0" = success.
infoMsg	String	Success/error message.
timestamp	Time	Server timestamp (milliseconds).
data	Object	Response data object
data.ordId	String	Cancelled Order ID (same as submitted).

Sample Response:

```
{
  "infoID": "0",
  "infoMsg": "success",
  "timestamp": 1738053270893,
  "data": {
    "ordId": "NZULR00005L1"
  }
}
```

4. Brokerage Charges

This API calculates brokerage and other charges for a hypothetical order.

Property	Value
Method	POST
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/order-services/api/order/v2/brokerage-charges

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- Key: sso (lowercase)
- Value: **True**

Request JSON:

Field	Type	Mandatory	Description
symbol	String	Yes	Internal trading symbol with segment and exchange info.
excToken	Integer	Yes	Exchange token/identifier for the instrument.
prdType	String	Yes	Product type (DELIVERY, INTRADAY, etc.).
instrument	String	Yes	Instrument category (STK, FUT, OPT).
exc	String	Yes	Exchange code (NSE, BSE).
orderAction	String	Yes	Order side (BUY or SELL).
qty	Integer	Yes	Quantity of shares/lots for the order.
price	Double	Yes	Order price per unit used for charge calculation.
lot	Double	No	Lot size multiplier for derivatives, if applicable.
ordType	String	Yes	Order type (Regular/MARKET/LIMIT).
transType	String	Yes	Transaction code (B for buy, S for sell).
orderFlag	String	Yes	Order state indicator (NEW/MODIFY/CANCEL).

Sample Request:

```
{
  "symbol": "STK_ADANIENT_EQ_NSE_25",
  "excToken": "25",
  "prdType": "DELIVERY",
  "instrument": "STK",
  "exc": "NSE",
  "orderAction": "BUY", "qty": "1",
  "price": "2184.6", "lot": "1",
  "ordType": "Regular",
  "transType": "B",
  "orderFlag": "NEW"
}
```

Response JSON:

Field	Type	Description
infoID	String	Status code. "0" = success.
infoMsg	String	Success/error message.
timestamp	Time	Server timestamp (milliseconds).
data	Object	Total available margin for trading. Used for position sizing validation.
data.brokerage.totalMargin	Double	Available balance after deducting all charges from totalMargin. Actual usable amount after order.
data.brokerage.availableBal	Double	Brokerage charges levied by broker. Percentage-based fee on trade value.
data.brokerage.brokerage.brokerage	Double	Stamp duty tax (applicable in certain states/products). Government levied transaction tax.
data.brokerage.brokerage.stampDuty	Double	Exchange transaction charges for clearing and settlement.
data.brokerage.brokerage.transactionCharges	Double	Clearing corporation charges for guaranteeing settlement.
data.brokerage.brokerage.clearingCharges	Double	Sum of brokerage + stamp + transaction + clearing charges. Total operational costs.
data.brokerage.brokerage.totalBrokerageAndCharges	Double	Securities Transaction Tax. Government tax on equity trades (0.1% for sells, except certain securities).
data.brokerage.brokerage.stt	Double	SEBI regulatory charges. Securities and Exchange Board India fee for market regulation.
data.brokerage.brokerage.sebi	Double	Goods and Services Tax on brokerage charges (18% on brokerage component).
data.brokerage.brokerage.gst	Double	Depository charges for demat transaction (applicable for DELIVERY trades).
data.brokerage.brokerage.dpcharges	Double	Flag indicating whether cautionary message should be displayed to user.
data.brokerage.showMessage	Boolean	Warning message if any (e.g., "Margin insufficient", "Price outside circuit limits").
data.brokerage.cautionaryMessage	String	Status code. "0" = success.

Sample Response:

```
{
  "infoID": "0",
  "infoMsg": "success",
  "timestamp": 1747035501469,
  "data": {
    "brokerage": {
      "totalMargin": "500000.00",
      "availableBal": "499791.57",
      "brokerage": {
        "brokerage": "20.0",
        "stampDuty": "0.0",
        "transactionCharges": "0.0",
        "clearingCharges": "0.0",
        "totalBrokerageAndCharges": "20.0",
        "stt": "0.0",
        "sebi": "0.0",
        "gst": "0.0",
        "dpcharges": "0.0"
      },
      "showMessage": false,
      "cautionaryMessage": ""
    }
  }
}
```

5. Order Book

This API retrieves all orders for the logged-in user.

Property	Value
Method	GET
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/portfolio-services/api/order/v1/order-book

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- **Key:** sso (lowercase)
- **Value:** True

Request Parameters:

No request body required. Authentication via session/loginKey header.

Response JSON:

Field	Type	Description
infoID	Boolean	Status code: "0" = success, non-zero = error
infoMsg	String	Human-readable status message
timestamp	Time	Server timestamp in milliseconds since epoch (IST: 2025-11-27 16:53:21)
data.orders	Object	Array of order objects representing all user orders
orders[].symbol	Object	Nested symbol details object with comprehensive security information
symbol.symbol	String	Full unique trading symbol: [INSTRUMENT][SYMBOL][SERIES][EXCHANGE][TOKEN]
symbol.dispSym	String	Display symbol for UI rendering (cleaner format)

Field	Type	Description
symbol.instrument	String	Instrument type: STK=stock, IDX=index, FUT=futures, OPT=options
symbol.baseSym	String	Base symbol name without exchange/series qualifiers
symbol.companyName	String	Full registered company legal name
symbol.isin	String	International Securities Identification Number (globally unique code)
symbol.exc	String	Primary exchange code: BSE
symbol.excTkn	Integer	Exchange token (numeric identifier)
symbol.series	String	Series classification: EQ=equity (main), BE=bulk deals, SM=SME
symbol.lotSize	Integer	Trading lot size; null = default lot of 1 share (equity)
symbol.tickSize	Double	Minimum price increment; prices move only in 0.01 steps
symbol.expiryDate	Date	Expiry date for derivatives; null for equity stocks
symbol.optionType	String	Option type (Call/Put); null for non-option instruments
symbol.strikePrice	Integer	Strike/exercise price for options; null for stocks
symbol.streamSym	String	Streaming symbol for market data feeds and live quotes
symbol.segment	String	Market segment designation; null if not applicable
symbol.fno	Boolean	Futures & Options eligible: false=equity only, true=derivatives available
symbol.mtf	Boolean	Margin Trading Facility eligible: false=not eligible, true=can use margin
symbol.multiplier	String	Contract multiplier (1 for stocks, 50-500 for derivatives)
symbol.freezeQty	Integer	Quantity freeze limit for day trading; null = no freeze
symbol.tradingSymbol	String	Trading symbol used for order placement
symbol.otherExc	Array	Array of other exchanges where security is listed; empty if single-exchange
symbol.isWeeklyExpiry	String	Weekly expiry flag for derivatives; null for stocks
orders[].ordId	String	System-generated unique order identifier
orders[].exchOrdId	Long	Exchange's order ID assigned during order acceptance
orders[].status	String	Current order status: Requested, Executed, Cancelled, Rejected, Pending
orders[].ordAction	String	Order side: BUY=buying, SELL=selling
orders[].ordType	String	Order type: Market, Limit, SL-M (Stop-Loss Market), Stop-loss
orders[].prdType	String	Product type: DELIVERY=T+2 demat settlement, INTRADAY=same-day square-off
orders[].ordValidity	String	Validity period: NONE=default (DAY), DAY, GTD (Good Till Date), IOC, GTC
orders[].modifiedBy	String	Source of order placement: MOBILE-Ex=mobile app, WEB, API, DESKTOP, SYSTEM
orders[].price	Double	Limit price for limit/SL orders; execution price threshold
orders[].triggerPrice	Double	Trigger price for SL orders; 0.0 = not a stop-loss order
orders[].rejReason	String	Rejection reason if status=Rejected; empty if accepted/executed
orders[].ordDate	Date Time	Order placement datetime (IST). Format: dd-MMM-yyyy hh24:mm:ss
orders[].excOrdTime	Date Time	Exchange acceptance/receipt timestamp (IST)
orders[].qty	Integer	Total order quantity placed
orders[].disQty	Integer	Disclosed quantity in iceberg orders; 0 = full qty visible

Field	Type	Description
orders[].tradedQty	Integer	Quantity already executed/filled; 0 = no fills
orders[].remainQty	Integer	Remaining quantity awaiting execution: qty - tradedQty - cancelledQty
orders[].cancelledQty	Integer	Quantity cancelled after partial fills; 0 = no cancellations
orders[].undAsset	String	Underlying asset type: STK=stock, FUT=futures, OPT=options, IDX=index
orders[].amo	Boolean	After-Market Order flag: false=market hours order, true=next session order
orders[].modifiable	Boolean	Whether order can be modified; false = cannot modify in current state
orders[].cancellable	Boolean	Whether order can be cancelled; false = cannot cancel in current state
orders[].bracketOrderModifyDetail	String	Bracket order modification details for advanced strategies; empty for simple orders

Sample Response

```
{
  "infoID": "0", "infoMsg": "success", "timestamp": 1764227601871,
  "data": { "orders": [
    { "symbol": {
      "symbol": "STK_IDEA_EQ_BSE_532822",
      "dispSym": "IDEA",
      "instrument": "STK",
      "baseSym": "IDEA",
      "companyName": "VODAFONE IDEA LIMITED",
      "isin": "INE669E01016",
      "exc": "BSE",
      "excTkn": 532822,
      "series": "EQ",
      "lotSize": null,
      "tickSize": "0.01",
      "expiryDate": null,
      "optionType": null,
      "strikePrice": null,
      "streamSym": "532822_BSE",
      "segment": null,
      "fno": false,
      "mtf": false,
      "multiplier": "1",
      "freezeQty": null,
      "tradingSymbol": "IDEA",
      "otherExc": [],
      "isWeeklyExpiry": null
    },
      "ordId": "NYOYX00007K;",
      "exchOrdId": "1764227052254054490",
      "status": "Cancelled",
      "ordAction": "BUY",
      "ordType": "Limit",
      "prdType": "DELIVERY",
      "ordValidity": "NONE",
      "modifiedBy": "MOBILE-Ex",
      "price": 10.0,
      "triggerPrice": 0.0,
      "rejReason": "",
      "ordDate": "2025-11-27 12:39:30",
    }
  ]
}
```

```
"excOrdTime": "2025-11-27 12:40:56",
"qty": 1,
"disQty": 0,
"tradedQty": 0,
"remainQty": 1,
"cancelledQty": 0,
"undAsset": "STK",
"amo": false, "modifiable": false,
"cancellable": false, "bracketOrderModifyDetail": "" }
```

6. Order Trail

This API retrieves the trail/history of modifications for a specific order.

Property	Value
Method	POST
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/portfolio-services/api/order/v2/order-trail

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- **Key:** sso (lowercase)
- **Value:** True

Request JSON:

Field	Type	Mandatory	Description
ordId	String	Yes	Order ID to retrieve trail for. Obtained from order-book or place-order response.
instrument	String	Yes	Instrument type of the order (STK, IDX, FUT, OPT). Used for validation and lookup.

Sample Request:

```
{
  "ordId": "NZULR00006H2",
  "instrument": "STK"
}
```

Response JSON:

Field	Type	Description
data.symbol	Object	Symbol details (can be null if not found).
data.orderDetails	Object	Original order details (can be null).
data.trails	Object	Array of trail objects, each representing a state change/event in order lifecycle.
data.symbol	String	Symbol details (can be null if not found).
data.orderDetails	String	Original order details (can be null).
data.trails	Object	Array of trail objects, each representing a state change/event in order lifecycle.
data.symbol	Object	Symbol details (can be null if not found).

Field	Type	Description
lupdateDateTime	String	Last update datetime. Format: dd-MMM-yyyy hh24:mm:ss. Marks when this state occurred.
ordDesc	String	Human-readable description of the change/action (e.g., "REJECTED MARKET order 7 qty...").
ordType	String	Order type at that point in history (Market, Limit, SL-M, Stop-loss).
ordValidity	String	Order validity at that time (DAY, GTD, IOC, GTC).
status	String	Status at that trail point (Rejected, Executed, Pending, Requested, Cancelled).
rejReason	String	Rejection reason if status=Rejected. Empty otherwise.
qty	Integer	Quantity at that state. Changes if order modified.
pendingQty	Integer	Pending/unfilled quantity at that state.
disQty	Integer	Disclosed quantity (iceberg orders).
price	Double	Price at that state (limit price for limit orders).
triggerPrice	Double	Trigger price at that state (0 for non-SL orders).
exc	String	Exchange code.
tradedQty	Integer	Quantity filled at that point (cumulative).
orderUpdatedAt	String	Timestamp of when this trail entry was recorded.

Sample Response:

```
{
  "infoID": "0",
  "infoMsg": "success",
  "timestamp": 1740376802377,
  "data": {
    "symbol": null,
    "orderDetails": null,
    "trails": [
      {
        "lupdateDateTime": "2025-02-24 10:54:32",
        "ordDesc": "REJECTED MARKET order 7 qty for MARKET at Rs 1002.35",
        "ordType": "Market",
        "ordValidity": "DAY",
        "status": "Rejected",
        "rejReason": "Security not traded. Market order not allowed.",
        "qty": 7,
        "pendingQty": 7,
        "disQty": 0,
        "price": 1002.35,
        "triggerPrice": 0,
        "exc": "NSE",
        "tradedQty": 0,
        "orderUpdatedAt": "2025-02-24 10:54:24"
      }
    ]
  }
}
```

7. Trade Book

This API retrieves all executed trades for the logged-in user.

Property	Value
Method	GET
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/portfolio-services/api/portfolio/v1/tradebook

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- **Key:** sso (lowercase)
- **Value:** True

Request Parameters:

No request body required.

Response JSON:

Field	Type	Description
infoID	String	Status code: "0" = success, non-zero = error
infoMsg	String	Human-readable status message
timestamp	Time	Server timestamp in milliseconds since epoch (IST: 2025-11-27 18:20:37)
data.trades	Object	Object of executed trade objects representing all fills
trades[].symbol	Array	Symbol details object for the traded security
symbol.symbol	String	Full unique trading symbol: [INSTRUMENT][SYMBOL][SERIES][EXCHANGE][TOKEN]
symbol.dispSym	String	Display symbol for UI rendering (cleaner format)
symbol.instrument	String	Instrument type: STK=stock, IDX=index, FUT=futures, OPT=options
symbol.baseSym	String	Base symbol name without exchange/series qualifiers
symbol.companyName	String	Full registered company legal name
symbol.isin	String	International Securities Identification Number (globally unique code)
symbol.exc	String	Primary exchange code: BSE
symbol.excTkn	Integer	Exchange token (numeric identifier)
symbol.series	String	Series classification: EQ=equity (main), BE=bulk deals, SM=SME
symbol.lotSize	Double	Trading lot size; null = default lot of 1 share (equity)
symbol.tickSize	Double	Minimum price increment; prices move only in 0.05 steps
symbol.expiryDate	Date	Expiry date for derivatives; null for equity stocks
symbol.optionType	String	Option type (Call/Put); null for non-option instruments
symbol.strikePrice	Double	Strike/exercise price for options; null for stocks
symbol.streamSym	String	Streaming symbol used by market data feeds
symbol.segment	String	Market segment designation; null if not applicable
symbol.fno	Boolean	Futures & Options eligible: false=equity only, true=derivatives available
symbol.mtf	Boolean	Margin Trading Facility eligible: false=not eligible, true=can use margin

Field	Type	Description
symbol.multiplier	String	Contract multiplier (1 for stocks, 50-500 for derivatives)
symbol.freezeQty	Integer	Quantity freeze limit for day trading; null = no freeze
symbol.tradingSymbol	String	Trading symbol used for order placement
symbol.otherExc	Array	Array of other exchanges where security is listed; empty if single-exchange
symbol.isWeeklyExpiry	String	Weekly expiry flag for derivatives; null for stocks
trades[].ordId	String	System-generated order ID from which this trade executed. Links trade back to original order.
trades[].exchTrdId	Integer	Exchange Trade ID assigned by exchange during execution. Unique globally; null if not yet assigned by exchange.
trades[].exchOrdId	Long	Exchange Order ID - order number assigned by exchange upon acceptance
trades[].prdType	String	Product type: DELIVERY=T+2 demat settlement, INTRADAY=same-day square-off
trades[].ordAction	String	Trade side: BUY=purchase, SELL=sale
trades[].ordType	String	Order type that generated trade: Market, Limit, SL-M (Stop-Loss Market), Stop-loss
trades[].tradedPrice	Double	Actual execution price - price at which trade filled
trades[].tradeTime	String	Trade execution timestamp (IST). Format: dd-MMM-yyyy hh24:mm:ss
trades[].tradedQty	Integer	Quantity filled in this trade execution
trades[].remainQty	Integer	Remaining quantity in original order after this trade. 0 = fully executed
trades[].qty	Integer	Original order quantity (can be 0 if this trade resulted from a modified order)
trades[].ordValidity	String	Order validity (DAY, GTD, IOC, GTC); null if not available or inherited
trades[].undAsset	String	Underlying asset type: STK=stock, FUT=futures, OPT=options, IDX=index

Sample Response:

```

{
  "infoID": "0",
  "infoMsg": "success",
  "timestamp": 1764232437274,
  "data": {
    "trades": [
      {
        "symbol": {
          "symbol": "STK_KOLTEPATIL_EQ_BSE_532924",
          "dispSym": "KOLTEPATIL",
          "instrument": "STK",
          "baseSym": "KOLTEPATIL",
          "companyName": "KOLTE-PATIL DEVELOPERS LTD.",
          "isin": "INE094I01018",
          "exc": "BSE",
          "excTkn": 532924,
          "series": "EQ",
          "lotSize": null,
          "tickSize": "0.05",
          "expiryDate": null,
          "optionType": null,
          "strikePrice": null,

```

```

        "streamSym": "532924_BSE",
        "segment": null,
        "fno": false,
        "mtf": false,
        "multiplier": "1",
        "freezeQty": null,
        "tradingSymbol": "KOLTEPATIL",
        "otherExc": [],
        "isWeeklyExpiry": null
    },
    "ordId": "NYOYX0000BK;",
    "exchTrdId": null,
    "exchOrdId": "1764228368631711110",
    "prdType": "DELIVERY",
    "ordAction": "SELL",
    "ordType": "Limit",
    "tradedPrice": 378.05,
    "tradeTime": "2025-11-27 14:02:30",
    "tradedQty": 3,
    "remainQty": 0,
    "qty": 0,
    "ordValidity": null,
    "undAsset": "STK"
},
]
}
}

```

PORTFOLIO

1. Holdings

This API retrieves all current holdings for the logged-in user.

Property	Value
Method	GET
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/portfolio-services/api/portfolio/v2/holdings

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- **Key:** sso (lowercase)
- **Value:** True

Request Parameters:

No request body required.

Response JSON:

Field	Type	Description
infoID	String	Status code: "0" = success, non-zero = error
infoMsg	String	Human-readable status message
timestamp	Time	Server timestamp in milliseconds since epoch (IST: 2025-11-21 17:47:28)

Field	Type	Description
data.invested	Double	Total amount invested across all holdings
data.unRealizedPnl	Double	Unrealized profit/loss on all holdings; changes daily with price movements
data.marketValue	Double	Current market value of all holdings all securities
data.holdings	Array	Array of individual holding objects (each representing one security owned)
holdings[].symbol	Array	Array of symbol detail objects
symbol[].symbol	String	Full unique trading symbol: [INSTRUMENT][SYMBOL][SERIES][EXCHANGE][TOKEN]
symbol[].dispSym	String	Display symbol for UI rendering (cleaner format)
symbol[].instrument	String	Instrument type: STK=stock, IDX=index, FUT=futures, OPT=options
symbol[].baseSym	String	Base symbol name without exchange/series qualifiers
symbol[].companyName	String	Full registered company legal name
symbol[].isin	String	International Securities Identification Number (globally unique code)
symbol[].exc	String	Exchange code: NSE = primary listing exchange
symbol[].excTkn	Integer	Exchange token for internal routing and identification
symbol[].series	String	Series designation: EQ=equity (main), BE=bulk deals, SM=SME platform
symbol[].lotSize	Double	Lot size for derivatives; null = default lot of 1 share (equity)
symbol[].tickSize	Double	Minimum price increment; prices move only in 0.01 steps
symbol[].expiryDate	Date	Expiry date for derivatives; null for equity stocks (no expiration)
symbol[].optionType	String	Option type (Call/Put); null for non-option instruments
symbol[].strikePrice	Double	Strike/exercise price for options; null for stocks
symbol[].streamSym	String	Streaming symbol used by market data feeds and live quote platforms
symbol[].segment	String	Market segment designation (e.g., main board, SME); null if not applicable
symbol[].fno	Boolean	Futures & Options eligible flag: false=equity only, true=derivatives available
symbol[].mtf	Boolean	Margin Trading Facility eligible: false=not eligible, true=can trade on margin
symbol[].multiplier	String	Contract multiplier (1 for stocks, 50-500 for derivatives)
symbol[].freezeQty	Integer	Quantity freeze limit for day trading; null = no freeze or not applicable
symbol[].tradingSymbol	String	Trading symbol for order placement and queries
symbol[].otherExc	Object	Array of other exchanges where security is listed; empty if single-exchange listing
symbol[].isWeeklyExpiry	String	Weekly expiry flag for derivatives; null for stocks
holdings[].ltp	Double	Last Traded Price (current market price) - updates intraday; used for valuation
holdings[].qty	Integer	Total quantity held across all statuses (includes free, pledged, margin-used, BTST)
holdings[].holdingQty	Integer	Quantity available for selling without restrictions (free quantity)
holdings[].usedQty	Integer	Quantity currently pledged or used for margin; locked and cannot be sold without release

Field	Type	Description
holdings[].btst	Integer	Buy Today Sell Tomorrow quantity; filled today but available for sale tomorrow (T+1 settlement)
holdings[].pledgeQty	Integer	Quantity pledged to lender for collateral/loan; remains pledged until depleted
holdings[].prdType	String	Product type: DELIVERY=permanent holding, INTRADAY=same-day square-off
holdings[].avgPrice	Double	Average buy price across all purchases; used to calculate cost basis and P&L
holdings[].invested	Double	Total invested amount for this holding = avgPrice × qty (initial capital deployed)
holdings[].haircut	Double	Haircut percentage for collateral valuation; percentage discount applied to market value
holdings[].pledgeable	Boolean	Whether quantity can be pledged for collateral; false=not pledgeable, true=can pledge
holdings[].freeQty	Integer	Quantity free and unrestricted, available for immediate sale; should equal holdingQty

Sample Response:

```
{
  "infoID": "0",
  "infoMsg": "success",
  "timestamp": 1763727248814,
  "data": {
    "invested": 1656.80000000000003,
    "unRealizedPnl": -176.78000000000000916,
    "marketValue": 1480.02,
    "holdings": [
      {
        "symbol": [
          {
            "symbol": "STK_BIOFILCHEM_EQ_NSE_4136",
            "dispSym": "BIOFILCHEM-EQ",
            "instrument": "STK",
            "baseSym": "BIOFILCHEM",
            "companyName": "BIOFIL CHEM & PHARMA LTD",
            "isin": "INE829A01014",
            "exc": "NSE",
            "excTkn": 4136,
            "series": "EQ",
            "lotSize": null,
            "tickSize": "0.01",
            "expiryDate": null,
            "optionType": null,
            "strikePrice": null,
            "streamSym": "524396_BSE",
            "segment": null,
            "fno": false,
            "mtf": false,
            "multiplier": "1",
            "freezeQty": null,
            "tradingSymbol": "BIOFILCHEM",
            "otherExc": [],
            "isWeeklyExpiry": null
          }
        ],
        "ltp": 37.33,
        "qty": 4,
        "holdingQty": 4,
        "usedQty": 0,
        "btst": 0,

```

```

        "pledgeQty": 0,
        "prdType": "DELIVERY",
        "avgPrice": 38.9,
        "invested": 155.6,
        "haircut": 0.0,
        "pledgeable": false,
        "freeQty": 0
    },
    }
],

```

2. POSITIONS

This API retrieves all current positions (intraday and delivery) for the logged-in user.

Property	Value
Method	GET
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/portfolio-services/api/portfolio/v1/position-book

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- **Key:** sso (lowercase)
- **Value:** True

Request Parameters:

No request body required.

Response JSON:

Field	Type	Description
infoID	String	Status code: "0" = success, non-zero = error
infoMsg	String	Human-readable status message
timestamp	Time	Server timestamp in milliseconds since epoch
data.positions	Object	Array of position objects representing all open trades/positions
positions[].symbol	Array	Symbol details object for the security
symbol.symbol	String	Full unique trading symbol: [INSTRUMENT][SYMBOL][SERIES][EXCHANGE][TOKEN]
symbol.dispSym	String	Display symbol for UI rendering
symbol.instrument	String	Instrument type: STK=stock, IDX=index, FUT=futures, OPT=options
symbol.baseSym	String	Base symbol name without exchange/series qualifiers
symbol.companyName	String	Full registered company legal name
symbol.isin	String	International Securities Identification Number (globally unique code)
symbol.exc	String	Exchange code: BSE = primary listing exchange
symbol.excTkn	Integer	Exchange token for internal routing and identification
symbol.series	String	Series designation: EQ=equity (main board)
symbol.lotSize	Double	Lot size for derivatives; null = default lot of 1 share (equity)

Field	Type	Description
symbol.tickSize	Double	Minimum price increment; prices move only in 0.01 steps
symbol.expiryDate	Date	Expiry date for derivatives; null for equity stocks
symbol.optionType	String	Option type (Call/Put); null for non-option instruments
symbol.strikePrice	Double	Strike/exercise price for options; null for stocks
symbol.streamSym	String	Streaming symbol used by market data feeds
symbol.segment	String	Market segment designation; null if not applicable
symbol.fno	Boolean	Futures & Options eligible: false=equity only, true=derivatives available
symbol.mtf	Boolean	Margin Trading Facility eligible: false=not eligible, true=can trade on margin
symbol.multiplier	String	Contract multiplier (1 for stocks, 50-500 for derivatives)
symbol.freezeQty	Integer	Quantity freeze limit for day trading; null = no freeze
symbol.tradingSymbol	String	Trading symbol for order placement
symbol.otherExc	Object	Array of other exchanges where security is listed; empty if single-exchange
symbol.isWeeklyExpiry	String	Weekly expiry flag for derivatives; null for stocks
positions[].prdType	String	Product type: DELIVERY=T+2 settlement, INTRADAY=same-day square-off
positions[].type	String	Position type: DAILY=intraday trade, CARRY_FORWARD=overnight holding
positions[].ltp	Integer	Last Traded Price (current market price); 0.0 = no recent trades/market closed
positions[].pnlPerc	Integer	Profit/Loss percentage = $(\text{netPnl} / \text{buyAmt}) \times 100$; shows return on capital
positions[].netPnl	Integer	Net Profit/Loss in rupees; positive=profit, negative=loss
positions[].prevPos	Integer	Previous day position quantity; used for tracking overnight changes
positions[].currPos	Integer	Current position quantity at this moment
positions[].netQty	Integer	Net quantity = $\text{buyQty} - \text{sellQty}$; positive=long, negative=short
positions[].buyQty	Integer	Total buy quantity across all buy trades
positions[].sellQty	Integer	Total sell quantity across all sell trades
positions[].dayBuyQty	Integer	Intraday buy quantity (today's trades for squareoff)
positions[].daySellQty	Integer	Intraday sell quantity (today's counter-trades)
positions[].cfBuyQty	Integer	Carry-forward (overnight) buy quantity
positions[].cfSellQty	Integer	Carry-forward sell quantity
positions[].buyAvgPrice	Double	Average price of all buy trades = $\text{total buy value} / \text{buyQty}$; entry price for longs
positions[].sellAvgPrice	Double	Average price of all sell trades; exit price for longs
positions[].dayBuyAvgPrice	Double	Intraday average buy price
positions[].daySellAvgPrice	Double	Intraday average sell price
positions[].cfBuyAvgPrice	Double	Carry-forward average buy price
positions[].cfSellAvgPrice	Double	Carry-forward average sell price
positions[].buyAmt	Double	Total rupee value of all buys = $\text{buyQty} \times \text{buyAvgPrice}$; capital deployed for buys
positions[].sellAmt	Double	Total rupee value of all sells = $\text{sellQty} \times \text{sellAvgPrice}$; proceeds from sells
positions[].cfBuyAmt	Double	Carry-forward buy amount in rupees
positions[].cfSellAmt	Double	Carry-forward sell amount in rupees
positions[].avgPrice	Double	Blended average price across buys and sells; reference price for unrealized P&L

Field	Type	Description
positions[].undAsset	String	Underlying asset type: STK=stock, FUT=futures, OPT=options, IDX=index
positions[].squareOff	Boolean	Whether position can be squared off; true=open/active, false=closed/locked
positions[].transferable	Boolean	Whether position is transferable to another account or demat
positions[].ordAction	String	Last order action: BUY=buying, SELL=selling; direction of most recent trade

Sample Response:

```

"infoID": "0", "infoMsg": "success", "timestamp": 1764226850800,
"data": { "positions": [ {
  "symbol": {
    "symbol": "STK_IDEA_EQ_BSE_532822",
    "dispSym": "IDEA",
    "instrument": "STK", "baseSym": "IDEA",
    "companyName": "VODAFONE IDEA LIMITED",
    "isin": "INE669E01016",
    "exc": "BSE", "excTkn": 532822,
    "series": "EQ",
    "lotSize": null, "tickSize": "0.01",
    "expiryDate": null, "optionType": null,
    "strikePrice": null,
    "streamSym": "532822_BSE", "segment": null,
    "fno": false, "mtf": false, "multiplier": "1",
    "freezeQty": null, "tradingSymbol": "IDEA",
    "otherExc": [],
    "isWeeklyExpiry": null
  },
  "prdType": "DELIVERY",
  "type": "DAILY",
  "ltp": 0.0,
  "pnlPerc": -0.0, "netPnl": 0.0,
  "prevPos": 0, "currPos": 0,
  "netQty": 1, "buyQty": 1, "sellQty": 0,
  "dayBuyQty": 0, "daySellQty": 0,
  "cfBuyQty": 0, "cfSellQty": 0,
  "buyAvgPrice": 10.16, "sellAvgPrice": 0.0,
  "dayBuyAvgPrice": 10.16, "daySellAvgPrice": 0.0,
  "cfBuyAvgPrice": 0.0, "cfSellAvgPrice": 0.0,
  "buyAmt": 10.16, "sellAmt": 0.0,
  "cfBuyAmt": 0.0, "cfSellAmt": 0.0,
  "avgPrice": 10.16, "undAsset": "STK",
  "squareOff": true, "transferable": true,
  "ordAction": "BUY"
} ],
},

```

3.Position Conversion

This API converts a position from one product type to another (e.g., INTRADAY to DELIVERY).

Property	Value
Method	POST
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/portfolio-services/api/portfolio/v1/convert-position

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- **Key:** sso (lowercase)
- **Value:** True

Request JSON:

Field	Type	Mandatory	Description
ordAction	String	Yes	Direction of position: BUY (long) or SELL (short) to be converted.
prdType	String	Yes	Current product type of position being converted.
toPrdType	String	Yes	Target product type to convert to.
qty	Integer	Yes	Quantity to convert. Must not exceed existing position qty.
symbol	String	Yes	Trading symbol identifier in format INSTRUMENT_SYMBOL_SERIES_EXCHANGE.
excToken	String	Yes	Exchange token for security.
exc	String	Yes	Exchange code (NSE, BSE, NFO, etc.).
lotSize	Integer	No	Lot size for derivatives. Defaults to 0 for equity.
instrument	String	Yes	Instrument type: STK, IDX, FUT, OPT.
type	String	Yes	Conversion type specifying timing or method.

Sample Request:

```
{
  "ordAction": "BUY",
  "prdType": "INTRADAY",
  "toPrdType": "DELIVERY",
  "qty": 7,
  "symbol": "TCS-EQ",
  "excToken": "11536",
  "exc": "NSE",
  "lotSize": 0,
  "instrument": "STK",
  "type": "DAY1"
}
```

Response JSON:

Field	Type	Description
infoID	String	Status code. "0" = success.
infoMsg	String	Information message
timestamp	Number	Server timestamp in milliseconds
data	Object	Response data object
data.message	String	Conversion status message

Sample Response:

```
{
  "infoID": "0",
  "infoMsg": "success",
  "timestamp": 1763727716823,
  "data": {
    "message": "Conversion Request Sent Successfully"
  }
}
```

FUNDS

1. Get Limits Details

This API retrieves fund and margin limits for the logged-in user.

Property	Value
Method	GET
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/payments/api/v1/get-fund-limit

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- **Key:** sso (lowercase)
- **Value:** True

Sample Request:

No request body required.

Response JSON:

Field	Type	Description
infoID	String	Information ID
infoMsg	String	Information message
timestamp	Time	Server timestamp in milliseconds
data	Object	Response data object
data.summary	Object	Summary of fund limits
data.detailedSummary	Object	Detailed breakdown of fund limits
availableMargin	Double	Available margin remaining for new trades. Deploy capital up to this limit without exceeding risk threshold.
utilizedMargin	Double	Margin currently locked in open positions. Ratio of utilizedMargin/availableMargin shows leverage usage.
deposit	Double	Total cash deposited by client. Base capital available in account.
fundsTransferredToday	Double	Funds transferred in/out during current calendar day. For settlement and reporting.
collateral	Double	Total collateral value available (pledged securities). Can be used as margin if linked.
creditForSale	Double	Credit available for short selling. Borrowed securities available against collateral.
optionCfs	Double	Option Cash Funding Source - credit limit specifically for options.

Field	Type	Description
limitUtilization	Double	Percentage of total available limit currently utilized. Shows leverage/risk level.
fundsWithdrawalAllocation	Double	Maximum amount available for withdrawal after meeting margin requirements.
mtmProfitLoss	Double	Mark-to-Market Profit/Loss on open positions. Changes intraday with price movements.
bookedProfitLoss	Double	Booked/Realized Profit/Loss on closed positions. P&L from executed/squared-off trades.

Sample Response:

```
{
  "infoID": "0",
  "infoMsg": "success",
  "timestamp": 1746689002385,
  "data": {
    "summary": {
      "availableMargin": 50000.0, "utilizedMargin": 0.0,
      "deposit": 50000.0, "fundsTransferredToday": 0.0,
      "collateral": 0.0, "creditForSale": 0.0, "optionCfs": 0.0,
      "limitUtilization": 0.0, "fundsWithdrawalAllocation": 50000.0,
      "mtmProfitLoss": 0.0, "bookedProfitLoss": 0.0
    },
    "detailedSummary": {
      "deposit": {
        "cashDeposit": 50000.0, "notionalDeposit": 0.0,
        "adhocDeposit": 0.0, "manualCollateral": 0.0
      },
      "collateral": { "dpCollateral": 0.0, "poolCollateral": 0.0,
        "sarCollateral": 0.0, "dpPledgedCollateral": 0.0,
        "poolPledgedCollateral": 0.0, "maximumCollateralLimit": 0.0
      },
      "creditForSale": {
        "dpCfs": 0.0, "poolCfs": 0.0,
        "sarCfs": 0.0, "maximumCfsLimit": 0.0
      }, "optionCfs": { "maximumOptionCfs": 0.0 },
      "limitUtilization": { "equityPosition": 0.0, "derivativePosition": 0.0,
        "commodityPosition": 0.0
      },
      "mtmProfitLoss": { "equityPosition": 0.0, "commodityPosition": 0.0,
        "currencyPosition": 0.0, "derivativePosition": 0.0
      },
      "bookedProfitLoss": { "equityPosition": 0.0, "derivativePosition": 0.0,
        "commodityPosition": 0.0, "currencyPosition": 0.0
      }
    }
  }
}
```

PROFILE

1. Account Info.

This API retrieves account and profile information for the logged-in user.

Property	Value
Method	GET
Base URL	https://livemiddleware.indiratrade.com
Endpoint	/user-services/api/user/v1/AccountInfo

Note: When using SSO user sessions, include the SSO field in the headers and set its value to true.

Sample:

- **Key:** sso (lowercase)
- **Value:** True

Request Parameters:

No request body required.

Response JSON:

Field	Type	Description
infoID	String	Information ID
infoMsg	String	Information message
timestamp	Time	Server timestamp in milliseconds
data	Object	Response data object
data.accountInfo	Object	Account information object
exc	Array	Array of enabled exchanges for this account. Determines which markets user can trade.
accName	String	Full name of account holder. Legal name for compliance.
email	String	Email address - partially masked for privacy. Shows first 2-3 and last 2 chars.
mobile	Long	Phone number - partially masked. Shows first 2 and last 2 digits.
dob	String	Date of birth if available. Format: dd-MMM-yyyy. May be empty if not provided.
pan	String	PAN (Permanent Account Number) - masked showing only last 3 chars.
bankDetails	Array	Array of linked bank accounts with settlement details.
bankDetails[].accNo	String	Bank account number - fully masked. Used for fund transfers.
bankDetails[].bankName	String	Bank name where account is held.
bankDetails[].ifscCode	String	IFSC code for bank branch identification.
bankDetails[].default	Boolean	Whether this is the default/primary bank for settlement.
dematId	String	Demat account ID linked to trading account. Securities settle into this demat.
nomineeDetails	Array	Names of nominees for account succession in case of demise.

Sample Response:

```
{
  "infoID": "0",
  "infoMsg": "success",
  "timestamp": 1746450219350,
  "data": {
    "accountInfo": {
      "exc": [
        "NSE",
        "NFO",
        "BSE",
        "BFO",
        "MCX",
        "NCDEX",
        "CDS",
        "BCD"
      ],
      "accName": "LAVANYA S",
      "email": "la*****07@gmail.com",
      "mobile": "72XXXXXX10",
      "dob": "",
      "pan": "XXXXXX302R",
      "bankDetails": [
        {
          "accNo": "1234567890",
          "bankName": "HDFC Bank",
          "ifscCode": "ABC123654789",
          "default": false
        }
      ],
      "dematId": "13235534353434",
      "nomineeDetails": [
        "abishek",
        "sidharath"
      ]
    }
  }
}
```