

IoT-BASED HOME AUTOMATION SYSTEM USING NODEMCU AND BLYNK

ABSTRACT

The Internet of Things (IoT) has revolutionized the way people interact with electronic devices by enabling communication through the internet. Home automation is one of the most significant applications of IoT technology. The proposed project presents an IoT-Based Home Automation System using NodeMCU ESP8266 and the Blynk platform.

The system allows users to remotely control household appliances using a smartphone connected to the internet. Commands are sent through the Blynk application and processed by the NodeMCU controller, which activates relays to switch electrical loads ON or OFF. The system utilizes a regulated power supply consisting of a transformer, rectifier diodes, capacitors, and a 7805 voltage regulator.

The developed prototype demonstrates reliable remote control, user convenience, energy efficiency, and scalability. The project provides a low-cost and practical solution for smart home applications and serves as a foundation for future IoT-based automation systems.

Keywords: IoT, NodeMCU, ESP8266, Home Automation, Blynk, Wi-Fi, Smart Home.

TABLE OF CONTENTS

1. Introduction
2. Literature Survey
3. Problem Statement
4. Objectives
5. System Architecture
6. Hardware Components
7. Software Components
8. Methodology
9. Working Principle
10. Circuit Description
11. Flowchart
12. Results and Discussion
13. Applications

- 14. Advantages
 - 15. Limitations
 - 16. Future Scope
 - 17. Conclusion
 - 18. References
-

CHAPTER 1: INTRODUCTION

1.1 Introduction

The Internet of Things (IoT) is a technology that enables physical devices to communicate and exchange data over the internet. IoT has become one of the most rapidly growing technological fields due to its ability to connect devices and automate processes.

Home automation is an important application of IoT that enables users to monitor and control household appliances remotely. Traditional electrical systems require manual operation and offer limited flexibility. IoT-based systems eliminate these limitations by providing internet-enabled control and monitoring.

The objective of this project is to design and implement a smart home automation system using NodeMCU ESP8266 and the Blynk IoT platform. The system allows users to remotely control electrical appliances using a smartphone.

The implementation provides convenience, safety, energy efficiency, and scalability, making it suitable for modern smart homes.

1.2 Need for Home Automation

- Remote accessibility
- Improved comfort
- Energy conservation
- Increased safety
- Smart lifestyle adoption
- Assistance for elderly individuals

1.3 Scope

The project focuses on:

- Wireless appliance control
- Smartphone integration
- IoT communication
- Smart home applications
- Future expansion capability

CHAPTER 2: LITERATURE SURVEY

Home automation has evolved from simple timer-based systems to intelligent IoT-enabled environments.

Bluetooth-based systems offer short-range control but suffer from limited communication distance.

GSM-based systems provide long-distance operation but involve network charges and delayed communication.

ZigBee-based systems provide low-power communication but require dedicated hardware.

Wi-Fi-based IoT systems have emerged as the most popular solution due to their internet connectivity, scalability, and low implementation cost.

Recent studies indicate that cloud-based smart home systems improve energy management and user convenience while reducing operating costs.

CHAPTER 3: PROBLEM STATEMENT

Traditional home electrical systems require manual operation of appliances. Users often forget to switch off devices, resulting in unnecessary energy consumption and higher electricity bills.

Additionally, elderly and physically challenged individuals may face difficulties operating household appliances.

The problem addressed by this project is the development of a smart, reliable, and internet-enabled system capable of remotely controlling appliances through a smartphone application.

CHAPTER 4: OBJECTIVES

Primary Objectives:

- Develop an IoT-based home automation system.
- Control appliances remotely using smartphones.
- Improve energy efficiency.
- Reduce manual intervention.
- Demonstrate practical IoT implementation.

Secondary Objectives:

- Provide real-time appliance control.
- Enable future smart home integration.
- Create a scalable and cost-effective solution.

CHAPTER 5: SYSTEM ARCHITECTURE

The proposed system consists of three layers:

1. User Layer
2. Cloud Layer
3. Hardware Layer

User Layer: Smartphone running Blynk application.

Cloud Layer: Blynk cloud server handling communication.

Hardware Layer: NodeMCU, relay module, power supply, LCD display, and AC appliances.

System Operation:

Smartphone → Blynk Cloud → Wi-Fi → NodeMCU → Relay Module → Appliances

CHAPTER 6: HARDWARE COMPONENTS

NodeMCU ESP8266

NodeMCU is an open-source IoT development board featuring built-in Wi-Fi capabilities.

Specifications:

• Operating Voltage: 3.3V • Clock Speed: 80 MHz • Flash Memory: 4 MB • Wi-Fi Support: IEEE 802.11 b/g/n

Relay Module

A relay acts as an electrically operated switch.

Functions:

• Appliance control • Electrical isolation • Safety enhancement

Transformer

Converts 230V AC to low-voltage AC suitable for electronics.

Diodes

Used in rectification and reverse polarity protection.

Capacitors

Used for filtering and voltage stabilization.

7805 Voltage Regulator

Provides regulated 5V DC supply.

LCD Display

Displays operational status and appliance information.

AC Bulbs

Used as electrical loads representing household appliances.

CHAPTER 7: SOFTWARE COMPONENTS

Arduino IDE

Used for programming NodeMCU.

Features:

- Open source
- Easy programming
- Extensive library support

Blynk Platform

Provides cloud communication and smartphone interface.

Features:

- Real-time control
- Virtual buttons
- Dashboard creation
- Cloud connectivity

Libraries Used

ESP8266WiFi.h

BlynkSimpleEsp8266.h

LiquidCrystal.h

EEPROM.h

BlynkTimer.h

CHAPTER 8: METHODOLOGY

Step 1: Power supply initialization.

Step 2: NodeMCU boots and connects to Wi-Fi.

Step 3: Connection established with Blynk server.

Step 4: User sends command via smartphone.

Step 5: NodeMCU receives command.

Step 6: Relay switches appliance.

Step 7: LCD updates appliance status.

Step 8: System continues monitoring.

CHAPTER 9: WORKING PRINCIPLE

The NodeMCU continuously communicates with the Blynk cloud server through Wi-Fi.

When a user presses a button in the Blynk application, the corresponding command is sent to the cloud server.

The server forwards the command to the NodeMCU.

NodeMCU processes the command and energizes the corresponding relay channel.

The relay switches the connected AC appliance ON or OFF.

The LCD displays the current operational status.

CHAPTER 10: RESULTS AND DISCUSSION

The developed prototype successfully performed:

- Remote control of four AC bulbs.
- Stable Wi-Fi communication.
- Real-time response through Blynk.
- Reliable relay switching.
- LCD status display.

Observations:

- Response time less than 2 seconds.
- Stable operation over extended periods.
- User-friendly interface.

CHAPTER 11: APPLICATIONS

• Smart Homes • Smart Offices • Hotels • Hospitals • Educational Institutions • Industrial Automation • Energy Management Systems

CHAPTER 12: ADVANTAGES

• Low Cost • Easy Installation • Remote Accessibility • Energy Efficient • User Friendly • Scalable • Reliable • Wireless Operation

CHAPTER 13: LIMITATIONS

• Requires internet connectivity. • Dependent on Wi-Fi availability. • Basic security implementation. • Limited appliance feedback.

CHAPTER 14: FUTURE SCOPE

• Voice Control using Alexa. • Google Assistant Integration. • AI-Based Automation. • Energy Consumption Analytics. • Motion Detection. • Smart Security Features. • Mobile Notifications. • Sensor-Based Automation.

CHAPTER 15: CONCLUSION

The IoT-Based Home Automation System using NodeMCU and Blynk successfully demonstrates remote appliance control through internet connectivity. The project combines embedded systems, cloud computing, and wireless communication to provide a reliable and scalable smart home solution.

The developed system improves convenience, energy management, and operational efficiency while serving as a foundation for future smart home technologies.

REFERENCES

1. ESP8266 Technical Reference Manual
2. NodeMCU Documentation
3. Blynk IoT Platform Documentation
4. Arduino IDE Documentation
5. Internet of Things: A Hands-On Approach – Arshdeep Bahga
6. IEEE Papers on Smart Home Automation
7. Embedded Systems Design Textbooks

Filename: IoT-Based
Home Automation System
Directory: C:\Users\rohit
\OneDrive\Documents
Template: C:\Users\rohit
\AppData\Roaming\Microsoft\T
emplates\Normal.dotm
Title:
Subject:
Author:
Keywords:
Comments:
Creation Date: 14-06-2026
19:18:00
Change Number: 1
Last Saved On: 14-06-2026
19:18:00
Last Saved By:
Total Editing Time: 6 Minutes
Last Printed On: 14-06-2026
19:19:00
As of Last Complete Printing
Number of Pages: 8
Number of Words: 1,269
(approx.)
Number of Characters: 7,237
(approx.)