

Write a C program to simulate disk scheduling algorithms(14&15)

- a) FCFS
- b) SCAN
- c) C-SCAN
- d) SSTF
- e) LOOK
- f) c-LOOK

```
/*FCFS*/
#include<stdio.h>
#include<stdlib.h>
int main()
{
    int RQ[100],i,n,TotalHeadMoment=0,initial;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);

    // logic for FCFS disk scheduling

    for(i=0;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    printf("Total head moment is %d",TotalHeadMoment);
    return 0;
}

/*SSTF*/
#include<stdio.h>
#include<stdlib.h>
int main()
{
    int RQ[100],i,n,TotalHeadMoment=0,initial,count=0;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);

    // logic for sstf disk scheduling

    /* loop will execute until all process is completed*/
```

```

while(count!=n)
{
    int min=1000,d,index;
    for(i=0;i<n;i++)
    {
        d=abs(RQ[i]-initial);
        if(min>d)
        {
            min=d;
            index=i;
        }
    }
    TotalHeadMoment=TotalHeadMoment+min;
    initial=RQ[index];
    // 1000 is for max
    // you can use any number
    RQ[index]=1000;
    count++;
}

printf("Total head movement is %d",TotalHeadMoment);
return 0;
}

```

/*SCAN*/

```

#include<stdio.h>
#include<stdlib.h>
int main()
{
    int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);
    printf("Enter total disk size\n");
    scanf("%d",&size);
    printf("Enter the head movement direction for high 1 and for low 0\n");
    scanf("%d",&move);

    // logic for Scan disk scheduling

    /*logic for sort the request array */
    for(i=0;i<n;i++)
    {
        for(j=0;j<n-i-1;j++)

```

```

    {
        if(RQ[j]>RQ[j+1])
        {
            int temp;
            temp=RQ[j];
            RQ[j]=RQ[j+1];
            RQ[j+1]=temp;
        }
    }
}

int index;
for(i=0;i<n;i++)
{
    if(initial<RQ[i])
    {
        index=i;
        break;
    }
}

// if movement is towards high value
if(move==1)
{
    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
    // last movement for max size
    TotalHeadMoment=TotalHeadMoment+abs(size-RQ[i-1]-1);
    initial = size-1;
    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

// if movement is towards low value
else
{
    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

```

```

        // last movement for min size
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i+1]-0);
        initial =0;
        for(i=index;i<n;i++)
        {
            TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
            initial=RQ[i];
        }
    }

    printf("Total head movement is %d",TotalHeadMoment);
    return 0;
}

```

/*C-SCAN*/

```

#include<stdio.h>
#include<stdlib.h>
int main()
{
    int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);
    printf("Enter total disk size\n");
    scanf("%d",&size);
    printf("Enter the head movement direction for high 1 and for low 0\n");
    scanf("%d",&move);

    // logic for C-Scan disk scheduling

    /*logic for sort the request array */
    for(i=0;i<n;i++)
    {
        for( j=0;j<n-i-1;j++)
        {
            if(RQ[j]>RQ[j+1])
            {
                int temp;
                temp=RQ[j];
                RQ[j]=RQ[j+1];
            }
        }
    }
}

```

```

        RQ[j+1]=temp;
    }

}

int index;
for(i=0;i<n;i++)
{
    if(initial<RQ[i])
    {
        index=i;
        break;
    }
}

// if movement is towards high value
if(move==1)
{
    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
    // last movement for max size
    TotalHeadMoment=TotalHeadMoment+abs(size-RQ[i-1]-1);
    /*movement max to min disk */
    TotalHeadMoment=TotalHeadMoment+abs(size-1-0);
    initial=0;
    for( i=0;i<index;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}
// if movement is towards low value
else
{
    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
    // last movement for min size
    TotalHeadMoment=TotalHeadMoment+abs(RQ[i+1]-0);
    /*movement min to max disk */
    TotalHeadMoment=TotalHeadMoment+abs(size-1-0);
    initial =size-1;
    for(i=n-1;i>=index;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

```

```

    }
}

printf("Total head movement is %d",TotalHeadMoment);
return 0;
}

```

/*LOOK*/

```

#include<stdio.h>
#include<stdlib.h>
int main()
{
    int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");
    for(i=0;i<n;i++)
        scanf("%d",&RQ[i]);
    printf("Enter initial head position\n");
    scanf("%d",&initial);
    printf("Enter total disk size\n");
    scanf("%d",&size);
    printf("Enter the head movement direction for high 1 and for low 0\n");
    scanf("%d",&move);

    // logic for look disk scheduling

    /*logic for sort the request array */
    for(i=0;i<n;i++)
    {
        for(j=0;j<n-i-1;j++)
        {
            if(RQ[j]>RQ[j+1])
            {
                int temp;
                temp=RQ[j];
                RQ[j]=RQ[j+1];
                RQ[j+1]=temp;
            }
        }
    }

    int index;
    for(i=0;i<n;i++)
    {
        if(initial<RQ[i])
        {
            index=i;

```

```

        break;
    }
}

// if movement is towards high value
if(move==1)
{
    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

// if movement is towards low value
else
{
    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

printf("Total head movement is %d",TotalHeadMoment);
return 0;
}

```

/*C-Look*/

```

#include<stdio.h>
#include<stdlib.h>
int main()
{
    int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
    printf("Enter the number of Requests\n");
    scanf("%d",&n);
    printf("Enter the Requests sequence\n");

```

```

for(i=0;i<n;i++)
    scanf("%d",&RQ[i]);
printf("Enter initial head position\n");
scanf("%d",&initial);
printf("Enter total disk size\n");
scanf("%d",&size);
printf("Enter the head movement direction for high 1 and for low 0\n");
scanf("%d",&move);

// logic for C-look disk scheduling

/*logic for sort the request array */
for(i=0;i<n;i++)
{
    for( j=0;j<n-i-1;j++)
    {
        if(RQ[j]>RQ[j+1])
        {
            int temp;
            temp=RQ[j];
            RQ[j]=RQ[j+1];
            RQ[j+1]=temp;
        }
    }
}

int index;
for(i=0;i<n;i++)
{
    if(initial<RQ[i])
    {
        index=i;
        break;
    }
}

// if movement is towards high value
if(move==1)
{
    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for( i=0;i<index;i++)
    {

```



```

        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}
// if movement is towards low value
else
{
    for(i=index-1;i>=0;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for(i=n-1;i>=index;i--)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }
}

printf("Total head movement is %d",TotalHeadMoment);
return 0
}

```