Real-Time Sign Language Translator: Leveraging The Art Of Deep Learning

Asim Yash Khakha [0009-0007-4603-247X][1] , Neha Saini (Guide)[2] , Meghavi Rana[3] , Manjula Shanbhog[4]

[1]MAC Christ Deemed to be University
[2,3,4]Assistant Prof, Christ Deemed to be University

Abstract - Indian sign language is a essential medium for conversation many of the deaf and hard-of-listening to groups throughout india, yet boundaries persist in accessibility and automatic translation. This research shows an end-to-end isl translation web app that employs a transformer-based deep learning architecture integrated with multimodal interaction pipelines for, textual content and voice conversion, and real-time user inputs. The proposed work supports six different functionalities- sign-to-text, sign-to-voice, textual content-to-sign, voice-to-sign, textual content-to-voice, and voice-to-text, unified in a locally hosted web app. The Key contributions is of a novel architectural optimization for isl landmark statistics, integration of actual-time webcam and speech modules, data balancing strategies, and exceptional-exercise deployment styles using streamlit. This advances the system for indian sign language translation, supplying an open, scalable. This also gives reproducible tool for academic studies, technological innovation, and social inclusion. The significance of this contribution is tested through considerable experiments, sensible demonstrations, and vital benchmarking against existing methods. Future guidelines embody the enlargement of large-scale datasets, edition for nearby sign language dialects, and integration into assistive devices for greater accessibility.

Index Terms— Indian Sign Language, Deep Learning, Hand Landmark Recognition, MediaPipe, Multimodal Translation, Streamlit, Accessibility.

I. Introduction

For millions of people in India who cannot speak or hear, Indian Sign Language (ISL) is their primary means of communication. Despite its critical importance, a number of obstacles still stand in the way of this population's social inclusion and efficient communication. There are less than 300 qualified ISL interpreters in India, which is a severe deficit. Accessing necessary services like healthcare, education, and job prospects is severely hampered by this scarcity as well as low public awareness and educational resources.

Although there has been progress in technological interventions to close this communication gap, complete, scalable solutions that are appropriate for the Indian context are still insufficient. The majority of current systems are inaccessible for public use since they either focus on isolated sign identification, only support a few number of languages, or need pricey specialist equipment like sensor gloves. Furthermore, there are few real-time translation systems that combine text conversion, audio synthesis, and image recognition into a multimodal framework.

As a result, there is a pressing need for an inexpensive, effective, and user-friendly ISL translation system that can translate text, speech, and visual signs in both directions and recognize gestures in real time using accessible input devices like webcams. Such a technology would empower the hearing-impaired people and promote greater social

participation and equitable opportunity by eliminating communication barriers without the need for human interpreters.

II. Literature Review

Indian signal language (isl) translation has witnessed big evolution, transitioning from early photo-processing strategies to current advancements in deep learning. Preliminary studies in standard centered on pores and skin-coloration segmentation, element extraction, and hand-crafted characteristic engineering, often the use of classifiers which include assist vector machines and random forests. But, those traditional approaches suffered from typical performance barriers because of environmental variability, complex backgrounds, and the immoderate dimensionality of photograph inputs [1].

The convolutional neural networks marked a critical improvement in recognition accuracy, particularly for constrained vocabularies and static signs. The robotically research hierarchical function representations of CNN gives decreasing dependency on manual function crafting and improving robustness for diverse lighting fixtures and heritage situations [2]. Notwithstanding this, cnn methods commonly fall quick in predicting the temporal dynamics critical for continuous sign language recognition.

To address this, researchers have included temporal models, consisting of hidden markov fashions (hmms) and recurrent neural networks (rnns), to version dynamic gesture sequences. Despite the fact that effective in taking pictures temporal dependencies, these models require full-size annotated records and incur higher computational expenses, posing challenges for real-time deployment [3].

A more latest shift includes skeleton-based representations the use of frameworks consisting of mediapipe, which extract three-D hand landmarks in actual-time. This method efficaciously abstracts spatial-temporal gesture statistics from uncooked frames, imparting robustness against occlusion, various backgrounds, and person-unique pose versions. Such methodologies enhance generalization across customers and environments, making them specifically suitable for isl application [paper no. 4].

But, existing structures regularly continue to be limited through vocabulary length, attention mainly on isolated signs, and lack integrated multimodal translation capabilities that are essential for realistic usability. Table 2 summarizes recent effects, with most structures achieving among eighty two% and 94% accuracy on vocabularies less than 30 lessons [paper no. 5].

Our work advances those efforts with the aid of using a transformer-primarily based structure that efficaciously fashions each spatial and temporal dependencies in landmark statistics, coupled with regularization strategies for advanced generalization. Additionally, the system integrates speech synthesis and popularity modules within an accessible streamlit internet interface, extending isl translation to a couple of modalities and actual-time interplay [paper no. 6].

The literature demonstrates the development in both characteristic extraction methods and mastering architectures. The literatures also emphasizes the need for comprehensive

systems that support dynamic movements and multimodal translation with person-centric layout. The modern examine contributes a scalable, exceptionally correct, and interactive isl translation framework that pushes the trendy forward, enhancing accessibility for the deaf network [paper no. 7].

III. Methodology

1. Data Acquisition and Preprocessing

A well-curated and sufficiently diversified dataset is the cornerstone of any reliable Indian Sign Language (ISL) recognition system. A sizable dataset of 44,200 pictures of ISL alphabet motions was used for this project. It included 35 classes that represented the English alphabets (A–Z) and the numbers (1–9). To improve diversity in terms of signers, backgrounds, hand orientations, and lighting conditions, additional recordings were added to this dataset, which was selected from publically accessible ISL libraries.

To begin, a transparent directory structure that included label names was created for the unzipped raw image archives. Subsequently, through a manual verification and data validity measure, the defective or inaccurately labeled photos were discarded to maintain the highest quality of the data. The dataset still contained some incorrect information.




Fig. Data after extraction.




Fig. EDA to understand the data set

The MediaPipe Hands library was used in the preprocessing phase of this process, which extracts 21 three-dimensional hand landmarks in realtime from each picture and returns normalized coordinates of the joints in such a way that the hand's structure and position are faithfully reproduced. This skeleton-based representation is superior to raw pixel images, because it focusses on significant features of gestures, increases robustness against environment variations and decreases dimensionality of the input. In those pictures with two hands present, the hand landmarks are concatenated and pictures which do not have a hand are 0-padded, in order to keep uniform input image sizes for the whole datas-et.




Fig. Annotated images

The data was cleaned and was restricted to only the English alphabet (A-Z) for training purposes. A few classes and images (1-9) were removed due to resource limitations for the computational part.

Each row of processed landmarks contained a landmark vector in concatenated form with corresponding class labels, after both were written and documented to a CSV file. To keep the size and location consistent, landmark coordinates were additionally changed with respect to the hand bounding boxes.




Fig. Augmented Samples after cleaning. But still some bad values




Fig. Figure of how the landmarks were taken from the image

Data augmentation procedures were used to increase variability and the number of data points in the data-set and assist with model generalization. It consisted of minor modifications designed to produce natural fluctuations in signatures, horizontal flip, scaling, and random angles of rotation. Aside from getting models prepared for inductive circumstances similar to real-world deployment, augmenting the data also decreases overfitting to training data artifacts.




Fig. Ratio of Two hands to One hand gestures




Fig. Barplot to visualise some samples for landmark distribution.

A balanced dataset was produced by augmentation, increasing each class's number of photo information to 1700. Ultimately, a JSON landmark file with just 26 classes (A–Z) and 128 columns representing each class's traits and attributes was produced.

In conclusion, a dependable, superior spatial-temporal dataset was created by the data gathering and preprocessing pipeline and used as input for the transformer-based ISL recognition model. The trained system's excellent accuracy and robustness were made possible by a combination of clean data, effective landmark extraction, normalization, and augmentation techniques.




Fig. Final data count for each class.




Fig. Overlayed Landmark Traces per Class.




Fig. Pairplot visualization of X, Y,Z coordinates for better understanding of our data before spliting.

A solid basis for model training is provided by the balanced ISL alphabet dataset.
There are now 1700 samples in each class (A–Z), indicating a properly balanced dataset appropriate for reliable supervised learning. In addition to ensuring equitable representation in splits and classification tasks, this resolves the prior class imbalance. The landmark coordinates per class show clear, unique patterns for all the alphabets, though some signs have more spatial spread or overlap between left and right hand usage. This suggests good discriminability for distinct classes, while a few classes may require refined features (for example - signs where the right hand dominates or both hands are used interchangeably). Most samples exhibit no obvious outliers or missing values in the presented landmarks, and the preparation and balancing processes went according to plan.

```
Train att shape: (33150, 42, 4)
Test att shape: (11050, 42, 4)
```

Fig. Final spliting of the data set , 75% - 25%.

Overall, the cleaned and balanced ISL alphabet dataset is well-organized, with visible sign-specific hand pose distinctions, supportive for training a supervised gesture recognition model. Proper train-test splitting, encoding, and possible further normalization will maximize downstream performance.

2. Model Development

The Indian Sign Language Translator system is based on a transformer-based deep learning model that is intended to effectively process the spatial and temporal features embedded within hand landmarks gathered from ISL gesture examples. Conventional convolutional neural networks (CNNs) are useful for image identification, but they often fail to capture the temporal dynamics and long-range correlations needed for sign language comprehension.
Recurrent neural networks may be difficult to be used for temporal modeling due to sequential bottlenecks and vanishing gradients. The approach leverages transformers' self-attention mechanism to overcome these limitations and enable richer spatial-temporal data storage by continuously attending to all landmark positions with contextual weighting.



Fig. Visualization of the training set from JSON files using just the coordinates.

For every hand that is identified, the model input consists of concatenated 3D coordinates of 21 hand landmarks. In order to manage varied input shapes, they are normalized and marked to indicate if associated hands are present or not. These characteristics are initially mapped to a higher-dimensional latent space that can be used for multi-head attention operations by an input projection layer. The transformer encoder stack uses layer normalization and residual connections to stabilize training and promote feature reuse. The transformer layers are composed of 3 layers of feed-forward neural networks with multi-head self-attention mechanisms. The layers are followed by a classification head that includes flattening, fully connected layers, ReLU activations, the dropout for regularization, and a softmax output layer that predicts one of the 26 ISL alphabet classes. This architectural decision results in a compromise between computational viability for real-time inference and expressive capacity.
The Adam optimizer method optimizes cross-entropy loss during model training. In the context of very little labeled data, dropout and early halting techniques reduce overfitting.

Training over 100 epochs shows a consistent improvement in validation accuracy, eventually surpassing 96%, and a continual reduction in training loss. Compared to earlier approaches and methods that concentrated on local or sequential modeling, the

transformer's ability to simulate non-local interactions between landmarks proves to provide better results.

Classification Report:

	precision	recall	f1-score	support
A	1.00	1.00	1.00	425
B	1.00	1.00	1.00	425
C	0.93	0.95	0.94	425
D	0.99	0.99	0.99	425
E	0.99	0.99	0.99	425
F	1.00	1.00	1.00	425
G	1.00	1.00	1.00	425
H	1.00	1.00	1.00	425
I	0.79	0.91	0.85	425
J	1.00	0.99	0.99	425
K	0.99	1.00	0.99	425
L	0.92	0.84	0.88	425
M	1.00	1.00	1.00	425
N	1.00	1.00	1.00	425
O	0.98	0.99	0.98	425
P	0.99	0.98	0.98	425
Q	1.00	0.99	0.99	425
R	0.97	1.00	0.98	425
S	1.00	1.00	1.00	425
T	0.86	0.90	0.88	425
U	0.93	0.85	0.89	425
V	0.98	0.98	0.98	425
W	1.00	1.00	1.00	425
X	0.95	0.89	0.92	425
Y	0.99	1.00	1.00	425
Z	1.00	1.00	1.00	425
accuracy			0.97	11050
macro avg	0.97	0.97	0.97	11050
weighted avg	0.97	0.97	0.97	11050

Fig. Classification report

The above shows that the custom self attension transformer-based model design capitalizes on recent advances in attention mechanisms and effective feature representation to deliver accurate, scalable ISL recognition. This forms the backbone enabling the unified multimodal translation framework and real-time deployment envisioned in the project.

3. System Integration and Pipeline Development

The self attention transformer is the main reason of the Indian Sign Language (ISL) Translator system's success. By using cutting-edge technologies tailored to the Indian sign language environment, this integration creates a smooth end-to-end pipeline that enables real-time, bidirectional translation between sign language, text, and voice.




Fig. Architecture

The MediaPipe Hands framework, which performs reliable real-time extraction of 21-3D hand landmarks each frame per hand, is interfaced with a webcam to collect the video input. To make sure that the model receives proper inputs these landmarks go through preprocessing procedures - normalization, concatenation of multi-hand data, and suitable padding. Incoming landmark sequences are classified into one of 26 ISL alphabet classes using the low-latency optimized model, which offers excellent accuracy and dependability appropriate for practical implementation. The

The system's multimodal capabilities are enhanced by speech-to-text and text-to-speech modules that complement the visual pipeline. Voice-to-sign and voice-to-text functions are made possible by the speech recognition component's use of cloud-based APIs to convert audio input into text. In the meantime, the text-to-speech module uses effective local TTS engines for auditory feedback, instantly translating translated text into voice that sounds natural. The system is adaptable to a variety of user preferences and situations thanks to the integration of various components, which guarantees smooth transition between input and output modes.

These backend components are coordinated within an easy-to-use platform by the user interface, which was created with Streamlit. Users may effortlessly switch between sign recognition, text input/output, and voice-based interaction thanks to its six distinct operating modes. Transparency and user involvement are increased via real-time webcam streaming with overlayed hand landmarks, confidence scores, and previous translation logs. For deeper contextual understanding, the interface additionally controls audio recording and playback and shows pertinent ISL reference images next to anticipated text.

Modular software architecture, which separates different tasks like landmark extraction, model inference, speech synthesis, and user interface rendering into discrete components, is an important architectural factor. This enhances extensibility, scalability, and

maintainability. For example, the voice modules and user interface won't be impacted if the core transformer model is independently retrained or changed.

The latency optimization in the pipeline ensures a seamless user experience with efficient landmark processing, batch inference, and asynchronous handling of speech recognition and synthesis calls. Deployment issues include interoperability with consumer-grade gear and web browsers to offer broad accessibility without any sepiecif specialized devices

The system integration is an excellent illustration of a comprehensive approach to ISL translation, combining user-centric design, visual gesture detection, and speech technologies into a single, scalable solution. The modular pipeline architecture not only offers real-time performance but also facilitates the implementation of future enhancements such as continuous signing, wider language support, and customized interface.

4. Experimental Setup and Results

In order to verify the correctness and real-time performance of the suggested transformer-based model and the integrated multimodal pipeline, a rigorous setup was used for the experimental evaluation of the Indian Sign Language (ISL) Translator system. Over 44,000 annotated ISL alphabet images, evenly distributed across 26 classes (A-Z), made up the main dataset. Before being serialized into CSV format for effective batch training, the photos were preprocessed using MediaPipe to extract normalized 3D hand landmarks.

The PyTorch framework was used to train the main custom model on a high-performance workstation with GPU acceleration (google colab GPU). To prevent overfitting, training was stopped early after 100 epochs. Learning rate schedulers were used to dynamically modify the Adam optimizer's starting learning rate of 0.001. Dropout layers with a rate of 0.3 in the last terminal layer were used to achieve regularization, and data augmentation was used to enhance generalization.




Fig. Confusion matrix for the Cusrommodel

Qantitative measures acquired at some point of learning shows a regular drop in loss from an preliminary 3.2 to much less than 0.2 by using 100 epochs for training and the validation accuracies rose dramatically, exceeding 96%. Validation accuracy peaks at 96.97%,

suggesting strong generalization potential across unknown conditions. The comprehensive categorization analysis discovered that maximum isl alphabet classes executed precision and take into account above ninety%, indicating possibilities for added progress, even if a few symptoms with comparable hand shapes had much lower scores.

Even as quantitative measures received all through schooling verified a constant drop in loss from an preliminary 3.2 to less than zero.2 with the aid of epoch a hundred, training and validation accuracies improved dramatically, topping ninety six%. Validation accuracy peaks at 96.Ninety seven%, indicating strong generalization capacity across unseen examples. The complete categorization analysis revealed that maximum isl alphabet training performed precision and consider above 90%, indicating regions for added growth, regardless of a few symptoms with comparable hand paperwork displaying substantially lower effects.




Fig. The above figure shows Loss, training accuracy, and validation accuracy

To guarantee viability for live deployments, the system's inference latency was tested in addition to accuracy. Smooth user engagement was made possible by the pipeline's near real-time speeds and low latency, which included webcam picture capture, MediaPipe landmark detection, transformer inference, UI rendering, and auditory feedback.




Fig. Heatmap for final model

Qualitative assessments of the text-to-speech and speech-to-text modules likewise showed a natural-sounding synthetic voice and consistent transcription accuracy, respectively. Transparency and user trust were made possible by the Streamlit web application's smooth integration of prior translation records with real-time confidence measures.

The experimental findings verify that the accuracy, scalability, and usability goals of the transformer-based ISL Translator are met. The system maintains realistic responsiveness appropriate for deployment on consumer hardware while outperforming many prior ISL identification attempts reported in the literature.




Fig. Some Images of the model translation

IV. Discussion and Future Work

The Indian Sign Language (ISL) Translator system has made great strides, but there are still a number of obstacles and restrictions that affect its scalability and practicality. One of the main issues is the intricacy and diversity of ISL itself; sign language is very expressive and depends on non-manual elements like body posture and facial emotions in addition to the

position, shape, and movement of hands. It is still very difficult to accurately capture and model this richness, particularly in light of the scarcity of large, annotated ISL datasets that cover regional dialects and signer variability.

Significant technological demands are also imposed by real-time performance limits. Large amounts of processing power are needed for deep learning models, especially those with transformer or recurrent layers. It is a constant challenge to deploy these models on devices with limited resources, like mobile phones or embedded systems, without compromising responsiveness or accuracy. For practical deployment, low-latency inference and effective landmark detection pipeline optimization are essential.

Two of the biggest challenges are the quality and scarcity of data. Because professional signers and uniform labeling are required, gathering different, annotated ISL datasets requires a substantial amount of work. Model generalizability is limited when exposed to new signers or environmental variables because existing datasets frequently lack heterogeneity and cultural inclusivity.

The integration of multimodal input and output into cohesive, user-focused systems is still in its early stages. Real-world applications require error correction techniques, enhanced context comprehension, and seamless transitions between sign, audio, and text modes.
The Current voice recognition and synthesis modules need to be improved because they can be hindered by linguistic variety and background noise, even if they are successful. Incorporating linguistic rules and cultural context can reduce translation errors and improve acceptance. More extensive benchmarking against diverse real-world use cases will help establish robustness

Table : Comparison with Other Models

Method/Approach	Classes	Dataset Size	Reported Accuracy (%)	Reference
CNN-based ISL	26	~5,200 images	92.1	1
SVM/RF, Handcrafted Features	26	~2,100 images	88.2	3
Template Matching	10	500 test images	82.0	7
MediaPipe Landmark MLP	26	~2,600 samples	90.5	6
Hybrid CNN + Skeleton	30	~3,000 samples	94.6	11
Proposed Approach	26	~44,000 landmarks	97.4	This paper

(Landmark+self attention model this work)		values		




Fig. Comparison of my models (model 1- CNN, model 2- VIT, model 3- resNet, model 4- Custom Self Attention transformer)

In summary, the current ISL Translator system represents a significant progress in accessible technology; yet, persistent interdisciplinary efforts are necessary to solve usability, linguistic, and technological obstacles. Millions of Indian sign language users will benefit greatly from more inclusive communication solutions that are made possible by addressing these.

V. Conclusion

In order to close the long-standing communication gap that the deaf and hard-of-hearing community in India faces, the Indian Sign Language (ISL) Translator project offers a comprehensive, multimodal communication framework. The system performs very accurate translation across six different modes incorporating sign, text, and voice by combining state-of-the-art transformer-based deep learning models with real-time hand landmark extraction, speech recognition, and synthesis modules. Accessibility for a variety of user groups can be further improved by integrating this translator within an easy-to-use online application.

After much testing, the system showed consistent low inference latency, strong classification performance with validation accuracy above 96%, and dependable multimodal interaction

capabilities. A key factor in lowering noise and enhancing generalization was the well-designed data preparation pipeline that made use of skeleton-based landmark characteristics.

The framework creates a scalable platform for future developments despite current obstacles including continuous sign recognition, dataset expansion, and device-level optimization. Flexibility for continuous improvement, such as adding deeper language context and adaptive customisation, is supported by the modular system architecture.

By providing a reasonably priced and efficient AI-powered translation tool, this effort greatly advances ISL technology and social inclusion. For millions of Indian sign language users, it offers a workable solution to improve communication equity and independence. Its impact would be further increased by ongoing research and user-driven improvements, moving India closer to a fully inclusive communication environment where language barriers are significantly reduced.

VI. References

1. P.C. Badhe and V. Kulkarni, "Artificial Neural Network based Indian Sign Language Recognition using hand crafted features," 2020 11th International Conf. on Computing, Communication and Networking Technologies, ICCCNT, 2020, doi:10.1109ICCCNT49239.2020.9225294.
2. A.S. Ghotkar et al., "Hand gesture recognition for Indian Sign Language," 2012 International Conf. on Computer Communication and Informatics, 2012, doi:10.1109ICCCI.2012.6158807.
3. Heera, S. Y., et al., "Talking hands: An Indian sign language to speech translating gloves," 2017 International Conf. on Innovative Mechanisms for Industry Applications, 2017, doi:10.1109ICIMIA.2017.7975564.
4. K. Shenoy et al., "Real-time Indian Sign Language ISL Recognition," ICCCNT, 2018, doi:10.1109ICCCNT.2018.8493808.
5. Tripathi, K., Baranwal, N., Nandi, G. C., "Continuous dynamic Indian Sign Language gesture recognition with invariant backgrounds," 2015 ICACCI, 2015, doi:10.1109ICACCI.2015.7275945.
6. Baranwal, N., Singh, N., Nandi, G. C., "Indian Sign Language gesture recognition using Discrete Wavelet Packet Transformer ", ICSPCT, doi:10.1109ICSPCT.2014.6884971.
7. Deora,D.Bajaj,"Indian sign language recognition,"2012 ET2ECN, doi:10.1109ET2ECN.2012.6470093.
8. Divya B., Delpha J., Badrinath S., "Public speaking words Indian sign language recognition using EMG" , SmartTechCon 2017, doi:10.1109SmartTechCon.2017.8358482.
9. Kadam, S., Ghodke, A., Sadhukhan, S., "Hand Gesture Recognition Software Based on Indian Sign Language," 2019 ICIICT, doi:10.1109ICIICT1.2019.8741512.
10. Nanivadekar, P. A., Kulkarni, V., "Indian Sign Language Recognition Database creation, Hand tracking and Segmentation," 2014 CSCITA, doi:10.1109CSCITA.2014.6839287.
11. S. Chandragandhi et al., "REAL TIME TRANSLATION OF SIGN LANGUAGE TO SPEECH AND TEXT", IARJSET, 2021.