

CASE STUDY

**COMPARATIVE STUDY OF SOBEL VS. CANNY FOR
MEDICAL X-RAY BOUNDARY DETECTION**

Submitted by:

S Radhitha Reddy - 22STUCHH010772

K Ranathi - 22STUCHH010770

CH Akshay Reddy - 22STUCHH010751

Manoj Patel - 22STUCHH010722

S Rohit Reddy - 22STUCHH010849

BACHELOR OF TECHNOLOGY(DS&AI)

Faculty Project Mentor

Dr. K Srinivasa Rao



Faculty of Science & Technology

IFHE University, Hyderabad

ABSTRACT

This project presents a comparative analysis of two major edge detection algorithms—Sobel and Canny—applied to medical X-ray images. Edge detection is a vital process in medical image analysis as it enhances important structural boundaries that aid in accurate segmentation and diagnosis.

The Sobel operator uses a gradient-based method that determines edges by measuring changes in intensity in horizontal and vertical directions. In contrast, the Canny algorithm employs a multistage approach that includes Gaussian smoothing, gradient computation, non-maximum suppression, and hysteresis thresholding, resulting in thinner, continuous, and noise-free edges.

The goal of this study is to evaluate both methods in terms of accuracy, clarity, computational efficiency, and noise resilience. The implementation is performed in Python using the OpenCV library within Google Colab, employing sample medical X-ray images as input data.

Results indicate that the Canny detector produces clearer and more continuous boundaries, outperforming Sobel in handling noise and preserving structural detail. Consequently, Canny is identified as the more suitable approach for medical image boundary detection and diagnostic applications.

Keywords: Medical Imaging, Edge Detection, Sobel Operator, Canny Algorithm, OpenCV, Boundary Detection

CHAPTER 1:PROBLEM STATEMENT

1.1 INTRODUCTION

Medical imaging techniques such as X-rays, CT, and MRI scans are essential diagnostic tools for healthcare professionals. Detecting edges in these images helps in identifying structural boundaries that reveal abnormalities such as fractures and tumors. Edge detection algorithms simplify the identification of intensity variations, allowing for the extraction of meaningful features.

However, X-ray images are often affected by noise, uneven brightness, and low contrast, making edge extraction challenging. The success of an algorithm depends on its design and how effectively it suppresses noise while preserving edge quality. This study compares the performance of the Sobel and Canny edge detectors to determine which provides better-defined and continuous boundaries in noisy medical images.

1.2 PROBLEM DEFINITION

Sobel and Canny are both well-known edge detectors, yet they differ in computational complexity and accuracy. Sobel's approach is faster but more sensitive to noise, whereas Canny's multi-stage filtering yields more accurate results but with higher computation time.

This study addresses the question:

“Which edge detection technique—Sobel or Canny—provides superior clarity, continuity, and noise reduction in medical X-ray images?”

1.3 RESEARCH QUESTIONS

1. Which algorithm produces clearer and more continuous edges in X-ray images?
2. How effectively does the Gaussian smoothing in Canny minimize noise compared to Sobel?
3. What are the computational trade-offs between the two methods?

1.4 PURPOSE

The purpose of this research is to compare the Sobel and Canny algorithms for medical X-ray image analysis and determine their suitability for real-world medical applications. Their strengths and weaknesses are evaluated through both qualitative and quantitative analysis.

1.5 SCOPE OF THE PROJECT

The project is implemented in Python using OpenCV in Google Colab and focuses on:

- Edge thickness and visibility
- Noise reduction and boundary continuity
- Simplicity and computational time

The research is limited to 2D grayscale X-ray images and does not include 3D reconstruction or advanced segmentation.

CHAPTER 2:LITERATURE REVIEW

2.1 INTRODUCTION

Edge detection is one of the fundamental processes in image processing and computer vision. In the context of medical imaging, it helps differentiate bones and tissues, improving diagnostic interpretation. Several algorithms have been proposed, ranging from simple gradient-based methods to complex multi-step techniques. This chapter reviews the Sobel and Canny methods and relevant literature comparing their effectiveness.

2.2 REVIEW OF THE EDGE DETECTION TECHNIQUES

Sobel Operator:

The Sobel operator is a gradient-based edge detector that applies convolution masks to compute intensity gradients along both the x and y directions. It enhances regions with strong intensity transitions, marking them as potential edges.

Advantages:

Simple to put into practice

Computationally quick

Perfect for creating robust borders

Limitations:

Noise-sensitive

Makes thick edges

less precise for small features

The Canny Edge Detector:

Developed by John Canny in 1986, the Canny algorithm follows a systematic multi-stage procedure involving Gaussian smoothing, gradient computation, non-maximum suppression, and hysteresis thresholding.

Advantages:

Identifies smooth and thin borders

Noise resistant

Yields outcomes that are aesthetically pleasing

Limitations:

High cost of computation

Parameters need to be adjusted (threshold values)

2.3 RELATED WORK

Research comparing Sobel and Canny has shown that the latter performs better in detecting fine details in medical and dental X-rays. Gonzalez and Woods (2018) note that gradient-based techniques like Sobel are effective for basic images but struggle in noisy medical data. Studies such as Das (2019) reaffirm that Canny achieves a better balance between precision and noise reduction.

2.3 SUMMAERY OF LITERATION

Key findings from the literature include:

- Sobel is suitable for quick and basic edge detection.
- Canny offers superior accuracy and continuity.
- Preprocessing and threshold settings significantly affect both algorithms' results.

Canny is therefore considered more suitable for high-accuracy medical image analysis.

CHAPTER 3: METHODOLOGY

3.1 TOOLS AND ENVIRONMENT

- **Programming Language:** Python
- **Environment:** Google Colab
- **Libraries Used:** OpenCV, NumPy, Matplotlib
- **Dataset:** Sample X-ray images (hand, chest, leg, etc.)

3.2 PROCESS FLOW

1. **Image Input:** Load medical X-ray images.
2. **Preprocessing:** Convert to grayscale and apply Gaussian blur.
3. **Edge Detection:**
 - **Sobel:** Calculate gradients (G_x , G_y) and magnitude.
 - **Canny:** Apply Gaussian filter, find gradients, suppress non-maximum pixels,
and apply thresholding.
4. **Result Comparison:** Visually and quantitatively compare outputs for edge clarity and continuity.

3.3 IMPLEMENTATION OVERVIEW

Sobel Operator:

$$G = \sqrt{G_x^2 + G_y^2}$$

Magnitude

Uses 3x3 kernels to compute horizontal and vertical derivatives.

Canny Algorithm Steps:

- Step 1: Gaussian Smoothing
- Step 2: Gradient Calculation
- Step 3: Non-Maximum Suppression
- Step 4: Hysteresis Thresholding

3.4 EVALUATION PARAMENTS

PARAMETER	SOBEL	CANNY
Edge Clarity	Moderate	Excellent
Noise Handling	Poor	High

Computational Cost	Low	Moderate
Edge Thickness	Thick	Thin
Continuity	Interrupted	Continuous

CHAPETR 4: RESULTS AND DISCUSSION

4.1 EXPERIMENTAL RESULTS

When applied to medical X-ray images, both algorithms exhibit distinct characteristics:

Sobel:

- Produces bold, thick edges.
- Sensitive to noise; sometimes detects irrelevant background structures.

Canny:

- Generates smooth, thin, and connected edges.
- Effectively suppresses noise through Gaussian filtering.
- Produces more diagnostic-quality results suitable for analysis.

4.2 VISUAL ANALYSIS




Figure 4.1 – Experimental Output on Sample Images

Comparison of Sobel and Canny edge detection applied on grayscale sample images (Camera and Coins). Sobel shows thick and bold edges, while Canny produces fine, continuous, and noise-free edges.




Figure 4.2 – Real X-Ray Image (Chest)

Chest X-ray processed with Sobel and Canny filters. Sobel highlights broad rib and lung structures, whereas Canny yields sharper, continuous edges with improved clarity and reduced noise.




Figure 4.3 – Real X-Ray Image (Leg)

Leg X-ray image processed using Sobel and Canny edge detectors. The Sobel output shows rough and uneven boundaries, while Canny effectively enhances bone contours with thin and precise edges.

4.3 DISCUSSION

Experimental outcomes confirm that Canny consistently outperforms Sobel in terms of clarity, edge precision, and noise resistance. While Sobel’s simplicity makes it suitable for real-time applications, it introduces unnecessary artifacts. Canny’s multistage filtering ensures high-quality, continuous boundaries that are essential for accurate medical diagnosis.

4.4 SUMMARY OF COMPARISON

Criteria	Sobel Operator	Canny Edge Detector
Algorithm Type	Gradient-Based	Multi-Stage filter
Noise Reduction	Low	High
Edge Sharpness	Moderate	Excellent
Computational Time	Low	Medium
Edge Continuity	Broken	Continuous
Suitability	Simple Detection	Diagnostic images

CHAPTER 5: CONCLUSION

A detailed comparative analysis of the Sobel and Canny edge detectors was performed on medical X-ray images to assess their performance in terms of clarity, precision, and noise reduction.

The study found that the **Sobel operator**, though computationally simple and fast, tends to produce thick, noisy edges, making it less effective for medical images. Conversely, the **Canny algorithm**—with its combination of Gaussian smoothing, gradient calculation, and thresholding—provides finer, continuous, and cleaner edges suitable for medical diagnostics.

The results clearly indicate that Canny is the preferred method for medical X-ray analysis due to its ability to maintain edge continuity and suppress noise effectively. Sobel remains useful for quick or real-time visualizations but lacks the precision required for diagnostic imaging.

In summary, the selection of an appropriate edge detection algorithm plays a crucial role in medical image analysis. Sobel provides simplicity and speed, while Canny offers the robustness and detail needed for accurate medical interpretation.

REFERENCES

- **John F. Canny** (1986), “*A Computational Approach to Edge Detection*”, IEEE Transactions on Pattern Analysis and Machine Intelligence, Vol. PAMI-8, No. 6, pp. 679–698.
— The original paper that introduced the Canny edge detection algorithm and its optimization criteria for edge accuracy, localization, and noise suppression.
- **Rafael C. Gonzalez and Richard E. Woods** (2018), “*Digital Image Processing*”, 4th Edition, Pearson Education.
— A foundational textbook covering theoretical and practical aspects of image enhancement, filtering, and edge detection techniques.
- **Pratt, W. K.** (2001), “*Digital Image Processing for Medical Applications*”, Cambridge University Press.
— Discusses medical image analysis techniques and the significance of boundary detection in diagnostic imaging.
- **Das, S.** (2019), “*Comparison of Edge Detection Techniques for Medical Imaging*”, International Journal of Computer Applications (IJCA), Vol. 181, Issue 20, pp. 18–22.
— A comparative study highlighting the advantages of Canny and its suitability for detecting fine edges in medical images.
- **OpenCV Documentation** — <https://docs.opencv.org>
— Official OpenCV documentation providing code examples, function references, and explanations for edge detection algorithms including Sobel and Canny.
- **Scikit-Image Library Documentation** — <https://scikit-image.org>
— A comprehensive Python library for image processing, used for algorithm testing and performance evaluation.

