



PTZ CAMERA

EIE-291125-DLP

5MP Network Camera- FHD Resolution

SYSTEM OVERVIEW

A PTZ (Pan-Tilt-Zoom) camera is a versatile surveillance solution essential for the dynamic environments of construction and demolition. Unlike fixed cameras, it offers a 360° field of view, allowing remote operators to pan across the horizon, tilt to view high-reach structures, and zoom in on specific details like safety hazards or equipment IDs.

Built to be "job-site tough," these cameras feature rugged, weatherproof housings that withstand dust and vibration. They provide 24/7 security, remote project management, and high-definition time-lapse recording, making them an all-in-one tool for monitoring progress and ensuring site safety.

FUNCTIONS

When a scene has both very dark and very bright areas, the high contrast can distort the image. WDR (Wide Dynamic Range) technology solves this by balancing the light, ensuring a clear and vivid picture even in tricky conditions. It is ideal for entryways, jewelry shops, and outdoor sites where lighting changes constantly.

When a scene is too dark, the camera uses Infrared (IR) light to illuminate the area, making it visible to the lens. The camera captures full-color images during the day and automatically switches to a black-and-white (monochrome) mode at night to ensure clear visibility in the dark.

This camera delivers sharper, high-quality images using Starlight technology, which significantly improves night vision. Even in very low light, it stays in color longer and provides much better detail than standard cameras.

Technical Specifications

- Image Sensor: 1/2.8" Progressive Scan CMOS
- Resolution: 5MP FHD
- Optical Zoom: 44× Optical Zoom
- Digital Zoom: 16x
- Pan Range: 360° endless rotation
- Tilt Range: -20° to 90° (Auto Flip 180°)
- IR Distance: Up to 300 meters
- Day/Night: True Day/Night (ICR)
- Video Compression: H.265 / H.264 / MJPEG
- Frame Rate: Up to 25/30 fps
- Network Interface: RJ45 10/100 Mbps Ethernet
- Protocols: TCP/IP, HTTP, HTTPS, RTSP, ONVIF
- Power Supply: 24 V AC / Hi-PoE
- Weather Protection: IP67 rated (Outdoor use)
- Operating Temperature: -30°C to +65°C
- Browser: Microsoft Edge and Chrome
- Operating Humidity: ≤ 95% RH, Non condensing
- Focus Control: Auto/Semi-Auto/Manual
- Angle of View: H: 65.7°-1.9°, V: 39.4°-1.1°, D: 73.1°-2.1°
- Close Focus Distance: 0.1 Mtr. – 1 Mtr.
- Manual Speed: Pan: 0.1° ~260° /s, Tilt: 0.1° ~120° /s
- Preset Speed: Pan: 300°/s, Tilt: 200°/s

