


TERANG

(Teknologi Estimasi keRugian bANgunan akibat Gempa)

Version 1.0
Manual



Prepared by:

Roi Milyardi ^{a,*}, Krishna Suryanto Pribadi^b, Muhamad Abduh^b, Irwan Meilano^c, Erwin Lim^b

^a Department of Civil Engineering, Institut Teknologi Bandung, Bandung 40132, Indonesia

^b Faculty of Civil and Environmental Engineering, Institut Teknologi Bandung, Bandung 40132, Indonesia

^c Faculty of Earth Science and Technology, Institut Teknologi Bandung, Bandung 40132, Indonesia



March, 2025

Table of Content

Table of Content.....	2
Disclaimer	3
Download and Contact.....	4
1. Installation	5
2. Introduction.....	7
2.a. TERANG limitation	9
3. Methodology and Computation Algorithms	10
3.a. HAZUS methodology	10
Hazard Analysis	10
Structure Analysis	11
Damage Analysis	11
Losses Analysis.....	12
3.b. Modification and Adaption of HAZUS parameters in TERANG software	13
4. TERANG User Guide.....	19
4a. Input Data & Explanation Tab	19
4b. Hazard Analysis Tab	21
4c. Structure Analysis Tab	22
4d. Damage Analysis Tab	23
4e. Loss Analysis Tab	24
5. Reference	24

Disclaimer

Copyright © 2025 Roi Milyardi, Krishna Suryanto Pribadi, Muhamad Abduh, Irwan Meilano, Erwin Lim. ALL RIGHTS RESERVED. PERMISSION TO USE, COPY, MODIFY, AND DISTRIBUTE THIS SOFTWARE AND ITS DOCUMENTATION FOR EDUCATIONAL, RESEARCH, AND NOT-FOR-PROFIT PURPOSES, WITHOUT

FEE AND WITHOUT A SIGNED LICENSING AGREEMENT, FALLS UNDER GNU GENERAL PUBLIC LICENSE AS PUBLISHED BY THE FREE SOFTWARE FOUNDATION, EITHER VERSION 3 LICENSE (<https://www.gnu.org/licenses/gpl.txt>), PROVIDED THAT THE ABOVE COPYRIGHT NOTICE, THIS PARAGRAPH AND THE FOLLOWING TWO PARAGRAPHS APPEAR IN ALL COPIES, MODIFICATIONS, AND DISTRIBUTIONS.

IN NO EVENT SHALL THE AUTHORS BE LIABLE TO ANY PARTY FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS, ARISING OUT OF THE USE OF THIS SOFTWARE AND ITS DOCUMENTATION, EVEN IF THE AUTHORS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

THE AUTHORS SPECIFICALLY DISCLAIMS ANY WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE SOFTWARE AND ACCOMPANYING DOCUMENTATION, IF ANY, PROVIDED HEREUNDER IS PROVIDED "AS IS". THE AUTHORS HAS NO OBLIGATION TO PROVIDE MAINTENANCE, SUPPORT, UPDATES, ENHANCEMENTS, OR MODIFICATIONS.

USERS ARE ADVISED TO REFERENCE THIS SOFTWARE AS FOLLOWS:

Milyardi, R. et al (2025) TERANG: Software for estimating direct physical and operational losses due to earthquakes in school building in the Indonesian region.

Download and Contact

GitHub repository: <https://github.com/RoiMilyardi/TERANGv1.0>

Support email for questions: terang.software@gmail.com

1. Installation

The step-by-step installation procedure of the software, in Windows, is discussed in this section. Note that TERANG v1.0 executable is only made available for Windows machines, however, the software can run directly on a Mac machine using the Matlab source code. Figure 1.1 shows all the files/folder that are downloaded by the user through the TERANG GitHub repository. These are as follows:

- TERANG_Installer.exe this is the main installation file.
- TERANG Manual.pdf this is TERANG's manual and installation guide.
- License.txt is license information file.
- Readme.txt is license information file.






Fig. 1.1 Downloaded software files and folders

The software can be installed by running the TERANG_V1.0.exe executable file. As demonstrated in Fig. 1.2, the installation process is like any software. The user is prompted to different windows to approve the installation process and set the installation directory. By default, the installation directory is “C:\Program Files\Institut Teknologi Bandung\TERANG”. Note that if MATLAB runtime was not already installed on the local PC, the user will be prompted to download the latest runtime environment (about 700Mb). An internet connection is required in this case. Once installed, the executable file TERANG_V1.0.exe, as well as other files, can be found in the default installation directory under “.....\Institut Teknologi Bandung\TERANG\application\TERANG.exe” as shown in Fig.1.3.








Fig. 1.2 Installation steps




Fig. 1.3 Installed files and folders in the default installation directory

2. Introduction

The HAZUS model developed by Federal Emergency Management Agency (FEMA), USA provides detailed pre-disaster earthquake loss estimation in the form of direct physical and operational losses supported by a complete building database at each regional level (FEMA-NIBS, 2020). The advantage of the HAZUS model is that it provides facilities for the public, not limited to engineers, to perform a series of complex loss estimation procedures through the simplification of cost and structure parameters based on building type supported by a simple software interface (FEMA, 2019). However, the HAZUS software interface is limited to the USA. Pre-disaster estimation models such as HAZUS are needed for disaster-prone countries such as Indonesia (Priyadi et al., 2023). Indonesia needs pre-disaster loss estimation data to prepare disaster-related financial planning. The challenge is that Indonesia does not yet have such a model nor a complete building database like in the USA. The adoption process is a strategic step in accelerating the fulfillment of estimation data needs. However, the constraints of different building characteristics, construction practices, and database availability require adjustments.

To address the above challenges, an open-source computational platform/software called 'TERANG' was developed, which is described in this article. TERANG is the Indonesian acronym for “Teknologi Estimasi keRugian bANgunan akibat Gempa”, which translates to “Technology for estimating building losses due to earthquakes”. TERANG software is a building loss estimation application specific to the Indonesian region with an adaptation of the HAZUS model with modifications to the parameters of reconstruction costs and building costs. In TERANG version 1.0, the building object focuses on school buildings, which according to disaster data are the public buildings most affected by earthquakes (BNPB, 2025). Another difference with the HAZUS interface software, TERANG, focuses the estimation process on 1 building unit. This was made because of the unavailability of school building property data in the national school database in Indonesia (Ministry of Education and Culture of Indonesia, 2025). So that the TERANG software functions as a tool to compile a database of school building properties in Indonesia with a bottom-up system through TERANG users from the school. This tends to be effective because users know their school buildings. In addition, using TERANG software, it serves as education and dissemination of earthquake disaster risk through loss estimation for users in considering risk mitigation with strategic steps of risk transfer (insurance) or investment in strengthening school buildings.

TERANG software is developed with a MATLAB-based user interface. The basic framework of the earthquake loss estimation model used is the HAZUS model. The model consists of 4 stages of analysis, namely hazard analysis, structure analysis, damage analysis, and loss analysis, as detailed in the software process shown in Fig.2.1.




Fig. 2.1. Workflow of the application software (TERANG)

The software TERANG calculates the estimation of earthquake losses in school buildings for the target user school admin but is not limited to civil engineers. Although TERANG is limited to the data set of Indonesia, it provides a significant impact in the form of an illustration of how to adopt the HAZUS model for countries that do not have a school building database like Indonesia for the low barrier user level. In addition, TERANG is also useful in providing significance in the form of earthquake disaster

risk education for school building stakeholders, private and public. The TERANG software has been utilized in research on loss estimation in Indonesia, including loss estimation for school buildings in the city of Bandung (R Milyardi et al., 2023), operational loss estimation for schools with $RT_{ds,i}$ modification due to the Mamuju earthquake in 2021 (Roi; Milyardi et al., 2024), and sensitivity analysis of the HAZUS structural EDP against loss estimation in a case study of school buildings in Indonesia (Roi Milyardi et al., 2025).

2.a. TERANG limitation

The TERANG software has several limitations, including that earthquake parameters are still limited to city areas (414 city in Indonesia) that are not yet based on real building location coordinates, BRC_i , $RENT_i$ and INC_i data taken based on data in the capital city of Jakarta because the data is dynamic based on the decision of the education minister each year. In the software TERANG version 1.0, the BRC_i value assumption taken is 5,000,000IDR/m² building area, the value INC_i assumption taken is 2,356.16IDR/m²/day, while the value $RENT_i$ used is 909.59IDR/m²/day. Even with this assumption, the estimated value can still be utilized through the ratio value to the building value. The structural types also limited to 3 structural types according to typical school buildings in Indonesia (Gentile et al., 2019; Roi Milyardi et al., 2023).

3. Methodology and Computation Algorithms

3.a. HAZUS methodology

The HAZUS earthquake loss estimation model developed by FEMA in 1992 to estimate earthquake loss in local, state, and regional level with state-of-the-art decision support software. The Geographic Information System (GIS)-based software was applied to small and large area with wide range of population and infrastructure (building, road, and lifeline infrastructures) database and can be implemented by user with varying expertise (FEMA-NIBS, 2020). For general building stock, HAZUS model has four main stage analysis, be made of hazard analysis, structure analysis, damage analysis, and losses analysis. The earthquake losses calculated based on building performance (spectral displacement) and spectral acceleration, with three main replacement components, consists of structural, non-structural drift sensitive, non-structural acceleration sensitive shown in Fig. 3.1 with simplified building performance based on type of structure and building height. The wide-used level expertise user, HAZUS models are reliable to get more wide area earthquake loss estimation. The damage probability on those components used to calculate replacement losses and operational losses. The opposite opinion, non-simplified building performance method conducted with more obstacle, such as limited building losses assessment that need detailed Engineering Demand Parameter (EDP) for each building. FEMA has officially used HAZUS model as an annual earthquake losses estimation in USA in the last 20years. The following sub-section explains more detail for each main stage analysis.






Fig. 3.1 HAZUS earthquake loss conceptual framework

Hazard Analysis

The HAZUS model using demand spectra as a hazard on the location observed shown in Fig. 3.2.b. Demand spectra is constructed based on response spectra parameter (Short period spectral acceleration, 1-second spectral acceleration, and specific site class) shown in Fig. 3.2.a. The response spectra parameters converted into demand spectra parameter (spectral displacement) using Eq.1, where S_D =spectral displacement (inch), S_A =spectral acceleration (g), and T =period for a given value of (seconds).



(a) Standardized Response Spectrum




(b) Demand spectra construction

Fig. 3.2. HAZUS earthquake loss hazard calculations (FEMA-NIBS, 2020)


$$S_D = 9.8 \times S_A \times T^2 \quad (1)$$

Structure Analysis

In structure analysis, HAZUS uses simplified building capacity performance based on typical building type, level of code, and building height. Total HAZUS has 16 types of structure consist of wood, steel, concrete structure, etc. The building capacity curve superimposed to demand spectra to get building performance shown in Fig. 2.3.a. Building capacity curve constructed using provided yield capacity point, and ultimate capacity can be found in HAZUS manual Table 5-7 until Table 5-10 with different of code level (high code, moderate code, low code, and pre-code) (FEMA-NIBS, 2020). Capacity curve constructed by connect two provided point as transits from elastic to nonlinear plastic states with ellipse form approach shown in Fig. 2.3.b and Eq. 2 to Eq.3, where ellipse parameter (A,B,C) solve with known parameter A_y , D_y , A_u , D_u (Cao & Petersen, 2006).



(a) Building capacity curve (FEMA-NIBS, 2020)



(b) Ellipse approach to c yield point to ultimate point (Cao & Petersen, 2006)

Fig. 2.3. HAZUS earthquake loss hazard calculation

$$\left(\frac{SD - D_u}{C} \right)^2 + \left(\frac{SA - A_x}{B} \right)^2 = 1 \quad (2)$$

$$\frac{dSA}{dSD} = - \left(\frac{SD - D_u}{SA - A_x} \right) \left(\frac{B^2}{C^2} \right) \quad (3)$$

Damage Analysis

Building Fragility Curves are conducted in damage analysis. Fragility curves are the lognormal probability functions for the structural and non-structural damage states (slight, moderate, extensive, and complete) to be reached or exceeded when the peak-responses displacement (SD) is given (Cao &

Petersen, 2006). Building Fragility Curves form shown in Fig. 2.4. Each fragility curve is characterized by median ($\bar{S}_{d,ds}$) and lognormal standard deviation (β_{ds}) show in Eq. 5 (FEMA-NIBS, 2020).




Fig. 2.4. Building Fragility Curve Form

$$P[ds \parallel S_d] = \Phi \left[\frac{1}{\beta_{ds}} \times \ln \left(\frac{S_d}{\bar{S}_{d,ds}} \right) \right] \quad (4)$$

$$P[ds \leq ds(i) \parallel S_d] = \frac{1}{2} \left(1 + \operatorname{erf} \left(\frac{\ln(S_d / \bar{S}_{d,ds})}{\sqrt{2}\beta_{ds}} \right) \right), i = 1, 2, 3, 4 \quad (5)$$

From Eq. 4, the equation can be rewritten in a more compact form by using the error function erf shown in Eq. 5, where, i , refer for each damage states(Cao & Petersen, 2006). The value $\bar{S}_{d,ds}$ and β_{ds} can be found in HAZUS manual Table 5-12 until Table 5-21 for structural and non-structural component with each damage states (FEMA-NIBS, 2020).

Losses Analysis

HAZUS calculates Earthquake direct economic losses component, contain building repair costs, building content losses, building inventory losses, relocation expenses, income loss, rental income losses, and wage losses. All of the losses component calculated based on previous stage analysis. For education facility, earthquake economic losses limited on some component due to different activity, especially on business activity. Earthquake economic losses that relevant in education facility calculated by formula shown in Eq.6 to Eq. 10. Structure repair cost calculated in Eq. 6, where BRC_i is Building replacement cost, $PMBTSTR_{ds,i}$ is probability of structure being in structural damage state, $RCS_{ds,i}$ structural repair cost ratio in damage state that provided in HAZUS manual Table 11-2 (FEMA-NIBS, 2020). In Eq. 7 and 8, Non-structural economic losses calculated into non-structural drift sensitive component and acceleration sensitive component, where $PONSA_{ds,i}$ = probability of building being in non-structural acceleration sensitive damage state, $RCA_{ds,i}$ is non-structural acceleration sensitive repair cost ratio in damage state that provide in HAZUS manual Table 11-3 (FEMA-NIBS, 2020), $PONSD_{ds,i}$ is probability of building being in non-structural drift sensitive damage state, $RCD_{ds,i}$ is non-structural drift sensitive repair cost ratio in damage state that provide in HAZUS manual Table 11-4(FEMA-NIBS, 2020). Relocation expenses conducted as losses that considered when existing building was repaired and calculated base time dependent function shown in Eq. 9, where FA_i is floor area of the

building, $\%OO_i$ is percent building occupied (95% for building school) (FEMA, 2021), DC_i is disruption cost (1.16 \$/ft² for building school) (FEMA, 2021), $RENT_i$ is the rental cost (0.04 \$/ft²/day for building school) (FEMA, 2021), and RT_{ds} is recovery time state that provide in HAZUS manual Table 11-8(FEMA-NIBS, 2020). Income losses considered losses of income during building recovery time shown in Eq. 10, where INC_i is income per day, and MOD_{ds} is loss of function time modifier for damage state that state provide in HAZUS manual Table 11-8 and Table 11-9 (FEMA-NIBS, 2020).

$$CS_{ds,i} = BRC_i \times \sum_{ds=1}^4 PMBTSTR_{ds,i} \times RCS_{ds,i} \quad (6)$$

$$CNSA_{ds,i} = BRC_i \times \sum_{ds=1}^4 PONS A_{ds,i} \times RCA_{ds,i} \quad (7)$$

$$CNSD_{ds,i} = BRC_i \times \sum_{ds=1}^4 PONS D_{ds,i} \times RCD_{ds,i} \quad (8)$$

$$REL_{ds,i} = FA_i \times \left[(1 - \%OO_i) \times \sum_{ds=1}^4 (POSTR_{ds,i} \times DC_i) + \%OO_i \times \sum_{ds=1}^4 (POSTR_{ds,i} \times (DC_i + RENT_i \times RT_{ds})) \right] \quad (9)$$

$$YLOS_i = (1 - RF_i) \times FA_i \times INC_i \times \sum_{ds=1}^4 POSTR_{ds,i} \times RT_{ds} \times MOD_{ds} \quad (10)$$

3.b. Modification and Adaption of HAZUS parameters in TERANG software

Modifications were made at each stage of the analysis. At the hazard analysis stage, a response spectrum curve was constructed, as shown in Fig.2b, following the procedure of the National Seismic Building Code (SNI 1726: 2019) (Badan Standardisasi Nasional, 2019), with 3 earthquake parameters (S_s , S_1 , TL) from the 2017 Indonesian National Earthquake Map, automatically obtained based on the seismicity area data selected in Data Input (Ministry of Public Works and Housing of Indonesia, 2021). In obtaining the parameters for the other 7 return periods (where the earthquake map only provides a return period of 1-2500 years), Eq. 11 from the Eurocode is used for their equivalence, where a_g = the value of the sought earthquake acceleration, a_{gR} = the reference value of the earthquake acceleration, T = the value of the sought earthquake recurrence period, T_R = the reference value of the recurrence period, and k = the seismic coefficient taken as 0.4(CEN, 2005).

$$\frac{a_g}{a_{gR}} = \left(\frac{T}{T_R} \right)^k \quad (11)$$

At the structural analysis stage, the capacity curve is constructed based on EDP yield point (D_y , A_y), and ultimate point (D_u , A_u) from the HAZUS model according to the type of structure as shown in Table 3.2. The structure type in TERANG v1.0 is limited to 3 structure types with varying levels of code and structure height according to typical school buildings in Indonesia(Roi Milyardi et al., 2023). Code level determination is adjusted to the development of Indonesian code as show in Table 3.1. In addition,

the elliptical equation that has been derived for the transfer of the yield point to the ultimate point is used, shown in Eq.12 to Eq. 15.

$$S_a = \sqrt{B^2 \times \left(1 - \frac{(S_d - D_U)^2}{C^2}\right)} + A_x \quad (12)$$

$$A_x = \frac{(D_Y - D_Y^2 + 2D_U D_Y - D_U^2) \times A_Y^2 - D_Y A_U^2}{(2D_Y A_Y - 2D_Y A_U - D_Y^2 A_Y + 2D_U D_Y A_Y - A_Y D_U^2)} \quad (13)$$

$$B = \sqrt{(A_U - A_x)^2} \quad (14)$$

$$C = \sqrt{\frac{B^2 - (D_Y - D_U)^2}{B^2 - (A_Y - A_X)^2}} \quad (15)$$

Table 3.1. Indonesia's Building seismic design level classification (Muntafi et al., 2020; Nugroho et al., 2022)

Seismic design level	Year of construction
High-Code	After 2012
Moderate Code	1991-2012
Low Code	1970-1991
Pre Code	Before 1970

Table 3.2. Adoption of HAZUS's EDP Structure Capacity Curve (FEMA-NIBS, 2020).

Level of Code	Type of Structure	Heigh of Structure	Structure ID	Dy (mm)	Ay (g)	Du (mm)	Au (g)
High-Code	S1 (Steel Moment Frame)	Low-Rise (1-3 Stories)	S1LH	15.5194	0.25	372.5418	0.749
		Mid-Rise (4-7 Stories)	S1MH	45.085	0.156	721.36	0.468
		High-Rise (8+ Stories)	S1HH	118.2878	0.098	1419.454	0.293
	C1 (Concrete Moment Frame)	Low-Rise (1-3 Stories)	C1LH	9.9314	0.25	238.4298	0.749
		Mid-Rise (4-7 Stories)	C1MH	29.2608	0.208	468.2744	0.624
		High-Rise (8+ Stories)	C1HH	51.0794	0.098	612.902	0.293
	RM1 (Reinforced Masonry Wall)	Low-Rise (1-3 Stories)	RM1LH	16.2306	0.533	259.8166	1.066
		Mid-Rise (4+Stories)	RM1MH	35.1536	0.444	374.904	0.889
Moderate-Code	S1 (Steel Moment Frame)	Low-Rise (1-3 Stories)	S1LM	7.7724	0.125	139.7	0.375
		Mid-Rise (4-7 Stories)	S1MM	22.5552	0.078	270.5354	0.234
		High-Rise (8+ Stories)	S1HM	59.1566	0.049	532.3078	0.147
	C1 (Concrete Moment Frame)	Low-Rise (1-3 Stories)	C1LM	4.9784	0.125	89.408	0.375
		Mid-Rise (4-7 Stories)	C1MM	14.6304	0.104	175.6156	0.312
		High-Rise (8+ Stories)	C1HM	25.527	0.049	229.8446	0.147
	RM1 (Reinforced Masonry Wall)	Low-Rise (1-3 Stories)	RM1LM	8.128	0.267	97.4344	0.533
		Mid-Rise (4+Stories)	RM1MM	17.5768	0.222	140.589	0.444
Low-Code	S1 (Steel Moment Frame)	Low-Rise (1-3 Stories)	S1LL	3.8862	0.062	58.2168	0.187
		Mid-Rise (4-7 Stories)	S1ML	11.2776	0.039	112.6998	0.117
		High-Rise (8+ Stories)	S1HL	29.5656	0.024	221.7928	0.073

Level of Code	Type of Structure	Heigh of Structure	Structure ID	Dy (mm)	Ay (g)	Du (mm)	Au (g)
	C1 (Concrete Moment Frame)	Low-Rise (1-3 Stories)	C1LL	2.4892	0.062	37.2618	0.187
		Mid-Rise (4-7 Stories)	C1ML	7.3152	0.052	73.1774	0.156
		High-Rise (8+ Stories)	C1HL	12.7762	0.024	95.758	0.073
	RM1 (Reinforced Masonry Wall)	Low-Rise (1-3 Stories)	RM1LL	4.064	0.133	40.5892	0.267
		Mid-Rise (4+Stories)	RM1ML	8.7884	0.111	58.5724	0.222
Pre-Code	S1 (Steel Moment Frame)	Low-Rise (1-3 Stories)	S1LP	3.8862	0.062	58.2168	0.187
		Mid-Rise (4-7 Stories)	S1MP	11.2776	0.039	112.6998	0.117
		High-Rise (8+ Stories)	S1HP	29.5656	0.024	221.7928	0.073
	C1 (Concrete Moment Frame)	Low-Rise (1-3 Stories)	C1LP	2.4892	0.062	37.2618	0.187
		Mid-Rise (4-7 Stories)	C1MP	7.3152	0.052	73.1774	0.156
		High-Rise (8+ Stories)	C1HP	12.7762	0.024	95.758	0.073
	RM1 (Reinforced Masonry Wall)	Low-Rise (1-3 Stories)	RM1LP	4.064	0.133	40.5892	0.267
		Mid-Rise (4+Stories)	RM1MP	8.7884	0.111	58.5724	0.222

At the damage analysis stage, the three fragility curves were created using EDP (β_{ds}) and median ($\bar{S}_{d,ds}$) for each damage level and curves based on HAZUS model data for structural components, non-structural drift-sensitive, and non-structural acceleration-sensitive components as shown in Table 3.3 until Table 3.5.

Table 3.3. Adoption of HAZUS's EDP Structural Component Fragility Curve (FEMA-NIBS, 2020).

Structure ID	Slight		Moderate		Extensive		Complete	
	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta
S1LH	33.02	0.80	65.79	0.76	164.59	0.69	438.91	0.72
S1MH	54.86	0.65	109.73	0.65	274.32	0.67	731.52	0.74
S1HH	85.60	0.64	171.20	0.64	427.99	0.65	1141.22	0.67
C1LH	22.86	0.81	45.72	0.84	137.16	0.86	365.76	0.80
C1MH	38.10	0.68	76.20	0.67	228.60	0.68	609.60	0.81
C1HH	54.86	0.66	109.73	0.64	329.18	0.67	877.82	0.78
RM1LH	18.29	0.84	36.58	0.86	109.73	0.92	320.04	1.01
RM1MH	30.48	0.71	60.96	0.80	182.88	0.77	533.40	0.75
S1LM	33.02	0.80	56.90	0.76	129.03	0.74	329.18	0.87
S1MM	54.86	0.65	95.00	0.68	214.88	0.69	548.64	0.87
S1HM	85.60	0.64	148.08	0.64	335.53	0.71	855.98	0.83
C1LM	22.86	0.89	39.62	0.90	106.68	0.90	274.32	0.88
C1MM	38.10	0.69	66.04	0.69	177.80	0.69	457.20	0.90
C1HM	54.86	0.66	95.00	0.67	256.03	0.76	658.37	0.91
RM1LM	18.29	0.96	31.75	1.00	85.60	1.05	240.03	0.94
RM1MM	30.48	0.82	52.83	0.82	142.49	0.80	400.05	0.88
S1LL	33.02	0.78	52.58	0.78	111.25	0.78	274.32	0.96
S1ML	54.86	0.68	87.38	0.78	185.42	0.85	457.20	0.98
S1HL	85.60	0.66	136.40	0.70	289.05	0.76	713.23	0.92

Structure ID	Slight		Moderate		Extensive		Complete	
	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta
C1LL	22.86	0.95	36.58	0.91	91.44	0.85	228.60	0.97
C1ML	38.10	0.71	60.96	0.74	152.40	0.86	381.00	0.98
C1HL	54.86	0.70	87.88	0.81	219.46	0.89	548.64	0.97
RM1LL	18.29	1.12	29.21	1.10	73.41	1.10	200.15	0.92
RM1ML	30.48	0.87	48.77	0.84	122.17	0.79	333.25	0.96
S1LP	26.42	0.85	41.91	0.83	88.90	0.79	219.46	0.95
S1MP	43.94	0.71	70.10	0.76	148.34	0.82	365.76	0.97
S1HP	68.58	0.68	109.22	0.71	231.39	0.85	570.48	0.93
C1LP	18.29	0.98	29.21	0.94	73.15	0.90	182.88	0.96
C1MP	30.48	0.73	48.77	0.77	121.92	0.84	304.80	0.98
C1HP	43.94	0.71	70.10	0.80	175.51	0.94	438.91	1.01
RM1LP	14.73	1.20	23.37	1.17	58.67	1.17	160.02	0.94
RM1MP	24.38	0.92	39.12	0.89	97.79	0.88	266.70	0.96

Table 3.4. Adoption of HAZUS's EDP nonstructural drift sensitive Component Fragility Curve (FEMA-NIBS, 2020).

Structure ID	Slight		Moderate		Extensive		Complete	
	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta
S1LH	21.84	0.81	43.94	0.85	137.16	0.77	274.32	0.76
S1MH	54.86	0.72	109.73	0.72	342.90	0.72	685.80	0.80
S1HH	114.05	0.72	228.35	0.71	713.23	0.74	1426.46	0.77
C1LH	18.29	0.85	36.58	0.88	114.30	0.90	228.60	0.89
C1MH	45.72	0.72	91.44	0.73	285.75	0.75	571.50	0.85
C1HH	87.88	0.71	175.51	0.71	548.64	0.78	1097.28	0.89
RM1LH	18.29	0.89	36.58	0.91	114.30	0.97	228.60	1.06
RM1MH	45.72	0.82	91.44	0.86	285.75	0.80	571.50	0.81
S1LM	21.84	0.85	43.94	0.83	137.16	0.79	274.32	0.87
S1MM	54.86	0.72	109.73	0.74	342.90	0.85	685.80	0.95
S1HM	114.05	0.71	228.35	0.73	713.23	0.84	1426.46	0.95
C1LM	18.29	0.92	36.58	0.96	114.30	0.95	228.60	0.89
C1MM	45.72	0.76	91.44	0.76	285.75	0.87	571.50	0.98
C1HM	87.88	0.74	175.51	0.81	548.64	0.95	1097.28	1.03
RM1LM	18.29	1.01	36.58	1.06	114.30	1.11	228.60	1.01
RM1MM	45.72	0.89	91.44	0.85	285.75	0.84	571.50	0.98
S1LL	21.84	0.86	43.94	0.84	137.16	0.88	274.32	1.00
S1ML	54.86	0.75	109.73	0.89	342.90	0.99	685.80	1.05
S1HL	114.05	0.75	228.35	0.87	713.23	0.97	1426.46	1.04
C1LL	18.29	1.00	36.58	0.96	114.30	0.90	228.60	1.02
C1ML	45.72	0.79	91.44	0.88	285.75	0.99	571.50	1.06
C1HL	87.88	0.87	175.51	0.96	548.64	1.02	1097.28	1.07

Structure ID	Slight		Moderate		Extensive		Complete	
	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta
RM1LL	18.29	1.16	36.58	1.12	114.30	1.03	228.60	0.99
RM1ML	45.72	0.89	91.44	0.89	285.75	1.00	571.50	1.05
S1LP	21.84	0.90	43.94	0.87	137.16	0.91	274.32	1.02
S1MP	54.86	0.80	109.73	0.92	342.90	1.00	685.80	1.06
S1HP	114.05	0.79	228.35	0.89	713.23	1.00	1426.46	1.07
C1LP	18.29	1.02	36.58	0.98	114.30	0.93	228.60	1.03
C1MP	45.72	0.82	91.44	0.91	285.75	1.02	571.50	1.06
C1HP	87.88	0.90	175.51	0.99	548.64	1.05	1097.28	1.10
RM1LP	18.29	1.22	36.58	1.14	114.30	1.03	228.60	1.00
RM1MP	45.72	0.93	91.44	0.92	285.75	1.02	571.50	1.07

Table 3.5. Adoption of HAZUS's EDP nonstructural acceleration sensitive Component Fragility Curve (FEMA-NIBS, 2020).

Structure ID	Slight		Moderate		Extensive		Complete	
	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta
S1LH	7.62	0.67	15.24	0.67	30.48	0.67	60.96	0.66
S1MH	7.62	0.67	15.24	0.68	30.48	0.67	60.96	0.67
S1HH	7.62	0.69	15.24	0.67	30.48	0.67	60.96	0.67
C1LH	7.62	0.67	15.24	0.68	30.48	0.67	60.96	0.67
C1MH	7.62	0.67	15.24	0.67	30.48	0.66	60.96	0.66
C1HH	7.62	0.66	15.24	0.66	30.48	0.66	60.96	0.66
RM1LH	7.62	0.71	15.24	0.67	30.48	0.67	60.96	0.63
RM1MH	7.62	0.72	15.24	0.66	30.48	0.65	60.96	0.65
S1LM	6.35	0.67	12.70	0.66	25.40	0.67	50.80	0.67
S1MM	6.35	0.66	12.70	0.67	25.40	0.67	50.80	0.67
S1HM	6.35	0.66	12.70	0.67	25.40	0.67	50.80	0.67
C1LM	6.35	0.67	12.70	0.66	25.40	0.66	50.80	0.66
C1MM	6.35	0.66	12.70	0.66	25.40	0.63	50.80	0.63
C1HM	6.35	0.65	12.70	0.67	25.40	0.67	50.80	0.67
RM1LM	6.35	0.69	12.70	0.67	25.40	0.67	50.80	0.67
RM1MM	6.35	0.67	12.70	0.64	25.40	0.67	50.80	0.67
S1LL	5.08	0.65	10.16	0.68	20.32	0.68	40.64	0.68
S1ML	5.08	0.66	10.16	0.69	20.32	0.69	40.64	0.69
S1HL	5.08	0.67	10.16	0.65	20.32	0.65	40.64	0.65
C1LL	5.08	0.65	10.16	0.68	20.32	0.68	40.64	0.68
C1ML	5.08	0.65	10.16	0.68	20.32	0.68	40.64	0.68
C1HL	5.08	0.67	10.16	0.67	20.32	0.67	40.64	0.67
RM1LL	5.08	0.66	10.16	0.66	20.32	0.64	40.64	0.64
RM1ML	5.08	0.64	10.16	0.66	20.32	0.64	40.64	0.64
S1LP	5.08	0.66	10.16	0.68	20.32	0.68	40.64	0.68

Structure ID	Slight		Moderate		Extensive		Complete	
	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta	Median (mm)	Beta
S1MP	5.08	0.66	10.16	0.69	20.32	0.69	40.64	0.69
S1HP	5.08	0.67	10.16	0.67	20.32	0.67	40.64	0.67
C1LP	5.08	0.66	10.16	0.68	20.32	0.68	40.64	0.68
C1MP	5.08	0.66	10.16	0.68	20.32	0.68	40.64	0.68
C1HP	5.08	0.67	10.16	0.67	20.32	0.67	40.64	0.67
RM1LP	5.08	0.66	10.16	0.67	20.32	0.66	40.64	0.66
RM1MP	5.08	0.64	10.16	0.66	20.32	0.65	40.64	0.65

At the loss analysis stage, Losses are categorized into physical losses, $RCL_{ds,i}$, and operational losses, $OCL_{ds,i}$, shown in Eq.16 and Eq.17. The modification of HAZUS parameters in TERANG software consists of $RCS_{ds,i}$ structural repair cost ratio in damage state (%), $RCA_{ds,i}$ is non-structural acceleration sensitive repair cost ratio in damage state (%), $RCD_{ds,i}$ is non-structural drift sensitive repair cost ratio in damage state (%), RT_{ds} is recovery time parameters (days), and $RENT_i$ is the building rental cost (IDR/m²/day), and INC_i is building income (IDR/m²/day) as shown in Table 5. The adjustment of $RENT_i$ and INC_i variables developed based on local data shown in Eq.18 and Eq.19, where HSBGN is the unit price of the building (IDR/m²), and BOS_n is the incentive value for school buildings (IDR/m²/day). HSBGN and BOS_n data taken based on data in the capital city of Jakarta (5,000,000IDR/m² and 1,720,000 IDR/year) because the data is dynamic based on the decision of the education minister each year. The remaining parameters %OO_i, DC_i, RF_i, MOD_{ds} are parameters adopted from the HAZUS model as shown in Table 3.6.

$$RCL_{ds,i} = CS_{ds,i} + CNSD_{ds,i} + CNSD_{ds,i} \quad (16)$$

$$OCL_{ds,i} = REL_{ds,i} + YLOS_{ds,i} \quad (17)$$

$$RENT_i = \frac{6.64\% \times HSBGN}{365} \quad (18)$$

$$INC_i = \frac{BOS_n}{730} \quad (19)$$

Table 3.6. Modification and Adoption of HAZUS's Loss Parameter

Parameter	Units	Level of Damage				Note
		Slight	Moderate	Extensive	Complete	
$RCS_{ds,i}$	%	3.32	3.32	10.72	40.88	From Local Earthquake Case (On-going Research)
$RCD_{ds,i}$	%	8.06	8.06	8.17	24.77	
$RCA_{ds,i}$	%	11.9	11.9	13.07	27.91	
RT_{ds}	days	768	768	768	768	From Mamuju Case Study Research (Roi Milyardi et al., 2024)
$RENT_i$	IDR/m ² /day	909.59				From Eq. 18, where HSBGN=5,000,000IDR/m ²
INC_i	IDR/m ² /day	2,356.16				From Eq. 19, where BOSn=1,720,000IDR/year

Parameter	Units	Level of Damage				Note
		Slight	Moderate	Extensive	Complete	
%OO _i	%	95				Adoption From HAZUS (FEMA, 2021)
DC _i	IDR/m ²	187,292.12				Adoption From HAZUS (FEMA, 2021)
RF _i	%	60				Adoption From HAZUS (FEMA, 2021)
MOD _{ds}	-	0.1	0.02	0.03	0.03	Adoption From HAZUS (FEMA-NIBS, 2020)

4. TERANG User Guide

In general, the TERANG software display consists of 6 tabs, namely Input Data Tab, Hazard Analysis Tab, Structure Analysis Tab, Damage Analysis Tab, Loss Analysis Tab, Type of Structure Explanation Tab as shown in Fig.4.1. This software provides 2 languages, namely English and Bahasa Indonesia, which can be clicked on the respective language selection buttons.

4a. Input Data & Type of Structure Explanation Tab

The Data Input tab is shown on Fig.4.1. In general, it consists of 3 group panels, namely School Data, Building Property Data, and Explanation of Data Input.

TERANG v.1.0

A software module that estimates the physical and operational losses of buildings due to earthquakes. In version v1.0, TERANG focused on school buildings, specifically in Indonesia region.

Input Data | Hazard Analysis | Structure Analysis | Damage Analysis | Loss Estimation | Type of Structure Expl.

School Data

School ID: 123456
School Name: Ganesha School
Address: Jl. Ganesa No.10
Ownership Status: Private
Province: JAWA BARAT
City: KOTA BANDUNG
District: Coblong
Sub-District: Lebak Siliwangi
Region Code: 32.73.02.1006
Building Name: CIBE
Coordinate: Latitude: -6.891428, Longitude: 107.605829
Earthquake Area: Bandung

Building Property Data

Year Built: 2015
Number of storeys: 6
Structure Type: C1
Building Area: 2000 m2
Number of students: 100 person

Explanation of Data Input

On the school land area, there is generally one school building or several school buildings (shown A,B,C, on the side). Building names are based on the name of the building used in the school. The building area is filled in based on the building area under review, not the total building area of the whole school. Coordinates (Longitude and Latitude) are attempted to be at the center of the building under review, or close to the center of the building, not at the location of the midpoint of the land owned by the school.

Clear Data | Continue

Fig. 4.1. TERANG's Input Data Tab

In the School Data group panel, the following data is inputted:

- School ID is filled in according to the ID from the Ministry of Education (MoE) data that can be accessed on the Page: <https://dapo.kemdikbud.go.id/>
- School Name is also filled in according to the MoE data.
- The address is filled with the school location
- Ownership status is filled with Private / Public status

- e. Province, selected according to the location of the school province. Territorial data is limited to Indonesia.
- f. The city will be automatically filtered according to the previously selected Province, then please select the city according to the location of the school.
- g. The district will be automatically filtered according to the previously selected City, then please select the district according to the school location.
- h. Sub-District will be automatically filtered according to the previously selected District, then please select the Sub-District according to the school location.
- i. The Region code will automatically appear according to the selected sub-district. The Region Code that appears is in accordance with the registration code of the Indonesian Ministry of Home Affairs
- j. In filling in the Building Name, it is necessary to see the illustration on the 'Explanation of Data Input' panel. So, the building name is filled in according to the building under review. One school may have more than one building.
- k. Coordinates filled in latitude and longitude in decimal format
- l. Earthquake area is selected based on the available city or region. If the city/region does not exist, the nearest region can be selected.

The Group panel 'Building Properties Data' is entered as follows:

- a. Year built in the observed building data. Remember, the year built in 1 school complex may be different from another.
- b. The number of floors is filled in the observed building
- c. For the structure type, C1, RM1, and S1 can be selected. If you have difficulty understanding the structure type, you can click the 'Structure Type Explanation' button which will take you to Fig.4.2. In the 'Type of Structure Expl.' tab, you can identify the type of building structure according to the explanation. When finished, click the 'Back to Input Data' button.
- d. Building area is filled in the total building area of the observed building
- e. Number of students is filled in the number of students who occupy the building in the observed building

The '**Clear data**' button is used to reset the data fields.

The '**Continue**' button is used to proceed to hazard analysis.

Data Input Tab. If the earthquake region is not found, the user can select the nearest earthquake region, or fill in the SS, S1, and TL parameters according to the building coordinates obtained from the website: <https://rsa.ciptakarya.pu.go.id/2021/>

- b. In the site class parameter, the VS30 parameter can be filled in according to the building coordinates obtained from the website: <https://usgs.maps.arcgis.com/apps/webappviewer/index.html?id=8ac19bc334f747e486550f32837578e1> . If the user finds it difficult to access the website, the VS30 value can be filled in as 0, with the consequences of the most extreme scenario.
- c. In the 8 Group Panel 2500 year return period to 100 year return period, and the hazard graph curve will be automatically filled in when pressing the '**Hazard Data Process**' and '**Draw Earthquake hazards**' buttons
- d. After both buttons are pressed, you can click '**Continue**'.

4c. Structure Analysis Tab

The structure analysis is shown in Figure 4.4. No data entry is required at this stage.




Fig. 4.4. TERANG's Structure Analysis Tab

Here are the detailed steps.

- a. In the Capacity Curve Data panel group, the Structure type, Dy, Ay, Du, and Au values will be automatically filled in according to the data input. For the parameters Dy, Ay, Du, and Au can be modified if the user has technical pushover building result data. This is only recommended for advance use who have structural engineer competence.

- b. In the Building Performance group panel, the performance of 2500 years to 100 years is automatically filled in as a result of the intersection of the hazard curve and the building capacity curve after clicking the '**Calculate Building Performance**' button
- c. The '**Continue**' button is pressed to proceed to the Damage analysis stage.

4d. Damage Analysis Tab

Damage analysis is shown in Figure 4.5. No data entry is required at this stage.




Fig. 4.5. TERANG's Damage Analysis Tab

Here are the detailed steps.

- a. In the group panels Fragility curve-Structural Component, Fragility curve-Nonstructural drift sensitive Component, and Fragility curve-Nonstructural acc. sensitive Component, the median and beta values for 4 damage levels (Slight, moderate, extensive, complete) will be automatically filled in according to the input data. The median and beta parameters can be modified if the user has Incremental Dynamic Analysis (IDA) technical result data for the building. This is only recommended for advance use who have structural engineer competence.
- b. In the group panel Damage level Probability-Structural Component, Damage level Probability-Nonstructural Component-drift sensitive, Damage level Probability-Nonstructural Component-Acc. sensitive is automatically filled in the results of the intersection of the building performance line against the fragility curve after clicking the 'Estimate Building Damage Level' button
- c. The 'Continue' button is pressed to continue at the Loss analysis stage.

4e. Loss Analysis Tab

Loss analysis is shown in Figure 4.6. No data entry is required at this stage.

TERANG v1.0
A software module that estimates the physical and operational losses of buildings due to earthquakes. In version v1.0, TERANG focused on school buildings, specifically in Indonesia region.

Input Data | Hazard Analysis | Structure Analysis | Damage Analysis | Loss Estimation | Type of Structure Expl.

At the Loss Estimation Stage, there is no need to fill in, just click "Calculate Loss Estimation". Click "Save Data" also to save .txt building data.

Physical Loss			Operational Loss		
Hazard Return Period Scenario	Monetary Value	Loss to building value ratio	Hazard Return Period Scenario	Monetary Value	Loss to building value ratio
2500 years	Rp 2413707381.36	24.14 %	2500 years	Rp 1374639533.72	13.75 %
2000 years	Rp 2355022574.97	23.55 %	2000 years	Rp 1367392344.80	13.67 %
1500 years	Rp 2271991095.28	22.72 %	1500 years	Rp 1353058068.30	13.53 %
1000 years	Rp 2187837602.62	21.88 %	1000 years	Rp 1330987636.16	13.31 %
750 years	Rp 2132135634.48	21.32 %	750 years	Rp 1310104324.79	13.10 %
500 years	Rp 2132135634.48	20.57 %	500 years	Rp 1270824733.04	12.71 %
250 years	Rp 1924550765.42	19.25 %	250 years	Rp 1156343955.47	11.56 %
100 years	Rp 1767018115.35	17.67 %	100 years	Rp 931074053.17	9.31 %
Annual Loss	Rp 19607479.09	1.96 %	Annual Loss	Rp 11350520.98	1.14 %

Assumptions Used:
 1. The estimated values generated are for budgeting purposes, not detailed estimation.
 2. Monetary Value of physical loss is calculated by assuming the Unit Price of Building is 5,000,000IDR/m².
 3. Monetary Value of operational losses is calculated assuming the Building Unit Price is 5,000,000IDR/m² of building area for relocation losses, and assuming school revenue of 2,356.16IDR/m²/day/student
 4. Operational losses are only calculated for private schools to represent business model losses during building reconstruction.

Calculate Loss Estimation | Save Data | Exit

Fig. 4.6. TERANG's Loss Analysis Tab

Here are the detailed steps.

- In the Physical Loss and Operational loss group panels, the formula calculation results are automatically filled in after clicking the '**Calculate Loss Estimation**' button.
- Pay attention to the value assumptions used. Although there is an assumed value used for monetary value, the Loss to building value ratio is still reliable.
- Click the '**Save Data**' button to save the building and annual loss data in a .txt file. Also send the .txt file to email terang.software@gmail.com to participate in building an opensource school building database.
- The '**Exit**' button is pressed to exit the application.

5. Reference

- Badan Standardisasi Nasional. (2019). SNI 1726-2019 - Procedures for Planning Earthquake Resistance for Building and Non-Building Structures. In *BSN* (Issue 8). <https://tekonsipil.sv.ugm.ac.id/wp-content/uploads/sites/938/2020/01/SNI-1726-2019-Persyaratan-Beton-Struktural-Untuk-Bangunan-Gedung.pdf>
- BNPB. (2025). *Disaster Information Data Indonesia (DIBI)*. <https://dibi.bnpb.go.id/>
- Cao, T., & Petersen, M. D. (2006). Uncertainty of earthquake losses due to model uncertainty of input ground motions in the Los Angeles area. *Bulletin of the Seismological Society of America*, 96(2), 365–376. <https://doi.org/10.1785/0120050130>

- CEN. (2005). *Eurocode 8 - Design of structures for earthquake resistance Part 2: Bridges* (Issue 1). <https://www.phd.eng.br/wp-content/uploads/2014/12/en.1998.2.2005.pdf>
- FEMA-NIBS. (2020). HAZUS Earthquake Model Technical Manual. *Federal Emergency Management Agency*, October. https://www.fema.gov/sites/default/files/2020-10/fema_hazus_earthquake_technical_manual_4-2.pdf
- FEMA. (2019). Hazus Earthquake Model User Guidance. *Fema*, October, 262.
- FEMA. (2021). *Hazus Inventory Technical Manual*. February, 185.
- Gentile, R., Galasso, C., Idris, Y., Rusydy, I., & Meilianda, E. (2019). From rapid visual survey to multi-hazard risk prioritisation and numerical fragility of school buildings. *Natural Hazards and Earth System Sciences*, 19(7), 1365–1386. <https://doi.org/10.5194/nhess-19-1365-2019>
- Milyardi, R, Pribadi, K. S., Meilano, I., & Lim, E. (2023). Identifying the potential development of HAZUS model as an earthquake disaster loss model for school buildings in Indonesia. *IOP Conference Series: Earth and Environmental Science*, 1244(1), 12022. <https://doi.org/10.1088/1755-1315/1244/1/012022>
- Milyardi, Roi, Pribadi, K. S. ., Abduh, M., Meilano, I., Lim, E., Wirahadikusumah, R. D. ., Kusumaningrum, P., Puri, E. R. ., & Hs, H. (2024). Development of a building repair time component for the disaster losses estimate in the Mamuju earthquake. *7th International Conference Series on Geotechnics, Civil Engineering and Structures (CIGOS)*, (On Progres).
- Milyardi, Roi, Desiani, A., Wong, H., Setiawan, D., & Husada, G. (2023). Assessment of Seismic Vulnerability of School Buildings: A case study in Bandung, West Java, Indonesia. *Disaster Advances*, 16(9), 49–59. <https://doi.org/10.25303/1609da049059>
- Milyardi, Roi, Firdaus, A., Pribadi, K. S., Abduh, M., Meilano, I., Lim, E., Wirahadikusumah, R. D., Kusumaningrum, P., Puri, E. R., & Hs, H. (2024). Development of a Building Repair Time Component for the Disaster Losses Estimate in the Mamuju Earthquake. In C. Ha-Minh, C. H. Pham, H. T. H. Vu, & D. V. K. Huynh (Eds.), *Proceedings of the 7th International Conference on Geotechnics, Civil Engineering and Structures, CIGOS 2024, 4-5 April, Vietnam* (pp. 1428–1436). Springer Nature Singapore. [https://doi.org/https://doi.org/10.1007/978-981-97-1972-3_157](https://doi.org/10.1007/978-981-97-1972-3_157)
- Milyardi, Roi, Pribadi, K. S., Abduh, M., Meilano, I., Lim, E., Wirahadikusumah, R., Kusumaningrum, P., & Puri, E. R. (2025). Sensitivity Analysis of Engineering Demand Parameters: Empirical and Analytical Approaches to Structural Loss Estimation. *Journal of Rehabilitation in Civil Engineering*, 25–46. <https://doi.org/10.22075/jrce.2025.35649.2193>
- Ministry of Education and Culture of Indonesia. (2025). *Basic Education Data*. <https://dapo.kemdikbud.go.id/>
- Ministry of Public Works and Housing of Indonesia. (2021). *Indonesia's Spectra Design*. <http://rsa.ciptakarya.pu.go.id/2021/>
- Muntafi, Y., Nojima, N., & Jamal, A. U. (2020). Damage Probability Assessment of Hospital Buildings

in Yogyakarta, Indonesia as Essential Facility due to an Earthquake Scenario. *Journal of the Civil Engineering Forum*, 6(3), 225. <https://doi.org/10.22146/jcef.53387>

Nugroho, W. O., Sagara, A., & Imran, I. (2022). The evolution of Indonesian seismic and concrete building codes: From the past to the present. *Structures*, 41(April), 1092–1108. <https://doi.org/10.1016/j.istruc.2022.05.032>

Pribadi, K. S., Abduh, M., Kusumaningrum, P., Hasiholan, B., Wirahadikusumah, R. D., & Milyardi, R. (2023). Promoting Humanitarian Engineering Approaches for Earthquake-Resilient Housing in Indonesia. In Y. Koumpouros, A. Georgoulas, & G. Kremmyda (Eds.), *Transcending Humanitarian Engineering Strategies for Sustainable Futures* (pp. 235–262). IGI Global. <https://doi.org/10.4018/978-1-6684-5619-4.ch012>