WhatsBizERP Retailer Onboarding, Feature Administration and Deboarding Guide

Document version: 1.0
Application: WhatsBizERP
Database baseline: V2 feature entitlements, RCDEV runtime objects, RCDEV009 printing, RCDEV010 customer notifications, V3 product images, V4 dashboard notifications

1. Scope and architecture

This guide covers feature access, database setup, configuration, imports, and onboarding/deboarding checklists for retailers.

The current application is multi-tenant. A retailer is represented by a tenant in the shared WhatsBizERP database. The supported flow creates a tenant and associates users, subscriptions, feature entitlements, company settings, warehouses, printers, and master data with that tenant. The current code does not automatically create one physical SQL database per retailer.

If separate physical database isolation is required, provision an empty database from the SQL project, deploy the complete post-deployment baseline, configure a separate API connection string, and run this checklist against that database. That is an infrastructure decision, not automatic application behavior today.

2. Enable or disable features

2.1 Tenant feature entitlement

Feature enablement is tenant-level. The effective decision is resolved from the active tenant assignment, plan feature, release state, and date window.

1. Create or identify the retailer tenant.
2. Confirm the feature exists in core.Features with ReleaseState = ACTIVE.
3. Assign it in core.TenantFeatures with IsEnabled = 1, or use the administration/API workflow.
4. If plan-controlled, confirm core.PlanFeatures.IsEnabled = 1 for the subscribed plan.
5. Sign out/in or refresh the session so the current-user feature snapshot is rebuilt.
6. Verify the administration hub, route, and API permission.

To disable a feature, set the tenant assignment IsEnabled = 0, set an EndDate, or disable the plan feature. Set the related integration/configuration inactive where applicable. Disabling access does not delete historical transactions.

2.2 User access

Feature entitlement and user authorization are separate:

- core.TenantFeatures: is the feature available to this retailer?
- Identity roles, role claims, and user-role membership: may this user perform the operation?
- API permission attributes and frontend permission guards: enforce access at both layers.

To enable a feature for one user, enable it for the tenant, then assign a role containing the required permissions. To disable it for one user, remove the role or permission claim. Do not rely on frontend-only changes.

Flow: active tenant feature + active release/plan + user permission + route/API authorization = usable feature.

3. Tables, versions, and flow

Area	Table	Purpose
Tenant	core.Tenants	Retailer identity and lifecycle anchor.
Feature catalog	core.Features	Feature key, name, module, release state, active flag.
Plans	core.Plans	Commercial plan definition.
Plan mapping	core.PlanFeatures	Features included by a plan.
Subscription	core.Subscriptions	Tenant-to-plan subscription and dates.
Tenant override	core.TenantFeatures	Tenant enablement, dates, reason, active state.
User identity	core.Users	Application user and tenant ownership.
User roles	Identity role/user-role/role-claim tables	User membership and permission claims.

Feature schema and seed flow: database/WhatsBiz.Database/Scripts/V2-FeatureEntitlements.sql.

Configuration area	Tables
Company/admin	admin.Companies, admin.ApplicationSettings, admin.PrinterSettings
Printers	printing.PrinterConfigurations, printing.PaperSizes
WhatsApp	integration.WhatsAppConfigurations, integration.WhatsAppWebhookEvents, integration.WhatsAppCommerceOrders
Dashboard alerts	dashboard.DashboardNotifications, inventory.InventoryAlerts, inventory.ReorderSuggestions
Product images	master.ProductImages, master.Products tenant/image columns from V3

Version/deployment flow

1. Publish the SQL project baseline and post-deployment scripts.
2. Apply V2 feature entitlement objects and feature catalog seed.
3. Apply RCDEV runtime, printing, and customer-notification changes.
4. Apply V3 product-image tenant/optimized-image schema.
5. Apply V4 dashboard notification procedures.
6. Deploy the matching API and frontend.
7. Create tenant and administrator.
8. Configure company, financial year, branches, warehouses, printers, integrations, users, roles, and feature assignments.

The deployment source of truth is database/WhatsBiz.Database/Scripts/PostDeployment.sql and its referenced scripts. Do not manually create only a subset of production tables.