

Submitted for the Degree of MEng in Computer Science
for the academic year of 2016/17.

Run Frank in Browser

Student Registration Number: 201349799

Student Name: Rokas Labeikis

Except where explicitly stated all the work in this report, including
appendices, is my own and was carried out during my final year. It has not
been submitted for assessment in any other context.

I agree to this material being made available in whole or in part to benefit
the education of future students.

Signature: _____ Date: _____

Supervised by:
Professor Conor McBride

University of Strathclyde, UK
February 2017

Abstract

Frank is strongly typed, strict functional programming language invented by Sam Lindley and Conor McBride and it is influenced by Paul Blain Levy's call-by-push-value calculus. Featuring a bidirectional effect type system, effect polymorphism, and effect handlers. This means that Frank supports type-checked side-effects which only occur where permitted. Side-effects are comparable to exceptions which suspend the evaluation of the expression where they occur and give control to a handler which interprets the command. However, when command is complete depending on the handler the system could resume from the point it was suspended. Handlers are very similar to typical functions but their argument processes can communicate in more advanced ways. So the idea is to utilize this functionality in the web. Side-effects might be various events such as mouse actions, http requests etc. and the handler would be the application in the web page.

The main top-level goal of the project is to compile Frank to JavaScript and run it in the browser. Thus, users would be able to use Frank for web development purposes. This involves creating a Compiler and Virtual Machine (abstract machine) which can support compiled Frank structure.

Acknowledgements

I would like to express my special thanks of gratitude to my supervisor, Conor McBride for his guidance, support and patients throughout this project.

Also, I would like to thank my friends for helping me think with our numerous technical discussions and contemplations.

Table of Contents

Abstract	i
Acknowledgements	ii
List of figures	iii
List of tables	iv
Abbreviations	v
1 Introduction	1
1.1 Background	1
1.2 Objectives	2
1.3 Project Outcome	3
1.4 Summary of chapters	3
2 Related Work	5
2.1 Vole	5
2.2 Shonky	5
2.3 Frankjnr	6
2.3.1 Frankjnr limitations	6
2.4 Haste	6
2.5 Conclusion	7
3 Problem Description and Specification	8
3.1 Problem overview	8
3.1.1 Project risks	9
3.2 Requirements Analysis	10
3.2.1 Development Tools and Languages	10

3.2.2	Vagrant	10
3.2.3	Webpack	11
3.2.4	JavaScript	11
3.2.4.1	Alternative - CoffeScript	11
3.2.5	Haskell	12
3.2.6	Report Markdown	12
3.3	Specification	12
3.3.1	Functional requirements	12
3.3.2	Non-functional requirements	13
3.3.3	Use Cases	13
3.4	Design Methodology	13
4	Initial development & experimental system	15
4.1	Introduction	15
4.2	Simple system	16
4.2.1	Language	16
4.2.2	Compiler	18
4.2.3	Abstract machine	19
4.2.4	Testing framework	24
4.2.4.1	Bash script	25
4.2.4.2	Expect script	26
4.3	Conclusion	27
5	Detailed Design and Implementation of the final system	29
5.1	Introduction	29
5.1.1	Disclaimer	29
5.2	Project folder structure	30
5.3	Compiler	31
5.3.1	Built in functions	32
5.4	Abstract machine	33
5.4.1	Implementation	33
5.4.1.1	Computation - “value”	34
5.4.1.2	Computation - “command”	35
5.4.1.3	Possible improvement	36
5.4.2	Helper functions	36

5.4.3	JavaScript type definitions	38
5.4.3.1	Possible improvement	40
5.5	Testing framework	40
5.5.1	Implementation	41
5.5.2	Possible improvements	42
5.6	Possible improvements	42
6	Results and Evaluation	43
7	Summary & Conclusion	44
7.1	Summary	44
7.2	Future work	44
	Appendix 1: Progress log	45
	Appendix 2: Usage & installation instructions	52
	Appendix 3: Test cases	54
8	Appendix 4: Project readme.md files	55
	References	61

List of figures

List of tables

Table 5.1 This is an example table . . .	pp
Table x.x Short title of the figure . . .	pp

Abbreviations

API	A pplication P rogramming I nterface
JSON	J ava S cript O bject N otation

Chapter 1

Introduction

This chapter focuses on explaining the project motivation, objectives and outcome. Also, in the last section report structure is displayed.

1.1 Background

Functional languages are evolving, they are constantly changing to innovate and adapt to ever changing needs of software engineering. Thus, concept of Frank language was created by Prof. Conor McBride and Prof. Sam Lindley followed by its implementation called Frank and more recently newer release - Frankjnr.

Frank is strongly typed, strict functional programming language designed around Plotkin and Pretnar's effect handler abstraction, strongly influenced by (B. C. Pierce and D. N. Turner 2000), (G. D. Plotkin and J. Power 2001b), (G. D. Plotkin and J. Power 2001a), (G. D. Plotkin and J. Power 2002), (G. D. Plotkin and J. Power 2003), (G. D. Plotkin and J. Power 2009), (G. D. Plotkin and M. Pretnar 2013) papers on algebraic effects and handlers for algebraic effects. It is, also, influenced by Paul Blain Levy's call-by-push-value calculus. Frank features a bidirectional effect type system, effect polymorphism, and effect handlers. This means that Frank supports type-checked side-effects which only occur where permitted. Side-effects are

comparable to exceptions which suspend the evaluation of the expression where they occur and give control to a handler which interprets the command. However, when command is complete depending on the handler the system could resume from the point it was suspended. Handlers are very similar to typical functions but their argument processes can communicate in more advanced ways.

Because of the distinct features of Frank, in particular its capability to support effects and handlers, it has potential to be used in web development context. However, neither of Frank implementations currently support this. Thus this projects motivation is to be able to use Frank for web development. Using functional language for web development could greatly ease the process of writing parsers and form validations in the web. Furthermore, Frank code would be essentially converted into JavaScript because of its support for functional programming. This means Frank would potentially gain all the JavaScript functionality and could even use JavaScript libraries. For example, Frank would be able to handle different http requests, such as GET or POST, Frank could fire events (ex. alert boxes) or handle events (ex. mouse clicks).

The most convenient way to achieve this is to utilize existing Frankjnr implementation, rewriting its Compiler and Abstract Machine. Compiler would take in parsed Frank code and output JavaScript which could be used by Abstract Machine at Run-time.

This projects requires knowledge how Compilers and Abstract Machines work and how to use them together them. Author chose this project while knowing that it would be extremely challenging but most effective learning experience.

1.2 Objectives

- Utilize Frankjnr implementation of Frank and Shonky language;
- Utilize Shonky syntax and data structures;
- Develop Code Compiler which compiles Shonky's code to JavaScript program;

- Develop Abstract Machine implementation which supports the output of the Compiler;
- Completed system must facilitate client-side communication of events and DOM updates between Frank code and the browser;

1.3 Project Outcome

During initial development stages experimental system was developed with its own language, compiler, virtual machine and testing framework in order to expand authors insight of the subject. Lessons learned and code style with few functions of experimental system were adapted in creation of the final system. Because of it, Author was successful in implementing new Abstract Machine and Compiler for Frankjnr. They were, also, successfully integrated into Frankjnr project. However, newly developed components are very much in prototype stage as they don't yet have full support of all Frank's features. Moreover, the project can still improve on variety of things, such as performance, building procedures and testing.

1.4 Summary of chapters

Chapter 2 - Related Work

The point of the chapter is to highlight work done by others that somehow ties in with this project. It may be work that author is basing his work of, work that shows others attempts to solve similar problems or connected projects which were partially used in the final implementation of the project.

Chapter 3 - Problem Description and Specification

This chapter briefly overviews the main problems and challenges of the project. It briefly explains requirement analysis stage and development tools, languages chosen. It, also, expands upon functional and non-functional requirements, followed by detailed specification and explanation of design methodology.

Chapter 4 - Initial development & experimental system

This chapter is focused on initial experimental system. It highlights the reasoning behind it, purpose of each component, their implementation, drawbacks and any possible improvements.

Chapter 5 - Detailed Design and Implementation of the final system

Chapter reflects upon implementation and design of the final compiler and abstract machine. It, also, explains project structure, developed testing framework, project connections between Shonky and Frankjnr as well as possible improvements and considered alternative approaches.

Chapter 6 - Verification and Validation

This chapter explains how the outcome of the project was validated and what testing procedures were followed during and after the project.

Chapter 7 - Results and Evaluation

Main idea of the chapter is to highlight summarized outcome of the project, how it was evaluated and explain relevant future work.

Chapter 2

Related Work

2.1 Vole

Vole is lightweight functional programming language with its own Compiler and two Abstract Machines. One Machine is written in Haskell and provides opportunity to run compiled Vole programs on the local machine. Other Virtual Machine is written in JavaScript, because of this it is possible to run Vole programs on the web, there are few working examples in the Git repository of Vole. It, also, has some support for effects and handlers, so it utilizes the ability to communicate between compiled Vole programs and application front-end on run-time.

In the context of this project - Vole is a useful resource, because it essentially tries to solve the same problem but for a different language. Author had to study Vole, to understand its technical implementation, usage of resources and to expand his knowledge of Compilers and Abstract Machines. Lastly, Vole is used for evaluation purposes as another benchmark comparison.

2.2 Shonky

Shonky is untyped and impure functional programming language. The key feature of Shonky is that it supports local handling of computational effect,

using the regular application syntax. This means one process can coroutine many other subprocesses. In that sense it is very similar to Frank, just without type support. Its interpreter is written in Haskell, although it has potential to be ported to JavaScript or PHP to support web operations.

In the context of the project Shonky language data structures are used by the Abstract Machine, in Chapter 5 it is explained in great detail of how exactly were they used and for what purpose. However, Shonky interpreter is completely scrapped and is only used as a reference in solving any Abstract Machine or Compiler difficulties.

2.3 Frankjnr

Frankjnr is an newest implementation of Frank functional programming language described in “*Do be do be do*” (Sam Lindley, Conor McBride & Craig McLaughlin 2016) paper. Frankjnr has a parser for Frank syntax, thus the user is able to use Frank to write expressions. After parsing Frank code it performs type check and other necessary operations followed by compilation to Shonky supported data structures which are then used by Shonky interpreter to run Frank.

2.3.1 FRANKJNR LIMITATIONS

- Only top-level mutually recursive computation bindings are supported;
- Coverage checking is not implemented;

2.4 Haste

Haste is an implementation of the Haskell functional programming language, designed for web applications and it is being used in the industry. It supports the full Haskell language, including GHC extensions because it is based on GHC compiler. Haste support modern web technologies such as WebSockets,

LocalStorage, Canvas, etc. . Haste, also, has support for effects and handlers. Furthermore, Haste programs can be compiled to a single JavaScript file. Haste wasn't used as a direct resource, however it provided Author with detailed description of another solution to similar problem.

2.5 Conclusion

Three main related projects are Vole, Shonky and Frankjnr. Vole was used as an working example of a solution for similar problem, which got author thinking of different ways to approach the problem. Shonky and Frankjnr were used directly, because Frankjnr is the newest implementation of Frank language and it uses Shonky's Abstract Machine (interpreter). So the idea was to take existing Frankjnr and replace the Shonky's interpreter with new Compiler and Abstract Machine which would support web development while keeping Shonky's syntax data structures. Other related work were used as examples of different solutions to overcome similar obstacles.

Chapter 3

Problem Description and Specification

This section discusses the project problem, challenges, requirements and involved risks.

3.1 Problem overview

The main aim of the project was to develop new Compiler and corresponding Abstract Machine for existing functional language Frank implementation called Frankjnr. The difference from the old ones was that new Compiler and Abstract Machine would support web development. Many different challenges follow from that. First one being authors initial lack of knowledge on Frank language. Frank being full and complex language author had to study it and overcome any difficulties regarding the language by researching the paper on Frank “*Do be do be do*” (Sam Lindley, Conor McBride & Craig McLaughlin 2016).

A second challenge was overcoming the complexity of existing systems. Because this project is not standalone, it strictly depends on the Shonky Syntax implementation as well as Frankjnr handling Frank’s code. Author had to take time and carefully research existing systems, to understand how ev-

everything fits together and how efficiently replace exiting Shonky interpreter with new Compiler and Abstract Machine.

Another challenge was the difficult nature of compilers and abstract machines. This was the most difficult challenge to overcome due to the depth and the amount of detail each of them have. Thus, the incremental approach was adapted, in order to for the author to learn step by step, starting with simpler things. Author started the project by developing experimental system with its own language, compiler and virtual machine to understand the crucial concepts of compiler and abstract machines.

Fourth challenge was testing and validation. Because the project is focused on developing completely new system without any usage of frameworks, testing framework had to be developed which could run test cases and check their correctness without any interaction of the user. Testing framework was developed by utilizing Bash Script, Expect Script languages and Node, Webpack, Ghci commands. It was firstly, created for experimental system and then based on observation and testing, altered and improved for the final system. In the end, it dramatically improved development time by constantly locating bugs and validating the correctness of the outputs.

The project was extremely broad and involved great deal of initial research as well as constant analysis of next steps, thus development was slow but effective. However, due to time constrains development time had to be planned very carefully, because of this some acknowledged directions of development had to be ignored to finish the prototype in time. For example, one of those directions was Haskell enforced type checker. Haskell compiler could have had a type checker which would prevent any bugs regarding generated JavaScript programs by enforcing its types. Now such bugs are spotted by the console window of the browser or testing framework.

3.1.1 PROJECT RISKS

- Dependence on Frank implementation (Frankjnr). Instances of Frank code will be tested to make sure it behaves as expected;
- Estimating and scheduling development time. Due to authors inexperience

rience with the subject of the project, correctly estimating and scheduling time is difficult. However, meetings with supervisor are organized regularly, to make sure the project is on track;

- Lack of resources, supervisor Conor McBride is the only resource of relevant and accurate information;
- Authors lack of experience with languages being used and overall analyzed concepts (compiler and virtual machines).

3.2 Requirements Analysis

Before any development could begin requirements needed to be gathered, author did this by discussing how the system should behave and what technologies it should utilize with the supervisor. He, also, attended programming languages seminar where Frank language was discussed, gaining different perspective on the whole project. Lastly, author read papers on relevant topics, such as “Compiling Exceptions Correctly” (Graham Hutton and Joel Wrigth 2004), to expand his knowledge and gain more insight in what to do. Further research was made to ensure the appropriateness of chosen languages and technologies.

3.2.1 DEVELOPMENT TOOLS AND LANGUAGES

This section will briefly explain used tools and languages and reasoning behind each of them.

3.2.2 VAGRANT

Vagrant is an optional tool to create separate development environment for the project. It runs on Virtual Box and it is essentially a server on your local computer which you can boot up and work on. Furthermore, Vagrant comes with up to date relevant libraries out of the box. Author used it to avoid installing software and managing libraries on local machine, thus speeding up development.

3.2.3 WEBPACK

Webpack is a module builder and it is available as npm package. In this project it is used for Abstract Machine development as it adds some wanted features to plain JavaScript, and in the end everything is compiled to a single light JavaScript file. The most important is an ability to create and export different modules, for example, module could be a function or a variable. This lets for improved project structure as you are able to keep JavaScript components in separate files, thus making it easier to develop and navigate through code.

3.2.4 JAVASCRIPT

JavaScript is a client side scripting language. In this project output of the compiler is generated in JavaScript, which is then used by Virtual Machine which is, also, written in JavaScript so that both could cooperate on run time without any further compilations.

JavaScript is used because of its key features. Firstly, it has support for functional programming by letting function arguments be other functions. Secondly, it is supported by all popular browsers. And finally, there are lots of libraries and features to support web development.

3.2.4.1 Alternative - CoffeeScript

CoffeeScript is much newer language and it improves upon JavaScript syntax, allowing for neater declarations, introduces new features and reinforces the structure of the code. CoffeeScript can run in any environment where JavaScript can run, because in the end it is compiled to JavaScript. It is available as npm package. However, it wasn't used because author didn't want another layer of compilation going on in the background.

3.2.5 HASKELL

Haskell is a statically, implicitly typed, lazy, standardized functional programming language with non-strict semantics. Haskell features include support for recursive functions, data types, pattern matching, and list comprehensions.

Haskell was a clear choice for compiler development because of its functional language features, like pattern-matching, efficient recursion, support for monadic structures. Moreover, Frankjnr and Shonky are written in Haskell, so it was easy to cooperate with those projects.

3.2.6 REPORT MARKDOWN

This report adapted the template of markdown developed by Tom Pollard, because of its flexible structure and features, such as support for Pandoc markdown and latex expressions. Everything is compiled to a single PDF by utilizing npm.

3.3 Specification

3.3.1 FUNCTIONAL REQUIREMENTS

- To create new back end for Frankjnr implementation:
 - Develop Compiler which uses Shonky’s language (Syntax file) and outputs a sensible and correct JavaScript code structure;
 - Develop Abstract Machine which can run previously compiled JavaScript code in the browser;
- To facilitate client-side communication of events and DOM updates between Frank code and the browser;

3.3.2 NON-FUNCTIONAL REQUIREMENTS

- To create set of tests which should always pass, before each new release of the system. Test cases should be increased after every iteration to validate new features and ensure the previous features are not broken;
- To develop testing framework, which tests the system using the list of predetermine test cases;
- To measure performance (in comparison with the existing back end and with other kinds of generated JavaScript);
- Client-side programming should become possible (example, complex parser of a text field);

3.3.3 USE CASES

Use cases are not really relevant to this project, since the developed compiler and abstract machine support full Frank language, which potentially can be used in infinite number of ways. But generally, the user puts sensible Frank code into a Frank file then initiate compilation by using project's compiler, the compiler will generate a JavaScript file which user can include in their web project. Furthermore, user needs to include the machine, which utilizes previously compiled code, into their project. For more detailed information on how to use the system, check usage instruction in the Appendix ???.

3.4 Design Methodology

The implementation of the project is fully focused on back end development. The adopted design methodology was iterative and incremental development (IID). The main reasons behind it were the difficult nature of the project and author's initial lack of knowledge on the subject; this methodology allows the developer to focus on few features at a time building the system incrementally, thus making it easier to learn as you go.

Iterative and incremental development (IID) is a process which grows the system incrementally, feature by feature during self-contained cycles of analysis,

design, implementation and testing which end when the system is finished. Meaning, the system is improved (more functionality added) through every iteration.

The core benefits of this methodology are:

- Regression testing is conducted after each iteration, where only few changes are made through single iteration, because of this faulty elements of the software are easily identified and fixed before starting the next iteration;
- Testing of systems features is a bit easier, because this methodology allows for targeted testing of each element within the system;
- System could easily shift directions of development after each iteration;
- Learning curve is much flatter than usual, because developer is focusing on few features at a given time.

Another big decision was to start with simpler system, an experimental throughout which the author could learn the basics and adapt gained knowledge in the development of the final system. The experiment took about four weeks and used the same methodology - iterative and incremental development.

Chapter 4

Initial development & experimental system

4.1 Introduction

Because of the complexity of overall project and the lack of initial author knowledge in the field the most optimal plan was to start with something small and expand gradually. The intricacies consist of:

- Frank is a complex functional language;
- Frankjnr adds another layer of complexity, since author needs to be aware of the implementation and compilation process;
- Dependence on Shonky's language, because the final implementation of the Compiler must be able to understand and compile Shonky language;
- Complexity of the Compilers and their implementation;
- Complexity of Abstract Machines and their implementation;

Thus, simpler language was developed with matching Compiler and Abstract Machine. Both, the Compiler and the Machine were developed while keeping in mind that their key parts will be used for the final product. So efficiency, reliability, structure were all key factors.

4.2 Simple system

System consists of:

- Compiler - written in Haskell;
- Language - written in Haskell;
- Machine - written in JavaScript, compiled with Webpack;
- Testing Framework - written in Bash and Expect scripts;

4.2.1 LANGUAGE

A simple language written in Haskell, which syntax supports few specific operations, such as, sum of two expressions, Throw & Catch, Set, Next, Get, new reference.

Full language definition

This section will focus on the exact definition of the language. Language is defined as Haskell data type. In this case it supports only different types of expressions.

```
data Expr =
```

Experimental language is focused on Integer manipulation, thus it only supports integer values. Here is a definition of a Integer value.

```
| Val Int
```

Definition of sum of two expressions.

```
| Expr :+: Expr
```

Syntax definition of a Throw and Catch commands. If the first expression of Catch is equal to Throw, meaning something went wrong then the second expression will be evaluated.

```
| Throw  
| Catch Expr Expr
```

Syntax definition of WithRef command. It creates new reference with a given value. First string variable of the command defines name of new reference. Second value is an expression which defines how to compute initial value of new reference. And the third value is the context in which the reference is valid. WithRef stack frame is the handler for “Get” and “:=” commands.

```
| WithRef String Expr Expr
```

Syntax definition of getting the value of a defined reference.

```
| Get String
```

Syntax definition of setting defined reference value to new expression.

```
| String := Expr
```

Syntax definition for evaluating two expressions one by one and taking value of the second. In most programming languages it is defined as “;”.

```
| Expr :> Expr
```

Each of the operations were carefully selected, where their implementation in the Abstract Machine varies significantly. Because the implementation of these operations will be generalized in the final system, for instance, code for sum of two expressions will cope with all arithmetic calculations of two expressions.

4.2.2 COMPILER

Purpose of the Compiler is to take an expression of the simple, experimental language described above and output a JavaScript working program, array of functions, which could be used by the Abstract Machine.

Below is a definition of code generation monad. It contains a constructor `MkCodeGen` and deconstructor `codeGen`.

```
newtype CodeGen val = MkCodeGen {  
    codeGen :: Int -- next available number (for naming helper functions)  
    -> ([ ( Int      -- this number...  
        , String    -- ...defined as this JS code  
        ) ]  
    , Int          -- next available number after compilation  
    , val          -- result of compilation process  
    ) -- usually the list of definitions will start with  
    -- the input "next number" and go up to just before  
    -- the output "next number"  
}
```

`MkCodeGen` is used to construct a definition in `genDef` function displayed below. `genDef` returns the definition number.

```
genDef :: String -> CodeGen Int  
genDef code = MkCodeGen $ \ next -> [(next, code)], next + 1, next)
```

`genDef` is used by `compile` function to make new function definitions. Below is the type of `compile` function. `compile` function takes in a valid language expression and outputs entry point of the compilation as well as compilation process which can be separated into chunks of JavaScript code.

```
compile :: Expr -> CodeGen Int
```

`compile` function is either used to create new function definitions...

```
help s (Val n) = genDef $
    "function(s){return{stack: \"++ s ++ \", tag: \"num\\\", data: \"++ show n ++\"}}
```

or to compile expressions to JavaScript.

```
help s (e1 :+: e2) = do
    f2 <- compile e2
    help ("{prev: \"++ s ++ \", tag: \"left\\\", data: \"++ show f2 ++\"}") e1
```

Formating and outputting to file

jsSetup takes a name of the array, the output of compile function and outputs a JavaScript formatted string.

```
jsSetup  :: String      -- array name
        -> CodeGen x    -- compilation process
        -> ( String     -- JavaScript code
            , x          -- result
          )
```

jsWrite takes an output of jsSetup and writes everything to a file “generated.js” which can be safely used by Abstract Machine.

```
jsWrite :: (String, x) -> IO()
jsWrite (code, x) = writeFile "dist/generated.js" code
```

4.2.3 ABSTRACT MACHINE

Purpose of the Abstract Machine is to take in a compiled program and run it in the browser. It gradually builds a stack from the given program, where each frame of the stack has a link to another frame. The elegant part of this is that, stack frames can be saved, updated, deleted and restored; thus, making the Machines data structure flexible.

Program Structure

Each program is an array and its entries are functions which take in a stack. This way it is possible to nest them while keeping track of the stack.

Below is an example of a compiled program ready to be used by Abstract Machine. This particular program is simple, it only adds two numbers “2 + 3”, so the expected output is “5”.

```
var ProgramFoo = [];  
  
ProgramFoo[0] = function (s) {  
    return {  
        stack: s, // stack  
        tag: "num", //expression type  
        data: 3 // expression value  
    }  
};  
  
ProgramFoo[1] = function (s) {  
    return {  
        stack: { // stack  
            prev: s, // link to previous frame  
            tag: "left", // command used for adding numbers  
            data: 0 // index of next operation  
        },  
        tag: "num", // expression type  
        data: 2 // expression value  
    }  
};
```

Abstract Machine Implementation

This section will explain detailed implementation of the experimental Abstract Machine. It is defined as a function which takes in a compiled program as an argument.

Initial definition of mode with starting values. Because the starting stack is empty the “stack” parameter is defined as “null”; the tag is an expression

type and if it is equal to “go”, the Machine must evaluate next function. Finally, the “data” parameter holds an index of next function, so the initial value is the index of last function in a program array.

```
var mode = {  
  stack: null,  
  tag: "go",  
  data: f.length - 1  
}
```

Mode is a function in a program array which takes in a stack as a parameter. Abstract Machine will operate until mode.tag is equal to “go”. If it is then mode must be reinitialized by getting getting a next function from program array and passing stack to it, so that the mode has access to previous stack.

```
while (mode.tag === "go") {  
  mode = f[mode.data](mode.stack);  
}
```

After the mode is reinitialized mode.tag can’t be equal to “go” and mode stack can’t be empty. If these requirements aren’t met then it means that execution is over.

```
while (mode.tag != "go" && mode.stack != null) {
```

If the execution is still going then the behavior of the Abstract Machine will differ based on mode’s tag parameter. Tag could be equal to these values:

- “**num**” - all of the basic evaluations of given expression:
 - Addition (“left” and “right”) - creates a stack frame with tag “right”, if the top of the stack tag is equal to “right” it means that Abstract Machine can add two of the top frames together, because all of the other computations are done.

- Catch - creates a stack frame with tag “catcher” and places it on the top of the stack. Its data parameter is equal to the index of second expression which will be evaluated if first expressions throws an exception.
- New reference - creates a stack frame with tag “WithRefRight”, it is different from other stack frames because it has a “name” parameter, which is needed to identify between different references. It, also, holds the value of the reference in its “data” parameter.
- Next (:>left and :>right) - implementation is similar to addition, however the key difference is that if the top stack frame tag is equal to “:>right” the Abstract Machine will take its data without adding anything and it will delete the used stack frame.
- Set (:=) - very similar to “Get” command, key difference is that it alters the stack frame which has tag “WithRefRight” and the given name of the reference. This command utilizes linked list stack saving to be able to restore the stack while saving any changes made. It could throw an exception if the reference is undefined.
- **“throw”** - it defines that something went wrong so the Abstract Machine will look for a “catch” usage in the previous stack, if it doesn’t find it then it will output an exception.

Machine checks if the top of the stack is equal to “catcher”, if it is then it means exception was handled, so Abstract Machine reinitializes mode to continue executions by taking “catcher” values of “stack” and “data”.

```
mode = {
    stack: mode.stack.prev,
    tag: "num",
    data: mode.stack.data
}
```

Else Machine drops the top of the stack and continues to look for “catcher” until stack is empty.

```
mode = {
  stack: mode.stack.prev,
  tag: "throw",
  data: "Unhandled exception!"
}
```

- “get” - goes through stack while looking for a reference, output’s either a value of the reference if it does find it or tries to throw an exception if it doesn’t. It, also, utilizes linked stack saving and restoring functions, in order to restore the stack if it does find a reference.

After the Abstract Machine finishes running it will output the final stack to the console by invoking a custom printer function for the user to clearly see the stack.

```
printer(mode);
```

And finally, Abstract Machine outputs final value of the execution on the separate line for testing purposes, it is used by Testing framework to check for expected and actual output of a test.

```
console.log(mode.data);
```

Linked Stack Saving and Restoring

Abstract Machine uses saver function in “get” and “:=” implementations. This function lets the Machine not only to inspect the depths of the stack but, also, to assign new values to existing frames of the stack. To achieve this, Abstract Machine saves each frame of the stack from top until it finds the frame it is looking for. Below “saveStack” function is displayed, the “m” variable represents the current stack frame.

```
save = {
  prev: save,
```



```
    tag: m.tag,  
    data: m.data,  
    name: m.name  
}
```

The save is reverse linked list of stack frames, thus it is possible to restore the original stack including all the changes made. After stack is successfully restored all of the save data must be destroyed and parameters reseted to keep future saves unaffected.

Limitations:

- Only one Stack save can exist at a given time.

Final Remarks

The Abstract Machine currently supports functionality for adding expressions, creating a reference, getting the value of a reference, setting new value of a given reference, throwing & catching an exception.

Room for improvement:

- Efficiency and optimization;
- Documentation;
- Functionality;

All of these are addressed in the final implementation.

4.2.4 TESTING FRAMEWORK

Testing framework consists of two files utilizing two different scripts: Bash script and Expect script. Its purpose is to automate the testing process. Below each of these scripts will be reviewed.

4.2.4.1 Bash script

Bash script is the main script in the testing framework which stores all test cases, then goes through them one by one.

Sample test case:

```
declare -A test0=(  
  [expr]='let xpr = Val 10'  
  [name]='test_num'  
  [expected]='10'  
)
```

Complex test case:

```
declare -A test9=(  
  [expr]='let xpr = WithRef "x" (Val 22) ("x" := (Get "x" :+: Val 11) :> (Get  
  [name]='test_withref_get_set_next'  
  [expected]='63'  
)
```

Each test case must store three values: expression to be tested, the name of the test and expected output.

For each test case it launches Expect script and passes parameters to it. It passes the expression to be tested and the name of the test.

```
./tests/helper.sh ${test[expr]} ${test[name]}
```

After, Expect script “helper.sh” finishes computing and generates new program, system must recompile Abstract Machines code to use newly generated program. Webpack is used for all JavaScript code compilations, dependencies and overall structure.

```
webpack --hide-modules #recompile code to output.js
```

After successful recompilation of JavaScript Bash script has to retrieve the output of the program by retrieving the last line of the console output utilizing Node functionality and some string manipulation.

```
output=$(node ./dist/output.js); #get output  
output="${output##*$'\n'}" #take only last line
```

Finally, Bash script just compares the expected output with actual output and gives back the result for the user to see.

```
if [ "$output" = "${test[expected]}" ]; then  
    echo -e "${GREEN}Test passed${NC}"  
else  
    echo -e "${RED}Test failed${NC}"  
fi
```

4.2.4.2 Expect script

Expect script is used because of its ability to send and receive commands to programs which have their own terminal, in this case GHCi.

Expect script takes the name of the test and the expression to be tested. Because it is only possible to pass one array to Expect script, the script performs some array manipulation to retrieve the name and the expression.

```
set expr [lrange $argv 0 end-1]  
set name [lindex $argv end 0]
```

After that it launches GHCi terminal.

```
spawn ghci
```

And waits for “>” character before sending the command to load the Compiler.hs file.

```
expect ">"
send ":load Compiler.hs\r"
```

Finally, Expect script sends the two following commands to generate the output of the Compiler and quits to resume the Bash script execution.

```
expect "Main>"
send "$b\r"
```

```
expect "Main>"
send "jsWrite (jsSetup \"$name\" (compile xpr))\r"
```

Possible improvements for the final testing framework:

- Speed & efficiency;
- Move test cases into separate file;
- More useful statistics at the end of computation;

For usage and installation instructions go to Appendix 2 section.

4.3 Conclusion

A preliminary experiment, implementing the essence of Frank-like execution for much simpler language, has been completed successfully. The key lessons were:

- Haskell syntax;
- Language creation and its syntax development;
- Compiler - parsing the input and generating valid JavaScript code;
- Machine - executing given program, and managing its resources, such as mode, stack and saved stack.

Key things to improve are optimization & performance.

The further plan is to roll out the lessons learned creating compiler and VM for more of the “Shonky” intermediate language that is generated by Frank compiler. This will be covered in the next chapter.

Chapter 5

Detailed Design and Implementation of the final system

Chapter focuses on implementation, design of the final compiler and abstract machine, as well as, any topics connected to them.

5.1 Introduction

Final system started to develop on week six of the second semester after the end of experimental system development. Some parts of the code were lifted from the earlier experiment and main concepts of how virtual machines and compilers should work are reused.

5.1.1 DISCLAIMER

Final system uses two other systems in its code base, thus not all of the code is written by the author of this project. Author's code will be clearly indicated. Two projects connected to the system are:

- **Frankjnr** - developed by Craig???. Final system is essentially new back end for Frankjnr. So the whole Frankjnr project was used and new back end was placing in ‘Backend’ folder. Parts of Frankjnr code were slightly updated to let the user choose between the old back end and the new one. Updated files were: Compile.hs and Frank.hs, updates are clearly indicated with comments;
- **Shonky** - developed by Conor McBride. Final compiler uses Shonky’s syntax file for its supported data structures and parse functions;

More detailed descriptions can be found at ‘Related work’ section of the report or at their respective Github pages.

5.2 Project folder structure

Final system is located in “final_implementation” folder. And all of the code for new compiler and abstract machine is located in “Backend” folder.

Table’s starting folder is “/final_implementation”.

Table 5.1: Project folder structure

Paths and Files	Summary
	Main directory for final implementation
Frank.hs	Main Frankjnr file
Compile.hs	Compiles Frank to Shonky data structures
/Backend	Machine and Compiler files
Compiler.hs	Main compiler
/Backend/machine	Abstract Machine files
webpack.js	Webpack configuration file
tester.html	HTML which includes output.js (testing purposes)

Paths and Files	Summary
<code>main.js</code>	Main machine function
<code>/Backend/machine/components</code>	Includes all components to construct Virtual Machine
<code>machine.js</code>	Main component for Virtual Machine
<code>printer.js</code>	Component responsible for result printing
<code>/Backend/machine/dist</code>	Generated files
<code>gen.js</code>	Compiler generated code
<code>output.js</code>	Webpack generated code (every JS file is packed into one)
<code>/Backend/Shonky</code>	Shonky project directory
<code>Syntax.hs</code>	Contains needed data structures
<code>/Backend/tests</code>	Test framework
<code>main.sh</code>	Main file (launch file)
<code>testcases.sh</code>	Contains all of the test cases
<code>/Backend/tests/test_cases</code>	Actual programs to test
<code>/Backend/tests/test_cases/old</code>	Test programs lifted from Frankjnr
<code>/Backend/tests/test_cases/new</code>	New test programs

5.3 Compiler

Compiler is located in *final_implementation/Backend/Compiler.hs* and it is written in Haskell. It is initiated when frank program compilation is called with flag “output-js”. Example with program named “foo.fk”:

```
frank foo.fk --output-js
```


Compiler receives list of program definitions from Frankjnr compiler in a form of Shonky syntax data type - [Def Exp].

Then it has to compile the environment followed by expressions. Compiler receives

5.3.1 BUILT IN FUNCTIONS

Current built in functions are “plus” and “minus”, in order to make integer manipulation possible. They are defined before the top-level function compilation begins in function *operatorCompile* and then just initialized together with them, like this:

```
let fs = [(f, (h, pse)) | DF f h pse <- ds] ++ builtins
```

However their current definitions are a bit different compared to others which are generated. Compiler is not able to give them meaning because he does not know how to manipulate two integer expressions; instead compiler must pass this functionality to the abstract machine, which can interpret those expressions and apply wanted arithmetic operation. Compiler codes wanted arithmetic operation into the function definition, like this:

```
DF "minus" [] [...], EV "x" :$ [EV "y", EV "y"]
```

“:\$” means application, compiler tries to apply integer variable “x” to list of integer variables “y”, which initially does not make any sense. However, machine has encoded semantics for this situation, therefore if integer is applied to a list of arguments that could only mean one of two things, either that integer needs to be added to first element of the list or subtracted from it. Machine determinse this by looking how many elements are in the list and applies the correct operation accordingly.

```
if (args.length === 2) { // minus
  answ = fun.int - args[0].value.int;
```

```

} else { // plus
  ans = fun.int + args[0].value.int;
}

```

Those were special cases when compiler is not able to deal with them, however other built in functions, which do not require arithmetic operations can easily be added without machine knowing about them. Such as, pairing two elements or getting first element out of a pair.

5.4 Abstract machine

Purpose of the abstract machine is to take in generated output of the compiler and run it in the web, thus completing the task of running Frank code in the browser. For full usage & installation instructions see Appendix 2.

Abstract machine modules are located in *final_implementation/Backend/machine* folder. They are written in JavaScript and are compiled to a single file *final_implementation/Backend/machine/dist/output.js* by utilizing webpack.

5.4.1 IMPLEMENTATION

Abstract machine takes contents of *gen.js* as an input, which contains two different arrays: operators and resumptions. Operators are equivalent to functions in Haskell, resumptions are computations waiting to be executed. In current implementation starting operator is always the first function, so main method should be at the top of file. And they return modes which are computation who store stack, here the machine defines initial mode with initial empty stack, no arguments and no environment:

```

var mode = operators[0].implementation(null, [], []);

```

The machine will keep executing in a while loop until stack becomes empty; before halting it will return the final mode and call printer helper function

to display the output. In each while cycle machine check the current computation tag, it can either be a “value” or a “command” and depending on which one it is, machine will act accordingly.

5.4.1.1 Computation - “value”

If the “mode.comp.tag” is equal to “value” then machine will look at the first frame of the stack to receive information on what to do next. There are four options depending on the frame tags, each of them will construct new mode building or reducing the stack in the process (look at *JavaScript type definitions* section to see their structure):

- **“car”** - will construct mode out of calling a resumption based on “mode.stack.frame.cdr” value. For resumption to construct a new mode they need two values, stack and an environment. Therefore, machine will pass in the stack and the environment as well. Although, it will alter the stack by removing top stack frame and creating a new one with a “cdr” tag and a car value.

```
frame: {  
  tag: "cdr",  
  car: mode.comp.value  
},
```

- **“cdr”** - will reduce the stack and return a pair of *car* and *cdr* as its computation. It will take *car* value from the current stack frame and *cdr* from current computation value.
- **“fun”** - means application, so some function needs to be applied to a list of arguments, which is essentially list of resumptions. If the list of arguments is empty that means the machine is ready to initiate the function application by calling helper “apply” function without any arguments. If, however, the argument list is not empty machine needs to construct new mode with frame tag “arg”. It creates new mode out of first argument resumption “resumptions[mode.stack.frame.args.head]” and passes all the needed information in the new stack frame:

```

frame: {
  tag: "arg",
  fun: mode.comp.value,
  env: mode.stack.frame.env,
  ready: [],
  waiting: mode.stack.frame.args.tail,
  handles: headHandles(intf),
  waitingHandles: tailHandles(intf)
},

```

“fun” field to keep the function that will be applied when the arguments “waiting” list is empty. “env” to keep the environment, “ready” list to know which arguments have been parsed, initially it is empty. “waiting” to keep track of list of arguments that are left unchecked. And, lastly, “handles” with “waitingHandles” to keep track which argument handle what commands, so if handles list is empty it means that this argument doesn’t handle any commands. It gets these values by applying helper functions, which return head and tail of the list. And the initial handle list is extracted from operators interface with helper function “interfaceF”, which simply returns given operators interface (list of commands that it can handle).

- “arg” - simply adds current head of arguments to the ready list and initiates helper function “argRight” which will return new mode (its functionality in detail is described in “Helper functions” section).

5.4.1.2 Computation - “command”

Because of “command” type of computations Frank is different from other functional languages. When command computation appears the current execution is interrupted and the control is given to the handler, which looks for the requested command in the stack while building a callback (checked stack frames) to restore the stack when the command is found and finished executing.

In this implementation, computations with tag equal to “command” are

created in a case when an atom is applied to a list arguments. Then the abstract machine goes down the stack while looking for the command. Each time it doesn't find it, it will place top frame in the callback and move down by one frame:

```
mode.comp.callback = {  
  frame: mode.stack.frame,  
  callback: mode.comp.callback  
}  
mode.stack = mode.stack.prev
```

For the machine to find a command in a frame, it must be an “arg” frame. And it must contain the command that the handler is looking for in its “handles” list (it indicates which commands does given “arg” handle).

```
if (mode.stack.frame.tag === "arg") {  
  for (var i = 0; i < mode.stack.frame.handles.length; i++) {  
    if (mode.stack.frame.handles[i] === mode.comp.command) {  
      ...  
    }  
  }  
}
```

When these conditions are met, the command handler is found. Therefore it will place the computation of the command on the “ready” argument list and will try to apply it by calling “argRight” helper function, which in turn will call “apply” helper function if there are no waiting resumptions.

5.4.1.3 Possible improvement

To store stack frames in chunks of frames, where only the top frame of a given chunk could potentially handle a command. This would skip checking all frames, which tags are not equal to “arg”, therefore improving performance.

5.4.2 HELPER FUNCTIONS

This section will describe the functionality of two main helper functions.

argRight - takes in stack tail, function to be applied, list of arguments that are ready, environment, list of arguments which are still waiting to be checked and list of handled commands. List of handled commands is kept for the machine to know what commands does the resumption handle. Same as in the “fun” case if the waiting list of resumptions (arguments) is empty then the machine is ready to apply the function, thus call apply function, if it is not then create new “arg” frame in the same fashion as in “fun” option. The key difference is that “fun” could be instantly applied if it didn’t have any arguments, thus not creating any “arg” frames. Moreover, there is potential to move all logic to “argRight” function without having any in “fun” case, improving code reuse and optimization.

apply - Depending on a “fun” computation value, constructs a mode from which to continue execution. “fun” computation could be one of the following:

- **“int”** - Applying int to an argument is not really sensible, however in this case it is possible because of built in operations (see *Built in functions* section). This custom functionality lets machine add and subtract integer values.
- **“local”** - Means a local function, and the machine is turning it into top level operator, concept introduced by (Thomas Jonson 1985) and it is named “Lambda Lifting”. Therefore, mode is constructed out of an operator variable.
- **“operator”** - Means top level function, mode is constructed from an operator depending on “fun.operator” value which is an index for operators array.
- **“atom”** - Applications of atoms mean a command is initiated; mode with command tag and command value should be created. It, also keeps the arguments and creates a “callback” value to be able to restore the stack successfully after finding required command in the stack. Thus new mode looks like this:

```
stack: stk,
```

```

comp: {
  tag: "command",
  command: fun.atom,
  args: vargs,
  callback: null
}

```

- **“thunk”** - Application of thunk pattern. Constructs a mode while ignoring any arguments; computation expression comes from “fun.thunk”. New mode is equal to:

```

stack: stk,
comp: fun.thunk

```

- **“callback”** - This means command has been found and executed and now the machine has to restore the stack to its original position. It does this looping through the “callback” while building the stack with callback’s frames. When it is done, machine returns a mode constructed of the restored stack and first argument.

```

stack: stack,
comp: args[0]

```

printer - takes the mode of finished execution, parses it to make it readable and displays it on the screen.

5.4.3 JAVASCRIPT TYPE DEFINITIONS

This section explains the JavaScript types used to enforce the data structure of programs.

“JSRun” is an operator, who always return mode. They are located in operators array in the generated program (“gen.js”). Mode has a stack and current computation; top stack frame and current computation both determine what to do next.

```
jstype JSRun = (JSStack, JSEnv, JSVal[]) -> JSMODE
jstype JSMODE = {stack: JSStack, comp: JSComp}
```

Stack could be empty or consist of a frame and a link to previous frame. The idea of these links are applied from linked list data structure, where each element of the list has a link to the next element. This structure is used regularly throughout the project.

```
jstype JSStack
= null
| {prev: JSStack, frame: JSFrame }
```

Stacks frame type, which determines the operation that needs to be done when current computation is equal to “value”.

```
jstype JSFrame
= null
| {tag:"car", env: JSEnv, cdr: Int }
| {tag:"cdr", car: JSVal }
| {tag:"fun", env: JSEnv, args: JSList Int }
| {tag:"arg", fun: JSVal, ready: JSComp[], env: JSEnv, waiting: JSList Int,
    headles: Int, waitingHandles: JSList Int }
```

List data structure, where it could be empty or have an current element and tailing list of elements.

```
jstype JSList x
= null
| {head : x, tail : JSList x}
```

Computation could either be a “value” or a “command”.

```
jstype JSComp
= {tag:"value", value: JSVal}
| {tag:"command", command: String, args: JSVal[], callback:JSCallBack}
```



```
jstype JSCallBack
  = null
  | {frame: JSFrame, callback: JSCallBack}
```

These are the types of what value can be. “atom” is just an value that cannot be deconstructed any further. “int” represents an integer value. “pair” is a pair of two values, one is held in “car” object and the other is in “cdr”. “operator” is a top level function. “callback” holds a “callback” object which has stack frames waiting to be restored after machine finds definition of command that it was looking for. “thunk” represents a thunk pattern. And “local” means local function, which do to procedure called “Lambda Lifting” (Thomas Jonson 1985), abstract machine will turn it into a top level function and execute.

```
jstype JSVal
  = {tag:"atom", atom: String}
  | {tag:"int", int: Int}
  | {tag:"pair", car: JSVal, cdr: JSVal}
  | {tag:"operator", operator: Int, env: JSEnv}
  | {tag:"callback", callback: JSCallBack}
  | {tag:"thunk", thunk: JSComp}
  | {tag:"local", env: JSEnv, operator: JSVal}
```

5.4.3.1 Possible improvement

Current state of JavaScript type definitions are not enforced by the compiler; so compiler trusts the programmer to encode them correctly. The improvement would be to enforce types with Haskell data structures, thus minimizing the risk of bugs in production.

5.5 Testing framework

Contained in *final_implementation/Backend/tests* folder. Framework is design to launch number of programs, located in *test_cases* folder, and give

back results to the user, which test programs succeeded and which failed. It eliminates manual testing, lets identify bugs faster, thus speeding up development process and easing maintenance. And it is fully written in Bash Script.

Some parts of the test framework were lifted from earlier experiment, however the key differences are that it is not using GHC compiler directly; so it eliminates the need for Expect Script (previously located in *helper.sh* file), thus improving performance of the framework. Another change is that test cases don't take in expressions anymore, instead they take in paths to actual programs, therefore providing ability to launch them and check their output.

For all test case programs, usage & installation instructions check Github or see Appendix.

5.5.1 IMPLEMENTATION

Similarly like in experimental systems test framework, test cases are stored in array. Each of them are objects which store three values: path of the test program, name of the test and expected output. They are looped through on by one displaying the name of the test to the user and recompiling the test with:

```
frank ${test[path]} --output-js
```

It generates the *gen.js* in *Backend/machine/dist* folder. At this point *Backend/machine/dist/output.js* needs to be recompiled to include new *gen.js* file.

```
webpack --hide-modules
```

Then it just retrieves the output with *Node* and checks if it as expected or not; letting the user know if test failed or passed. Finally, some statistics are shown: how many tests in total have passed and failed with corresponding percentages.

5.5.2 POSSIBLE IMPROVEMENTS

- Providing more statistics when all tests are finished running;
- Timestamp tests, letting the user know how much time it took to run individual tests and all of them together;
- Improve performance by not trying to launch programs which fail to compile by Frankjnr compiler.

5.6 Possible improvements

use chunks of stacks when top of the chunk is possible needed stack frame and others are not (speedup)

turn local functions into top level operators is called “Lambda-lifting” it was invented by Thomas Jonson in 1985 (Springer LNCS 201). it’s used in eg. GHC

Match-this-or-bust pattern matching is late 60s technology:

Computer Aided Manipulation of Symbols F.V. McBride PhD thesis, 1970, Queen’s University Belfast

The more efficient compilation by building a tree of switches is

Compiling Pattern Matching Lennart Augustsson in Functional Programming and Computer Architecture 1985 Springer LNCS 209 # Verification and Validation

Chapter 6

Results and Evaluation

Chapter 7

Summary & Conclusion

7.1 Summary

7.2 Future work

Appendix 1: Progress log

JANUARY

January 4th:

Research:

Looked over Frankjnr, Shonky, Vole implementations.

January 5th:

Tried to install Frankjnr for a period of time, however couldn't resolve all the errors.

January 7th:

Research:

Looked at Vole with a bit more detail.

January 9th:

Tried to install Frankjnr by using Cabal dependency management tool, no success (deprecated dependencies).

Presentation & Report work:

Worked on project specification, plan and presentation.

January 10th:

Research:

Looked at Vole, in particular Machine.lhs, Compile.lhs and Vole.js.

January 11th:

Presentation & Report work:

Worked on project specification, plan and presentation.

January 16th:

Research:

Looked at Shonky stack implementation, tried to output it on the screen.

January 17th:

Machine Development:

Implemented simple linked list stack in JavaScript, just as a practice.

January 18th:

Research:

Looked again at Shonky's Abstract Machine, particularly the order the input is parsed.

January 24th:

Machine Development:

Implemented simple Abstract Machine, which can sum 2 numbers.

January 25th:

Machine Development:

Machine now works with stack larger than 2.

Updated the way it stores functions, now it uses Array data structure.

Research:

Looking into how to implement throw, catch and compiler.

January 26th:

Compiler Development:

Created basic language in Haskell. Which supports expressions and sum of expressions.

Developed monadic structure for the compiler.

January 30th:

Compiler Development:

Finished the basic layout, however it doesn't display any results yet.

Presentation & Report Work:

Setup of latex with lex2tex.

January 31th:

Machine Development:

Implemented Throw and Catch for Abstract Machine.

Presentation & Report work:
Worked on structure of the report.

FEBRUARY

February 01:
Presentation & Report work:
Worked on latex configurations.

February 02:
Machine Development:
Implemented early versions of stack saving, restoring and support for Set command.

February 04:
Presentation & Report work:
Report work - Introduction sections.

February 06:
Compiler Development:
Tried to implement Show instance for CodeGen function.

February 07:
Research:
Looked at the lifecycle and expected behaviour of the Compiler.
Compiler Development:
Implemented Compiler Catch and Throw.

February 08:
Compiler Development:
Implemented Get, Next, WithRef commands.
Machine Development:
Implemented support for Next commands.
Added new examples of working programs.

February 09:
Machine development:
Implemented early version of stack saving and restoring.
Implemented support for Set commands.

Added new working examples.

Reworked Next command support, should work as expected.

February 10:

Test Framework development:

Implemented test framework by utilizing Bash and Expect scripts.

Machine development:

Divided code into separate classes and files.

Added printer class, which just outputs the current stack to the console.

February 13:

Started to rework Abstract Machine, to closer match the implementation required.

Machine development:

Reworked Catch and Throw command support.

Compiler development:

Small efficiency adjustments.

Test Framework development:

Added more test cases.

General bug fixes.

February 14: *Test Framework development:*

Fixed major bug with string parsing.

Added more test cases.

Machine development:

Completely reworked support for Get, Set and WithRef commands.

General bug fixes.

February 15:

Progress report.

February 16:

Progress report.

February 24:

Final Compiler development:

Outputting generated code to js file.

Researched top level functions.

Project

Updated project structure.

March

March 05:

Report

Chapter 4 almost done.

Project

Improvements all around: bug fixes, documentation updates.

March 07:

Report

Related work section

Introduction chapter summarization

Final Compiler development:

Attempt to implement operators array

Looking into how to compile operator variables

March 08:

Report

Background section

Final Compiler development:

Various fixes

operatorCompile function adjustment

File Writer adjustment

March 09:

Report

Related work section

Final Compiler development:

Adjusted file generation

Fixed operatorCompile function

Final Abstract Machine development:

Initialized project structure with webpack

Initial implementation of final Machine (support for CAR and CDR operations)

March 10:

Final Compiler development:

Adjusted type definitions

Added one layer of structure to Computations

Final Abstract Machine development:

Fixed bugs regarding CAR and CDR

Optimization- “go” tag is not needed, creating modes directly

CDR now returns pair

March 11:

Final Compiler development:

Added needed functionality to compiler to support ‘application’ operations

Final Abstract Machine development:

Added functionality for FUN and ARG, still need to figure out how to apply a function to ready list

March 12:

Final Compiler development:

Added parser functions, now the compiler is able to covert Shonky language to its syntax

Final Testing Framework development:

Created initial structure of the framework as well as sample test case

Report

Problem overview section

March 13:

Final Compiler development:

Commands development

Final Abstract Machine development:

Commands development

Report

Specification section

March 14:

Final Compiler development:

Bug fixes

Final Abstract Machine development:

Bug fixes, command support implemented

Report

Requirement analysis section

Project structure

Frankjnr now uses new back end

March 15:

March 16:

March 17:

Test framework development

Compiler and Machine - added Built in function support

Machine Print function development

March 18:

Report work - Final implementation section and appendixes

March 19:

Report:

Abstract machine sections

Appendix 2: Usage & installation instructions

Experimental test framework

Pre-requirements

- Node;
- npm;
- Webpack;
- GHC;
- Expect Script - install by typing this command:

```
apt-get install expect
```

Usage

To run simply type in the terminal window:

```
./tester.sh
```

Troubleshooting

If files don't have permission, do:

```
chmod +x tester.sh
```

```
chmod +x helper.sh
```

Final test framework

Pre-requirements

- Node;
- npm;
- Webpack;
- GHC;
- Frank - instructions how to setup are on Frankjnr Github *readme.md* file or in the Appendix 4 of this report.

Usage

To run simply type in the terminal window:

```
./tester.sh
```

You should be able to see tests going through with some feedback.

Troubleshooting

If *tester.sh* have issues with permission, do:

```
chmod +x tester.sh
```

Appendix 3: Test cases

Experimental system

```
declare -A test0=( [expr]='let xpr = Val 10' [name]='test_num' [expected]='10' ) declare -A test1=( #addition [expr]='let xpr = Val 2
:+: (Val 4 :+: Val 8)' [name]='test_sum' [expected]='14' ) declare
-A test2=( # Throw [expr]='let xpr = Val 2 :+: (Val 4 :+: Throw)'
[name]='test_throw' [expected]='Unhandled exception!' ) declare -A
test3=( # Catch [expr]='let xpr = Catch (Val 2 :+: (Val 4 :+: Throw))
(Val 2)' [name]='test_catch' [expected]='2' ) declare -A test4=( # Catch
with previous stack [expr]='let xpr = ((Val 5) :+: (Catch (Val 2 :+: (Val 4
:+: Throw)) (Val 2)))' [name]='test_catch_stack' [expected]='7' )
```

```
declare -A test5=( # Simple WithRef, value is not used [expr]="let xpr
= WithRef "x" (Val 2) (Val 5 :+: Val 3)" [name]='test_simple_withref'
[expected]='8' ) declare -A test6=( # [expr]='let xpr = Get "x" :+: Val
2' [name]='test_get_false' [expected]='Exception: Undefined expression:
x' ) declare -A test7=( # [expr]='let xpr = WithRef "x" (Val 2) (Val
5 :+: (Get "x"))' [name]='test_withref_get' [expected]='7' ) declare -A
test8=( # might need to adjust this [expr]='let xpr = WithRef "x" (Val 2)
(("x" := (Get "x" :+: Val 11)) :> Get "x")' [name]='test_withref_get_set'
[expected]='13' ) declare -A test9=( # [expr]='let xpr = WithRef
"x" (Val 22) ("x" := (Get "x" :+: Val 11) :> (Get "x" :+: Val 30))'
[name]='test_withref_get_set_next' [expected]='63' ) declare -A test10=(
# [expr]='let xpr = Val 2 :> Val 5 :+: Val 8 :> Val 1000 :> Val 20 :+: Val
3' [name]='test_next' [expected]='23' )
```

Final system

Chapter 8

Appendix 4: Project readme.md files

Run Frank in Browser

Frankjnr

An implementation of the Frank programming language described in the paper “Do be do be do” by Sam Lindley, Conor McBride, and Craig McLaughlin, to appear at POPL 2017; preprint: <https://arxiv.org/abs/1611.09259>

Installation procedure

The easiest way to install **frank** is to use stack <https://www.haskellstack.org>), <https://github.com/commercialhaskell/stack>):

```
stack setup
```

The above command will setup a sandboxed GHC system with the required dependencies for the project.

```
stack install
```

The above command builds the project locally (`./.stack-work/...`) and then installs the executable **frank** to the local bin path (executing `stack path --local-bin` will display the path).

Running a Frank program

To run a `frank` program `foo.fk`:

```
frank foo.fk
```

By default the entry point is `main`. Alternative entry points can be selected using the `--entry-point` option.

Some example `frank` programs can be found in `examples`. They should each be invoked with `--entry-point tXX` for an appropriate number `XX`. See the source code for details.

Optionally a `https://github.com/pigworker/shonky` file can be output with the `--output-shonky` option.

Limitations with respect to the paper

- Only top-level mutually recursive computation bindings are supported
- Coverage checking is not implemented

Report template

Template for writing a PhD thesis in Markdown

This repository provides a framework for writing a PhD thesis in Markdown. I used the template for my PhD submission to University College London (UCL), but it should be straightforward to adapt suit other universities too.

Citing the template

If you have used this template in your work, please cite the following publication:

Tom Pollard et al. (2016). Template for writing a PhD thesis in Markdown. Zenodo. <http://dx.doi.org/10.5281/zenodo.58490>

Why write my thesis in Markdown?

Markdown is a super-friendly plain text format that can be easily converted to a bunch of other formats like PDF, Word and Latex. You'll enjoy working in Markdown because:

- it is a clean, plain-text format...
- ...but you can use Latex when you need it (for example, in laying out mathematical formula).
- it doesn't suffer from the freezes and crashes that some of us experience when working with large, image-heavy Word documents.
- it automatically handles the table of contents, bibliography etc with Pandoc.
- comments, drafts of text, etc can be added to the document by wrapping them in `<!-- -->`
- it works well with Git, so keeping backups is straightforward. Just commit the changes and then push them to your repository.
- there is no lock-in. If you decide that Markdown isn't for you, then just output to Word, or whatever, and continue working in the new format.

Are there any reasons not to use Markdown?

There are some minor annoyances:

- if you haven't worked with Markdown before then you'll find yourself referring to the style-guide fairly often at first.
- it isn't possible to add a short caption to tables ~~and figures~~ (figures are now fixed). This means that `/listoftables` includes the long-caption, which probably isn't what you want. If you want to include the list of tables, then you'll need to write it manually.
- the style documents in this framework could be improved. The PDF and HTML outputs are acceptable, but ~~HTML~~ and Word needs work if you plan to output to this format.
- ... if there are more, please add them here.

How is the template organised?

- README.md => these instructions.
- License.md => terms of reuse (MIT license).
- Makefile => contains instructions for using Pandoc to produce the final thesis.
- output/ => directory to hold the final version.
- source/ => directory to hold the thesis content. Includes the references.bib file.
- source/figures/ => directory to hold the figures.
- style/ => directory to hold the style documents.

How do I get started?

1. Install the following software:
 - A text editor, like Sublime, which is what you'll use write the thesis.
 - A LaTeX distribution.
 - Pandoc, for converting the Markdown to the output format of your choice. You may also need to install Pandoc cite-proc to create the bibliography.
 - Install shortcaption module for Pandoc, with `pip install pandoc-shortcaption`
 - Git, for version control.
2. https://github.com/tompollard/phd_thesis_markdown/fork
3. Clone the repository onto your local computer (or download the Zip file).
4. Navigate to the directory that contains the Makefile and type “make pdf” (or “make html”) at the command line to update the PDF (or HTML) in the output directory.
In case of an error (e.g. `make: *** [pdf] Error 43`) run the following commands:

```

sudo tlmgr install truncate
sudo tlmgr install tocloft
sudo tlmgr install wallpaper
sudo tlmgr install morefloats
sudo tlmgr install sectsty
sudo tlmgr install siunitx
sudo tlmgr install threeparttable
sudo tlmgr update l3packages
sudo tlmgr update l3kernel
sudo tlmgr update l3experimental

```

5. Edit the files in the ‘source’ directory, then goto step 4.

What else do I need to know?

Some useful points, in a random order:

- each chapter must finish with at least one blank line, otherwise the header of the following chapter may not be picked up.
- add two spaces at the end of a line to force a line break.
- the template uses John Macfarlane’s Pandoc to generate the output documents. Refer to this page for Markdown formatting guidelines.
- PDFs are generated using the Latex templates in the style directory. Fonts etc can be changed in the tex templates.
- To change the citation style, just overwrite `ref_format.csl` with the new style. Style files can be obtained from citationstyles.org/
- For fellow web developers, there is a Grunt task file (`Gruntfile.js`) which can be used to ‘watch’ the markdown files. By running `$ npm install` and then `$ npm run watch` the PDF and HTML export is done automatically when saving a Markdown file.
- You can automatically reload the HTML page on your browser using LiveReload with the command `$ npm run livereload`. The HTML page will automatically reload when saving a Markdown file after the export is done.

Contributing

Contributions to the template are encouraged! There are lots of things that could improved, like:

- finding a way to add short captions for the tables, so that the lists of tables can be automatically generated.
- cleaning up the Latex templates, which are messy at the moment.
- improving the style of Word and Tex outputs.

Please fork and edit the project, then send a pull request.

References

- B. C. Pierce and D. N. Turner, 2000. *Local type inference*,
- G. D. Plotkin and J. Power, 2001a. *Adequacy for algebraic effects*,
- G. D. Plotkin and J. Power, 2003. *Algebraic operations and generic effects*,
- G. D. Plotkin and J. Power, 2009. *Handlers of algebraic effects*,
- G. D. Plotkin and J. Power, 2002. *Notions of computation determine monads*,
- G. D. Plotkin and J. Power, 2001b. *Semantics for algebraic operations*,
- G. D. Plotkin and M. Pretnar, 2013. *Handling algebraic effects*,
- Graham Hutton and Joel Wrigth, 2004. *Compiling Exceptions Correctly*,
- Sam Lindley, Conor McBride & Craig McLaughlin, 2016. *Do be do be do*,
- Thomas Jonson, 1985. *Springer LNCS 201*,