

Session Planner — ER-Modell

PostgreSQL / JPA · 3 Tabellen · UUID-Primärschlüssel · snake_case

users		
FELD	TYP	CONSTRAINTS
id	uuid	PK
name	varchar	NOT NULL
nickname	varchar	NOT NULL Anzeigename, z.B. „Peter K.“
role	varchar	NOT NULL Enum · MVP nur ADMIN
github_name	varchar	UNIQUE NOT NULL Login-Matching
email	varchar	UNIQUE NOT NULL
avatar_url	varchar	NULLABLE

cohorts		
FELD	TYP	CONSTRAINTS
id	uuid	PK
name	varchar	UNIQUE NOT NULL z.B. wd_onl_de_220626
nickname	varchar	NULLABLE interner Spitzname, z.B. „Flamingos“
color	varchar(7)	NOT NULL Hex, z.B. #4F9DDE
start_date	date	NOT NULL
end_date	date	NOT NULL
federal_state	varchar	NOT NULL Bundesland · für Feiertage

shifts		
FELD	TYP	CONSTRAINTS
id	uuid	PK
title	varchar	NOT NULL
date	date	NOT NULL
start_time	time	NOT NULL
end_time	time	NOT NULL
cohort_id	uuid	FK → cohorts.id NOT NULL
coach_id	uuid	FK → users.id NULLABLE null = unassigned

Beziehungen

- cohorts 1** —< * **shifts** — jeder Shift gehört zu **genau einer** Cohorte (cohort_id NOT NULL).
- users 0..1** —< * **shifts** — ein Shift hat **keinen oder einen** Coach; ein User coacht viele Shifts (coach_id NULLABLE = „unassigned“).