



Review of C# Syntax

What Is .NET?

- CLR
 - Robust and secure environment for your managed code
 - Memory management
 - Multithreading
- Class library
 - Foundation of common functionality
 - Extensible
- Development frameworks
 - WPF
 - Entity Framework
 - ASP.NET

What Is C#?

- A language on top of .NET
- Statements ending with a semi colon
- Case sensitive

Creating a .NET Application

1. In Visual Studio, on the **File** menu, point to **New**, and then click **Project**.
2. In the **New Project dialog** box, choose a template, location, name, and then click **OK**.

```
using System;
using System.Collections.Generic;
using System.Linq;
using System.Text;
using System.Threading.Tasks;

namespace ConsoleApplication1
{
    class Program
    {
        static void Main(string[] args) { }
    }
}
```

What are Data Types?

- int – whole numbers
- long – whole numbers (bigger range)
- float – floating-point numbers
- double - double precision
- decimal - monetary values
- char - single character
- bool - Boolean
- DateTime - moments in time
- string - sequence of characters

Declaring and Assigning Variables

- Declaring variables:

```
int price;  
// OR  
int price, tax;
```

- Assigning variables:

```
price = 10;  
// OR  
int price = 10;
```

- Implicitly typed variables:

```
var price = 20;
```

Expressions and Operators in Visual C#

Example expressions:

- + operator

```
a + 1
```

- / operator

```
5 / 2
```

- + and – operators

```
a + b - 2
```

- + operator (string concatenation)

```
"ApplicationName: " + appName.ToString()
```

Casting Between Data Types

- Implicit conversion:

```
int a = 4;  
long b = 5;  
b = a;
```

- Explicit conversion:

```
int a = (int) b;
```

- **Native Type conversion**

```
string possibleInt = "1234";  
int count = int.Parse(possibleInt);
```

- **System.Convert** conversion:

```
string possibleInt = "1234";  
int count = Convert.ToInt32(possibleInt);
```


Implementing Conditional Logic

- **if** statements

```
if (response == "connection_failed") { . . . }  
else if (response == "connection_error") { . . . }  
else { }
```

- **select** statements

```
switch (response)  
{  
  case "connection_failed":  
    . . .  
    break;  
  case "connection_success":  
    . . .  
    break;  
  default:  
    . . .  
    break;  
}
```

Console and Interpolated Strings

- To output text to the console

```
Console.WriteLine("Some text");
```

- To read text from the console

```
var input = Console.ReadLine(); //input is a string here!
```

- Interpolated strings

```
Console.WriteLine($"Hello {firstName}!");
```

Parsing values from strings

- Parsing is the ability to generate a variable of their underlying type given a textual equivalent
 - Useful since all string input from the user arrives as string data

Lab 1

<https://github.com/RolandGuijt/csharpworkshop>

Implementing Iteration Logic

- **for** loop

```
for (int i = 0 ; i < 10; i++) { ... }
```

- **foreach** loop

```
string[] names = new string[10];  
foreach (string name in names) { ... }
```

- **while** loop

```
bool dataToEnter = CheckIfUserWantsToEnterData();  
while (dataToEnter)  
{  
    ...  
    dataToEnter = CheckIfUserHasMoreData();  
}
```

- **do** loop

```
do  
{  
    ...  
    moreDataToEnter = CheckIfUserHasMoreData();  
} while (moreDataToEnter);
```

Practicing iteration

- Create an int variable that is initialized to 0.
- Create a for loop that adds 1 to the int.
- Print out the int afterwards with a `Console.WriteLine` and observe it.
- Achieve the same functionality with a while loop.

Lab 2

Creating and Using Arrays

- Creating an array:

```
int[] arrayName = new int[10];
```

```
int[] arrayName = { 1, 2, 3, 4, .. };
```

- Accessing data in an array:

- By index

```
int result = arrayName[2];
```

- In a loop

```
for (int i = 0; i < arrayName.Length; i++)  
{  
    int result = arrayName[i];  
}
```


Using Breakpoints in Visual Studio

- Breakpoints enable you to view and modify the contents of variables:
 - Immediate Window
 - Autos, Locals, and Watch panes
- Debug menu and toolbar functions enable you to:
 - Start and stop debugging
 - Enter break mode
 - Restart the application
 - Step through code

Lab 3