

```
#define PIN_SWDI0 7 // SPI MISO
#define PIN_SWDI0_MOSI 7 // SPI MOSI
#define PIN_SWCLK 6
#define PIN_TDO 8 // device TDO -> Host Data Input
#define PIN_TDI 9
#define PIN_nTRST 4 // optional
#define PIN_nRESET 5
```



J1
Cortex Debug 10pin connector

Signal	Pin
Vtref	1
TMS/SWDIO	2
VCOM_TX	3
TCK/SWCLK	4
VCOM_RX	5
TDO/SWO	6
VTarget	7
TDI	8
GND	9
nRST	10

J2
ARM Standard JTAG

Signal	Pin	Signal	Pin
VTref	1		2
nTRST	3		4
TDI	5		6
TMS/SWDIO	7		8
TCK/SWDCCLK	9		10
VCOM_TX	11		12
TDO/SWO	13		14
nRST	15		16
VCOM_RX	17		18
VTarget	19		20

VTref

GND

```

.param pulse_width = 1
.param period = 20u
; .dc pulse_width 0.1 0.9 0.1
.OPTIONS METHOD=GEAR
.OPTIONS RELTOL=0.01
.OPTIONS VNTOL=10uV

```



Title: Xiao_ESP32C3_wireless_DAP

Rev: ver 0.1

Id: 1/1