


```
#define PIN_SWDI0 7 // SPI MISO
#define PIN_SWDI0_MOSI 7 // SPI MOSI
#define PIN_SWCLK 6
#define PIN_TDO 8 // device TDO -> Host Data Input
#define PIN_TDI 9
#define PIN_nTRST 4 // optional
#define PIN_nRESET 5
```



.param pulse_width = 0.1
 .param period = 20u
 .dc pulse_width 0.1 0.9 0.1
 .OPTIONS METHOD=GEAR
 .OPTIONS RELTOL=0.01
 .OPTIONS VNTOL=10uV



J2
ARM Standard JTAG

Signal	Pin	Signal	Pin
VTref	1	nTRST	2
nTRST	3	TDI	4
TDI	5	TMS/SWDIO	6
TMS/SWDIO	7	TCK/SWDCLK	8
TCK/SWDCLK	9	VCOM_TX	10
VCOM_TX	11	VCOM_RX	12
VCOM_RX	13	TDO/SWO	14
TDO/SWO	15	nRST	16
nRST	17	VCOM_RX	18
VCOM_RX	19	VTref	20

GND



Title: Xiao_ESP32C3_wireless_DAP

Size: A4	Date: 2025-12-29	Rev: ver 0.1
KiCad E.D.A. 9.0.6		Id: 1/1