

Raspberry

Accessing the Raspberry

1. `sudo apt update`
2. `sudo apt upgrade`
3. `sudo apt-get install openssh-client` (if it's the first time using raspberry in this computer)
4. `sudo ip addr add 156.189.56.4/24 dev enx00e04c680f61INTERFACE_YOU_WANT`
interface you want found with `ip link` → it's the one that says `<BROADCAST,MULTICAST,UP,LOWER_UP>` and starts with `en/eth` (ethernet)
5. `ssh host@156.189.56.3`
password: `smart_card`
if terminal times out, do `rm -r ~/.ssh/known_hosts` and go back to 4.

now this terminal window is controlling the raspberry

Developing in the Raspberry

1. In a new terminal window, do `nano ~/.ssh/config` [the new window must be of your computer, not already connected to raspberry]
2. in the contents of the config, write:
`Host 156.189.56.3`
`HostName 156.189.56.3`
`User host`
3. if not already installed, install Remote - SSH extension by Microsoft on VSCode
4. Use that extension to connect to host

Configure the Raspberry for Wifi and Remote Root Access

1. write the wifi name and password in a file on the `wifi_connectivity` directory of the Pi

2. run the script using `./wifi_update_create.sh`
3. using the terminal (not controlling the raspberry) find the wireless network being used with `ip -a` (looking for the subnet with an interface starting with wlp)
4. use that subnet for the following command: `sudo nmap -sn X.X.X.X/24`
the Nmap scan report for discretion is the one you're looking for. that's the raspberry wireless IP, which can be useful for the VSCode extension or to connect via a terminal (using `ssh host@X.X.X.X`)

For the rasp.c → `gcc rasp.c -o rasp $(pkg-config --cflags --libs libpcsclite) -g -Wall -Wextra -Wpedantic -fsanitize=address -fsanitize=undefined -I/usr/include/PCSC -lpcsclite`

For the app → `npx ts-node server.ts`

not localhost:3000 → `X.X.X.X:3000`