

Conception de Systèmes Interactifs Design Rationale

Université Nice Sophia Antipolis (Polytech)

Marco Winckler

Université Nice Sophia (Polytech) | I3S | SPARKS team | bureau 453

winckler@i3s.unice.fr

<http://www.i3s.unice.fr/~winckler/>



References

- Carroll, J. M., & Rosson, M. B. (2003) Design Rationale as Theory. Ch. 15 in J.M. Carroll (Ed.), HCI Models, Theories, and Frameworks. San Francisco: Morgan Kaufmann
- MacLean, Allan; Young, Richard M.; Bellotti, Victoria M. E., and Moran, Thomas P. Questions, Options, and Criteria: Elements of Design Space Analysis. Lawrence Erlbaum Associates; 1991; 6, pp. 201-250.
- Célia Martinie, Philippe A. Palanque, Marco Winckler, Stéphane Conversy: DREAMER: a design rationale environment for argumentation, modeling and engineering requirements. SIGDOC 2010: 73-80


Structure of the lecture

- About design process
- What is Design Rationale?
- What is the purpose?
- How is it conducted?
- Contributions to HCI
- Notations

First, about design

- **Design** is a problem-solving process whose objective is describe and find a way to...
implement requirements, respecting constraints, and ensure good quality
- The result of the process includes:
 - **Specification** of the product to be implemented
 - A set of design **decisions**

Taking decisions



The design process

- A designer has to face with several issues
 - Each issue part of the overall problem
 - Each issue might be solved by more than one design option
 - The designer makes a decision to resolve every issue
- This process implies to chose the best option among the alternatives

What is Design rationale?

- Rationale has to do with logical explanations and reasoning
- Discussions, debates, negotiations
- Reasons for features
- Reasons against features
- Weighing of tradeoffs

Why to use Design Rationale?

- Increase understanding interaction situations by:
 - Documentation
 - Analysis
 - Descriptions
 - Causes and consequences
- Showing important aspects about:
 - Context
 - Applicability
 - Scope

Steps in Design Rationale

- Scenarios
- Narratives
- Generating claims
- Claims analysis

Scenarios

- Describe user interaction
 - Created or observed situations
 - Documented as narratives
 - Several scenarios are recommended
-
- Typical scenarios comes from theory, observation, field studies, personal experiences, documented experiences
 - We look for situations where contradictions are obvious

Types of scenarios

- Goals: what can I do?
 - What - other than sending e-mails - does this system support?
- Opportunism: what does this do?
 - What does the “Rules” preference support?
- How-To: carrying out procedures.
 - How do you add mailboxes and hierarchies of mailboxes?
- Sense-Making: what happened?
 - Why is there suddenly a mailbox for drafts?

Claim analysis

- Claims are statements
 - interpreted as design suggestions
 - are carefully examined
- Every claim is associated with benefits and drawbacks, systematically documented
- Decisions are supported by theories relevant for the current situation

Supporting theories

- Psychological theories (see second class...)
 - Memory
 - Gestalt laws
 - etc.
- Sociological theories
- Ergonomics
- Different point of views according to users
- ...

Tradeoff analysis

Goals	Medical researchers	Health analysts	Non-functional requirements		
			Accuracy	Security	Usability
Plot data on maps	✓	✓✓			++
Show hotspots on maps	-	✓✓✓			++
Provide simple statistics	✓	✓✓			+
Annotate maps	-	✓✓✓			+
Check data errors	✓✓	✓	++	+	
Provide advanced statistics	✓✓✓	-	++		

Example

- Have a shared calendar at work:
 - + saves time when meetings are scheduled.
 - + easy to know when people are available.
 - but people have to remember to make a note of everything they do.
 - but people might not feel comfortable that everyone knows where they are and what they do.


How to find claims

- Text analysis
 - Scanning for causes & effects
- Pose questions related to situations/actions/goals
 - what made her click there?
- **Analyze scenarios with users**
- Reuse of prior analyses
- **Use Norman's stages of action**

Norman's stages of action

- Forming the goal
- Forming the intention
- Specifying an action
- Executing the action
- Perceiving the state of the world
- Interpreting the state of the world
- Evaluating the outcome


Interaction gulfs (according to D. Norman, 1986)




Execution gulf is the effort required for a user to express an intention in terms of commands or instructions

Evaluation gulf refers to the way the results provided by the system are meaningful or understandable by the users, and in accordance with their goals

Task-artifact cycle



Design artefact and knowledge reuse



Summary

- Design rationale at several levels:
 - A tool for communicating design alternatives/decisions to users or clients
 - Contributes to general design knowledge
 - Supports research approaches contributing to HCI theory


Exercise for the TD

- Examine and discuss scenarios and claims for the design options described with your prototypes
 - Are the scenarios plausible?
 - Is it clear how the claims are identified?
 - What HCI knowledge grounds the claims analysis?
 - Can other claims be identified?
- See slide 15 for an example

Design Rationale Notations

- gIBIS (Conklin & Begeman, 1988)
- QOC (MacLean & McKerlie, 1995)
- DREAM TEAM (Lacaze, Palanque, Barboni & David Navarre, 2005)
 - Based on QOC


QOC (Question, Options, Criteria)



The TEAM Notation

Questions, Option,
Criteria:

- + factors associated to criteria
- + assessment of options
- + traceability of options selected
- + view of participants
- + task models associated to options
- + executable scenarios for an options




Extensions on the TEAM **Notation**


Requirements







Questions







Options




Criteria



Factors



Scenarios, Tasks, Arguments



Case Study

- Source: DGAC (French Civil Aviation Authority)
- Goals on this project:
 - a) To develop a formal description technique for describing widgets in user applications for cockpit display system; This issue has been addressed by extending the ICO notation;
 - b) To specify user applications compliant with ARINC 661 standard, which is an aeronautical international standard.

The standard ARINC 661

3.0 WIDGET LIBRARY

Table 3.3.34-1 RadioBox Parameters Table

Parameters	Change	Description
<i>Commonly used parameters</i>		
WidgetType	D	A661_RADIO_BOX
WidgetIdent	D	Unique identifier of the widget.
ParentIdent	D	Identifier of the immediate container of the widget.
Visible	DR	Visibility of the widget
Enable	DR	Ability of the widget to be activated

RadioBox2 alternatives for look and feel”

Description:

A RadioBox widget enables a crew to select one Button out of “n” exclusive ones. The children of the widget should be indicated by any graphical representation.

Restriction:

The children of the widget will be positioned relative to the parent of the widget. A RadioBox has only children types:

ToggleButton

PushButton
CHECKBUT2

Only one child of a given RadioBox at a time. The CD (Child) must be consistent (selected) at all times, including when the widget is disabled. This prevents the user from selecting a child of a RadioBox (this is a select and one for select).

CHECKBUT2
CHECKBUT2
CHECKBUT2

CHECKBUT2
CHECKBUT2
CHECKBUT2

Table 3.3.34-2 RadioBox Creation Structure Table

CreateParameterBuffer	Type	Size (bits)	Value/Range When Necessary
WidgetType	ushort	16	A661_RADIO_BOX
WidgetIdent	ushort	16	
ParentIdent	ushort	16	
Enable	uchar	8	A661_FALSE A661_TRUE
Visible	uchar	8	A661_FALSE A661_TRUE

The RadioBox widget does not send any event.


Available SetParameter identifiers and associated data structure are defined in Table 3.3.34-3.

Table 3.3.34-3 RadioBox Runtime Modifiable Parameters Table

Name of the Parameter to Set	Type	Size (bits)	ParameterIdent Used in the ParameterStructure	Type of Structure Used (Refer to Section 4.5.4.5)
Enable	uchar	8	A661_ENABLE	A661_ParameterStructure_1Byte
Visible	uchar	8	A661_VISIBLE	A661_ParameterStructure_1Byte


ARINC 661 RadioBox 2 in context:

Multi Purpose Interactive Application (MPIA)



Rationalizing the Design of the ARINC RadioBox2

- Known requirements are added to the diagram;
- Questions raised by designers during brainstorming meetings are included in the diagram;
- For each question raised, several options are explored and the relationships between them are depicted by edges in the diagram;
- Any artifacts (i.e. ICO models in the ARINC RadioBox2) related to a particular element are added to the corresponding design option;
- Criteria and factors influencing the choice are added to the diagram (e.g. ISO 9126 standard on Software Quality);
- Edges are added for connecting options and criteria;



DREAM diagram for the design of the behavior of the ARINC 661 RadioBox2 widget



Tool Support: DREAMER

The screenshot shows the DREAMER tool interface with the following components and annotations:

- participants**: Points to the "Team involved" panel on the left, which lists:
 - Maker
 - Célia
 - Decider
 - Marco
 - Philippe
- sessions**: Points to the "Sessions" panel on the left, which lists:
 - Fri Jun 04 13:47:48 CEST 2010
 - Fri Jun 04 12:16:32 CEST 2010
- zooming pan**: Points to the "Overview" panel on the left, which displays a network diagram of requirements and their relationships.
- Main edition area**: Points to the central workspace containing:
 - A top bar with requirement categories: REQ001 - RadioBox2 Categories, REQ002 - RadioBox2 children widgets restriction, REQ003 - RadioBox2 Parameters, REQ004 - RadioBox2 Creation Structure Table, REQ005 - RadioBox2 Runtime Modifiable, REQ006 - RadioBox2 Creation Errors, and REQ007 - RadioBox2 Runtime Errors.
 - Two "Colored matrix visualization" windows:

	Learning effort	Manage to use it	Frequency of failure
One and only one selected	Green	Green	Green
0 or 1 selected	Green	Green	Green
Focus taken into account	Green	Green	Red
Focus not taken into account	Green	Green	Green
Keep state on procedure call	Green	Green	Green
Change state on procedure call	Green	Green	Red

	One and only one s...	Focus taken into ac...	Change state on pr...	Keep state on proc...	Focus not taken int...	0 or 1 selected
REQ002 - RadioB...	Green	Red	Red	Red	Red	Red
REQ008 - RadioB...	Green	Red	Green	Green	Green	Green
Formal description...	Green	Red	Green	Green	Green	Green
REQ001 - RadioB...	Green	Green	Green	Green	Green	Green
REQ003 - RadioB...	Green	Green	Green	Green	Green	Green
REQ004 - RadioB...	Green	Green	Green	Green	Green	Green
REQ005 - RadioB...	Green	Green	Green	Green	Green	Green
REQ006 - RadioB...	Green	Green	Green	Green	Green	Green
REQ007 - RadioB...	Green	Green	Green	Green	Green	Green
 - A bottom diagram showing a network of nodes and relationships, including nodes like "the model", "taken into account", "use it", "Operability", "Frequency of failure", "Reliability", and "Change state on procedure call".