

CEIHM

Modèle de Tâches

Université Nice Sophia Antipolis (Polytech)

Marco Winckler

Université Nice Sophia (Polytech) | I3S | SPARKS team | bureau 446

winckler@i3s.unice.fr

<http://www.i3s.unice.fr/~winckler/>



References

Palanque P., Martinie C., Winckler M. (2017) Designing and Assessing Interactive Systems Using Task Models. In: Bernhaupt R., Dalvi G., Joshi A., K. Balkrishan D., O'Neill J., Winckler M. (eds) Human-Computer Interaction – INTERACT 2017. INTERACT 2017. Lecture Notes in Computer Science, vol 10516. Springer


Structure of the lecture

- Introduction to Model-based Approaches
- State of art in Task Models
- ConcurTaskTrees
- Task Models for Cooperative Applications
- HAMSTERS
- Task Models in Usability Evaluation


Why Model-based approaches?

- Highlight important information
- Help to manage complexity
- Useful to support design methods
- One important aspect of most development methods
- Reason about models
- Documentation and user help
- ...

How does an interactive UCD Process look like



How does an interactive UCD Process look like






user/task matrix

Tasks	Browser	Searcher for a specific item	Buyer
Flip catalog pages and look at pictures	Frequent	Never	Never
Mark items for future reference	Frequent	Sometimes	Never
Search for a specific type of item	Sometimes	Frequent	Frequent
Compare prices and quality	Sometimes	Frequent	Sometimes
Select an item to buy	Sometimes	Frequent	Frequent
Give credit card information	Sometimes	Frequent	Frequent

Figure 11-13 User/task matrix for catalog users in different roles.

multi-level flowchart



...and so on

Figure 11-15 If you have a complex process and want to show it in detail, consider a multi-level flowchart like this one.

Task analysis: Definitions

- Task
- Goal
- Basic Task
- Task Analysis <> Activity analysis
- Task Modeling

What is the point of task analysis?

- Determine
 - What the users do
 - The tools they use to do their work
 - The information they know or the information they must know for performing their work
- Cover all/most cases
- Cover all/most users

One small example

- To clean the house
 - Take the vacuum cleaner
 - Plug it in
 - Use it in all the rooms
 - When the bag is full, empty it
 - Store the vacuum cleaner
- You must know
 - Where is the vacuum cleaner
 - Where are the plugs
 - How to remove the bag
 - Where are the new bags
 - Evaluate if a room is clean or not

Information gathering

- Planned procedure
 - Ask the boss
 - Look at the manual
- Actual procedure
 - Ask the operator
 - Record operator behaviour
- Optimal procedure
 - The target for a good system

Task Analysis (Web application for museum)

- Tourist
 - general and clear information in limited amount
 - access by spatial representations
 - guided navigation
- Art student
 - some basic knowledge
 - choice among different types of information
- Expert
 - precise requests
 - detailed description of the information requested


Beware about the abstraction level

- If you ask the following question:
What are you doing?
- You can get:
 - I am striking ctrl-B keys
 - I make "bonjour" in bold
 - I make on word bold
 - I highlight a word
 - I am modifying a document
 - I am writing a letter
 - I keep contact with my family
 - I am waiting for a phone call ☹️

Building the task tree

- 1 Build a list of tasks
- 2 Gather high-level tasks
- 3 Breakdown low level tasks
- Where to stop ?
 - Is the action « empty bag » decomposed enough?
 - Objective: only decompose pertinent tasks (objective optimization/automation of work)
 - User actions: cognitive/motor usually not that interesting to decompose (except for performance evaluation)
 - System activity MUST not be represented (will be in other models)
- Highest level = reproduction of the specie
- Lowest level = biological life (breathe, drink a coffee , ...)

Example: make a cup of tea




Refining Models


- Once the model is built (whatever notation you use)
 - How to be sure that it is correct?
 - How to improve it?
- Some heuristics
 - Coupled actions: e.g., where is "turn gas on"?
 - Restructure : e.g. make a task generic “make pot”
 - Balance : e.g. is “pour tea” simpler than “make pot”?
 - Generalise: e.g. make one cup ... make many

Example: make a cup of tea

0.
make cups
of tea



Example: make a cup of tea




Examples of task analysis

- Tourist
 - Book a train ticket
 - Find a monument in the city
 - Game of 15
- A client using a cash machine
 - Withdraw money
 - Check the balance on the account
 - ...

Party : The game of 15

- The game is played by 2
- You have the following tokens 1, 2, 3, 4, 5, 6, 7, 8, 9
- People play in turn, each player take one token at a time, one token can only be taken once
- The first with 3 token of which the sum adds up to 15 is the winner



Play this game without tool (paper, pencil or other!)


Party : The game of 15

- Analyze one player task
 - Propose a decomposition in sub tasks
- Propose an interface (paper +pencil or computer tool) for this game
 - The user interface must (of course) help the player to achieve his task

Beware !

- Not a cognitivist approach
- Don't include the system
- Make sure models are correct
- No algorithmic description (calculation of who is the winner)
- No task migration (the system performs tasks assigned to the player)
- Who starts (difference between you play together and you play with ME - elbow communication)

Task Analysis




Your solution



Another solution

8	3	4
1	5	9
6	7	2



Functioning versus Usage Structuring



- Extraterrestrial
- Example of a computer system
 - We have a database with the following schema:



- Propose a menu tree allowing to manipulate that database

Functioning structure

- View of the computer Scientist
 - The tree structure reflects the database structure
 - Grouping is made by function code similarity




Example of task described as a scenario

- « I spent my day at work entering information for new clients and I must associate them with the more suitable sales man (according to various criteria) ... sometimes I receive an invoice from a sales man recently recruited. In such a case, I must create both the new sales man and the client. Sometimes a sales man quits the company. Usually they leave the company for another one and the clients follow them. I then have to delete the sales man and all its related ... »
- Propose a tree structure adapted to the tasks

Usage structure (1/2)

- User interface is structured according to the task

Sales Management



Things are still problematic

- There is no
 - Menu for deleting clients (without sales man)
 - Client modification
 - ...
- There is
 - Access to clients through their sales man
 - Display of client information without getting to their sales man first
 - ...

$$\mathbf{U=1/F}$$

Engineering task models

- Flexible and expressive notations
- Systematic methods able to indicate how to use information in the task models
- Availability of automatic tools to use such information efficiently

The many possible task models

- Existing System
 - One or many systems
 - One or many operators
- Envisioned System
 - One or many systems
 - One or many operators
- Variation of models (co-evolution)

Use of Task Models

- Better understanding of the application (and in particular its use)
- Record discussions (multidisciplinary)
- Help design
- Help usability evaluation
- Help performance evaluation
- Help user in performing the tasks (contextual help)
- Documentation (content + structure)

Representations of Task Models

- Hierarchical task analysis
- GOMS family
- UAN
- K-made (web)
- AMBOSS (web)
- **HAMSTERS**
- Different syntax (textual vs graphical)
- Different level of formality
- Different set of operators for task composition

GOMS Example

GOAL: EDIT-MANUSCRIPT

GOAL: EDIT-UNIT-Task repeat until no more unit tasks

GOAL: ACQUIRE-UNIT-TASK

GET-NEXT-PAGE if at end of manuscript

GET-NEXT-TASK

GOAL: EXECUTE-UNIT-TASK

GOAL:LOCATE-LINE

[select: USE-QS-METHOD
USE-LF-METHOD]

GOAL: MODIFY-TEXT

[select: USE-S-METHOD
USE-M-METHOD]

VERIFY-EDIT

Exemple GOMS-KLM

Description	Operation	Time (sec)
Reach for mouse	H[mouse]	0.40
Move pointer to "Replace" button	P[menu item]	1.10
Click on "Replace" command	K[mouse]	0.20
Home on keyboard	H[keyboard]	0.40
Specify word to be replaced	M4K[word]	2.15
Reach for mouse	H[mouse]	0.40
Point to correct field	P[field]	1.10
Click on field	K[mouse]	0.20
Home on keyboard	H[keyboard]	0.40
Type new word	M4K[word]	2.15
Reach for mouse	H[mouse]	0.40
Move pointer on Replace-all	P[replace-all]	1.10
Click on field	K[mouse]	0.20
Total		10.2

Limitations of GOMS

- It does not consider user errors
- It does not consider the possibility of interruptions
- It considers only sequential tasks
- It can be inadequate for distributed applications (such as web-based applications)

UAN - User Action Notation

- 2 complementary set of information
 - A hierarchy of tasks LOTOS (proche de CTT)
 - A table for describing states and feedback
- Textual notation
- Introduced in 1992 (Hix & Hartson huge success Developing user interfaces Ensuring, Usability Through Product & Process)

Example of UAN specification

Task: BuildRequest:
*((SelR / ClearR / IconifyR)**
--> SpecField+)

Task: SelApplication

User Action	Interface Feedback	Interface State
$\sim[x,y \text{ in AppICON}]$ $\vee \wedge (t < t_{\text{doubleClick}}) \vee \wedge$	$w'! : w' - !$ UnMap(PrevAppliMenu) Map(AppMenu) UnMap(AppICON)	CurAppli=App CurMenu=AppMenu

ConcurTaskTrees

- Focus on Activities
- Hierarchical Structure
- Graphical Syntax
- Rich set of temporal operators
- Task allocation
- Objects and task attributes

Task Models vs Scenarios

- Scenarios are informal descriptions of a specific use in a specific context
- Task models describe the possible activities and their relationships
- Scenarios can support task development
- Task models can support scenarios identification

Moving from scenarios to tasks


The screenshot shows a software interface with three main panels. The left panel, titled 'Scenario', contains a 'Scenario Description' section with the text 'scen1.0_1603am' and a 'Rationale' section. The middle panel, titled 'Roles Specification', contains a 'Roles specification' section with a list of roles: Ground, Pilot, and Pilot. The right panel, titled 'Task Model Builder', contains a 'Tasks Role specification' section with a list of tasks. The tasks are listed in a table with columns for 'Task Name' and 'Task Description'. The tasks are: 'looking at the taxiways', 'monitoring of the traffic', 'hand over the aircraft to the tower controller', 'Coordination with tower', 'communicating to the pilot the tower radio frequency', 'asks the tower controller to delay the take-off of one aircraft', 'gives the aircraft the instruction to clear the runway', 'hand over the aircraft to the departure co-ordinator', 'clears to reach the holding position', 'issues the instruction to shift to the tower controller radio frequency', 'having noticed the position of the aircraft', 'looking at the taxiways', and 'putting the corresponding strip onto the tower's departures strips bay'. The 'Task Description' section for the selected task 'looking at the taxiways' states: 'The Ground performs the monitoring of the traffic visually, looking at the taxiways through the window'. At the bottom, there are two sections: 'Objects associated with selected Task' and 'Role Objects List'. The 'Objects associated with selected Task' section contains a list of objects: 'taxiways' and 'taxiways'. The 'Role Objects List' section contains a list of objects: 'flight strips (coordination with tower)', 'tower radio frequency (communicating to the pilot the tower radio frequency)', 'tower radio frequency (issues the instruction to shift to the tower controller radio frequency)', 'taxiways (looking at the taxiways)', 'flight strip (putting the corresponding strip onto the tower's departures strips bay)', and 'strips bay (putting the corresponding strip onto the tower's departures strips bay)'.

- Find verbs = tasks
- Find words = objects
- Find adverbs = temporal relationships


Temporal Operators

- Enabling $T1 \gg T2$ or $T1 [] \gg T2$
- Disabling $T1 [> T2$
- Interruption $T1 | > T2$
- Choice $T1 [] T2$
- Iteration $T1^*$ or $T1\{n\}$
- Concurrency $T1 ||| T2$ $T1 |[]| T2$
- Concurrency (must finish first) $T1 |=| T2$
- Optionality $[T]$

CTT Editor



Task Simulator



HAMSTERS Software installation / Slides

- Slides are available
- Need java to be installed on your computer
<http://www.oracle.com/technetwork/java/javase/downloads/jre8-downloads-2133155.html>
- Need to get Hamsters tool and examples
- Need to get the Hamsters video (file HAMSTERS - Create a project - Create a task model.WMV)

Past-Current Research Projects

- Air Traffic Management (enroute ATC workstations) 1995-2001 & 2010-2014 HALA! Network of excellence & SPAD
 - Dynamic instantiation of widgets, Post WIMP interfaces
 - Time constraint about 3mn (speed vector)
 - Automation and automation degradation / tasks migrations
- Space domain : R&T IMAGES (2004-2006) R&T TORTUGA (2008-2011) R&T ALDABRA (2011-2012) R&T MARACCAS (2012-2013)
 - Specification of satellite ground segments with multimodal interfaces
 - Target application: AGENDA & spacecraft-debris collision avoidance system
 - Collaborative distributed operations / time constraint 24h
- Civil aviation Thales (2001-2004) 2009-2016 (Airbus – dependable interactive cockpits)
 - Interactive Cockpits (ARINC 661 standards)
 - Specification of system architectures for dependable interactive systems – Time constraints 30 sec

Work on task modeling -> HAMSTERS

- Philippe A. Palanque, Rémi Bastide, V. Sengès: Validating interactive system design through the verification of formal task and system models. IFIP Engineering HCI (1995): 189-212
- Philippe A. Palanque, Rémi Bastide: Synergistic Modelling of Tasks, Users and Systems using Formal Specification Techniques. Interacting with Computers 9(2): 129-153 (1997)
- David Navarre, Philippe A. Palanque, Fabio Paternò, Carmen Santoro, Rémi Bastide: A Tool Suite for Integrating Task and System Models through Scenarios. DSV-IS (2001): 88-113
- Marco Winckler, Philippe A. Palanque, Christelle Farenc, Marcelo Soares Pimenta: Task-Based Assessment of Web Navigation Design. TAMODIA Task Models and Diagrams for User Interface Design (2002): 161-169
- Philippe A. Palanque, Sandra Basnyat: Task Patterns for Taking Into Account in an Efficient and Systematic Way Both Standard and Erroneous User Behaviours. Human Error, Safety and Systems Development (2004): 109-130
- Célia Martinie, Philippe A. Palanque, Marco Winckler: Structuring and Composition Mechanisms to Address Scalability Issues in Task Models. INTERACT (2011) 589-609

Course objectives

- Know the benefits of using task description techniques to design interactive systems (tasks-based design)
- Be able to describe users' activities in a systematic and structured way (examples and practical exercises)
- Know how to use the HAMSTERS notation and tool for editing, analyzing and simulating task models (according to the current state of interaction what are the available tasks) help understand if it is a correct description
- Have experience in analyzing an interactive systems focusing on the tasks the users have to perform (manual and tool supported by HAMSTERS)
- Interact altogether on experiences on task-based design


Descriptions of Tasks

- Record information gathered during tasks analysis
- One important aspect of most development methods
- Useful for designing an interactive system that fits user work
 - Identify complex activities in the current work
 - Allocation of tasks to different actors
 - Identify good candidate for automation

Why Model-based approaches?

- Highlight important/relevant information
- Focus on abstract information (stay away from non relevant details)
- Help to manage complexity
- One important aspect of most development methods
- Possibility to reason about models
- Support collaboration amongst stakeholders

Affordance/Usability of models



Significant Models in HCI

- Task models
- Cognitive models e.g. SRK
- User models e.g. edutainment
- Domain Models e.g. UML class diagrams
- Context Models e.g. location aware systems
- Presentation Models e.g. widgets libraries
- Dialogue models e.g. state machines
- Platform models e.g. cellphones descriptions (display, CPU, ...)

Task models (versus task analysis)

- Manage information gathered from task analysis
 - Structure
 - Record
 - Refine
 - Analyze
 - Reuse
- 3 Fundamental concepts in tasks modelling
 - Hierarchical structure of tasks: Hierarchical Task Analysis (Annett & Duncan, 1967) (Annett, 2004)
 - Knowledge representation: Task Knowledge Structure (Johnson et al. 1989)
 - Multi-user/Collaborative activities: Groupware Task Analysis (van der Veer 1996)


What is the point of task analysis?

- Determine
 - What the users do
 - The tools they use to do their work
 - The information they know or the information they must know for performing their work
 - The knowledge they have (or must have)
 - The objects they must or can use to perform their tasks
 - The strategies they apply (or must know) for performing the tasks
- Cover all/most cases
- Cover all/most users

One small example

Jens Rasmussen. Skills, rules, and knowledge; signals, signs, and symbols, And other distinctions in human performance models. IEEE transactions on systems, man, and cybernetics, vol. Smc-13, no. 3, may / june 1983, 257-266.

- To clean the house
 - Take the vacuum cleaner
 - Plug it in
 - Use it in all the rooms
 - When the bag is full, empty it
 - Stop when finished
 - Store the vacuum cleaner
- You must know
 - Where is the vacuum cleaner?
 - Where are the plugs?
 - How to remove the bag?
 - Where are the empty bags?
 - Should I start by the entrance or by the end of the room? – strategy (related to context)
 - Should I have vacuum cleaner at maximum speed? – strategy
 - Evaluate if a room is clean or not – situational knowledge



Information gathering

- Operators/users work
 - Planned procedure
 - Ask the boss (regulations)
 - Look at the manual or training material
 - Actual procedure
 - Ask the operator
 - Record operator behavior
 - Optimal/Minimal procedure
 - The target for an optimal system (maybe not the best one – e.g. aircraft cockpits)
- Tools around the workspace
 - Post-it, memory joggers, annotations ...

Beware about the abstraction level

Example from A. Dix

- If you ask the following question:
What are you doing?
- You can get:
 - I am striking ctrl-B keys
 - I make the word "bonjour" in bold
 - I make one word bold
 - I highlight a word
 - I am modifying a document
 - I am writing a letter
 - I keep contact with my family
 - I am waiting for a phone call ☹

Task models as the corner stone of successful design

Task models as the corner stone of successful design

- Main elements of the course
 - HAMSTERS notation
 - Task model creation, edition and validation
- Practical work on an illustrative real life interactive system
- Not presented but included in the annex:
- « Which notation to choose? »: a review of of notations and tools for describing users' tasks

In this part, you will learn how to

- Create a task model
- Build a task model
- Validate a task model
- Modify a task model

Example: Obtain money from an ATM



Photo credit: Adam De Almeida

Why the ATM ?


(Automated Teller Machine)

- Simple but meaningful example:
- System and activities already known by the audience
- Requires manipulation of several types of data
- Several versions of the system for withdrawing money:
 - Manual way (at the bank office)
 - ATM in public spaces
 - Java version of the ATM (for the course)




HAMSTERS TOOL

How to start HAMSTERS


- Make sure Java JRE 8 is installed
<http://www.oracle.com/technetwork/java/javase/downloads/jre8-downloads-2133155.html>
- Go in directory hamster/bin
- Launch hamsters.exe 
- Menu File/new project or click on icon

Launch HAMSTERS




Create a project


Menu File/New
Project




Create a project



Click Next



Enter the name of your project



The image shows the 'New Project' dialog box in NetBeans. The title bar reads 'New Project'. On the left, a 'Steps' panel lists: 1. Choose Project, 2. C. The main area is titled 'C' and contains three text fields: 'Project Name:' with 'MyATM' entered, 'Project Location:' with 'C:\Users\martinie\Documents\NetBeansProjects' entered, and 'Project Folder:' with 'C:\Users\martinie\Documents\NetBeansProjects\MyATM' entered. A 'Browse...' button is to the right of the Project Location field. At the bottom, there are five buttons: '< Back', 'Next >', 'Finish' (highlighted with a blue border), 'Cancel', and 'Help'.

Steps

1. Choose Project
2. C

C


Project Name: MyATM

Project Location: C:\Users\martinie\Documents\NetBeansProjects

Project Folder: C:\Users\martinie\Documents\NetBeansProjects\MyATM

< Back Next > **Finish** Cancel Help

Project created



Main directories in the project

Roles

- Contains task models

Subroutines

Components

- Contain reusable task models (presented in part 2)

Objects


- Contain manipulated data: information, physical objects...

Actors

Trainee

Practical sessions

Interactive system runtime and training (not presented today)





HAMSTERS

HUMAN-CENTERED ASSESSMENT AND MODELLING TO SUPPORT ENGINEERING FOR RESILIENT SYSTEMS

Elements of the notation HAMSTERS

- Hierarchy
- Temporal ordering
- Refined task types
- Manipulated objects/information/devices
- Knowledge

Hierarchy

- Decomposition of activities according to goals
- Goals into sub-goals
- Sub-goals into tasks
- Tasks into actions
- ...

Exercise 1

Model the main tasks to withdraw money

- Goal: Withdraw money
- Prerequisites:
 - Have a withdrawal card
 - Know the amount that has to be withdrawn
 - Know the PIN number
- Results:
 - Take money
 - Take back the withdrawal card

Exercise: ATM constraints

- Insert_Card, Enter_Code, Witdraw_Card
- Request_Cash, Select_Amount, Withdraw_Cash


Request_Cash - - - - - before - - - - - *Select_Amount*

Select_Amount
and
Insert_Card] - - - - - before - - - - - *Withdraw_Cash*

Insert_Card - - - - - before - - - - - *Withdraw_Card*

Enter_Code - - - - - just after - - - - - *Insert_Card*

One example of ATM functioning



The image shows a graphical user interface for an ATM. The window has a title bar with the text "ATM" and standard window controls (minimize, maximize, close). The main area is divided into two sections. The left section contains a text input field with the prompt "Please enter your code:". Below this field is a numeric keypad with buttons for digits 1 through 9, 0, *, and #. To the right of the keypad are three buttons: "Validate", "Correct", and "Cancel". At the bottom of the left section is a horizontal progress bar. The right section of the window is mostly empty, with a small horizontal progress bar near the top and a large orange rectangle near the bottom right corner.

ATM

Please enter your code:


1 2 3 Validate

4 5 6 Correct

7 8 9 Cancel

* 0 #

Exercise 1




Building the task tree

- 1 - Build a list of tasks
- 2 - Gather high-level tasks
- 3 - Breakdown low-level tasks
- Where to stop ?
 - Is the action “identify” decomposed enough?
 - Objective: only decompose pertinent tasks (objective optimization/automation of work)
 - User actions: perceptive/cognitive/motor usually not that interesting to decompose (except for performance evaluation or for interaction design)
 - System activity MUST not be represented (will be in other models) but connections to it yes
- Highest level = reproduction of the species ;-)
- Lowest level = biological life (breathe, drink, contract muscle ...)


Installation Game (end of the game)

- Identify your hardware/software platform
- Downloading tool / getting a USB Key
- Installing HAMSTERS
- Create your first task model

Video about HAMSTERS installation




Create a task model



Icon New
File


Create a task model

1. In the panel « Categories », select Hamsters
2. In the panel « File Types », select « TaskModel.hmst »




Create a task model

Select
TaskModel.hmst



Enter the name of the task model



New TaskModel.hmst

Steps

1. Choose File Type
2. **Name and Location**

Name and Location


File Name:


Project:

Folder:


Created File:

< Back Next > **Finish** Cancel Help





Exercise 1 – you edit this small model



Temporal ordering

- Temporal operators to describe temporal relationships between tasks
- Additional properties for the tasks:
 - Optional (otherwise means mandatory)
 - Iterative (otherwise means executed once)

Wilson S., Johnson P., Kelly C., Cunningham J. and Markopoulos P. **Beyond hacking: A model based approach to user interface design**, Proceedings of HCI'93, 217—23, Cambridge University Press, BCS HCI.

Temporal Operators

- Enabling $T1 \gg T2$
- Disabling $T1 [> T2$
- Interruption $T1 | > T2$
- Choice $T1 [\] T2$
- Concurrency $T1 ||| T2$
- Order independant $T1 |=| T2$

Wilson S., Johnson P., Kelly C., Cunningham J. and Markopoulos P. **Beyond hacking: A model based approach to user interface design**, Proceedings of HCI'93, 217—23, Cambridge University Press, BCS HCI.

Fabio Paternò, Cristiano Mancini, Silvia Meniconi: **ConcurTaskTrees (CTT): A Diagrammatic Notation for Specifying Task Models**. INTERACT 1997: 362-369

Temporal properties of the task

- Optional



Request receipt

optional	<input checked="" type="checkbox"/>
iterative	<input type="checkbox"/>
number of iteration	0


























- Iterative



Change requested amount


optional	<input checked="" type="checkbox"/>
iterative	<input checked="" type="checkbox"/>
number of iteration	3

Task types

		Abstract	Input	Output	I/O	Processing	Group
Abstract			Not applicable	Not applicable	Not applicable	Not applicable	
User	Indiv.						
	Coop.						
Interactive	Indiv.					Not applicable	
	Coop.					Not applicable	
System							


Human/operator behavioral tasks

- Precise and detailed description of human activities
- Perceptive, motor, cognitive (Card, Moran, Newell 1983)
- Cognitive analysis, cognitive decision (Parasuraman 2000)




Tool palette in HAMSTERS (1/2)


- Abstract tasks
- User Tasks
- Interactive Tasks
- Operators
- System Tasks
- Collaborative Tasks
- Data
- Human Error
- Structuring Models



Tool palette in HAMSTERS (1/2)



Exercise 2: Refine the task model



Objects, Information, Knowledge, Devices and Software applications

I: (user) Information

I: (system) Information

Phy O: Physical object (system side)

Phy O: Physical Object (user side)

O: Object (system side)

i/o D: Input Device

i/o D: Output Device

i/o D: Input/Output Device

Sw A: Software Application


D K: Declarative Knowledge

SiK: Situational Knowledge

St K: Strategic Knowledge


Data flow

- Precise and detailed description of users' knowledge, manipulated objects and devices used
- Read (data used for performing the task)
- Write (data produced for performing the task)
- Read/write (data modified while performing the task)




Description of objects manipulated by the user and by the system

- Input and output devices
- Physical objects



Exercise 3: Add data flows in model



Exercise 3: Add data flows in model

- Add device(s)
- Add credit card
- Add information in the head of the user
- Add objects in the system side

Validation of the model

- Simulation of the model
- Scenarios
 - Identification of scenarios
 - Production of scenarios
 - Storage of scenarios

hamstersapplication 201502250047

File Edit View Team Window

Search (Ctrl+F)

Projects Files Services

MyATM

- Hamsters Files
- Roles
- Subroutine
- Component
- Objects
- Scenario
- Actor
- Trainee
- Practical se

Visual Source History

Withdraw cash

Open

Run simulator

Set as Main Role model

Cut Ctrl+X

Copy Ctrl+C

Delete Supprimer

Rename...

Save As Template...

History

Tools

Properties

Launch Simulator

Identify

Insert card

Insert code

Find out available

Put card in card slot

Insert card

Ask for PIN code

Enter PIN num 1

Enter Pin num 2

Enter PIN

Palette

- Information Object
- Object
- Physical Object
- Situational Knowledge Object
- Strategic Knowledge Object
- Human Error
- Interactive Tasks
 - Input Task
 - I/O Task
 - Interactive Task
 - Output Task
- User Tasks
 - Abstract User Task
 - Motor Task
 - Perceptive Task
 - User Task

Withdraw cash.hmst - Properties

Properties

Name	Withdraw cash
Extension	hmst
File Size	5076
Modification Time	10 mars 2015 11:52:38
All Files	C:\Users\martine\Do...

Withdraw cash.hmst

Navigator

Tree View

- Parent : >>
- Parent : Identify
- Parent : >>
- Select amount
- Process request
- Finalize withdrawal
- Parent : Withdraw money

Output

hamstersapplication 201502250047

File Edit View Team Window

Projects X Files Services

MyATM

- Hamsters Files
 - Roles
 - Withdraw cash.hmst
 - Subroutines
 - Component
 - Objects
 - Scenario
 - Actor
 - Trainee
 - Practical sessions

Navigator X

- Tree View
 - Parent : >>
 - Parent : Identify
 - Parent : >>
 - Select amount
 - Process request
 - Finalize withdrawal
 - Parent : Withdraw money

Visual Source History

New Scenario

Enter new scenario name

Phil withdraws 20

OK Annuler

Insert card

Insert code

Find out availabl

Put card in card slot

Insert card

Ask for PIN code

Enter PIN num 1

Enter Pin num 2

Enter PIN

Output X

Palette X

Information Object

Object

Physical Object

Situational Knowledge Object

Strategic Knowledge Object

Human Error

Interactive Tasks

- Input Task
- Interactive Task
- Perceptive Task
- I/O Task
- Output Task
- Motor Task
- User Task

User Tasks

- Abstract User Task
- Motor Task
- User Task

Withdraw cash.hmst - Properties X

Properties

- Name Withdraw cash
- Extension hmst
- File Size 6075
- Modification Time 10 mars 2015 11:52:38
- All Files C:\Users\martine\Do...

Withdraw cash.hmst

Enter name
of the scenario

hamstersapplication 201502250047

File Edit View Team Window

Projects Files Services

MyATM

- Hamsters Files
 - Withdraw cash.hmst
 - Subroutines
 - Component
 - Objects
 - Scenario
 - Phil withdraws 20.scen
 - Actor
 - Trainee
 - Practical sessions

Navigator

Tree View

- Parent : >>>
- Parent : Identify
 - Parent : >>>
 - Select amount
 - Process request
 - Finalize withdrawal
 - Parent : Withdraw money

Visual Source History

Simulation panel

New scenario has been created

Identify

Insert card

Insert code

Put card in card slot

Insert card

Ask for PIN code

Enter PIN num 1

Enter Pin num 2

Fin

Simulator Window Withdrawal card - Properties

Execution

Start simulation Restart simulation

Roles

Withdraw cash


Executable tasks:

Current Task


Perform task

No task selected


Scenario



Modifying models / sequence



Modifying models / interleaving



Refining Models


- Once the model is built (whatever notation you use)
 - How to be sure that it is correct?
 - How to improve it?
- Some heuristics
 - Coupled actions: e.g., where is “Put card in card slot”?
 - Restructure : e.g. make a task generic “Enter PIN digit”
 - Balance : e.g. is “Select amount” simpler than “Identify”?
 - Generalize: e.g. always withdraw a particular amount...
withdraw different amounts

Analysis of the completed models

- Qualitative
- Consistency of the users actions
- Detection of usability issues
- Quantitative
- Task complexity: How many actions have to be performed to reach the goal?
- Which are the different possible sequence of actions (scenarios) and what is the estimated min/max time for achieving them?
- What is the exhaustive list of required knowledge?
- Which information will have to be remembered and for how long?

Supported by HAMSTERS tool

- Distribution the total number of tasks across task types (Statistics panel)
- Estimated minimum and maximum time to perform a scenario (Statistics panel)
- Structural verification of the task model (Verification panel)




"Designing" task models

- Dealing with alternative options
- Functioning versus usage
- Interviews/scenarios for informing task model design
- Types of task models
- Relationship with types of procedures

Dealing with alternative options

- Money withdrawal at the cashier



Structuring: Functioning versus Usage


- Extraterrestrial example (J. Grudin, A case against consistency, INTERACT 90)
- Example of a computer system
 - We have a database with the following schema:




- Propose a menu tree allowing to manipulate that database

Functioning structure goes to prototype directly

- View of the Computer Scientist
 - No tasks analysis/modeling is needed
 - The tree structure reflects the database structure
 - Grouping is made according to code similarity



Tasks model




Example of Informal Task Description

- « I spent my day at work entering information for new clients and I must associate them with the more suitable sales man (according to various criteria) ... sometimes I receive an invoice from a sales man recently recruited. In such a case, I must create both the new sales man and the client. Sometimes a sales man quits the company. Usually they leave the company for another one and the clients follow them. I then have to delete the sales man and all its related ... »
- Exercise: Propose a tree structure adapted to the tasks described in this scenario

Usage structure (1/2)

- User interface is structured according to the task




Things are still problematic

- There is no
 - Menu for deleting clients (without sales man)
 - Client modification
 - ...
- There is
 - Access to clients through their sales man
 - Display of client information without getting to their sales man first
 - Duplication of menu items in the hierarchy
 - ...


$$U=1/F$$

(W. Buxton BCS HCI 96)


Task model in HAMSTERS




Examples of menu items duplication MS Word




Example MS Word



Example MS Word



Example MS Word



Various types of task models

- Existing (extant) System
 - One or many systems
 - One or many operators organization
- Envisioned System
 - One or many systems
 - One or many operators organization
- Variation of models (co-evolution) as tasks are performed on a given system – task modeling is a moving target

Carroll, J. M., Kellogg, W. A. and Rosson, M. B. 1991. The task-artifact cycle. Designing interaction: Psychology at the human-computer interface.

Carroll, J. M. Cambridge, England, Cambridge University Press: 74-102.

Summary

- Main principles of task modeling
- A notation for describing user tasks
- A tool to create, edit and simulate task models
- A simple technique to describe and analyze user tasks

Advanced design and fine tuning of interaction supported by task models

- Structuring mechanisms in task models and in HAMSTERS
- Industrial case study: UI for satellite platform monitoring and control
- Modeling process
 - Performance analysis
 - Exploiting task model for re-design/automation design/task migration
 - Task-based design of interactive systems
- Advanced practice of HAMSTERS tool and exercises
- Beyond (task-based UI design, human error, multiuser, training)
- Limitations (UX, co-execution, interface generation, ...)

Thank you for your attention

- Acknowledgements
- Thanks to Racim Fahssi who is in charge of developing the edition module of the HAMSTERS tool
- Thanks to the ICS (Interactive Critical Systems) team for helping us with the testing of the tool