

An Usability Design Approach of Tailored Visualizations for Mobile Applications

DIPLOMARBEIT

zur Erlangung des akademischen Grades

Diplom-Ingenieurin

im Rahmen des Studiums

Wirtschaftsinformatik

eingereicht von

Romana Jakob, BSc.

Matrikelnummer 1227095

an der Fakultät für Informatik

der Technischen Universität Wien

Betreuung: Ao.Univ. Prof. Mag. Dr. Margit Pohl

Mitwirkung: Mag. Dr. Gerhard Engelbrecht

Wien, 1. Mai 2018

Romana Jakob

Margit Pohl

An Usability Design Approach of Tailored Visualizations for Mobile Applications

DIPLOMA THESIS

submitted in partial fulfillment of the requirements for the degree of

Diplom-Ingenieurin

in

Business Informatics

by

Romana Jakob, BSc.

Registration Number 1227095

to the Faculty of Informatics

at the TU Wien

Advisor: Ao.Univ. Prof. Mag. Dr. Margit Pohl

Assistance: Mag. Dr. Gerhard Engelbrecht

Vienna, 1st May, 2018

Romana Jakob

Margit Pohl

Erklärung zur Verfassung der Arbeit

Romana Jakob, BSc.
Nabegg 53/2, 3323 Neustadt

Hiermit erkläre ich, dass ich diese Arbeit selbständig verfasst habe, dass ich die verwendeten Quellen und Hilfsmittel vollständig angegeben habe und dass ich die Stellen der Arbeit – einschließlich Tabellen, Karten und Abbildungen –, die anderen Werken oder dem Internet im Wortlaut oder dem Sinn nach entnommen sind, auf jeden Fall unter Angabe der Quelle als Entlehnung kenntlich gemacht habe.

Wien, 1. Mai 2018

Romana Jakob

Acknowledgements

I want to thank everyone who has contributed in any way to my study and the making of this thesis. First, I want to thank Margit Pohl, my thesis advisor for her support and not giving up on me, despite longer breaks.

I am grateful to Gerhard Engelbrecht not only for his feedback but also for the opportunity to write the thesis in cooperation with Siemens. Thanks to my boss at Siemens, Herwig Schreiner, for giving me the freedom to pursue this thesis.

Thanks to everyone who spared time to test the mobile application which was developed within this thesis. Your feedback was very helpful and contributed a lot to its further development. Finally, thanks to my friends during my study time for the mutual support.

Kurzfassung

Ihr Text hier.


Abstract

Enter your text here.

Contents

Kurzfassung	ix
Abstract	xi
Contents	xiii
1 Introduction	1
1.1 Motivating Scenario	1
1.2 Problem Statement	2
1.3 Aim of the work	2
1.4 Methodological Approach	4
1.5 Structure of the work	6
2 State of the Art	7
2.1 Usability engineering	7
2.2 User Classification	9
2.3 Elicitation of requirements with Paper Prototyping	15
2.4 Usability Tests	16
2.5 User study	17
2.6 Evaluation	17
2.7 Existing approaches	17
2.8 Comparison of existing approaches	17
2.9 Serious games	18
2.10 Persuasive System	18
List of Figures	19
List of Tables	21
List of Algorithms	23
Index	25
Glossary	27
	xiii

Acronyms	29
Bibliography	31



Introduction

In the age of social media, where information is tailored to users' interests, preferences and state of education, the question arises how to integrate this phenomenon into common mobile applications. Especially when the aim of the application is education or changing a user's behaviour an adaption of the user interface to various requirements might be beneficial.

This thesis investigates whether tailoring the interface of a mobile application to a user's state of knowledge has effects on the usefulness of the application. The state of knowledge and the needs of the users are gathered into user groups, in order to limit the amount of possibilities.

1.1 Motivating Scenario

This thesis is written in cooperation with Siemens AG Austria, within a research project that deals with the Seestadt in Aspern. The Seestadt is one of the biggest city development projects in Europe ¹. The Aspern Smart City Research GmbH & Co KG ² (ASCR) is an exclusive technology partner of Siemens AG. The Aspern project has the overall goal of finding smarter solutions for energy consumption with the help of smart grids, power supplies, building systems, intelligent power grids and communication technologies. Another side goal is an optimal interaction of all these components. The ASCR infrastructure manages the data coming from smart grids and smart buildings such as temperature, energy consumption, water consumption, power demand as well as external data sources such as weather, city events, energy market, traffic reports etc.

¹<https://www.aspern-seestadt.at/> Accessed 10.01.2018

²<http://www.ascr.at/> Accessed 10.01.2018

[PDE15] In total 1.5 million values are measured per day. To create something useful out of this amount of data is a big task.³

Take, for example, an application that informs you about your electricity consumption. What can be assumed, is that the user wants an easy-to-use application which shows the power consumption in an understandable way. The problem that we observed is that the majority of users lack the feeling for the size of one kilowatt hour. The same can be witnessed when it comes to CO₂ emission. The unit of kilograms of CO₂ is an information that mostly only experts can grasp and can relate to.

1.2 Problem Statement

In the field of software development the interaction with the user is important, including the consideration of a user's knowledge. Numerous applications aim at motivating the user to save energy or CO₂ but neglect the incomprehensibility of units of measurements one does not deal with on a daily basis. The sense of trying to motivate the user to save energy by displaying the electricity consumption in kilowatt hours, might have less impact than setting it at least in relation to an average consumption of electricity or even visualizing it with a gamification approach. On the other hand, for someone who is easy on these types of measurement a visualization with colors or graphs might be too much.

So, the problem we are facing is to develop a mobile application that is beneficial for all types of users, starting from users who do not have a feeling for kilowatt hours or kilograms of CO₂ up to users having a great affinity for electricity and carbon-dioxide emission.

To address this bandwidth of user knowledge and visualization possibilities, this thesis investigates the usefulness of tailoring a mobile application to a users knowledge. Furthermore design principles and criteria that shall help front-end developers, usability engineers as well as software architects to develop applications customized to a users level of knowledge shall be investigated.

We evaluate different types of users and their preferred way of gathering information. Ranging from the ones who show only interest in their overall behavior, meaning if they are better or worse than the average, over others, who want to know their power consumption more detailed but still can't grasp the measurement of one kilowatt hour, up to users, who are deep into the topic and are keen on extensive figures.

1.3 Aim of the work

The overall goal of this thesis is to identify the benefits or even drawbacks of providing a user interface in a mobile application with various possibilities of presenting information

³<http://www.report.at/index.php/energie/wirtschaft-a-politik/item/91884-lebendes-stadtlabor> Accessed 10.01.2018

to switch between. We want to investigate if a user makes use of different visualizations or the presented way is excepted and therefore an adaptation of the user to the application takes place.

This thesis contributes (1) a prototype of a mobile application aiming at increasing CO₂ awareness with the help of customized visualizations and (2) a catalog of criteria of design principles for tailoring visualizations containing information of consumption data.

The central research question is the following:

What are the effects on knowledge acquisition in mobile applications when providing visualizations tailored to users' knowledge?

The central research question can be answered after having found a solution to the sub-questions:

(a) What are the characteristics of a user group with the same state of knowledge? In order to answer this research question we first conduct a literature review in the area, followed by a user survey detecting the state of knowledge in the field of electricity units of measurements, i.e. the size of one kilowatt hour, one kilogram of CO₂. These findings will help in identifying groups and their characteristics.

(b) Which criteria do questions have to meet, that shall identify the type of a user? The findings of the sub-research question (a) will have an influence on the questionnaire needed for defining which group a user can be assigned to. This questionnaire will be the first contact point in the mobile application.

(c) What are the design possibilities when it comes to tailoring interfaces to a users' state of knowledge in the scope of electricity consumption data? This question can be answered by conducting a literature review and considering the characteristics of a user group.

(d) Do the characteristics of user groups correlate with the users' preferred type of visualization? The results elicited for research question a) are the foundation for defining the correlation between groups of users and their preferred type of visualization. Assuming the favourite type of visualization is the most used one, allows to identify the preferred type of visualization by analysing the log files.

(e) Does a user switch between various screens showing the same information represented in different ways? We answer this by looking at the log files and also by observing the interaction with the mobile application in the usability tests.

1.4 Methodological Approach

In order to fulfill the research questions the methodological approach comprises the following steps:

1. Literature Review

The first step is to dive into the topic of usability engineering, especially different forms of visualizations and graphical user interfaces in the scope of mobile applications. That implies a research about paper prototyping, usability testing in the mobile context as well as user classification and carbon dioxide awareness. The goal is to get an insight of all relevant aspects which will serve as foundation for the following steps.

2. Comparative analysis of alternatives and comparison of existing approaches

In this step, the market and competition analysis which was done when the problem arose will be done in more depth. The questions that shall be answered in this steps are the following.

- Which applications are there within the topics of energy saving and CO2 awareness?
- Which approaches and visualizations do these applications make use of to increase awareness?
- How do these applications handle the users' level of education concerning energy units of measurements, such as kWh?

3. Elicitation of requirements with Paper Prototyping

The second step is to do "Paper Prototyping" in order to elicit the requirements for the graphical user interfaces and overall for the CO2 awareness app. According to [Lan04] the numerous benefits of early usability studies are vastly superior. It may seem low-tech, but conducting usability tests at this step show what users really expect on a quite detailed level which gives maximum feedback for minimum effort [Wei03].

At first a group of people containing at least one user for each user type will be put together. Next, hand-sketched drafts will be drawn, showing the app with menus, dialog boxes, notifications and buttons. Then, different tasks that can be done with the app shall be defined. These tasks are then conducted by the users. The feedback from the users show what they expect from the app which is of great value for the implementation later on [Sny03].

4. Architectural Design of the CO2 awareness mobile application

The insights from the previous steps will influence the architecture and the designs of the CO2 awareness mobile application. With focus on design and usability an architectural design will be developed including a development plan. At this step,

the different data resources for the computation of the personal CO₂ emission, such as power consumption, water consumption, nutrition lifestyle, transportation habits, size of the living space, place of living, family situation etc. must be considered.

The app shall be usable for all users but will be particularly useful for inhabitants of the Aspern Seestadt in Vienna, as we have a database for the dwellers of the student dorm, the schoolhouse and one residential building. This data comes from the Aspern Smart City Research⁴ (ASCR) project where Siemens plays an essential role in collaboration research.

5. Technical Implementation of the CO₂ awareness mobile application

According to the architecture description from step 4 the mobile application will be implemented using an agile software development process and a fully native approach targeting Android Devices.

6. Usability Tests

In order to avoid distorting of the research results the graphical user interface will be tested empirically with 4-5 usability tests, that means the usability is accessed by testing the interface with real users [Nie94b].

7. User study

The design of the user study will follow the seminal guidelines for conducting case study research in software engineering as proposed by Runeson et al. [RHRR12]. The target group will consist of at least one user for each type of energy user. The study protocol will follow the check-lists for reading and reviewing case studies from Höst and Runeson [HR07].

8. Evaluation

In this step the developed mobile app will be empirically evaluated against a valuation model in a user study to identify the success of the research. The evaluation model comprises of numerous Key Performance Indicators (KPIs). An extraction of these KPIs is listed in the following:

- a) More than 50 % of all the users using the app state that the possibility of switching between different ways to display the information is useful
- b) More than 50 % state, that they are more aware of what to do to avoid CO₂ than before using the app
- c) More than 50 % of the users state that they understand and get a feeling of how much CO₂ they are producing

⁴<http://www.ascr.at/>. Accessed 9.11.2017

1.5 Structure of the work

The remainder of this thesis is structured as follows: Chapter 2 provides an overview of related work where the main approaches of tailoring user interfaces are discussed. This chapter is concluded by a comparison with the existing approaches.

State of the Art

In the following sections the theoretical background for the topics that this thesis deals with will be presented. In particular, usability engineering especially different forms of visualizations and graphical user interfaces in the scope of mobile applications. That implies a research about paper prototyping, usability testing in the mobile context as well as user classification for the definition of user groups and carbon dioxide awareness in general. Finally, we will have a look on existing approaches, such as serious games and a comparative analysis of alternatives.

2.1 Usability engineering

The International Organization for Standardization (ISO) defines usability as the "Extent to which a product can be used by specified users to achieve specified goals with effectiveness, efficiency and satisfaction in a specified context of use" [Bev98]. This definition comprises three measurable attributes which are the following:

- **Effectiveness:** Accuracy and completeness with which users achieve specified goals.
- **Efficiency:** Resources expended in relation to the accuracy and completeness with which users achieve goals.
- **Satisfaction:** Freedom from discomfort, and positive attitudes towards the use of the product.

The ISO standard also identifies three factors that should be considered when evaluating usability:

- **User:** Person who interacts with the product.
- **Goal:** Intended outcome.
- **Context of use:** Users, tasks, equipment (hardware, software and materials), and the physical and social environments in which a product is used.

Nielsen [Nie94b] also identified five attributes of usability and factors having an impact on how the user interacts with a system. In addition to the above ones Nielsen [Nie94a] states:

- **Learnability:** The user should get work done rapidly which is possible if the system is easy to use.
- **Efficiency:** Once the user has learned to operate with the system, the productivity should be high.
- **Memorability:** In case a user does not use the system in a longer period, it should, nevertheless, be easy remembered without having to learn everything all over again.
- **Errors:** When using the system, the user makes few errors and is able to return and recover easily after an error. Further, catastrophic errors must not occur.
- **Satisfaction:** The system is highly accepted as the user has positive attitudes towards the system and finds it pleasant to use.

2.1.1 Usability engineering in the context of mobile applications

The focus on usability and interaction between human and hand-held electronic devices has its origin within the emergence of mobile devices. The approach of Nielsen, mentioned above, was expanded with the scope of mobile applications by Zhang and Adipat [ZA05] who highlighted a number of issues by the advent of mobile devices. The issues mentioned are:

- mobile context
- connectivity
- small screen
- different display resolution
- limited processing capability and power and
- data entry methods

Zhang et al. mention that these restrictions are especially a problem when it comes to usability testing methods, as all these issues must be considered in order to select an appropriate research methodology. It must be kept in mind that contextual factors on perceived usability can occur when they are not considered in a study.

Harisson et al. [HFD13] build up on the terms mentioned before and introduced a PACMAD (People At the Centre of Mobile Application Development) model which was designed to address the limitations of existing usability models when applied to mobile devices. PACMAD extends the theories of usability with more aspects such as *user task* and *context of use*. The existing usability models such as those proposed by Nielsen [Nie94b] and ISO [Bev98] also recognize these factors as crucial parts on which the successfulness of the usability of an application depends. The difference is that PACMAD includes all the factors into one model to ensure a complete usability evaluation.

Deka [Dek16] discusses how data-driven approaches are tools for mobile app design. A relevant field mentioned is interaction mining, that captures the static part, such as layouts and visual details, as well as the dynamic part, like user flows and motion details, of app design.

Fogarty and Hudson [FH03] presented an experimental toolkit to support optimization for interface and display generation. This approach

The decades of research in adaptive user interfaces were summarized by Gajos et al. [GWW08]. They conclude that personalized user interfaces have the ability to improve user satisfaction and performance, when the interface is adapted to the device, task, preferences and abilities of a person. To automatically generate user interfaces they use decision-theoretic optimization which includes functional specifications of the interface, constraints of the devices e.g. screen size and a list of available interactors, a typical usage trace and a cost function. The cost function holds user preferences and the expected speed of operation.

2.2 User Classification

Weiss [Wei03] discussed the balance of ease of use compared to the ease of learning. A huge emphasis is laid on the first, and according to Weiss, the most important step in the design and development process, the understanding of the audience. The purpose of the audience definition is to describe the target group, its' traits and ranges.

2.2.1 User Segmentation according to Smart Cities Demo Aspern

Aspern Smart City Research GmbH & Co KG (ASCR) also lays emphasis on understanding the user. The research group defines a smart user as a person who has the knowledge for sustainable decisions in relation to his or her lifestyle. Saving CO₂ and energy should be the overall goals of a smart user.

Nevertheless, not all smart users are the same and not all share the same state of knowledge or interest. Therefore, in 2015 ASCR conducted a socio-scientific study to find out how much know-how a smart user has in the field of technology and energy and also how much interest they have in the topics of energy and sustainability. The research was done in an apartment block named D12, where the possibility to test solutions is given, as the apartments in this block are equipped with systems that collect data including

- electricity consumption
- room temperature
- warm/cold water consumption and
- air quality.

Over half of the households in the apartment block D12 agreed on making their data available for research purposes and to participate in surveys and workshops. In total, 85 households took part in the study in 2015. In the starting phase two studies were done. At first a qualitative study with personal interviews with selected tenants of the building D12 was done followed by a quantitative study with written questionnaires. One outcome of these studies was the segmentation of users into groups. Different types of users were clustered into four segments according to their state of knowledge and their interest in technology and energy. The user groups also serve as target groups for the development of new technology solutions such as home automation, mobile application and for the development of range of services. The segmentation into groups also makes communication easier as the used methods of communication can be tailored to the needs of a group.

The qualitative study with its interviews was done before the tenants moved into the apartments in Seestadt. Surprisingly the majority stated that it has basic knowledge for the interpretation of the energy consumption and energy data in general. Often they stated that they do not know how much on kilowatt hour is. In most cases the main source of information for energy topics is the energy consumption calculation. Unfortunately the calculation does not state the behaviour or the devices which use up the most energy. Exactly these two aspects are the most wished information for the users when it comes to saving energy.

The aim of a segmentation in its statistical way is to find distinct groups with significant differences [PS83]. Within a group the characteristics should be homogeneous. An established way for segmentation in statistics is to do two statistic procedures, beginning with a factor analysis, followed by a cluster analysis [Tuf11].

The factor analysis reduces dimensions [WOB10]. In the quantitative questionnaires multiple variables are collected and in the factor analysis these variables are reduced to so called latent variables or factors. Therefore, the factor analysis shows which dimensions are underlying the whole questionnaire.

In the socio economic study of ASCR an explorative non-rotating factor analysis was calculated. Afterwards the scree test showed the amount of factors, which was in this case four. In terms of content the analysis of the factor showed the following dimensions:

- **Comfort-centered:** This factor covers aspects like home automation, energy relevant user behavior such as lighting and circulation behavior and hot water usage.
- **Technology-centered:** Also covers aspects like home automation but more with the sense of interest in the technology rather than the comfort aspect.
- **Data sensibility:** Concerns regarding the further use of the collected data.
- **Living in Seestadt:** The aspect of living in the Seestadt as an extra dimension shows that it is some kind of prestige to live there.

Finally a cluster analysis was done to identify the user segments. Cluster analysis is an exploratory process with the aim of finding groups of similar objects [Tuf11]. Different hierarchical analysis were calculated to find an appropriate amount of clusters. Appropriate means in this case having an big enough group of cases/persons and groups having distinct features. The data set comprised 121 handed back questionnaires and the cluster analysis could identify four clusters. The four clusters correspond to the four user groups. The result of the cluster analysis is shown in 2.1 and explained in the following.




Figure 2.1: Result of the cluster analysis: Four user groups

"Professionals" (48 %): The Professionals are the biggest group. The members of this group are technically competent and interested in topics concerning energy.

The main characteristics are:

- High proportion of persons having an abitur or university graduates
- Highest proportion of people in managerial positions, a quarter works (also) at home
- All household sizes (also households with children)
- Knowledge about energy
- High technical competence and interest in Technology. (Experience with home automation, a quarter has programming skills)
- Interested in sustainability
- Use of media or Internet is primarily for professional purposes

Typical segment behavior regarding home equipment:

- "Reasonable" use of hot water ("I do not shower longer than necessary")
- "Reasonable" use of lighting ("I turn down the light when I leave a room")
- Make use of the "ECO-Button" (installed tool in the apartments of D12 which helps to save energy) when leaving the apartment

Due to their technical expertise, their experience with home automation and their interest in energy issues they are the most appropriate target group for home automation and mobile application solutions. Rationally justified explanations and instructions for use meet their information style. Professionals also expect more detailed information in individual offers such as energy feedback.

"Optimizer" (30 %):

The second largest segment comprises people who primarily aim to optimize energy costs. Optimizer have little knowledge about energy and are no technophiles.

The main characteristics are:

- High proportion of persons having an abitur or university graduates
- Highest proportion of people in managerial positions
- More women
- All household sizes (also households with children)
- Interested in sustainability
- Little to no knowledge about home automation

- no technophiles
- Use of media or Internet is not very noticeable

Typical segment behavior regarding home equipment:

- Prefer to air manually rather than to make use of the automatic ventilation system
- A quarter never uses the "ECO-Button"

The use of the home furnishings indicates a poor understanding of their usability or less time of interaction with them. Due to their much lower competence in energy and technology compared to the professionals, the planned solutions and measures should focus very strongly on the following points:

- Clear and concrete instructions for behavior, for example in the form of energy-saving tips or concrete, close to reality explanations and concrete benefits.
- Avoid technical language in communication and use personalized examples.
- Reduce energy feedback to essential information. Optimizer do not need detailed explanations.
- Enable trouble shooting: Optimizer want a quick solution to an energy problem, as they do not want to spend lot of time on energy topics.

"Indifferents" (13 %):

The "Indifferents" have low competence in energy and technology and no interest in energy topics or sustainability.

The main characteristics are:

- Young segment
- High proportion of Non-workers
- No interest in sustainability
- Low technical competence (no experience with home automation)
- Information research and streaming is above average

Typical segment behavior regarding home equipment:

- Hedonistic use of hot water: They enjoy taking long showers and baths

- Smallest number on different device types
- Little satisfaction with the provided air ventilation

The "Indifferents" have low interest in the research topic and it's solution in general. To address this group with the necessary knowledge and to awaken their interest for energy and sustainability, a bigger effort has to be done than for the above groups. A typical representative of this group is a person who has just moved out from the parental home and who now has to organize the household on his/her own and to develop independence.

"Hedonists" (9 %):

The "Hedonists" are technical competent but are indifferent to energy and sustainability topics.

The main characteristics are:

- Young segment
- More mens, more single households
- Technical competent and partly with programming skills
- Intensive use of mobile Apps and Internet
- Hedonistic use of gaming and social media

Typical segment behavior regarding home equipment:

- Highest number on different device types
- Carefree use of lighting and hedonistic use of hot water
- Frequent use of "ECO-Button"
- High satisfaction with the provided air ventilation
- Weak identification with Seestadt

The youngest segment has good preconditions to make a good use of mobile application with feedback of their energy use. Nevertheless, the motivation to deal with energy topic is rather low. The hedonistic lifestyle with its strong convenience and comfort orientation is in the foreground. Despite the high usage of apps it may be difficult to win them around for energy feedback. The comfort gain is of great relevance.

2.3 Elicitation of requirements with Paper Prototyping

In order to elicit the requirements for the graphical user interfaces and overall for the CO2 awareness app we make use of Paper Prototyping. According to [Lan04] the numerous benefits of early usability studies are vastly superior. Besides saving time and money by solving problems before the implementation even begins, Paper Prototyping stimulates creativity as it allows to experience with different ideas before committing to one [Sny03]. It may seem low-tech, but conducting usability tests at this step show what users really expect on a quite detailed level which gives maximum feedback for minimum effort [Wei03].

A highly recommended introduction into effective prototyping is provided by Arnowitz et al. [AAB10] as well as by Bernard and Summers [BS10] which inducted into dynamic prototyping. Arnowitz et al. [AAB10] proposed the following Step-by-Step guide to create a Paper Prototype:

1. **Create scenario.** Before starting to draw anything the main user goals and tasks have to be portrayed. This can be done in a scenario narration.
2. **Inventory UI elements.** The next step is to make a checklist of all UI elements that may be needed to support the scenario.
3. **Create UI elements.** All the UI elements from the checklist from the previous step are now created in paper form. There are a lot of tools and materials that can come in handy at this step. The following list of materials might help the process: paper, sticky notes, whiteboard, sketchbook, notebook, napkin, cards, overhead sheet, cardboard, carton, scissors, markers, UI stencil, correction fluid and tape and transparency sheet.
4. **Run through scenario.** In this step a dry-run through the scenario with the paper prototype should be done and missing parts should be found and recreated.
5. **Internal review.** The last step in the first round is the internal review with the team where the audience is defined, the goals for each version of the prototype is reviewed, the expectation of the reviewers are found out and the next steps are planned.

The next Step-By-Step Guide is following the first. It was also proposed by Arnowitz et al. [AAB10] and is for testing the Paper Prototype:

1. **Revise scenario.** The internal review may have uncovered some tweaks that you want to change. Be careful for changes at the scenario as it may cause a ripple effect which can lead to necessary changes in user interface elements or even new screens. Keeping changes to minimum is recommended. If changes are necessary keep in mind that this may result in the inventory of user interface.

2. **Revise inventory UI elements.** Until now maybe multiple run throughs through the prototype have been done and you noticed that some vital pieces of the interface are missing. Now is a good time to check completeness of the UI elements checklist. Developing a set of UI elements for cases that you did not anticipate may be also useful.
3. **Create UI elements.**
4. **Pilot run through scenario.** Before presenting the prototype to the user it has to be tried out first. You can give the Prototype to anyone, e.g. a team member, to try it out. The aim here is to find missing pieces to be prepared for everything they do. The run through will ensure that you haven't created a half-baked prototype.
5. **Internal review.**

The last step in the first round is the internal review with the team where the audience is defined, the goals for each version of the prototype is reviewed, the expectation of the reviewers are found out and the next steps are planned.
6. **Prepare Kit.** Before running the prototype session the papers have to be arranged in a way that makes it easy to find the various UI elements. Also blank paper, sticky notes and pens should be prepared for further ideas.
7. **The Prototype Session.** The user study session is an interactive process where one or more participants and a facilitator are involved. In a dialogue the participant completes tasks provided by the facilitator. The session is used to get user opinions about early design and task flow ideas represented on paper. The sessions are typically recorded for later examination. The feedback from the users show what they expect from the app which is of great value for the implementation later on [Sny03]. Weiss [Wei03, p. 144] proposes to invite not only one, but two respondents at a time for paper prototype usability tests. He mentions that two respondents feel more comfortable in the casual environment that paper prototyping creates, whereas one single respondent can easily become overwhelmed by the experience.
8. **Reiterate.** After each prototype session an review and evaluation about what went good and what bad can be done. Although it might be tempting to change things after each session, it is better to wait until all the planned user sessions are done to do an overall comparative review at the end.

2.4 Usability Tests

mobile context In order to avoid distorting of the research results the graphical user interface will be tested empirically with 4-5 usability tests, that means the usability is accessed by testing the interface with real users [Nie94b].

2.5 User study

The design of the user study will follow the seminal guidelines for conducting case study research in software engineering as proposed by Runeson et al. [RHRR12]. The target group will consist of at least one user for each type of energy user. The study protocol will follow the check-lists for reading and reviewing case studies from Höst and Runeson [HR07].

2.6 Evaluation

In this step the developed mobile app will be empirically evaluated against a valuation model in a user study to identify the success of the research. The evaluation model comprises of numerous Key Performance Indicators (KPIs). An extraction of these KPIs is listed in the following:

1. More than 50 % of all the users using the app state that the possibility of switching between different ways to display the information is useful
2. More than 50 % state, that they are more aware of what to do to avoid CO₂ than before using the app
3. More than 50 % of the users state that they understand and get a feeling of how much CO₂ they are producing

Carbon dioxide awareness

[MGM⁺17]

2.7 Existing approaches

2.8 Comparison of existing approaches

In this step, the market and competition analysis which was done when the problem arose will be done in more depth. The questions that shall be answered in this steps are the following.

- Which applications are there within the topics of energy saving and CO₂ awareness?
- Which approaches and visualizations do these applications make use of to increase awareness?
- How do these applications handle the users' level of education concerning energy units of measurements, such as kWh?

2.9 Serious games

The Energy Piggy Bank - A Serious Game for Energy Conservation

Serious games are games that educate, train, and inform

Serious games are gaining importance recently. These games aim at behavior change and education.

Hedin et al. [BLWM17] describe a serious game that shall help people learn more about their energy consumption. They designed the game according to the taxonomy of Bartles Player Types that constitute of four Types having different motivation for playing games.

They also evaluated the behaviour

self-assessed future behaviour change

The outcome of the work is a strong correlation between self-assessed future behavior change and perceived value/usefulness of the application independent of the player type.

Bartle Player Types

Serious games have attracted much attention recently and are used to in an engaging way support for example education and behavior change. In this paper, we present a serious game designed for helping people learn about their own energy consumption and to support behavior change towards more sustainable energy habits. We have designed the game for all the four Bartle Player Types, a taxonomy used to identify different motivations for playing games. Engagement of the participants has been evaluated using the Intrinsic Motivation Inventory, and we have measured self-assessed future behavior change. We found a statistically significant positive correlation between self-assessed future behavior change and perceived value/usefulness of the application independent of player type. Our study indicates the player type “Achievers” might perform better using this type of application and find it more enjoyable, but that it can be useful for learning energy conserving behavior independent of player type

2.10 Persuasive System

Tailoring and personalizing the content to the potential needs, interests, usage context or other factors is outlined by [OKH09] in the context of a Persuasive System. They studied how a persuasive system must be designed with tailored and personalized content to maximize the change in the user’s behaviour. Although the outcome on the behaviour change is not relevant, the findings on the tailor aspects are highly interesting for the proposed thesis.

At first a group of people containing at least one user for each user type will be put together. There, hand-sketched drafts will be drawn, showing the app with menus, dialogue boxes, notifications and buttons. Then, different tasks that can be done with the app shall be defined. These tasks are then conducted by the users.

List of Figures

2.1	Result of the cluster analysis: Four user groups	11
-----	--	----

List of Tables

List of Algorithms

Index

distribution, 5

Glossary

editor A text editor is a type of program used for editing plain text files.. 5

Acronyms

CTAN Comprehensive TeX Archive Network. 11

FAQ Frequently Asked Questions. 11

PDF Portable Document Format. 6, 10, 11, 15

SVN Subversion. 10

WYSIWYG What You See Is What You Get. 9

Bibliography

- [AAB10] Jonathan Arnowitz, Michael Arent, and Nevin Berger. *Effective prototyping for software makers*. Elsevier, 2010.
- [Bev98] N Bevan. Iso 9241: Ergonomic requirements for office work with visual display terminals (vdts)-part 11: Guidance on usability. *TC*, 159, 1998.
- [BLWM17] Hedin Björn, Anton Lundström, Magnus Westlund, and Erik Markström. The energy piggy bank - a serious game for energy conservation. In *The Fifth IFIP Conference on Sustainable Internet and ICT for Sustainability, Funchal, Portugal, December 6-7, 2017* :, 2017. QC 20171218.
- [BS10] Chris Bernard and Sara Summers. *Dynamic Prototyping with SketchFlow in Expression Blend: Sketch Your Ideas... And Bring Them to Life!, Portable Documents*. Pearson Education, 2010.
- [Dek16] Biplab Deka. Data-driven mobile app design. In *Proceedings of the 29th Annual Symposium on User Interface Software and Technology*, pages 21–24. ACM, 2016.
- [FH03] James Fogarty and Scott E Hudson. Gadget: A toolkit for optimization-based approaches to interface and display generation. In *Proceedings of the 16th annual ACM symposium on User interface software and technology*, pages 125–134. ACM, 2003.
- [GWW08] Krzysztof Z Gajos, Daniel S Weld, and Jacob O Wobbrock. Decision-theoretic user interface generation. In *AAAI*, volume 8, pages 1532–1536, 2008.
- [HFD13] Rachel Harrison, Derek Flood, and David Duce. Usability of mobile applications: literature review and rationale for a new usability model. *Journal of Interaction Science*, 1(1):1, 2013.
- [HR07] Martin Host and Per Runeson. Checklists for software engineering case study research. In *Empirical Software Engineering and Measurement, 2007. ESEM 2007. First International Symposium on*, pages 479–481. IEEE, 2007.

- [Lan04] A Lancaster. Paper prototyping: the fast and easy way to design and refine user interfaces. *IEEE Transactions on Professional Communication*, 47(4):335–336, 2004.
- [MGM⁺17] Hessam Mohammadmoradi, Omprakash Gnawali, David Moss, Rainer Boelzle, and Gene Wang. Effectiveness of a task-based residential energy efficiency program in oahu. 2017.
- [Nie94a] Jakob Nielsen. *Usability engineering*. Elsevier, 1994.
- [Nie94b] Jakob Nielsen. Usability inspection methods. In *Conference companion on Human factors in computing systems*, pages 413–414. ACM, 1994.
- [OKH09] Harri Oinas-Kukkonen and Marja Harjumaa. Persuasive systems design: Key issues, process model, and system features. *Communications of the Association for Information Systems*, 24(1):28, 2009.
- [PDE15] Josiane Xavier Parreira, Deepak Dhungana, and Gerhard Engelbrecht. The role of rdf stream processing in an smart city ict infrastructure-the aspern smart city use case. In *International Semantic Web Conference*, pages 343–352. Springer, 2015.
- [PS83] Girish Punj and David W Stewart. Cluster analysis in marketing research: Review and suggestions for application. *Journal of marketing research*, pages 134–148, 1983.
- [RHRR12] Per Runeson, Martin Host, Austen Rainer, and Bjorn Regnell. *Case study research in software engineering: Guidelines and examples*. John Wiley & Sons, 2012.
- [Sny03] Carolyn Snyder. *Paper prototyping: The fast and easy way to design and refine user interfaces*. Morgan Kaufmann, 2003.
- [Tuf11] Stéphane Tufféry. *Data mining and statistics for decision making*, volume 2. Wiley Chichester, 2011.
- [Wei03] Scott Weiss. *Handheld usability*. John Wiley & Sons, 2003.
- [WOB10] Brett Williams, Andrys Onsman, and Ted Brown. Exploratory factor analysis: A five-step guide for novices. *Australasian Journal of Paramedicine*, 8(3), 2010.
- [ZA05] Dongsong Zhang and Boonlit Adipat. Challenges, methodologies, and issues in the usability testing of mobile applications. *International journal of human-computer interaction*, 18(3):293–308, 2005.